

Technical Data Sheet

Icorene N4450-1200 NAT



Polypropylene, Homopolymer

Product Description

Icorene N4450 is a polypropylene homopolymer with a high fluidity, a good transparency and gloss properties. It contains a combined a processing and an antistatic additive package. This grade is suitable for injection moulding and masterbatch applications. Its main applications are thin walled packaging items or housewares.

Processing Method	Compounding
Attribute	Good Processability; High Clarity; High Flow; High Gloss; Homopolymer
Forms	Powder
Application	Masterbatch; Thin-walled Packaging

Typical Properties	Nominal Value	Units	Test Method
Physical			
Melt Flow Rate, (230 °C/2.16 kg)	47	g/10 min	ASTM D1238
Density	0.905	g/cm ³	ASTM D1505
Mechanical			
Tensile Strength at Yield	41	MPa	ASTM D638
Tensile Strength at Break	22	MPa	ASTM D638
Flexural Modulus	1900	MPa	ASTM D790
Tensile Elongation at Break	500	%	ASTM D638
Impact			
Charpy Impact Strength - Notched, (23 °C, Type 1, Edgewise, Notch A)	2.0	kJ/m ²	ISO 179
Thermal			
Deflection Temperature Under Load Unannealed (0.45 MPa)	108	°C	ISO 75-2/B