

Technical Data Sheet

Adstif HA5029



Polypropylene, Homopolymer

Product Description

Adstif HA5029 is a high crystallinity polypropylene homopolymer with extremely high stiffness, high flowability, high gloss, high HDT, and has long term heat resistance. Typical customer applications are parts for electrical appliances such as electric kettle, coffee maker, electric fan housing, and also for TWIM and food containers. It is also used by customers for parts of automotive interior trim.

Application	Housewares; Small Appliances
Market	Consumer Products; Electrical / Electronics
Processing Method	Injection Molding
Attribute	Good Processability; Good Thermal Aging Resistance; High Stiffness; Homopolymer

Typical Properties	Nominal Value	Units	Test Method
Physical			
Melt Flow Rate, (230 °C/2.16 kg)	65	g/10 min	ASTM D1238
Density	0.90	g/cm ³	ASTM D792
Mechanical			
Flexural Modulus	2200	MPa	ASTM D790
Tensile Strength at Yield	41	MPa	ASTM D638
Tensile Elongation at Yield	6	%	ASTM D638
Impact			
Notched Izod Impact Strength, (23 °C)	20	J/m	ASTM D256
Hardness			
Rockwell Hardness, (R-Scale)	117		ASTM D785
Thermal			
Deflection Temperature Under Load, (0.46 N/mm ²)	140	°C	ASTM D648