



## Hifax TYC 762PLS

### Compounded Polyolefin

#### Product Description

*This information has been secured during the course of product development. Both the product and its properties are subject to change before final commercialization.*

Hifax TYC 762PLS very high melt flow, 2,100 MPa flexural modulus, precolored, UV-stabilized, mineral-filled, paintable thermoplastic elastomeric olefin has an excellent balance of properties, processability, and paintability. It was designed primarily for automotive bumper fascias.

#### Product Characteristics

Test Method used	ISO
Processing Methods	Injection Molding
Features	Good Dimensional Stability, Good Impact Resistance , Good Moldability , Paintable, High Stiffness
Typical Customer Applications	Exterior Applications

Typical Properties	Method	Value	Unit
<b>Physical</b>			
Density	ISO 1183	1.08	g/cm <sup>3</sup>
Melt flow rate (MFR) (230°C/2.16Kg)	ISO 1133	19	g/10 min
Note: Alternative test method is ASTM D 1238-01.			
<b>Mechanical</b>			
Tensile Stress at Yield	ISO 527-1, -2	19	MPa
Flexural modulus	ISO 178	2100	MPa
<b>Impact</b>			
Notched izod impact strength	ISO 180		
(23 °C)		43	kJ/m <sup>2</sup>
(-40 °C)		4.0	kJ/m <sup>2</sup>
<b>Hardness</b>			
Durometer Hardness (Shore D)	ASTM D 2240	60	
Note: 15 second dwell			
<b>Thermal</b>			
Heat deflection temperature A (1.80 MPa) Unannealed	ISO 75A-1, -2	56	°C
<b>Additional Information</b>			
Mold shrinkage	ISO 294-4		