

Technical Data Sheet

Moplen HP500D

Polypropylene, Homopolymer

Product Description

Moplen HP500D is a high molecular weight polypropylene homopolymer resin, with good stiffness, good heat resistance, low sagging, low yellowness, low odor, and excellent chemical resistance. Typical customer applications are extrusion of sheets, profiles and non-pressure pipes, as well as for trays and containers, for food or electronic components.

Application	Containers; General Sheet Extrusion; Thermoformed Food Containers
Market	Consumer Products; Rigid Packaging
Processing Method	Sheet; Sheet and Profile Extrusion; Thermoforming
Attribute	High Molecular Weight; High Stiffness; Homopolymer

Typical Properties	Nominal Value	Units	Test Method
Physical			
Melt Flow Rate, (230 °C/2.16 kg)	0.5	g/10 min	ASTM D1238
Density	0.90	g/cm ³	ASTM D792
Mechanical			
Flexural Modulus	1560	MPa	ASTM D790
Tensile Strength at Yield	35	MPa	ASTM D638
Tensile Elongation at Yield	12	%	ASTM D638
Impact			
Notched Izod Impact Strength, (23 °C)	104	J/m	ASTM D256
Thermal			
Deflection Temperature Under Load	103	°C	ASTM D648