	(	(+) 18816996168	
SAFETY DATA SHEET		onciplastics.com	lvoodollbacoll
according to Regulation (EC) No.	1907/200	Ю	lyondellbasell
CirculenRenew C14 L	03020	К	Gen. Variant: SDS_AT
Version 1.0 Revision Dat			/05/2022 SDS No.: BE43067
1. Identification of the substance	/mixture	e and of the company/u	ndertaking
1.1 Product identifier			
Trade name		ulenRenew C14 LD3020k	K
Synonyms Substance name		ene, homopolymer, PE	
Substance No.		vethylene 2-88-4	
Chemical characterization		vethylene Homopolymer	
1.2 Relevant identified uses of the	ne substa	ance or mixture and us	es advised against
Identified uses		ufacture of plastic article ther conversion process.	s by injection molding, extrusion
Prohibited uses	devi App	ces; Health Canada clas	nent implantation into the body;
1.3 Details of the supplier of the	safety d		
Company Basell Sales & Marketing Compa Delftseplein 27E 3013 AA Rotterdam Netherlands	any B.V.	Registration nur NA	nber Telephone 31 (0) 10 275 55 00
E-mail address Responsible/issuing person	: produc	ct.safety@lyb.com	
1.4 Emergency telephone number	er		
Basell Sales & Marketing Compa	any B.V.		+32 3 575 1235
Poison Center: Gesundheid Österreich GMBH AT: +43 1 406 43 43 24 hours all days			
		1 / 16	
		1/10	

SAFETY	DATA	SHEET	

(+) **18816996168** 

Ponciplastics.com

according to Regulation (EC) No. 1907/2006

## CirculenRenew C14 LD3020K

Version 1.0

Revision Date 09/15/2021

Print Date 01/05/2022

SDS No.: BE43067

lvondellbasell

Gen. Variant: SDS AT

2. Hazards identification

## 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

## 2.2 Label elements

## Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

## 2.3 Other hazards

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

May decompose releasing irritating and toxic gases.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

## 3. Composition/information on ingredients

## 3.1 Substances

## Components

Chemical name	CAS-No. EINECS-No. / ELINCS No./EC-No.	<u>Weight %</u>	Component Type
Polyethylene	9002-88-4	<=100.0 %	

## 4. First aid measures

## 4.1 Description of first-aid measures

General advice	: Take proper precautions to ensure your own health and safety
	before attempting rescue and providing first aid.

## If inhaled : Remove person to fresh air. If signs/symptoms continue, get

2 / 16

 $(+)\,18816996168$ 

Ponciplastics.com



Version 1.0       Revision Date 09/15/2021       Print Date 01/05/2022       SDS No.: BE43         medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, mow the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated. <b>2. Most important symptoms and effects, both acute and delayed</b> Symptoms       : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. <b>3 Indication of any immediate medical attention and special treatment meeded</b> Treatment       : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.   <	CirculenRenew	C14LD3	020K		Gen. V	/ariant: SDS_AT	I
In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Atazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. I treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.				Print Date 01/	05/2022	SDS No.: BE4	4306
large amounts of water to cool the affected tissue and polymer.       Do not attempt to peel polymer from skin as this will remove the skin.         Obtain immediate emergency medical attention if burn is deep or extensive.       In case of eye contact       : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes.         Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s).       Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated. <b>2. Most important symptoms and effects, both acute and delayed</b> Symptoms       : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. <b>3 Indication of any immediate medical attention and special treatment needed</b> Treatment       : Treatment of overxposure should be directed at the control of symptoms and the clinical condition of the patient. <b>Fire-fighting measures 1</b>			In case of ex- generated d fresh air. Obtain medi Keep persor Resuscitatio	xcessive inhalatior luring heating of th ical attention. n warm, if necessa on (CPR)	nis material, ary give Care	move the person to dio-Pulmonary	
medical attention if discomfort persists.         :       In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       :         .       Adverse health effects due to ingestion are not anticipated.         .       2 Most important symptoms and effects, both acute and delayed         Symptoms       :         .       Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       :         .       Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         .3       Indication of any immediate medical attention and special treatment needed         Treatment       :         .       Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.         .       Fire-fighting measures        1       Extinguishing media	In case of skin con	tact :	large amour polymer. Do not atten the skin. Obtain imme	nts of water to coo npt to peel polyme ediate emergency	I the affecte	d tissue and as this will remove	)
A.2 Most important symptoms and effects, both acute and delayed         Symptoms       : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         A.3 Indication of any immediate medical attention and special treatment needed         Treatment       : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.         S. Fire-fighting measures         A.1 Extinguishing media	In case of eye cont		medical attention In case of end Continuously 15 minutes. Beyond flust adherent to	ention if discomfort ye contact with mo y flush eye(s) with hing, DO NOT atte the eye(s).	persists. olten polyme cool runnin empt to rem	er: g water for at least	k
Symptoms       : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         .3 Indication of any immediate medical attention and special treatment needed         Treatment       : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.         Fire-fighting measures         .1 Extinguishing media	If swallowed	:	Adverse hea	alth effects due to	ingestion ar	e not anticipated.	
in the nose and throat and coughing.         Hazards       : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         .3 Indication of any immediate medical attention and special treatment needed         Treatment       : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.         . Fire-fighting measures         .1 Extinguishing media	.2 Most important syr	nptoms and e	effects, both	acute and delaye	ed		
Molten polymer may cause thermal burns.  .3 Indication of any immediate medical attention and special treatment needed Treatment Treatme	Symptoms	:				nay cause soreness	
symptoms and the clinical condition of the patient. 5. Fire-fighting measures 5.1 Extinguishing media	Hazards	:					
. Fire-fighting measures	.3 Indication of any ir	nmediate me	dical attentic	on and special tre	atment nee	eded	
5.1 Extinguishing media	Treatment	:					of
5.1 Extinguishing media 3 / 16	5. Fire-fighting measu	res					
3 / 16	5.1 Extinguishing med	lia					
			3	3 / 16			

SAFETY	DATA	SHEET
0,		

 $(+)\,18816996168$ 

Ponciplastics.com



CirculenRenew C14 LI	D3020K Gen. Variant: SDS_AT
Version 1.0 Revision Dat	te 09/15/2021 Print Date 01/05/2022 SDS No.: BE430
Suitable extinguishing media Unsuitable extinguishing	<ul> <li>SMALL FIRE: Use dry chemical, CO2, or water spray.</li> <li>LARGE FIRES: Use water spray hose nozzles from a safe location.</li> <li>None known.</li> </ul>
media 5.2 Special hazards arising from	
Specific hazards during fire fighting	<ul> <li>Keep away from heat and sources of ignition.</li> <li>In case of fire hazardous decomposition products may be produced such as:</li> <li>Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).</li> </ul>
5.3 Advice for firefighters	
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	<ul> <li>Combustible particulate solid, will decompose under fire conditions.</li> <li>Calorific Value: 8000 - 11000 kcal/kg</li> <li>Fight fire from safe distance with hose lines or monitor nozzles.</li> <li>Heat from fire may melt, decompose polymer, and generate flammable vapors.</li> <li>Move containers from fire area if it can be done without risk.</li> <li>Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container.</li> <li>Always stay away from tanks engulfed in fire.</li> <li>Do not attempt to get on top of storage containers involved in fire.</li> <li>Cool storage containers with large volumes of water even after fire is out.</li> </ul>
6. Accidental release measures	
5.1 Personal precautions, protec	ctive equipment and emergency procedures
Personal precautions	<ul> <li>Equip responders with proper protection.</li> <li>Creates dangerous slipping hazard on any hard smooth surface.</li> <li>Equip emergency responders with proper personal protective</li> </ul>
	4 / 16

 $(+)\,18816996168$ 

Ponciplastics.com



CirculenRenew C14 L	D3020K	Gen. V	ariant: SDS_AT
	ate 09/15/2021	Print Date 01/05/2022	SDS No.: BE430
	with compre Potential co Polymer par surfaces. : May Contair	ating dust. rsal of dust in the air (i.e., clear ssed air). mbustible dust hazard. ticles create slipping hazard or n trace amounts of light hydroca	h hard smooth
	of oxidation,	aldehydes and acids	
2 Environmental precautions			
Environmental precautions	: Do not flush	into surface water or sanitary	sewer system.
6.3 Methods and materials for o	containment and	cleaning up	
Methods for containment / Methods for cleaning up	vacuum usir On water, m solid. All recovered transported applicable la	eep/shovel into suitable disposing equipment which avoids igninaterial is insoluble; collect and disposed of or reclaimed i aws and regulations and in con practices. Reclaim where possi	ition risk. contain as any , labeled, n conformance with formance with good
7. Handling and storage 7.1 Precautions for safe handli	na		
Advice on safe handling	•	n a pellet form.	
	If converted handling, or concentration Avoid dust a Avoid gener presence of hazard. Static discha environment explosion Electrostation Equipment I	to small particles during furthe by other means, may form cor	nbustible dust e. d in air and in the al dust explosion ources, in high dust It in a dust eying or handling.
	Ę	5 / 16	

 $(+)\,18816996168$ 

Ponciplastics.com



<b>CirculenRenew C14</b>	D3020K	Gen. Va	ariant: SDS_AT
	Date 09/15/2021	Print Date 01/05/2022	SDS No.: BE4306
	should be g All electrica codes and r combustible After handlin water. When bring	iners involved in the transfer of rounded and bonded. I equipment should conform to a egulatory requirements for area e dusts. ng, always wash hands thoroug ing the material to processing to b may condense in the exhaust	applicable electric is handling hly with soap and emperatures vapors
Fire-fighting class	: Polymer wil	I burn but does not easily ignite	
7.2 Conditions for safe storag	e, including any ii	ncompatibilities	
Requirements for storage areas and containers	and handling should be u Store away oxidizing ag Keep contal Take measu : Maximum a 60 days. Avoid direct Avoid direct Store either	ousekeeping practices during s g. Process enclosures and ade sed to avoid excessive dust acc from excessive heat and away	quate ventilation cumulation. from strong ation. lectrostatic charge. 50°C for maximum ces of heat.
7.3 Specific end use(s)	: See Sectior	ı 1.2.	
8. Exposure controls/personal 8.1 Control parameters Ingredients with workpla Occupational Exposure L	ce control parame imits	<b>ters</b> 5 / 16	

 $(+)\,18816996168$ 

Ponciplastics.com



according to Regulation (EC) No. 1907/2006

CirculenRen	ew C14 LD3020K	Gen. V	ariant: SDS_AT
Version 1.0	Revision Date 09/15/2021	Print Date 01/05/2022	SDS No.: BE43067

Components	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can be formed when		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
handling this product: Non-					
specified (inert or nuisance) dust					
Materials that can be formed when handling this		TWA	3 mg/m3 respirable	US (ACGIH) 2005	
product: Non- specified (inert or					
nuisance) dust					

Consult local authorities for acceptable exposure limits.

## 8.2 Exposure controls

#### Engineering measures

Follow the recommendations in international standard NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

#### Personal protective equipment

Respiratory protection	<ul> <li>Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.</li> <li>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.</li> <li>Use appropriate respiratory protection where atmosphere exceeds recommended limits.</li> <li>Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.</li> </ul>
Hand protection	: Wear gloves that provide thermal protection where there is a
	7 / 16

(+) **18816996168** 

Ponciplastics.com



rsion 1.0 Rev		3020K		n. Variant: SDS_AT
	ision Date	09/15/2021	Print Date 01/05/2022	SDS No.: BE4
		potential for	r contact with heated mater	ial.
Eye and face protect	ion	injury or oth	e goggles should be worn t her irritation to eyes due to a from handling this product.	
Skin and body protec	tion	: Wear suital	ble protective clothing.	
Hygiene measures		be based o of the prote performed, hazards an during use. Use good p Wash hand facilities.	f appropriate personal prote n an evaluation of the perfo ctive equipment relative to conditions present, duration d/or potential hazards that n personal hygiene practices. s before eating, drinking, so ntaminated clothing and wa	rmance characteristics the task(s) to be n of use, and the may be encountered moking, or using toilet
Environmental expo	osure cont	rols		
General advice		: See section	n 6.	
Physical and chemica Information on basic Appearance		and chemica : pellets	l properties	
Physical and chemica Information on basic Appearance		and chemica : pellets solid		
Physical and chemica Information on basic Appearance Color		and chemica : pellets solid : Translucent		
Physical and chemica Information on basic Appearance Color Odor		and chemica : pellets solid : Translucent : Slight.	to white	
Physical and chemica Information on basic Appearance Color		and chemica : pellets solid : Translucent	to white	
Physical and chemica Information on basic Appearance Color Odor	c physical	and chemica : pellets solid : Translucent : Slight. : No Data Av : The minimu	to white	
Physical and chemica Information on basic Appearance Color Odor Flash point	t physical	and chemica : pellets solid : Translucent : Slight. : No Data Av : The minimu	to white vailable. um explosive concentration rding to particle size distrib	
Physical and chemica Information on basic Appearance Color Odor Flash point Lower explosion limit	t t	and chemica : pellets solid : Translucent : Slight. : No Data Av : The minimu varies acco : Not applica	to white vailable. um explosive concentration rding to particle size distrib	ution.
Physical and chemica Information on basic Appearance Color Odor Flash point Lower explosion limit	t t	and chemica : pellets solid : Translucent : Slight. : No Data Av : The minimu varies acco : Not applica : Polymer wi	to white railable. Im explosive concentration rding to particle size distrib ble.	ution.

 $(+)\,18816996168$ 

	Gen. Variant: SDS AT		
CirculenRenew C14 LI Version 1.0 Revision Da	e 09/15/2021 Print Date 01/05/2022 SDS No.: BE43		
Autoignition temperature	: > 300 °C		
Decomposition temperature	: not determined		
Melting point/range	: 50 - 170 °C		
Boiling point/boiling range	: Not applicable.		
Vapor pressure	: Not applicable.		
Density	: <1 g/cm3		
Water solubility	: Insoluble.		
Partition coefficient: n-	: No Data Available.		
octanol/water Viscosity, dynamic	: Not applicable.		
Relative vapor density	: Not applicable.		
Evaporation rate	: Not applicable.		
Explosive properties	: No Data Available.		
9.2 Other information			
Other information	: No additional information available.		
I0. Stability and reactivity			
I0.1 Reactivity			
No known reactivity hazards.			
10.2 Chemical stability			
Stable under normal condition	S.		
10.3 Possibility of hazardous re	ictions		
Hazardous reactions	: Will not occur.		
10.4 Conditions to avoid			
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or		
	9 / 16		

 $(+)\,18816996168$ 

Ponciplastics.com

according to Regulation (EC) No. 1907/2006

Gen. Variant: SDS\_AT

CirculenRenew C Version 1.0 Revis	Date 09/15/2021 Print Date 01/05/2022 SDS No.: BE4306
	open flame.
0.5 Incompatible materi	
Materials to avoid	: Material may be softened by some hydrocarbons.
0.6 Hazardous decompo	ion products
Hazardous decompos	n : Not expected to decompose under normal conditions.
products Thermal decompositio	: Note: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
1. Toxicological informa	n
1.1 Information on toxic	ogical effects
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation tox	y : Not classified
Acute dermal toxicit	: Not classified
Skin corrosion/irritat	Not a skin irritant.
Serious eye damage irritation	<i>ie</i> : Not an eye irritant. Mechanical irritation is possible.
Respiratory or skin sensitization	: Not classified
Chronic toxicity	
Carcinogenicity	: Not classified
	10 / 16

	(+) 18816996168	
SAFETY DATA SHEET	(+) <b>18816996168</b> Ponciplastics.com	lyondellbasell
according to Regulation (EC) No. 1	907/2006	1 1 111 11
CirculenRenew C14 LD		Gen. Variant: SDS_AT
Version 1.0 Revision Date	e 09/15/2021 Print Date 01/05	5/2022 SDS No.: BE43067
Germ cell mutagenicity	: Not classified	
Reproductive toxicity		
Effects on fertility /	: Not classified	
Effects on or via lactation Effects on Development	: Not classified	
Target Organ Systemic Toxic	cant - Single exposure	
	: The substance or mixture is not organ toxicant, single exposure.	
Target Organ Systemic Toxic	cant - Repeated exposure	
	: The substance or mixture is not organ toxicant, repeated expose	
Aspiration hazard	: Not applicable.	
12. Ecological information		
12.1 Ecotoxicology Assessment Short-term (acute) aquatic	: Not classified	
hazard	: Not classified	
Long-term (chronic) aquatic hazard		
12.2 Persistence and degradabili	ty	
Biodegradability	: Not expected to be biodegradab	le.
12.3 Bioaccumulative potential		
Bioaccumulation	: This material is not expected to	bioaccumulate.
12.4 Mobility in soil		
	11 / 16	

	(+) 18816996168			
SAFETY DATA SHEET according to Regulation (EC) No. 1	907/2006 Iyondellbasell			
CirculenRenew C14 LD3020K Gen. Variant: SDS_AT				
Version 1.0         Revision Date 09/15/2021         Print Date 01/05/2022         SDS No.: BE43067				
Mobility	: no data available			
12.5 Results of PBT and vPvB as	essment			
Result	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).			
12.6 Other adverse effects				
Environmental fate and pathways	: This material is not volatile and insoluble in water.			
12.7 Other information				
Additional ecological information	<ul> <li>Ecotoxicity is expected to be minimal based on the low water solubility of polymers.</li> <li>No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.</li> </ul>			
13. Disposal considerations				
13.1 Waste treatment methods				
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.			
14. Transport information				
Not regulated for transport				
	12 / 16			

(+) 18816996168

Ponciplastics.com

according to Regulation (EC) No. 1907/2006

## CirculenRenew C14 LD3020K

Version 1.0

Revision Date 09/15/2021

Print Date 01/05/2022

SDS No.: BE43067

lvondellbasell

Gen. Variant: SDS AT

## 15. Regulatory information

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **REACh** status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that the chemical substance in this product has been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

#### Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

Contact product.safety@lyb.com for additional global inventory information.

## 15.2 Chemical safety assessment

No information available.


## 16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

13 / 16

 $(+)\,18816996168$ 

Ponciplastics.com





Version 1.0

Revision Date 09/15/2021

Print Date 01/05/2022

SDS No.: BE43067


lyondellbasell

Gen. Variant: SDS\_AT

Material safety datasheet sections which have been updated:
First Edition Abbreviations and Acronyms
ACGIH - American Conference of Governmental Industrial Hygienists ACGIH_BEIs - American Conference of Governmental Industrial Hygienists_Biological Exposure Indices
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road AICS - Australian Inventory of Chemical Substances ASTM - American Society for Testing and Materials
BEL - Biological Exposure Limits BTEX - Benzene, Toluene, Ethylbenzene, Xylenes CAS - Chemical Abstracts Service
CEFIC - European Chemical Industry Council CLP - Classification Packaging and Labelling COC - Cleveland Open-Cup
CS - Consumer Scenario DIN - Deutsches Institut für Normung DN(M)EL - Derived No (Minimal) Effect Level
DSL - Canada Domestic Substance List EC - European Commission EC50 - Median Effective Concentration
ECETOC - European Center on Ecotoxicology and Toxicology of Chemicals ECHA - European Chemicals Agency EL50 - Effective Loading fifty
ELINCS - EHR-Lab Interoperability and Connectivity Specification ENCS - Japanese Existing and New Chemical Substances Inventory ERC - Environmental Release Category
EUSES - European Union System for the Evaluation of Substances EWC - European Waste Code GHS - Globally Harmonized System of Classification and Labelling of Ch
IARC - International Agency for Research on Cancer IATA - International Air Transport Association IC50 - Inhibitory Concentration fifty IL50 = Inhibitory Level fifty
IMDG - International Maritime Dangerous Goods IECSC - Chinese Chemicals Inventory IOELV - Indicative Occupational Exposure Limit Values
IP346 - Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables
KECI - Korea Existing Chemicals Inventory Koc - Organic Carbon/Water Partition Coefficient LC50 - Lethal Concentration fifty
LD50 - Lethal Dose fifty per cent. LL/EL/IL - Lethal Loading/Effective Loading/Inhibitory Loading LL50 - Lethal Loading fifty
14 / 16

(+) **18816996168** 

Ponciplastics.com



# Gen. Variant: SDS AT

Version 1.0

Revision Date 09/15/2021

Print Date 01/05/2022

SDS No.: BE43067

MAK Commission - Permanent Senate Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area MARPOL - International Convention for the Prevention of Pollution from Ships No. - Number NOEC/NOEL - No Observed Effect Concentration / No Observed Effect Level NZIoC - New Zealand Inventory of Chemicals OE\_HPV - Occupational Exposure - High Production Volume OECD - Organization for Economic Co-operation and Development **OEL - Occupational Exposure Limit** PBT - Persistent, Bio accumulative and Toxic PICCS - Philippine Inventory of Chemicals and Chemical Substances PNEC - Predicted No Effect Concentration **PPE - Personal Protective Equipment PROC - Process Category** QSAR - Quantitative Structure-Activity Relationship REACH - Registration Evaluation and Authorization of Chemicals RID - Regulations Relating to International Carriage of Dangerous Goods by Rail SDS - Safety Data Sheet SKIN DES - Skin Designation STEL - Short term exposure limit STP - Standard Temperature and Pressure TCSCA - Taiwan inventory of chemicals TGD - Technical Guidance Document TRA - Targeted Risk Assessment TSCA - US Toxic Substances Control Act TWA - Time-Weighted Average **UN - United Nations** vPvB - very Persistent and very Bioaccumulative WGK - German Water Endangerment Class

## Disclaimer

Multiple legal entities and registration numbers may be displayed in Section 1. The Recipient shall refer to the shipping documents to identify the legal entity that supplied this product.

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/

15 / 16

(+) 18816996168

Ponciplastics.com

according to Regulation (EC) No. 1907/2006

lvondellbasell Gen. Variant: SDS AT

## CirculenRenew C14 LD3020K

Version 1.0

Revision Date 09/15/2021

Print Date 01/05/2022

SDS No.: BE43067

## Disclaimer

The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

## Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

## Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

## End of Material Safety Data Sheet