| | (+) 18 | 8816996168 | | | |
|--|----------------------------|--|---|--|--|
| | Poncip | 3816996168 | | | |
| SAFETY DATA SHEET according to Regulation (EC) No. 19 | 07/2006 | | lyondellbasell | | |
| Lucalen A2700H | | | Gen. Variant: SDS_AT | | |
| Version 1.4 Revision Date (|)5/24/2020 | Print Date 01 | /05/2022 SDS No.: BE8177 | | |
| 1. Identification of the substance/mixture and of the company/undertaking | | | | | |
| 1.1 Product identifier | | | | | |
| Trade name : Synonyms : Substance name : | acrylate-eth | l, butyl ester, polyr nylene copolymer | mer with ethylene, Butyl , polymer with ethene | | |
| Substance No. | 25750-84-9 | • | , polymer with ethene | | |
| Chemical characterization : | Polyethyler | ne copolymer | | | |
| 1.2 Relevant identified uses of the | substance o | r mixture and use | es advised against | | |
| Identified uses : | | e of plastic articles nversion process. | s by injection molding, extrusion | | |
| Prohibited uses : | devices; He Application | ealth Canada clas | s; European class III medical s IV Medical Devices; nent implantation into the body; cations | | |
| 1.3 Details of the supplier of the sa | fety data she | eet | | | |
| Company Basell Sales & Marketing Company Delftseplein 27E 3013 AA Rotterdam Netherlands | B.V. | Registration nur NA | mber Telephone 31 (0) 10 275 55 00 | | |
| E-mail address : Responsible/issuing person | product.safet | y@lyb.com | | | |
| 1.4 Emergency telephone number | | | | | |
| Basell Sales & Marketing Company | B.V. | | +32 3 575 1235 | | |
| Poison Center: Gesundheid Österreich GMBH AT: +43 1 406 43 43 24 hours all days | | | | | |
| | | | | | |
| 1 / 17 | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |



according to Regulation (EC) No. 1907/2006

Lucalen A2700H

Version 1.4

Print Date 01/05/2022

SDS No.: BE8177

lyondellbasell

Gen. Variant: SDS AT

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Revision Date 05/24/2020

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

2.3 Other hazards

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

May decompose releasing irritating and toxic gases.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

3. Composition/information on ingredients

3.1 Substances

Chemical nature : Substance

Components

| Chemical name | CAS-No. EINECS-No. / ELINCS No./EC-No. | <u>Weight %</u> | Component Type |
|--|--|-----------------|-------------------|
| 2-Propenoic acid, butyl ester, polymer with ethene | 25750-84-9 | 100.0 % | |

4. First aid measures

4.1 Description of first-aid measures

| (+)18816996168 |
|-------------------|
| Ponciplastics.com |

according to Regulation (EC) No. 1907/2006

Gen. Variant: SDS_AT

Lucalen A2700H Revision Date 05/24/2020

Version 1.4

Print Date 01/05/2022

SDS No.: BE8177

| | General advice | : | Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. | |
|-----|---|-----|--|--|
| | If inhaled | : | Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) | |
| | In case of skin contact | : | If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. | |
| | In case of eye contact | : | Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. | |
| | | : | In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. | |
| | If swallowed | : | Adverse health effects due to ingestion are not anticipated. | |
| 4.2 | Most important symptoms and | l e | ffects, both acute and delayed | |
| | Symptoms | : | Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. | |
| | Hazards | : | Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. | |
| 4.3 | .3 Indication of any immediate medical attention and special treatment needed | | | |
| | Treatment | : | Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. | |
| | | | 3 / 17 | |
| | | | <i>o,</i> | |
| | | | | |
| | | | | |

| | (+) 18816 Ponciplas | 5996168 stics.com | |
|--|--|---|--|
| SAFETY DATA SHEET according to Regulation (EC) No. | | | lyondellbasel |
| | 1907/2000 | | Gen. Variant: SDS_AT |
| Lucalen A2700H Version 1.4 Revision Dat | e 05/24/2020 | Print Date 01/05/2 | |
| | | | |
| . Fire-fighting measures | | | |
| .1 Extinguishing media | | | |
| Suitable extinguishing media | : SMALL FIRE: Use dry chemica | al, CO2, or water | spray. |
| | : LARGE FIRES: Use water spray | | om a safe location. |
| Unsuitable extinguishing media .2 Special hazards arising from | : None known. the substance or m | nixture | |
| Specific hazards during fire fighting | : Keep away from In case of fire ha produced such a | n heat and source azardous decomp as: de, carbon dioxide | position products may be |
| .3 Advice for firefighters | | | |
| Special protective equipment for fire-fighters | | positive pressure irefighter protectiv | e self-contained breathing ve clothing. |
| Further information | conditions. Calorific Value: 4 Fight fire from sa nozzles. Heat from fire m flammable vapor Move containers Evacuate immed container pressu Always stay awa | 8000 - 11000 kca afe distance with hay melt, decomports. s from fire area if diately in the ever ure relief devices ay from tanks eng | hose lines or monitor ose polymer, and generate it can be done without risk. nt of opening of storage or discoloration of container. |
| | after fire is out. | _ | e volumes of water even |
| | 4 / 17 | 7 | |

| SAFETY DATA SHEET according to Regulation (EC) No. 190 Lucalen A2700H Version 1.4 Revision Date C | | Gen. Variant: SDS_AT |
|--|--|---|
| 6. Accidental release measures | | |
| 6.1 Personal precautions, protective | e equipment and emergency | procedures |
| Personal precautions : | equipment (PPE) Avoid generating dust. | nazard on any hard smooth s with proper personal protective a air (i.e., clearing dust surfaces azard. |
| : | May Contain trace amounts of oxidation, aldehydes and a | of light hydrocarbons, compounds acids |
| 6.2 Environmental precautions | | |
| Environmental precautions : | Do not flush into surface wate | er or sanitary sewer system. |
| 6.3 Methods and materials for conta | ainment and cleaning up | |
| Methods for containment / : Methods for cleaning up | solid. All recovered material should transported and disposed of | ich avoids ignition risk. le; collect and contain as any d be packaged, labeled, or reclaimed in conformance with ns and in conformance with good |
| 7. Handling and storage | | |
| 7.1 Precautions for safe handling | | |
| | Material is in a pellet form. If converted to small particles handling, or by other means, concentrations in air. | |
| | 5 / 17 | |
| | | |

(+) 18816996168 Ponciplastics.com SAFETY DATA SHEET lvondellbasell according to Regulation (EC) No. 1907/2006 Gen. Variant: SDS AT Lucalen A2700H Print Date 01/05/2022 Version 1.4 Revision Date 05/24/2020 SDS No.: BE8177 Avoid dust accumulation in enclosed space. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Fire-fighting class : Polymer will burn but does not easily ignite. 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage : Store in a dry location. areas and containers Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. : Maximum allowed storage temperatures of 50°C for maximum 60 days. Avoid direct insufflation of air. Avoid direct sunlight and contact with sources of heat. Store either in the closed original containers in well ventilated area or in silos with vents. 7.3 Specific end use(s) : See Section 1.2. 6/17



according to Regulation (EC) No. 1907/2006

Lucalen A2700H

Version 1.4

Print Date 01/05/2022

SDS No.: BE8177

lyondellbasell

Gen. Variant: SDS AT

8. Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Revision Date 05/24/2020

Occupational Exposure Limits

| Components | CAS-No. | Туре | Limit Value | Basis Revision Date | Additional Information |
|---|---------|------|-----------------------|------------------------|---------------------------|
| Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust | | TWA | 10 mg/m3 inhalable | US (ACGIH) 2005 | |
| Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust | | TWA | 3 mg/m3 respirable | US (ACGIH) 2005 | |

Consult local authorities for acceptable exposure limits.

8.2 Exposure controls

Engineering measures

Follow the recommendations in international standard NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection : Use proc

: Use process enclosures, local exhaust ventilation, or other

(+) 18816996168 Ponciplastics.com

SAFETY DATA SHEET lyondellbasell according to Regulation (EC) No. 1907/2006 Gen. Variant: SDS AT Lucalen A2700H Print Date 01/05/2022 Version 1.4 Revision Date 05/24/2020 SDS No.: BE8177 engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators. Hand protection : Wear gloves that provide thermal protection where there is a potential for contact with heated material. Eye and face protection : Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product. Skin and body protection : Wear suitable protective clothing. Selection of appropriate personal protective equipment should Hygiene measures be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse. Environmental exposure controls General advice : See section 6. 9. Physical and chemical properties 9.1 Information on basic physical and chemical properties Appearance : Pellets. Color : Translucent to white Odor : Slight. 8 / 17



according to Regulation (EC) No. 1907/2006

Lucalen A2700H Revision Date 05/24/2020

Version 1.4

Print Date 01/05/2022

SDS No.: BE8177

lyondellbasell

Gen. Variant: SDS_AT

| Flash point | : No Data Available. |
|--|--|
| Lower explosion limit | : The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution. |
| Upper explosion limit | : Not applicable. |
| Flammability (solid, gas) | : Polymer will burn but does not easily ignite. |
| Oxidizing properties | : Not considered an oxidizing agent. |
| Autoignition temperature | : > 300 °C |
| Decomposition temperature | : not determined |
| Melting point/range | : 50 - 170 °C |
| Boiling point/boiling range | : Not applicable. |
| Vapor pressure | : Not applicable. |
| Density | : <1 g/cm3 |
| Water solubility | : Insoluble. |
| Partition coefficient: n- octanol/water | : No Data Available. |
| Viscosity, dynamic | : Not applicable. |
| Relative vapor density | : Not applicable. |
| Evaporation rate | : Not applicable. |
| Explosive properties | : No Data Available. |
| 9.2 Other information | |
| Other information | : No additional information available. |
| | |
| | |
| | |
| | 9 / 17 |

| SAFETY DATA SHEET according to Regulation (EC) No. | (+) 18816996168 Ponciplastics.com | lyondellbasell | | |
|---|--|--|--|--|
| Lucalen A2700H | | Gen. Variant: SDS_AT | | |
| Version 1.4 Revision Date | e 05/24/2020 Print Date 01 | 1/05/2022 SDS No.: BE8177 | | |
| | | | | |
| 10. Stability and reactivity | | | | |
| 10.1 Reactivity | | | | |
| No known reactivity hazards. | | | | |
| 10.2 Chemical stability | _ | | | |
| Stable under normal conditions 10.3 Possibility of hazardous rea | | | | |
| Hazardous reactions | : Will not occur. | | | |
| 10.4 Conditions to avoid | | | | |
| Conditions to avoid | : Avoid contact with strong oxi open flame. | idizers, excessive heat, sparks or | | |
| 10.5 Incompatible materials | | | | |
| Materials to avoid | : Material may be softened by | some hydrocarbons. | | |
| 10.6 Hazardous decomposition p | products | | | |
| Hazardous decomposition | : Not expected to decompose | under normal conditions. | | |
| products Thermal decomposition | : Note: Carbon monoxide, olef trace amounts of organic aci alcohols may be formed. | finic and paraffinic compounds, ids, ketones, aldehydes and | | |
| 11. Toxicological information | | | | |
| 11.1 Information on toxicological | leffects | | | |
| Acute toxicity | | | | |
| Acute oral toxicity | : Not classified | | | |
| Acute inhalation toxicity | : Not classified | | | |
| Acute dermal toxicity | : Not classified | | | |
| Skin corrosion/irritation | : Not a skin irritant. | | | |
| 10 / 17 | | | | |
| | | | | |

| SAFETY DATA SHEET according to Regulation (EC) No. 1 Lucalen A2700H Version 1.4 Revision Date | | Gen. Variant: SDS_AT | | | |
|--|---|---|--|--|--|
| Serious eye damage/eye irritation | : Not an eye irritant. Mechanical irritation is possil | ble. | | | |
| Respiratory or skin sensitization Chronic toxicity | : Not classified | | | | |
| Carcinogenicity | : Not classified | | | | |
| Germ cell mutagenicity | : Not classified | | | | |
| Reproductive toxicity | | | | | |
| Effects on fertility / Effects on or via lactation | : Not classified | | | | |
| Effects on Development | : Not classified | | | | |
| Target Organ Systemic Toxic | | | | | |
| | : The substance or mixture is organ toxicant, single exposit | not classified as specific target ure. | | | |
| Target Organ Systemic Toxic | ant - Repeated exposure | | | | |
| | : The substance or mixture is organ toxicant, repeated exp | | | | |
| Aspiration hazard | : Not applicable. | | | | |
| 12. Ecological information | | | | | |
| 12.1 Ecotoxicology Assessment | | | | | |
| 11 / 17 | | | | | |
| | | | | | |
| | | | | | |

| | (+) 18816996168 | |
|-------------------------------------|---|---|
| SAFETY DATA SHEET | Ponciplastics.com | luce de llbe e e ll |
| according to Regulation (EC) No. 19 | 07/2006 | lyondellbasell |
| Lucalen A2700H | | Gen. Variant: SDS_AT |
| Version 1.4 Revision Date | 05/24/2020 Print Date 01 | /05/2022 SDS No.: BE8177 |
| | | |
| Short-term (acute) aquatic hazard | Not classified | |
| | Not classified | |
| | | |
| 12.2 Persistence and degradability | | |
| Biodegradability | : Not expected to be biodegrad | lable. |
| 12.3 Bioaccumulative potential | | |
| Bioaccumulation | : This material is not expected | to bioaccumulate. |
| 12.4 Mobility in soil | | |
| | : no data available | |
| MODINITY | | |
| 12.5 Results of PBT and vPvB asse | ssment | |
| Result | | ains no components considered cumulative and toxic (PBT) or ccumulative (vPvB). |
| 12.6 Other adverse effects | | |
| Environmental fate and pathways | : This material is not volatile a | nd insoluble in water. |
| 12.7 Other information | | |
| | , i | minimal based on the low water |
| information | | duct. However, birds, fish and |
| | other wildlife may eat pellets intestinal tracts. | which may obstruct their |
| | | |
| | | |
| | 12 / 17 | |
| | | |
| | | |
| | | |

| | | (+) 1881699 Ponciplastic | 6168 | | |
|-----------------------------------|--|------------------------------------|-----------------------------|--|--|
| | | Ponciplastic | s. com | | |
| - | ATA SHEET egulation (EC) No. 1907 | 7/2006 | | lyondellbasell | |
| Lucalen A | 2700H | | | Gen. Variant: SDS_AT | |
| Version 1.4 | Revision Date 05 | /24/2020 Print | Date 01/05 | | |
| | | | | | |
| 13. Disposal co | onsiderations | | | | |
| 13.1 Waste trea | atment methods | | | | |
| Product | | | osed of or r regulations | reclaimed in conformance with and in conformance with good | |
| 14. Transport i | nformation | | | | |
| Not regulated fo | or transport | | | | |
| 15. Regulatory 15.1 Safety. he | | al regulations/legis | ation speci | ific for the substance or mixture | |
| | | | anon opool | | |
| | | | | | |
| If the product registered in | REACh status If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that the chemical substance in this product has been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006) | | | | |
| Other inte | rnational regulations | | | | |
| | S. | | - | emical inventory requirements or | |
| | *Additional Explanatory | | | - | |
| | Country/Region Australia | AICS | Status Compl | s Description | |
| | Canada | DSL | Compl | | |
| | China | IECSC | Compl | | |
| | | | | | |
| | 13 / 17 | | | | |
| | | | | | |
| | | | | | |
| | | | | | |



according to Regulation (EC) No. 1907/2006

Revision Date 05/24/2020

Lucalen A2700H

Version 1.4

Print Date 01/05/2022

SDS No.: BE8177

lyondellbasell

Gen. Variant: SDS AT

| Europe | REACH | See REACH Compliance Statement |
|--------------------------|-------|--------------------------------|
| Japan | ENCS | Compliant |
| Korea | KECI | Compliant |
| New Zealand | NZIoC | Compliant |
| Philippines | PICCS | Compliant |
| United States of America | TSCA | Compliant |
| Taiwan | TCSCA | Compliant |

Contact product.safety@lyb.com for additional global inventory information.

15.2 Chemical safety assessment

No information available.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 Abbreviations and Acronyms

ACGIH - American Conference of Governmental Industrial Hygienists

ACGIH_BEIs - American Conference of Governmental Industrial Hygienists_Biological Exposure Indices

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road AICS - Australian Inventory of Chemical Substances ASTM - American Society for Testing and Materials

BEL - Biological Exposure Limits

BTEX - Benzene, Toluene, Ethylbenzene, Xylenes

CAS - Chemical Abstracts Service

CEFIC - European Chemical Industry Council

CLP - Classification Packaging and Labelling

COC - Cleveland Open-Cup

CS - Consumer Scenario

DIN - Deutsches Institut für Normung DN(M)EL - Derived No (Minimal) Effect Level

DSL - Canada Domestic Substance List

EC - European Commission

EC50 - Median Effective Concentration

ECETOC - European Center on Ecotoxicology and Toxicology of Chemicals

ECHA - European Chemicals Agency

EL50 - Effective Loading fifty



according to Regulation (EC) No. 1907/2006

Revision Date 05/24/2020

Lucalen A2700H

Version 1.4

Print Date 01/05/2022

SDS No.: BE8177

lvondellbasell

Gen. Variant: SDS_AT

ELINCS - EHR-Lab Interoperability and Connectivity Specification ENCS - Japanese Existing and New Chemical Substances Inventory ERC - Environmental Release Category EUSES - European Union System for the Evaluation of Substances EWC - European Waste Code GHS - Globally Harmonized System of Classification and Labelling of Ch IARC - International Agency for Research on Cancer IATA - International Air Transport Association IC50 - Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG - International Maritime Dangerous Goods IECSC - Chinese Chemicals Inventory **IOELV - Indicative Occupational Exposure Limit Values** IP346 - Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables **KECI - Korea Existing Chemicals Inventory** Koc - Organic Carbon/Water Partition Coefficient LC50 - Lethal Concentration fifty LD50 - Lethal Dose fifty per cent. LL/EL/IL - Lethal Loading/Effective Loading/Inhibitory Loading LL50 - Lethal Loading fifty MAK Commission - Permanent Senate Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area MARPOL - International Convention for the Prevention of Pollution from Ships No. - Number NOEC/NOEL - No Observed Effect Concentration / No Observed Effect Level NZIoC - New Zealand Inventory of Chemicals OE HPV - Occupational Exposure - High Production Volume OECD - Organization for Economic Co-operation and Development **OEL - Occupational Exposure Limit** PBT - Persistent, Bio accumulative and Toxic PICCS - Philippine Inventory of Chemicals and Chemical Substances PNEC - Predicted No Effect Concentration PPE - Personal Protective Equipment PROC - Process Category QSAR - Quantitative Structure-Activity Relationship REACh - Registration Evaluation and Authorization of Chemicals RID - Regulations Relating to International Carriage of Dangerous Goods by Rail SDS - Safety Data Sheet SKIN_DES - Skin Designation STEL - Short term exposure limit STP - Standard Temperature and Pressure TCSCA - Taiwan inventory of chemicals TGD - Technical Guidance Document TRA - Targeted Risk Assessment TSCA - US Toxic Substances Control Act TWA - Time-Weighted Average

(+) **18816996168** Ponciplastics.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Lucalen A2700H

Version 1.4

Revision Date 05/24/2020 Print Date 01/05/2022

SDS No.: BE8177

lvondellbasell

Gen. Variant: SDS AT

UN - United Nations vPvB - very Persistent and very Bioaccumulative WGK - German Water Endangerment Class

Disclaimer

Multiple legal entities and registration numbers may be displayed in Section 1. The Recipient shall refer to the shipping documents to identify the legal entity that supplied this product.

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet

| (+) 18816996168 | |
|-------------------|--|
| Ponciplastics.com | |

according to Regulation (EC) No. 1907/2006

Lucalen A2700H

Version 1.4

Revision Date 05/24/2020 Print Date 01/05/2022

SDS No.: BE8177

Gen. Variant: SDS_AT