	(+)1	8816996168	
	Ponci	8816996168	
SAFETY DATA SHEET according to Regulation (EC) No. 1			lyondellbasell
Lucalen A2700P			Gen. Variant: SDS_AT
Version 1.4 Revision Date	04/15/2020	Print Date 01	1/05/2022 SDS No.: BE3323
1. Identification of the substance/	mixture and	of the company/u	undertaking
1.1 Product identifier			
Trade name Synonyms			ymer with ethylene, Butyl r
Substance name		· •	er, polymer with ethene
Substance No. Chemical characterization	: 25750-84- : Polyethyle	ene copolymer	
1.2 Relevant identified uses of the	substance	or mixture and us	sos advisod against
Identified uses			es by injection molding, extrusion
		onversion process.	
Prohibited uses	devices; I Applicatio	Health Canada clas	es; European class III medical ss IV Medical Devices; anent implantation into the body; ications
1.3 Details of the supplier of the s	afety data sl	heet	
Company Basell Sales & Marketing Compar Delftseplein 27E 3013 AA Rotterdam Netherlands	y B.V.	Registration nui NA	umber Telephone 31 (0) 10 275 55 00
E-mail address : Responsible/issuing person	product.safe	ety@lyb.com	
1.4 Emergency telephone number	r		
Basell Sales & Marketing Company	y B.V.		+32 3 575 1235
Poison Center: Gesundheid Österreich GMBH AT: +43 1 406 43 43 24 hours all days			
		1 / 17	
		() 11	



according to Regulation (EC) No. 1907/2006

Lucalen A2700P

Version 1.4

Print Date 01/05/2022

SDS No.: BE3323

lyondellbasell

Gen. Variant: SDS AT

2. Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Revision Date 04/15/2020

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

2.3 Other hazards

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

May decompose releasing irritating and toxic gases.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

3. Composition/information on ingredients

3.1 Substances

Chemical nature : Substance

Components

Chemical name	CAS-No. EINECS-No. / ELINCS No./EC-No.	<u>Weight %</u>	Component Type
2-Propenoic acid, butyl ester, polymer with ethene	25750-84-9	100.0 %	

4. First aid measures

4.1 Description of first-aid measures

(+)18816996168
Ponciplastics.com

according to Regulation (EC) No. 1907/2006

Gen. Variant: SDS_AT

Lucalen	A2700P
Varaian 4.4	David

Revision Date 04/15/2020 Version 1.4

Print Date 01/05/2022

SDS No.: BE3323

	General advice	: Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.
	lf inhaled	 Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)
	In case of skin contact	 If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive.
	In case of eye contact	: Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists.
		 In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.
	If swallowed	: Adverse health effects due to ingestion are not anticipated.
4.2 I	Most important symptoms and	effects, both acute and delayed
	Symptoms	: Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.
	Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
4.3 I	ndication of any immediate me	edical attention and special treatment needed
	Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
		3 / 17

	(+) 18816996168 Ponciplastics.com
SAFETY DATA SHEET	
according to Regulation (EC) No. 7	1907/2006 Iyondellbasel
Lucalen A2700P	Gen. Variant: SDS_AT
Version 1.4 Revision Date	e 04/15/2020 Print Date 01/05/2022 SDS No.: BE3323
5. Fire-fighting measures	
5.1 Extinguishing media	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising from Specific hazards during fire	: Keep away from heat and sources of ignition.
fighting	In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
5.3 Advice for firefighters	
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	: Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg
	Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate
	flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in
	fire. Cool storage containers with large volumes of water even after fire is out.
	4 / 17

SAFETY DATA SHEET according to Regulation (EC) No. 190 Lucalen A2700P Version 1.4 Revision Date C		Gen. Variant: SDS_AT /05/2022 SDS No.: BE3323
6. Accidental release measures		
6.1 Personal precautions, protective		-
Personal precautions :	equipment (PPE) Avoid generating dust.	azard on any hard smooth with proper personal protective air (i.e., clearing dust surfaces
:	May Contain trace amounts of oxidation, aldehydes and a	of light hydrocarbons, compounds acids
6.2 Environmental precautions		
Environmental precautions :	Do not flush into surface wate	er or sanitary sewer system.
6.3 Methods and materials for conta	ainment and cleaning up	
Methods for containment / : Methods for cleaning up	solid. All recovered material should transported and disposed of	ich avoids ignition risk. le; collect and contain as any l be packaged, labeled, or reclaimed in conformance with ns and in conformance with good
7. Handling and storage		
7.1 Precautions for safe handling		
	Material is in a pellet form. If converted to small particles handling, or by other means, concentrations in air.	
	5 / 17	

(+) 18816996168 Ponciplastics.com SAFETY DATA SHEET lvondellbasell according to Regulation (EC) No. 1907/2006 Gen. Variant: SDS AT Lucalen A2700P Print Date 01/05/2022 Version 1.4 Revision Date 04/15/2020 SDS No.: BE3323 Avoid dust accumulation in enclosed space. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Fire-fighting class : Polymer will burn but does not easily ignite. 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage : Store in a dry location. areas and containers Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. : Maximum allowed storage temperatures of 50°C for maximum 60 days. Avoid direct insufflation of air. Avoid direct sunlight and contact with sources of heat. Store either in the closed original containers in well ventilated area or in silos with vents. 7.3 Specific end use(s) : See Section 1.2. 6/17



according to Regulation (EC) No. 1907/2006

Lucalen A2700P

Version 1.4

Revision Date 04/15/2020 Print Date 01/05/2022 SDS No.: BE3323

lyondellbasell

Gen. Variant: SDS AT

8. Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	3 mg/m3 respirable	US (ACGIH) 2005	

Consult local authorities for acceptable exposure limits.

8.2 Exposure controls

Engineering measures

Follow the recommendations in international standard NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

: Use process enclosures, local exhaust ventilation, or other Respiratory protection

(+) **18816996168** Ponciplastics.com

SAFETY DATA SHEET lyondellbasell according to Regulation (EC) No. 1907/2006 Gen. Variant: SDS AT Lucalen A2700P Print Date 01/05/2022 Version 1.4 Revision Date 04/15/2020 SDS No.: BE3323 engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators. Hand protection : Wear gloves that provide thermal protection where there is a potential for contact with heated material. Eye and face protection : Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product. Skin and body protection : Wear suitable protective clothing. Selection of appropriate personal protective equipment should Hygiene measures be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse. Environmental exposure controls General advice : See section 6. 9. Physical and chemical properties 9.1 Information on basic physical and chemical properties Appearance : Pellets. Color : Translucent to white Odor : Slight. 8 / 17



according to Regulation (EC) No. 1907/2006

Revision Date 04/15/2020

Lucalen A2700P

Version 1.4

Print Date 01/05/2022

SDS No.: BE3323

Gen. Variant: SDS_AT

Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: < 1 g/cm3
Water solubility	: Insoluble.
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
2 Other information	

9.2 Other information

Other information

: No additional information available.

SAFETY DATA SHEET according to Regulation (EC) No. 1 Lucalen A2700P		16996168 astics.com	Gen. Variant: SDS_AT
Version 1.4 Revision Date	9 04/15/2020	Print Date 01	/05/2022 SDS No.: BE3323
10. Stability and reactivity			
10.1 ReactivityNo known reactivity hazards.10.2 Chemical stability			
Stable under normal conditions			
10.3 Possibility of hazardous read Hazardous reactions	ctions : Will not occur		
	. Whit hot occur		
10.4 Conditions to avoid Conditions to avoid	: Avoid contact open flame.	with strong oxi	dizers, excessive heat, sparks or
10.5 Incompatible materials Materials to avoid	: Material may	be softened by	some hydrocarbons.
10.6 Hazardous decomposition p	roducts		
Hazardous decomposition products Thermal decomposition	: Note: Carbon	monoxide, olefi	under normal conditions. nic and paraffinic compounds, ds, ketones, aldehydes and
11. Toxicological information			
11.1 Information on toxicological	effects		
Acute toxicity			
Acute oral toxicity	: Not classified		
Acute inhalation toxicity	: Not classified		
Acute dermal toxicity	: Not classified		
Skin corrosion/irritation	: Not a skin irrit	ant.	
	10	/ 17	

	(+) 18816996168 Ponciplastics.com	
SAFETY DATA SHEET according to Regulation (EC) No. 1		lyondellbasell
Lucalen A2700P		Gen. Variant: SDS_AT
Version 1.4 Revision Date	e 04/15/2020 Print Date 01	/05/2022 SDS No.: BE3323
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possib	ble.
Respiratory or skin sensitization	: Not classified	
Chronic toxicity		
Carcinogenicity	: Not classified	
Germ cell mutagenicity	: Not classified	
Reproductive toxicity		
Effects on fertility / Effects on or via lactation	: Not classified	
Effects on Development	: Not classified	
Target Organ Systemic Toxic	cant - Single exposure	
	: The substance or mixture is norgan toxicant, single exposu	not classified as specific target ire.
Target Organ Systemic Toxic	cant - Repeated exposure	
	: The substance or mixture is norgan toxicant, repeated expo	
Aspiration hazard	: Not applicable.	
12. Ecological information		
12.1 Ecotoxicology Assessment		
	11 / 17	

	(+) 18816996168 Ponciplastics.com	
SAFETY DATA SHEET	Ponciplastics.com	
according to Regulation (EC) No. 190	07/2006	lyondellbasell
Lucalen A2700P		Gen. Variant: SDS_AT
Version 1.4 Revision Date 0	04/15/2020 Print Date 01	1/05/2022 SDS No.: BE3323
Short-term (acute) aquatic :	Not classified	
hazard Long-term (chronic)	Not classified	
aquatic hazard		
12.2 Paraistance and degradability		
12.2 Persistence and degradability		
Biodegradability	Not expected to be biodegrad	dable.
12.3 Bioaccumulative potential		
Bioaccumulation	This material is not expected	I to bioaccumulate.
12.4 Mobility in soil		
Mobility	no data available	
12.5 Results of PBT and vPvB asse	ssment	
Result		ains no components considered cumulative and toxic (PBT) or accumulative (vPvB).
12.6 Other adverse effects		
Environmental fate and spathways	This material is not volatile a	nd insoluble in water.
12.7 Other information		
Additional ecological	Ecotoxicity is expected to be solubility of polymers.	minimal based on the low water
		duct. However, birds, fish and
	intestinal tracts.	which may obstruct their
	12 / 17	

		(+) 18816	5996168	
		(+) 18816 Ponciplas	tics.com	
-	ATA SHEET egulation (EC) No. 190	7/2006		lyondellbasell
	U ()	772000		Gen. Variant: SDS_AT
Lucalen A	Revision Date 04	4/15/2020	Print Date 01	
	Revision Date of	4/15/2020 r		103/2022 3D3 No BE3323
13. Disposal c	onsiderations			
13.1 Waste tre	atment methods			
Product	:	transported and applicable laws a	disposed of and regulatio tices. Recla	d be packaged, labeled, or reclaimed in conformance with ons and in conformance with good im where possible.
14. Transport i	information			
Not regulated for	or transport			
15. Regulatory	information			
15.1 Safety, he	ealth and environment	tal regulations/le	gislation sp	pecific for the substance or mixture
registered i	ct has been purchased n the European Union,	we confirm that the	ne chemical	ondellBasell group of companies substance in this product has been orth in REACh. (Regulation (EU) No.
Other inte	rnational regulations			
	S.	·	-	chemical inventory requirements or
	*Additional Explanator	y Status Stateme	nts follow the	e table, as necessary.
	Country/Region	Invento		atus Description
	Australia Canada	AICS DSL		mpliant mpliant
	China	IECSC		mpliant
		13 / 1	7	
		1371	1	



according to Regulation (EC) No. 1907/2006

Revision Date 04/15/2020

Lucalen A2700P

Version 1.4

Print Date 01/05/2022

SDS No.: BE3323

lyondellbasell

Gen. Variant: SDS AT

Europe	REACH	See REACH Compliance Statement	
Japan	ENCS	Compliant	
Korea	KECI	Compliant	
New Zealand	NZIoC	Compliant	
Philippines	PICCS	Compliant	
United States of America	TSCA	Compliant	
Taiwan	TCSCA	Compliant	

Contact product.safety@lyb.com for additional global inventory information.

15.2 Chemical safety assessment

No information available.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 Abbreviations and Acronyms

ACGIH - American Conference of Governmental Industrial Hygienists

ACGIH_BEIs - American Conference of Governmental Industrial Hygienists_Biological Exposure Indices

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road AICS - Australian Inventory of Chemical Substances

ASTM - American Society for Testing and Materials

BEL - Biological Exposure Limits

BTEX - Benzene, Toluene, Ethylbenzene, Xylenes

CAS - Chemical Abstracts Service

CEFIC - European Chemical Industry Council CLP - Classification Packaging and Labelling

COC - Cleveland Open-Cup

CS - Consumer Scenario

DIN - Deutsches Institut für Normung

DN(M)EL - Derived No (Minimal) Effect Level

DSL - Canada Domestic Substance List

EC - European Commission

EC50 - Median Effective Concentration

ECETOC - European Center on Ecotoxicology and Toxicology of Chemicals

ECHA - European Chemicals Agency

EL50 - Effective Loading fifty



according to Regulation (EC) No. 1907/2006

Revision Date 04/15/2020

Lucalen A2700P

Version 1.4

Print Date 01/05/2022

SDS No.: BE3323

lvondellbasell

Gen. Variant: SDS_AT

ELINCS - EHR-Lab Interoperability and Connectivity Specification ENCS - Japanese Existing and New Chemical Substances Inventory ERC - Environmental Release Category EUSES - European Union System for the Evaluation of Substances EWC - European Waste Code GHS - Globally Harmonized System of Classification and Labelling of Ch IARC - International Agency for Research on Cancer IATA - International Air Transport Association IC50 - Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG - International Maritime Dangerous Goods IECSC - Chinese Chemicals Inventory **IOELV - Indicative Occupational Exposure Limit Values** IP346 - Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables **KECI - Korea Existing Chemicals Inventory** Koc - Organic Carbon/Water Partition Coefficient LC50 - Lethal Concentration fifty LD50 - Lethal Dose fifty per cent. LL/EL/IL - Lethal Loading/Effective Loading/Inhibitory Loading LL50 - Lethal Loading fifty MAK Commission - Permanent Senate Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area MARPOL - International Convention for the Prevention of Pollution from Ships No. - Number NOEC/NOEL - No Observed Effect Concentration / No Observed Effect Level NZIoC - New Zealand Inventory of Chemicals OE HPV - Occupational Exposure - High Production Volume OECD - Organization for Economic Co-operation and Development **OEL - Occupational Exposure Limit** PBT - Persistent, Bio accumulative and Toxic PICCS - Philippine Inventory of Chemicals and Chemical Substances PNEC - Predicted No Effect Concentration PPE - Personal Protective Equipment PROC - Process Category QSAR - Quantitative Structure-Activity Relationship REACh - Registration Evaluation and Authorization of Chemicals RID - Regulations Relating to International Carriage of Dangerous Goods by Rail SDS - Safety Data Sheet SKIN_DES - Skin Designation STEL - Short term exposure limit STP - Standard Temperature and Pressure TCSCA - Taiwan inventory of chemicals TGD - Technical Guidance Document TRA - Targeted Risk Assessment TSCA - US Toxic Substances Control Act TWA - Time-Weighted Average

(+) **18816996168** Ponciplastics.com

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006

Lucalen A2700P

Version 1.4

Print Date 01/05/2022

SDS No.: BE3323

lvondellbasel

Gen. Variant: SDS AT

UN - United Nations vPvB - very Persistent and very Bioaccumulative WGK - German Water Endangerment Class

Revision Date 04/15/2020

Disclaimer

Multiple legal entities and registration numbers may be displayed in Section 1. The Recipient shall refer to the shipping documents to identify the legal entity that supplied this product.

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet

(+) 18816996168		
Ponciplastics.com		

according to Regulation (EC) No. 1907/2006

Lucalen A2700P

Version 1.4

Revision Date 04/15/2020 Pr

Print Date 01/05/2022

SDS No.: BE3323

Gen. Variant: SDS_AT