	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	
	lyondellbasell	
Petrothene NA960070	Gen. Variant: SDS_US_GHS	
Version 1.2 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE1807	
1. IDENTIFICATION OF THE SUBS	TANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING	
Trade name CAS Number:	: Petrothene NA960070 : 9002-88-4	
Chemical characterization	: Polyethylene Homopolymer	
Chemical name Synonyms	: Polyethylene : Ethene, homopolymer, PE	
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.	
Prohibited uses	 FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications 	
<u>Company Address</u> Equistar Chemicals, LP LyondellBasell Tower, Suite 30 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583	Customer Service 888 777-0232 0 product.safety@lyb.com	
Emergency telephone number EQUISTAR 800-245-4532	<u>er</u>	
E-mail address Responsible/issuing person	: product.safety@lyb.com	
2. HAZARDS IDENTIFICATION		
GHS Classification		
Combustible dust		
Label elements		
Signal word	: Warning	
Hazard Statements	: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.	
Other hazards		
	1 / 13	

	(+)18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell
Petrothene NA960070Version 1.2Revision Date	10/01/2019 Print Date 01/0	Gen. Variant: SDS_US_GHS 5/2022 SDS No.: BE1807
No additional information av		
Mixtures Components		
Chemical name	CAS-No.	Weight %
Polyethylene	9002-88-4	98.0 - 100.0 %
Contains: Additives and stabili 4. FIRST AID MEASURES	zers	
General advice	: Take proper precautions to before attempting rescue ar	ensure your own health and safety nd providing first aid.
If inhaled	medical attention. In case of excessive inhalat	If signs/symptoms continue, get ion of fumes that may be generated ial, move the person to fresh air. ssary give Cardio-Pulmonary
In case of skin contact	large amounts of water to co Do not attempt to peel polyr skin.	he skin, immediately flush with ool the affected tissue and polymer. mer from skin as this will remove the cy medical attention if burn is deep
In case of eye contact	: Flush eyes thoroughly with medical attention if discomformed	water for several minutes and seek ort persists.
	minutes.	ith cool running water for at least 15 attempt to remove the material
If swallowed	: Adverse health effects due	to ingestion are not anticipated.
	2 / 13	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com yondelbase Gen. Variant: SDS_US_GHS
Petrothene NA960070 Version 1.2 Revision Date 1	
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
. FIRE-FIGHTING MEASURES Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	: Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as:
	Carbon monoxide, carbon dioxide and unburned hydrocarbor (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after the storage container even after even after the storage container even after even after
	fire is out.
	0710

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	lyondellbasel
Petrothene NA960070	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE180
. ACCIDENTAL RELEASE MEAS	SURES
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth
Environmental precautions	surfaces. : Do not flush into surface water or sanitary sewer system.
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
7. Handling and storage Precautions for safe handlin Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion
	hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.
	4 / 13

SAFETY DATA SHEET	(+) 18816996168 Ponciplastics.com
Petrothene NA960070 Version 1.2 Revision Date	Gen. Variant: SDS_US_GHS
	e 10/01/2019 Phili Date 01/05/2022 SDS No DE 1807
	Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
Fire-fighting class	: Polymer will burn but does not easily ignite.
Conditions for safe storage	, including any incompatibilities
Requirements for storage areas and containers	 Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge.
Specific end use(s)	: See Section 1.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

CAS-No.	Туре	Limit Value	Basis	Additional
			Revision Date	Information
	TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
	CAS-No.		TWA 10 mg/m3	TWA 10 mg/m3 US (ACGIH)

(+) **18816996168**

Ponciplastics.com

SAFETY	DATA	SHEET	

Petrothene NA960070 Revision Date 10/01/2019

Version 1.2

Print Date 01/05/2022

Gen. Variant: SDS US GHS SDS No.: BE1807

Iyondellbasel 111

Materials that can	TWA	3 mg/m3	US (ACGIH)	
be formed when		respirable	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust Materials that can	TWA	15 mg/m3	US (OSHA)	
be formed when		total dust	2005	
handling this		total dust	2000	
product: Non-				
specified (inert or				
nuisance) dust				
Materials that can	TWA	5 mg/m3	US (OSHA)	
be formed when		respirable	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust				

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators. 	
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.	
Eye and face protection	: Dust service goggles should be worn to prevent mechanical	
	6 / 13	

(+) 18816996168

	(+) 18810990108	
SAFETY DATA SHEET	Ponciplastics.com	
		lyondellbase
Petrothene NA960070		Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	10/01/2019 Print Date (01/05/2022 SDS No.: BE18
	injury or other irritation to may result from handling	eyes due to airborne particles which this product.
Skin and body protection	: Wear suitable protective	clothing.
Hygiene measures	be based on an evaluation of the protective equipmed performed, conditions printer hazards and/or potential during use. Use good personal hygie Wash hands before eating facilities.	personal protective equipment should on of the performance characteristics ent relative to the task(s) to be esent, duration of use, and the hazards that may be encountered one practices. ng, drinking, smoking, or using toilet lothing and wash before reuse.
Appearance	: Pellets.	
Color	: Translucent to white	
Odor	: Slight.	
Odor Threshold	: No value available.	
Flash point	: No Data Available.	
Lower explosion limit		
	varies according to parti	concentration (MEC) for polymer dus cle size distribution.
Upper explosion limit	varies according to part	
Upper explosion limit Flammability (solid, gas)	0.1	cle size distribution.
	: Not applicable.	cle size distribution. es not easily ignite.
Flammability (solid, gas)	: Not applicable. : Polymer will burn but do	cle size distribution. es not easily ignite.
Flammability (solid, gas) Oxidizing properties	Not applicable.Polymer will burn but doNot considered an oxidi	cle size distribution. es not easily ignite.
Flammability (solid, gas) Oxidizing properties Autoignition temperature	 Not applicable. Polymer will burn but do Not considered an oxidi > 300 °C 	cle size distribution. es not easily ignite.
Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	 Not applicable. Polymer will burn but do Not considered an oxidi > 300 °C not determined 	cle size distribution. es not easily ignite.
Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range	 Not applicable. Polymer will burn but do Not considered an oxidi > 300 °C not determined 50 - 170 °C 	cle size distribution. es not easily ignite.
Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range Boiling point/boiling range	 Not applicable. Polymer will burn but do Not considered an oxidi > 300 °C not determined 50 - 170 °C Not applicable. 	cle size distribution. es not easily ignite.

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Petrothene NA960070 Version 1.2 Revision Date	
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
0. STABILITY AND REACTIVITY	,
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition	: Not expected to decompose under normal conditions.
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
1. TOXICOLOGICAL INFORMAT	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 13

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SAFEIT DATA SHEET	lyondellbasell
Petrothene NA960070	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE1807
Respiratory or skin sensitization	: Not classified
Chronic toxicity	
Carcinogenicity	: Not classified
	Not classified Not listed by IARC, NTP, OSHA or EPA.
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility / Effects on or via lactation	: Not classified
Effects on Development	: Not classified
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	: Not applicable.
12. Ecological information	
Ecotoxicology Assessment	
Short-term (acute) aquatic hazard	: Not classified
Long-term (chronic) aquatic hazard	: Not classified
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
	9 / 13
l	

	(+) 18816996168				
SAFETY DATA SHEET	Ponciplastics.com				
	lyondellbasell				
Petrothene NA960070Gen. Variant: SDS_US_GHSVersion 1.2Revision Date 10/01/2019Print Date 01/05/2022SDS No.: BE1807					
Version 1.2 Revision Date	10/01/2019 Print Date 01/05/2022 SDS No.: BE1807				
Bioaccumulative potential					
Bioaccumulation	: This material is not expected to bioaccumulate.				
Mobility in soil					
Mobility	: no data available				
Other adverse effects					
Environmental fate and pathways	: This material is not volatile and insoluble in water.				
Other information					
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts. 				
13. Disposal considerations Waste treatment methods Product 14. TRANSPORT INFORMATION	 All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible. This material is classified as a Non-hazardous Material by RCRA. 				
Not regulated for transport					
	10 / 13				

1.1	-	0	0.		0	0	0	-	0	~
(+)	1	Q	0	16	a	a	6	1	6	Q
		0	0	ιυ	J	J	υ		υ	О

Ponciplastics.com

SAFETY DATA SHEET

Petrothene NA960070

Version 1.2

Revision Date 10/01/2019

Print Date 01/05/2022

.... Gen. Variant: SDS US GHS

Ivondellbase

SDS No.: BE1807

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act. However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains no known chemicals regulated by New Jersey's Worker and Community Right to

Know Act.

No components are subject to the Massachusetts Right to Know Act.

This product contains no known chemicals regulated by Pennsylvania's Right to Know Act.

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

ntry/Region	Inventory	Status Description
tralia	AICS	Compliant
	11 / 1	3

		(+) 1881699	96168		
0455		Ponciplasti	cs. com		
SAFE	TY DATA SHEET			lyondellbasell	
Petro	othene NA960070			Gen. Variant: SDS_US_GHS	
Versior	n 1.2 Revision Date 10	0/01/2019 Pri	nt Date 0	1/05/2022 SDS No.: BE1807	
	Canada	DSL	Complia		
	China				
	Europe	REACH ENCS		ACH Compliance Statement	
	Japan Korea	KECI	Complia Complia		
	New Zealand	NZIOC	Complia		
	Philippines	PICCS	Complia		
	United States of America	TSCA	Complia		
	Taiwan	TCSCA	Complia	ant	
registere 1907/20 Contact	ed in the European Union, we ed under REACh, in accordan	confirm that all su ce with the deadlir	bstances nes set fo	ndellBasell group of companies is in this preparation have been orth in REACh. (Regulation (EU) No.	
	aterial safety datasheet secti wised Section(s): 15 16	ions which have	been up	dated:	
шм	IIS Classification	Health Hazard: 0			
		Flammability: 1 Physical hazards:	0	0 1 0	
NF	PA Classification :	Health Hazard: 0 Fire Hazard: 1 Instability: 0		0 0	
	rther information				
	/IS rating scale (0 = minimal h PA rating scale (0 = minimal l		,		
		12 / 13			

	(+)18816996168					
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell				
Petrothene NA960070 Gen. Variant: SDS_US_GHS						
Version 1.2 Revision Date 10/01/2019 Print Date 01/05/2022 SDS No.: BE1807						
	Disclaimer					
Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.						
In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.						
<u>Numerical Data Presentation</u> The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.						
Language Translations The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.						
End of Material Safety Data Sheet						
	13 / 13					