	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SALET DATA SHEET	<u> と タ の 和 明 根 系 Iyondellbasell 18816996168</u>
Adstif EA648P	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Dat	e 10/01/2019 Print Date 01/04/2022 SDS No.: BE6704
1. IDENTIFICATION OF THE SU	BSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name CAS Number:	: Adstif EA648P : 9010-79-1
Chemical characterization	: Polypropylene copolymer
Chemical name	: 1-Propene, Polymer with Ethene
Synonyms	: Ethylene-Propylene copolymer, 1-Propene-Ethylene- Copolymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	 FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications
Company Address Equistar Chemicals, LP LyondellBasell Tower, Suite 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583	
Emergency telephone num EQUISTAR 800-245-4532	<u>iber</u>
E-mail address Responsible/issuing person	: product.safety@lyb.com
2. HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
	1 / 13

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com ESDATINHK系 18816996168 Convining CDC US
Adstif EA648P Version 1.1 Revision Date	Gen. Variant: SDS_US_GHS te 10/01/2019 Print Date 01/04/2022 SDS No.: BE6704
Other hazards No additional information	available.
. COMPOSITION/INFORMATIO	N ON INGREDIENTS
lixtures Components	
Chemical name	CAS-No. <u>Weight %</u>
1-Propene, Polymer with Ethe	ene 9010-79-1 98.0 - 100.0 %
. FIRST AID MEASURES	
General advice	: Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.
If inhaled	 Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)
In case of skin contact	 If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive.
In case of eye contact	: Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists.
	 In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.
If swallowed	: Adverse health effects due to ingestion are not anticipated.

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics. com 文夕风行明状系 18816996168
Adstif EA648P	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	10/01/2019 Print Date 01/04/2022 SDS No.: BE670
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient.
FIRE-FIGHTING MEASURES Suitable extinguishing media	 SMALL FIRE: Use dry chemical, CO2, or water spray. LARGE FIRES:
Unsuitable extinguishing	Use water spray hose nozzles from a safe location. : None known.
media Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
	3 / 13

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	と少の作用状 系 18816996168
Adstif EA648P	Gen. Variant: SDS_US_GHS
	te 10/01/2019 Print Date 01/04/2022 SDS No.: BE67
ACCIDENTAL RELEASE MEA	ASURES
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth aurfacea
Environmental precautions	surfaces. : Do not flush into surface water or sanitary sewer system.
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
Handling and storage	
Precautions for safe handl	ing
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard.
	Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion
	Electrostatic charge may build during conveying or handling.
	4 / 13

<section-header><section-header></section-header></section-header>			(+) 188	16996168		
Additional content in the second control of the second conterol of the second control of the second c	SAFETY DATA S	HEET				
Adstif EA648P Gen. Variant: SDS_US_GHS Version 1.1 Revision Date 10/01/2019 Print Date 01/04/202 SDS No.: BE67 Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers: Involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing. Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities : Store in a dry location. areas and containers : Store in a dry location. Store away from stores enclosures and adequate ventilation. Store away form screess inclosures and adway from storage oridizing agents. Keep contract cost of a sovid excessive dust accumulation. Store away from screess in closures and adway from storage oridizing agents. Requirements for storage : Store in a dry location. areas and containers : Store in a dry location. <			18	夕 <u>凤竹明</u> 坂 81699616	iyonae	elidasei
Version 1.1 Revision Date 10/01/2019 Print Date 01/04/2022 SDS No.: BE67 Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded (earthed) and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When Dringing the material to processing temperatures vapors may develop may condence in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities : Store in a dry location. areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store awary from stores and adequate ventilation should be control parameters Specific end use(s) : See Section 1. : See Section 1. : See Section 1.	Adstif EA648P					SDS_US_GHS
grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Processive heat and away from strong oxidizing agents. Keep container closed to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. : See Section 1. Components CAS-No. Type Limit Value Basis Materials that can be formed when be of med when be of		vision Date 10	/01/2019	Print Date 01/0	04/2022 5	SDS No.: BE670
grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing. Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage : Store in a dry location. use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. :						
grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage : Store in a dry location. areas and containers : Store in a dry location. use good housekeeping practices during storage, transferring aform excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. components CAS-No. Type Limit Value Basis Additional Information Materials that can be formed when handling this product: Non-specific (inert or nuisance) dust TWA 10 mg/m3 US (ACGIH) Materials that can be formed when handling this produ			Equipment	handling polyme	er should be conduc	ctive and
should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handing combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage : Requirements for storage : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. : Specific end use(s) : See Section 1. components CAS-No. Type Limit Value Basis Additional Information formation produce the prevent with produce control parameters Occupational Exposure Limits TWA 10 mg/m3 US (ACGIH) <tr< td=""><td></td><td></td><td>grounded</td><td>(earthed) and bor</td><td>nded.</td><td></td></tr<>			grounded	(earthed) and bor	nded.	
codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION Components CAS-No. Naterials that can be formed when handling this product. Non-specific (net or produce on the store) and information inhalable and profile approximation inhalable and profil			should be	grounded and bo	nded.	
After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manulacturing. Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. ExPOSURE CONTROLS/PERSONAL PROTECTION Activational Exposure Limits Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust			codes and	regulatory requir		
When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Processive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : : See Section 1. : See Section 1. : See Section 1. : See Section 1.					hands thoroughly	with soap and
may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. Components CAS-No. Type Limit Value Basis Additional Information Materials that can be formed when handling this product: Non-specified (net or specified (net				aina the material	to processing temp	peratures vapors
Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities : Store in a dry location. areas and containers : Store in a dry location. ureas and containers : Store in a dry location. use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. c. EXPOSURE CONTROLS/PERSONAL PROTECTION Control parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Information be formed when handling this product: Non-specified (inert or nuisance) dust 			may develo	op may condense		
Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION Control parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional information Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust TWA 10 mg/m3 US (ACGIH) 2005			Refer to N	FPA 654, Standa		
Conditions for safe storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. Control parameters : See Section 1. Ingredients with workplace control parameters : Secupational Exposure Limits Components CAS-No. Type Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust TWA 10 mg/m3 US (ACGIH) : Source of the product in the parameter of the product in the parameter of the param			•		-	-
Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION Control parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Information inhalable Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust TWA 10 mg/m3 US (ACGIH) 2005	Fire-fighting class	:	Polymer w	ill burn but does	not easily ignite.	
areas and containers Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION control parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. TWA 10 mg/m3 US (ACGIH) and Information and Informat	Conditions for sat	fe storage, in	cluding any	v incompatibilitie	es	
and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. Control parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Information Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust	•	-			actices during stora	nce transferring
Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. Store away from excessive heat and away from strong oxidizing agents. Take measures to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. Store away from excession of the build up of electrostatic charge. Specific end use(s) : See Section 1. Store away from excession of the build up of electrostatic charge. Specific end use(s) : See Section 1. Store away from excession of the build up of electrostatic charge. Specific end use(s) : See Section 1. Store away from excession of the build up of electrostatic charge. Specific end use(s) : See Section 1. Store away from excession of the build up of electrostatic charge. Specific end use (s) : See Section 1. Store away from excession of the build up of electrostatic charge. : See Section 1. Specific end use (s) : Type : Limit Value Basis Additional Information Materials that can be formed when handling this product: Non- specified (inert or ruisance) dust : TWA 10 mg/m3 i			and handli	ng. Process encl	osures and adequa	te ventilation
Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1. Section 1. Section 1. Control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Information Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust TWA 10 mg/m3 US (ACGIH) 2005 Image: Colspan="2">Colspan="2">Colspan="2">Costic Colspan="2">Costic Colspan= 2" Costic Colspan="2">Costic Colspan="2" Costic Colspan="2" Costic Colspan="2" Costic Colspan="2" Costic Colspan="2" Costic Colspan="2" Costic Colspan="2" Costic Colspan="2" Costic Colspan="2" Costic Colspan="2"			Store away	y from excessive		
Specific end use(s) : See Section 1. • EXPOSURE CONTROLS/PERSONAL PROTECTION Control parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Information Materials that can TWA 10 mg/m3 US (ACGIH) be formed when Information Inhalable 2005 Information handling this India inhalable 2005 Information			Keep cont	ainer closed to pr		
: See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION control parameters Ingredients with workplace control parameters Occupational Exposure Limits <u>Components</u> <u>CAS-No.</u> <u>Type</u> <u>Limit Value</u> <u>Basis</u> <u>Additional</u> <u>Materials that can</u> <u>be formed when</u> <u>handling this</u> <u>product: Non-</u> <u>specified (inert or</u> <u>nusance) dust</u>	Specific and use/	c)		·		, C
EXPOSURE CONTROLS/PERSONAL PROTECTION control parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Revision Date Information Materials that can TWA 10 mg/m3 US (ACGIH) be formed when TWA 10 mg/m3 US (ACGIH) handling this Inhalable 2005 product: Non- US (ACGIH) 2005 specified (inert or nuisance) dust US (ACGIH) 2005	Specific end use(s		See Section	n 1		
Control parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust TWA 10 mg/m3 US (ACGIH) Output						
Control parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust TWA 10 mg/m3 inhalable US (ACGIH) 2005 Image: Colspan="4">CAS-No.						
Control parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust TWA 10 mg/m3 inhalable US (ACGIH) 2005 Image: Colspan="4">CAS-No.						
Ingredients with workplace control parametersOccupational Exposure LimitsComponentsCAS-No.TypeLimit ValueBasis Revision DateAdditional InformationMaterials that can be formed when handling this product: Non- specified (inert or nuisance) dustTWA10 mg/m3 InhalableUS (ACGIH) 2005US (ACGIH) 2005	. EXPOSURE CONTR	OLS/PERSON	AL PROTE	CTION		
Components CAS-No. Type Limit Value Basis Revision Date Additional Information Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust TWA 10 mg/m3 inhalable US (ACGIH) 2005 JUS (ACGIH) 2005	ontrol parameters					
ComponentsCAS-No.TypeLimit ValueBasis Revision DateAdditional InformationMaterials that can be formed when handling this product: Non- specified (inert or nuisance) dustTWA10 mg/m3 inhalableUS (ACGIH) 2005	Ingredients with v	workplace cor	ntrol param	eters		
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dustTWA10 mg/m3 inhalableUS (ACGIH) 2005	Occupational Exp	osure Limits				
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dustTWA10 mg/m3 inhalableUS (ACGIH) 2005	Components	CAS-No.	Туре	Limit Value		
handling this product: Non- specified (inert or nuisance) dust			TWA		US (ACGIH)	
specified (inert or nuisance) dust	handling this				2003	
5 / 13						
			5	/ 13		

SAFETY DATA SHEE	T 18	astics.com 夕风竹用水 81699616	s lyond	ellbase
Adstif EA648P			Gen. Variant	: SDS_US_GHS
Version 1.1 Revision	n Date 10/01/2019	Print Date 01/0)4/2022	SDS No.: BE67
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment


Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

AFETY DATA SHEET	Ponciplastics.com
	シック作用状系 18816996168 」
Adstif EA648P	Gen. Variant: SDS_US_GHS
ersion 1.1 Revision Date	e 10/01/2019 Print Date 01/04/2022 SDS No.: BE67
	injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
PHYSICAL AND CHEMICAL P Appearance Color	: Pellets.
	: Translucent to white
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: <1 g/cm3
Water solubility	: Insoluble.
	7 / 13

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics. com 文学页和印刷茶系 18816996168
Adstif EA648P	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	e 10/01/2019 Print Date 01/04/2022 SDS No.: BE670
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
0. STABILITY AND REACTIVITY	,
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition	: Not expected to decompose under normal conditions.
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
1. TOXICOLOGICAL INFORMAT	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 13

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics. com 文夕风行用状系 18816996168
Adstif EA648P	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	10/01/2019 Print Date 01/04/2022 SDS No.: BE670
Respiratory or skin sensitization Chronic toxicity	: Not classified
Carcinogenicity	: Not classified
	Not listed by IARC, NTP, OSHA or EPA.
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility / Effects on or via lactation	: Not classified
Effects on Development	: Not classified
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	: Not applicable.
12. Ecological information	
Ecotoxicology Assessment	
Short-term (acute) aquatic hazard	: Not classified
Long-term (chronic) aquatic hazard	: Not classified
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
	9 / 13

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	シタの作用状系 18816996168 IVONDEIIbasell
Adstif EA648P Version 1.1 Revision Date	Gen. Variant: SDS_US_GHS 10/01/2019 Print Date 01/04/2022 SDS No.: BE6704
Version 1.1 Revision Date	10/01/2019 Plint Date 01/04/2022 SDS No BE0/04
Bioaccumulative potential	
Bioaccumulation	: This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	: no data available
Other adverse effects	
Environmental fate and pathways	: This material is not volatile and insoluble in water.
Other information	
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations Waste treatment methods Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with
	applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	: This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
Not regulated for transport	
15. REGULATORY INFORMATION	
	10 / 13



TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

14807-96-6 Talc, Magnesium Silicate

No components are subject to the Massachusetts Right to Know Act.

This product contains no known chemicals regulated by Pennsylvania's Right to Know Act.

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description	
Australia	AICS	Compliant	
Canada	DSL	Compliant	
China	IECSC	Compliant	
	11 / 1	3	

	(+) 188169	96168	
SAFETY DATA SHEET	Ponciplast		
	エクリ	<u>大学员和开展</u> 关系 18816996168	
	1001	0990100	Gen. Variant: SDS_US_GHS
Adstif EA648P	Data 40/01/2010	int Data 01/01/2	
Version 1.1 Revision	Date 10/01/2019 P	rint Date 01/04/20	022 SDS No.: BE670
I —			
Europe	ENCS		Compliance Statement
Japan Korea	KECI	Compliant Compliant	
New Zealand	NZIOC	Compliant	
Philippines	PICCS	Compliant	
United States of Ame	erica TSCA	Compliant	
Taiwan	TCSCA	Compliant	
the product has been purcha egistered in the European Uni egistered under REACh, in ac 907/2006) ontact product.safety@lyb.co	on, we confirm that all s cordance with the dead	ubstances in this ines set forth in I	s preparation have been REACh. (Regulation (EU) No.
6. OTHER INFORMATION Material safety datashed Revised Section(s): 15		e been updated:	
Material safety datashee)	0 1 0
Revised Section(s): 15	16 : Health Hazard: (Flammability: 1	: 0	
Material safety datashed Revised Section(s): 15 4 HMIS Classification NFPA Classification	 Health Hazard: (Flammability: 1 Physical hazards Health Hazard: (Fire Hazard: 1 Instability: 0) : 0	0 1 0
Material safety datashed Revised Section(s): 15 4 HMIS Classification NFPA Classification	 Health Hazard: (Flammability: 1 Physical hazards Health Hazard: (Fire Hazard: 1 Instability: 0 	: 0)	0 1 0
Material safety datashed Revised Section(s): 15 4 HMIS Classification NFPA Classification Further information HMIS rating scale (0 = mi	 Health Hazard: (Flammability: 1 Physical hazards) Health Hazard: (Fire Hazard: 1 Instability: 0 	e hazard) e hazard)	0 1 0
Material safety datashed Revised Section(s): 15 4 HMIS Classification NFPA Classification Further information HMIS rating scale (0 = mi	 Health Hazard: (Flammability: 1 Physical hazards Health Hazard: (Fire Hazard: 1 Instability: 0 	e hazard) e hazard)	0 1 0

	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics. com 文学员科明教系 18816996168			
Adstif EA648P	Gen. Variant: SDS_US_GHS			
Version 1.1 Revision Date 10	0/01/2019 Print Date 01/04/2022 SDS No.: BE6704			
Disclaimer				
The document is designed to pr processing, storage, transportat or quality specification, either ex	accurate to the best of our knowledge at the date of publication. rovide users general information for safe handling, use, ion, disposal and release and does not constitute any warranty xpress or implied, including any warranty of merchantability or e. Users shall determine whether the product is suitable for y and legally.			
further prohibit or restrict the sa information, please contact a Ly at: https://www.lyondellbasell.co	f use specifically noted in this document, LyondellBasell may le of its products into certain applications. For further rondellBasell representative or visit the LyondellBasell website om/en/products-technology/product-safety-stewardship/ section 1 is a trademark owned or used by the LyondellBasell			
toxicological values, is expresse	lata, such as that used for physical and chemical properties and ed using a comma (,) to separate digits into groups of three and ser. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.			
LyondellBasell believes to be r effort to verify the accuracy of t	this document has been translated from English by a vendor reliable. LyondellBasell and its vendor have made a good-faith the translation, but assume no liability or other responsibility for rred. Please refer to our web site (www.lyondellbasell.com) for English.			
End	of Material Safety Data Sheet			