	(+) 18816996168
	Ponciplastics.com
SAFETY DATA SHEET	lyondellbasel
Dexflex 992 NH696 BL	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	
I. IDENTIFICATION OF THE SUB	STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name	: Dexflex 992 NH696 BLK
CAS Number: Chemical name	: Mixture : Compounded polyolefin
Synonyms	: Polyolefin, Compounded polymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical
	devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body;
	Life-sustaining medical applications
	Commonse Talanhana
<u>Company Address</u> Equistar Chemicals, LP	<u>Company Telephone</u> Customer Service 888 777-0232
LyondellBasell Tower, Suite 3	
1221 McKinney St.	
P.O. Box 2583 Houston Texas 77252-2583	
Emergency telephone num	ber
EQUISTAR 800-245-4532	
E-mail address	: product.safety@lyb.com
Responsible/issuing person	
. HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing,
	handling or by other means, may form combustible dust concentrations in air.
Other hazards	
	1 / 13

	(+) 18816996168				
SAFETY DATA SHEET	Ponciplastics.com	lvoodollbacoll			
		lyondellbasell			
Dexflex 992 NH696 BLK	Dexflex 992 NH696 BLK Gen. Variant: SDS_US_GHS				
Version 1.2 Revision Date 10	0/01/2019 Print Date 01/06	5/2022 SDS No.: BE6638			
No additional information avai	lable.				
3. COMPOSITION/INFORMATION O	N INGREDIENTS				
Mixtures					
Components					
Chemical name	CAS-No.	<u>Weight %</u>			
Proprietary blend of polyolefinic polymers	Mixture	95.0 - 100.0 %			
Contains: Additives and stabilize	ers				
4. FIRST AID MEASURES					
General advice	· Take proper precautions to	ensure your own health and safety			
General advice	before attempting rescue an				
If inhaled	medical attention.	If signs/symptoms continue, get			
		on of fumes that may be generated al, move the person to fresh air.			
	Obtain medical attention. Keep person warm, if neces	sary give Cardio-Pulmonary			
	Resuscitation (CPR)				
In case of skin contact	: If molten material contacts th	ne skin, immediately flush with			
		ool the affected tissue and polymer. her from skin as this will remove the			
	skin. Obtain immediate emergenc	y medical attention if burn is deep			
	or extensive.	,			
In case of eye contact	: Flush eves thoroughly with v	water for several minutes and seek			
	medical attention if discomfo				
	: In case of eye contact with r	nolten polymer: th cool running water for at least 15			
	minutes.	ttempt to remove the material			
	adherent to the eye(s).				
	Immediately seek medical a	uenuon.			
If swallowed	Adverse health effects due t	o ingestion are not anticipated.			
	2 / 13				

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	lyondellbase
Dexflex 992 NH696 BL	
Version 1.2 Revision Date	10/01/2019 Print Date 01/06/2022 SDS No.: BE663
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient.
. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as:
	Carbon monoxide, carbon dioxide and unburned hydrocarbon (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	: Combustible particulate solid, will decompose under fire conditions.
	Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate
	flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage
	container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire.
	Cool storage containers with large volumes of water even after fire is out.
	3 / 13

SAFETY DATA SHEET Gen. Variant: SDS_US_O Dexflex 992 NH696 BLK Gen. Variant: SDS_US_O Version 1.2 Revision Date 10/01/2019 Print Date 01/06/2022 SDS No.: BE ACCIDENTAL RELEASE MEASURES Personal precautions : Equip mergency responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid generating dust. Avoid generating dust. Avoid generating dust. Avoid generating dust. Novide generating dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system. On water, material is insoluble; collect and containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and containes any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with g engineering practices. Reclaim where possible. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handing, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation is neclosed space. Use dust collection systems designed per NFPA 654 to ax dust accumulation. Avoid dust accumulation is neclosed space. Use dust collection systems designed per NFPA 654 to ax dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Avoid dust accumulation is not ner of an iar and in the presence of an ignition source is a potential dust explosion hazard.		(+) 18816996168 Ponciplastics.com
ACCIDENTAL RELEASE MEASURES Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid generating dust. Avoid generating dust. Avoid generating dust. Avoid generating dust. Avoid generating dust. Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system. Methods for containment / Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or conformance with g engineering practices. Reclaim where possible. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handing, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation. Avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high c environments may ignite the dust and result in a dust explosion. Electrostatic charge may build during conveying or handling equipment handling polymer should be conductive and	SAFETY DATA SHEET	lyondellbase
ACCIDENTAL RELEASE MEASURES Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system. Methods for containment / Methods for cleaning up ' On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with g engineering practices. Reclaim where possible. Handling and storage Precautions for safe handling Advice on safe handling Material is in a pellet form. If converted to small particles during further processing, handing, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in th preserve of an ignition sources in high c environments may ignite the dust and result in a dust explosion Equiposion		
Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance v applicable laws and regulations and in an in the roncentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high of environments may ignite the dust and result in a dust explosion Electrosatic charge may build during conveying or handling.	Version 1.2 Revision Date	10/01/2019 Finit Date 01/00/2022 3D3 No.: DE00
Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with g engineering practices. Reclaim where possible. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high of environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling equipment handling polymer should be conductive and	. ACCIDENTAL RELEASE MEAS	SURES
Methods for containment / Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with g engineering practices. Reclaim where possible. Handling and storage Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high of environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and	Personal precautions	 Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth
Methods for cleaning up Vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with g engineering practices. Reclaim where possible. Handling and storage Precautions for safe handling Advice on safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high of environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and	Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high of environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and		 vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good
 Advice on safe handling Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high of environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and 	Handling and storage	
If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high of environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and		-
4 / 13	Advice on safe handling	 If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling.
		4 / 13

		(+) 188	16996168		
SAFETY DATA S		Poncip1;	astics.com	li i a a al a	
SAFEIT DATA O				Iyonae	ellbasell
Dexflex 992 NH				Gen. Variant:	SDS US GHS
	evision Date 10	/01/2019	Print Date 0		SDS No.: BE6638
			(earthed) and b ainers involved	oonded. in the transfer of this	s material
		should be	grounded and	bonded.	
				hould conform to app uirements for areas h	
		combustibl		sh hands thoroughly	with soon and
		water.	iiiiy, aiways wa	ISTI HARIOS THOROUGHIY	with soap and
			op may conden	al to processing temp se in the exhaust ver	
		Refer to N	FPA 654, Stand	dard for the Preventio	
				Manufacturing, Proc Particulate Solids, for	
Fire-fighting class	:	Polymer w	ill burn but doe	s not easily ignite.	
Conditions for sa	fe storage, inc	luding any	incompatibili	ties	
Requirements for s areas and containe	Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong				
	oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge.				
Specific end use(s)				
	:	See Section	on 1.		
3. EXPOSURE CONTR	OLS/PERSON/	AL PROTE	CTION		
Control parameters					
Ingredients with	workplace con	trol param	eters		
Occupational Exp	osure Limits				
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can		TWA	10 mg/m3	US (ACGIH)	Information
be formed when handling this			inhalable	2005	
product: Non-					
specified (inert or nuisance) dust					
		.1			
		5	/ 13		

(+) 18816996168

Ponciplastics.com

SAFETY	DATA	SHEET	

Iyondellbasel 111

Dexflex 992 NH696 BLK

Revision Date 10/01/2019 Version 1.2 Print Date 01/06/2022

Gen. Variant: SDS US GHS SDS No.: BE6638

Materials that can be formed when handling this product: Non- specified (inert or	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
nuisance) dust				
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

(+) 18816996168

	(+) 18816996168		
SAFETY DATA SHEET	Ponciplastics.com		
	lyondellbase		
Dexflex 992 NH696 BL			
Version 1.2 Revision Date	e 10/01/2019 Print Date 01/06/2022 SDS No.: BE66		
	injury or other irritation to eyes due to airborne particles which may result from handling this product.		
Skin and body protection	: Wear suitable protective clothing.		
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse. 		
Appearance	: Pellets.		
Color	: Black		
Odor	: Slight.		
Odor Threshold	: No value available.		
Flash point	: No Data Available.		
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer due varies according to particle size distribution.		
Upper explosion limit	: Not applicable.		
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.		
Oxidizing properties	: Not considered an oxidizing agent.		
Autoignition temperature	: > 300 °C		
Decomposition temperature	: not determined		
Melting point/range	: 50 - 170 °C		
Boiling point/boiling range	: Not applicable.		
Vapor pressure	: Not applicable.		
Density	: <1 g/cm3		
Water solubility	: Insoluble.		
	7 / 13		

	(+) 18816996168		
AFETY DATA SHEET	Ponciplastics.com		
exflex 992 NH696 BL ersion 1.2 Revision Date			
Partition coefficient: n- octanol/water	: No Data Available.		
Viscosity, dynamic	: Not applicable.		
Relative vapor density	: Not applicable.		
Evaporation rate	: Not applicable.		
Explosive properties	: No Data Available.		
Other Information	: No additional information available.		
STABILITY AND REACTIVITY	(
Reactivity	: No known reactivity hazards.		
Chemical stability	: Stable under normal conditions.		
Hazardous reactions	: Will not occur.		
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.		
Materials to avoid	: Material may be softened by some hydrocarbons.		
Hazardous decomposition	: Not expected to decompose under normal conditions.		
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.		
TOXICOLOGICAL INFORMA	ΓΙΟΝ		
Acute toxicity			
Acute oral toxicity	: Not classified		
Acute inhalation toxicity	: Not classified		
Acute dermal toxicity	: Not classified		
Skin corrosion/irritation	: Not a skin irritant.		
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.		
	8 / 13		

	(+) 1881	6996168		
SAFETY DATA SHEET	Poncipla	stics.com	lyoodollb	
		_	lyondellb	שכם
Dexflex 992 NH696 BL	<		Gen. Variant: SDS	_US_GHS
/ersion 1.2 Revision Date	10/01/2019	Print Date 01/06	5/2022 SDS N	o.: BE66
Respiratory or skin sensitization	: Not classifi	ed		
Chronic toxicity				
Component Name	NTP	IARC	OSHA	
Carbon Black		2B	Present	
Titanium Dioxide		2B	Present	
Carcinogenicity	: Not classifie	ed		
Germ cell mutagenicity		ase under normal a.	in a thermoplastic resin conditions of use, trans	
Reproductive toxicity Effects on fertility / Effects on or via lactation	: Not classifie			
Effects on Development				44
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.			
Target Organ Systemic Toxicant - Repeated exposure		nce or mixture is a ant, repeated exp	not classified as specific osure.	target
Aspiration hazard	: Not applica	ble.		
2. Ecological information				
Ecotoxicology Assessment				
Short-term (acute) aquatic hazard	: Not classified			
Long-term (chronic) aquatic hazard	: Not classifie	ed		
	9.	/ 13		

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Dexflex 992 NH696 BLK	
Version 1.2 Revision Date 1	0/01/2019 Print Date 01/06/2022 SDS No.: BE6638
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
Bioaccumulative potential	
Bioaccumulation	: This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	: no data available
Other adverse effects	
Environmental fate and pathways	: This material is not volatile and insoluble in water.
Other information	
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations	
Waste treatment methods	
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	: This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
	10 / 13

(+) 18816996168

Ponciplastics.com

Dexflex 992 NH696 BLK

SAFETY DATA SHEET

Version 1.2

Revision Date 10/01/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE6638

yondellbase

Not regulated for transport

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN	Type of Toxicity					
		Carcinogen	Developmental	Repro-Male	Repro- Female		
Hexachlorobenzene	118-74-1	Х	Х				

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

1333-86-4 Carbon Black

14807-96-6 Talc, Magnesium Silicate

No components are subject to the Massachusetts Right to Know Act.

11 / 13

(+)	1	8	8	1	6	q	q	6	1	68	
(1)	1	0	0	1	U	J	J	U	1	00	1

Ponciplastics.com

Dexflex 992 NH696 BLK

SAFETY DATA SHEET

Version 1.2

Revision Date 10/01/2019

Print Date 01/06/2022

SDS No.: BE6638

Iyondellbase

.... Gen. Variant: SDS US GHS

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

1333-86-4 Carbon Black

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.


16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

HMIS Classification

: Health Hazard: 0 Flammability: 1 Physical hazards: 0



12 / 13

