	(+) 18	816996168	
SAFETY DATA SHEET according to Regulation (EC) No. 190		lastics.com	lyondellbasell
Hifax BB 73 G C12716			Gen. Variant: SDS_AT
Version 1.4 Revision Date (04/06/2020	Print Date 01	/06/2022 SDS No.: BE1629
1. Identification of the substance/m	ixture and o	f the company/u	ndertaking
1.1 Product identifier			
Trade name:Synonyms:Substance name:		3 G C12716 Compounded poly ed polyolefin	/mer
1.2 Relevant identified uses of the	substance o	r mixture and us	es advised against
Identified uses :		e of plastic article nversion process.	s by injection molding, extrusion
Prohibited uses :	devices; He Application	ealth Canada clas	s; European class III medical s IV Medical Devices; nent implantation into the body; cations
1.3 Details of the supplier of the sat	fety data she		
Company Basell Sales & Marketing Company Delftseplein 27E 3013 AA Rotterdam Netherlands	B.V.	Registration nur NA	nber Telephone 31 (0) 10 275 55 00
E-mail address : Responsible/issuing person	product.safet	y@lyb.com	
1.4 Emergency telephone number			
Basell Sales & Marketing Company	B.V.		+32 3 575 1235
Poison Center: Gesundheid Österreich GMBH AT: +43 1 406 43 43 24 hours all days			
2. Hazards identification			
2.1 Classification of the substance or mixture			
		1 / 16	



according to Regulation (EC) No. 1907/2006

Hifax BB 73 G C12716

Version 1.4

Revision Date 04/06/2020

Print Date 01/06/2022

SDS No.: BE1629

lyondellbasell

Gen. Variant: SDS AT

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

2.3 Other hazards

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

3. Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC) No 1272/2008)	Weight %
Proprietary blend of polyolefinic polymers	Mixture	Not Classified	50.0 - 80.0 %

Contains: Additives, stabilizers and fillers

4. First aid measures


4.1 Description of first-aid measures

General advice	: Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.
If inhaled	 Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air.
	2 / 16



	icording to Regulation (EC) No.			Gen. Variant: SDS AT
Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 2 Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient. Fire-fighting measures : Use dry chemical, CO2, or water spray.			Print Date 01/06	
large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 2 Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient. Fire-fighting measures : SMALL FIRE: Use dry chemical, CO2, or water spray.		Keep persor	n warm, if necessary	/ give Cardio-Pulmonary
medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 2 Most important symptoms and effects, both acute and delayed : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. 2 Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient. Fire-fighting measures : SMALL FIRE: Use dry chemical, CO2, or water spray.	In case of skin contact	large amoun polymer. Do not atten the skin. Obtain imme	its of water to cool th npt to peel polymer f ediate emergency m	he affected tissue and from skin as this will remove
If swallowed : Adverse health effects due to ingestion are not anticipated. 2 Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. B Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient. Fire-fighting measures I Extinguishing media Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray.	In case of eye contact	 medical attention In case of ey Continuously 15 minutes. Beyond flush adherent to attention 	ention if discomfort per ye contact with molte / flush eye(s) with c hing, DO NOT attem the eye(s).	ersists. en polymer: cool running water for at least npt to remove the material
Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient. Fire-fighting measures Extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray.		: Adverse hea	alth effects due to ing	gestion are not anticipated.
Molten polymer may cause thermal burns. Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient. Fire-fighting measures Extinguishing media Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray.		: Inhalation of	f process fumes and	l vapors may cause soreness
Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. Fire-fighting measures Extinguishing media Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray.	Hazards		•	
Fire-fighting measures Extinguishing media Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray.	Indication of any immediate	medical attentio	n and special treat	tment needed
Extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray.	Treatment			
Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray.	Fire-fighting measures			
Use dry chemical, CO2, or water spray.				
3 / 16	Suitable extinguishing media	-		r spray.
		3	3 / 16	

	(+) 18816996168 Ponciplastics.com	
SAFETY DATA SHEET according to Regulation (EC) No. 19		lyondellbasell
Hifax BB 73 G C12716	04/06/2020 Print Data 01	Gen. Variant: SDS_AT
Version 1.4 Revision Date	04/06/2020 Print Date 01	/06/2022 SDS No.: BE1629
	: LARGE FIRES: Use water spray hose nozzle	es from a safe location.
Unsuitable extinguishing media 5.2 Special hazards arising from th	: None known. ne substance, or mixture	
	 Keep away from heat and so In case of fire hazardous dec produced such as: Carbon monoxide, carbon did hydrocarbons (smoke). 	composition products may be
5.3 Advice for firefighters		
Special protective equipment for fire-fighters	: Wear approved positive press apparatus and firefighter prot	
Further information	flammable vapors. Move containers from fire are Evacuate immediately in the container pressure relief devi Always stay away from tanks	kcal/kg with hose lines or monitor ompose polymer, and generate ea if it can be done without risk. event of opening of storage ces or discoloration of container. engulfed in fire. of storage containers involved in
6. Accidental release measures		
6.1 Personal precautions, protectiv		-
Personal precautions	 Equip responders with proper Creates dangerous slipping h surface. Equip emergency responders equipment (PPE) Avoid generating dust. 	•
	4 / 16	



7.1 Precautions for safe handling	
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling
	5 / 16

		(+) 18	816996168 lastics.com		
SAFETY DATA SH	лсст	Poncip	lastics.com		
according to Regulation		/2006		Iyona	ellbasell
Hifax BB 73 G C				Gen. Varian	t: SDS_AT
Version 1.4 Re	vision Date 04/	06/2020	Print Date 01	/06/2022	SDS No.: BE1629
		water. When bring	ng, always wash ing the material to	hands thoroughly v o processing tempe in the exhaust vent	eratures vapors
Fire-fighting class			l burn but does no	ot easily ignite.	
7.2 Conditions for safe	storage, inclu	ding any ii	ncompatibilities		
Requirements for st areas and container	orage : s	Store in a d Use good h and handlin should be u Store away oxidizing ag Keep conta	ry location. ousekeeping prace g. Process enclos sed to avoid exce from excessive h jents. iner closed to pre	ctices during storages sures and adequate essive dust accume eat and away from vent contamination e build up of electr	e ventilation ulation. strong
7.3 Specific end use(s)					
	: :	See Sectior	n 1.2.		
8. Exposure controls/pe 8.1 Control parameters Ingredients with w	;		fors		
Occupational Expo					
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	



according to Regulation (EC) No. 1907/2006

Hifax BB 73 G C12716

Version 1.4

Revision Date 04/06/2020

Print Date 01/06/2022

SDS No.: BE1629

lyondellbasell

Gen. Variant: SDS AT

Materials that can	TWA	3 mg/m3	US (ACGIH)	
be formed when		respirable	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust				

Consult local authorities for acceptable exposure limits.

8.2 Exposure controls

Engineering measures

Follow the recommendations in international standard NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection :	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.		
Hand protection :	Wear gloves that provide thermal protection where there is a potential for contact with heated material.		
Eye and face protection :	Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product.		
Skin and body protection :	Wear suitable protective clothing.		
7 / 16			

	(+) 18816996168					
	(+) 18816996168 Ponciplastics.com					
SAFETY DATA SHEET according to Regulation (EC) No.	1907/2006	lyondellbasell				
Hifax BB 73 G C12716	Hifax BB 73 G C12716 Gen. Variant: SDS_AT					
Version 1.4 Revision Date	e 04/06/2020 Print Date 01/	/06/2022 SDS No.: BE1629				
Hygiene measures		onal protective equipment should the performance characteristics				
	of the protective equipment re performed, conditions present hazards and/or potential haza during use. Use good personal hygiene p	elative to the task(s) to be t, duration of use, and the ards that may be encountered practices. rinking, smoking, or using toilet				
Environmental exposure cor						
General advice	: See section 6.					
9. Physical and chemical propert 9.1 Information on basic physica						
Appearance	: Pellets.					
Color	: Black					
Odor	: Slight.					
Flash point	: No Data Available.					
Lower explosion limit	: The minimum explosive conc varies according to particle si	entration (MEC) for polymer dust ze distribution.				
Upper explosion limit	: Not applicable.					
Flammability (solid, gas)	: Polymer will burn but does no	ot easily ignite.				
Oxidizing properties	: Not considered an oxidizing a	agent.				
Autoignition temperature	: > 300 °C					
Decomposition temperature	: not determined					
Melting point/range	: 50 - 170 °C					
Boiling point/boiling range	: Not applicable.					
	8 / 16					

SAFETY DATA SHEET according to Regulation (EC) N	No. 1907/2006
Hifax BB 73 G C127	16 Gen. Variant: SDS_AT
Version 1.4 Revision	Date 04/06/2020 Print Date 01/06/2022 SDS No.: BE16
Vapor pressure	: Not applicable.
Density	: > 1 g/cm3
Water solubility	: Insoluble.
Partition coefficient: n-	: No Data Available.
octanol/water Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
10. Stability and reactivity	
10.1 Reactivity	
No known reactivity hazard	ls.
10.2 Chemical stability	
Stable under normal condit	
10.3 Possibility of hazardous Hazardous reactions	: Will not occur.
10.4 Conditions to avoid	. Whithou occur.
Conditions to avoid	· Avoid contact with strong ovidizors, overssive best, sparks or
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
10.5 Incompatible materials	
10.5 Incompatible materials Materials to avoid	: Material may be softened by some hydrocarbons.

SAFETY DATA SHEET according to Regulation (EC) No.	(+) 18816996168 Ponciplastics.com 1907/2006
Hifax BB 73 G C12716	Gen. Variant: SDS_AT
Version 1.4 Revision Dat	e 04/06/2020 Print Date 01/06/2022 SDS No.: BE1629
Hazardous decomposition products Thermal decomposition	 Not expected to decompose under normal conditions. Note: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
11. Toxicological information	
11.1 Information on toxicologica	I effects
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
Respiratory or skin sensitization	: Not classified
Chronic toxicity	
Carcinogenicity	: Not classified
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility / Effects on or via lactation	: Not classified
	10 / 16

	(+) 18816996168 Ponciplastics.com			
SAFETY DATA SHEET according to Regulation (EC) No. 1		lyondellbasell		
Hifax BB 73 G C12716 Gen. Variant: SDS_AT				
Version 1.4 Revision Date 04/06/2020 Print Date 01/06/2022 SDS No.: BE1629				
Effects on Development	: Not classified			
Target Organ Systemic Toxicant - Single exposure				
	: The substance or mixture is n organ toxicant, single exposur			
Target Organ Systemic Toxic	cant - Repeated exposure			
	: The substance or mixture is n organ toxicant, repeated expo			
Aspiration hazard	: Not applicable.			
12. Ecological information				
12.1 Ecotoxicology Assessment				
Short-term (acute) aquatic hazard	: Not classified			
Long-term (chronic) aquatic hazard	: Not classified			
12.2 Persistence and degradabili	ity			
Biodegradability	: Not expected to be biodegrada	able.		
12.3 Bioaccumulative potential				
Bioaccumulation	: This material is not expected	to bioaccumulate.		
12.4 Mobility in soil				
Mobility	: no data available			
12.5 Results of PBT and vPvB assessment				
11 / 16				

	(+) 18816996168 Ponciplastics.com			
SAFETY DATA SHEET according to Regulation (EC) No. 15		lyondellbasell		
Hifax BB 73 G C12716 Gen. Variant: SDS_AT				
Version 1.4 Revision Date	04/06/2020 Print Date 01	/06/2022 SDS No.: BE1629		
Result	: This substance/mixture conta to be either persistent, bioaco very persistent and very bioac	cumulative and toxic (PBT) or		
12.6 Other adverse effects				
Environmental fate and pathways	: This material is not volatile an	nd insoluble in water.		
12.7 Other information				
Additional ecological information	solubility of polymers.	minimal based on the low water duct. However, birds, fish and which may obstruct their		
13. Disposal considerations				
13.1 Waste treatment methods				
Product		or reclaimed in conformance with ns and in conformance with good		
14. Transport information				
Not regulated for transport				
15. Regulatory information				
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture				
12 / 16				



according to Regulation (EC) No. 1907/2006

Hifax BB 73 G C12716

Version 1.4

Revision Date 04/06/2020

Print Date 01/06/2022

SDS No.: BE1629

lyondellbasell

Gen. Variant: SDS AT

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Not Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Not Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

Contact product.safety@lyb.com for additional global inventory information.

15.2 Chemical safety assessment

No information available.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 Abbreviations and Acronyms



according to Regulation (EC) No. 1907/2006

Hifax BB 73 G C12716

Version 1.4

Revision Date 04/06/2020

Print Date 01/06/2022

SDS No.: BE1629

lyondellbasell

Gen. Variant: SDS AT

ACGIH - American Conference of Governmental Industrial Hygienists ACGIH BEIs - American Conference of Governmental Industrial Hygienists Biological Exposure Indices ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road AICS - Australian Inventory of Chemical Substances ASTM - American Society for Testing and Materials **BEL - Biological Exposure Limits** BTEX - Benzene, Toluene, Ethylbenzene, Xylenes CAS - Chemical Abstracts Service **CEFIC - European Chemical Industry Council** CLP - Classification Packaging and Labelling COC - Cleveland Open-Cup CS - Consumer Scenario DIN - Deutsches Institut für Normung DN(M)EL - Derived No (Minimal) Effect Level DSL - Canada Domestic Substance List EC - European Commission EC50 - Median Effective Concentration ECETOC - European Center on Ecotoxicology and Toxicology of Chemicals ECHA - European Chemicals Agency EL50 - Effective Loading fifty ELINCS - EHR-Lab Interoperability and Connectivity Specification ENCS - Japanese Existing and New Chemical Substances Inventory ERC - Environmental Release Category EUSES - European Union System for the Evaluation of Substances EWC - European Waste Code GHS - Globally Harmonized System of Classification and Labelling of Ch IARC - International Agency for Research on Cancer IATA - International Air Transport Association IC50 - Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG - International Maritime Dangerous Goods **IECSC - Chinese Chemicals Inventory** IOELV - Indicative Occupational Exposure Limit Values IP346 - Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables KECI - Korea Existing Chemicals Inventory Koc - Organic Carbon/Water Partition Coefficient LC50 - Lethal Concentration fifty LD50 - Lethal Dose fifty per cent. LL/EL/IL - Lethal Loading/Effective Loading/Inhibitory Loading LL50 - Lethal Loading fifty MAK Commission - Permanent Senate Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area MARPOL - International Convention for the Prevention of Pollution from Ships No. - Number NOEC/NOEL - No Observed Effect Concentration / No Observed Effect Level 14 / 16



according to Regulation (EC) No. 1907/2006

Hifax BB 73 G C12716

Version 1.4

Revision Date 04/06/2020

Print Date 01/06/2022

SDS No.: BE1629

lvondellbasel

Gen. Variant: SDS_AT

NZIoC - New Zealand Inventory of Chemicals OE_HPV - Occupational Exposure - High Production Volume OECD - Organization for Economic Co-operation and Development **OEL - Occupational Exposure Limit** PBT - Persistent, Bio accumulative and Toxic PICCS - Philippine Inventory of Chemicals and Chemical Substances PNEC - Predicted No Effect Concentration PPE - Personal Protective Equipment **PROC** - Process Category QSAR - Quantitative Structure-Activity Relationship REACh - Registration Evaluation and Authorization of Chemicals RID - Regulations Relating to International Carriage of Dangerous Goods by Rail SDS - Safety Data Sheet SKIN_DES - Skin Designation STEL - Short term exposure limit STP - Standard Temperature and Pressure TCSCA - Taiwan inventory of chemicals TGD - Technical Guidance Document TRA - Targeted Risk Assessment TSCA - US Toxic Substances Control Act TWA - Time-Weighted Average **UN - United Nations** vPvB - very Persistent and very Bioaccumulative WGK - German Water Endangerment Class

Disclaimer

Multiple legal entities and registration numbers may be displayed in Section 1. The Recipient shall refer to the shipping documents to identify the legal entity that supplied this product.

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.



according to Regulation (EC) No. 1907/2006

Hifax BB 73 G C12716

Version 1.4

Revision Date 04/06/2020

Print Date 01/06/2022

SDS No.: BE1629

lyondellbasell

Gen. Variant: SDS AT

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet