	(+) 18816996168
	Ponciplastics.com
SAFETY DATA SHEET	lyondellbasel
lifay 7/20D 38N Gran	ite Grav Gen. Variant: SDS_US_GHS
Hifax 7430P 38N Gran /ersion 1.3 Revision Date	
IDENTIFICATION OF THE SUE	STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name	: Hifax 7430P 38N Granite Gray
CAS Number: Chemical name	: Mixture
Synonyms	Compounded polyolefin Polyolefin, Compounded polymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical
	devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body;
	Life-sustaining medical applications
	Commony Tolonhous
<u>Company Address</u> Equistar Chemicals, LP	Company Telephone Customer Service 888 777-0232
LyondellBasell Tower, Suite 3	
1221 McKinney St.	,, , , , , , , , , , , , , , , , ,
P.O. Box 2583	
Houston Texas 77252-2583	
Emorgonov tolonhono num	hor
Emergency telephone num EQUISTAR 800-245-4532	
E-mail address	: product.safety@lyb.com
Responsible/issuing person	
HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing,
	handling or by other means, may form combustible dust concentrations in air.
Other hazards	
	1 / 13

	(+) 18816996168	
AFETY DATA SHEET	Ponciplastics.com	lyondellbase
lifax 7430P 38N Grar ersion 1.3 Revision Da	te Gray te 10/02/2019 Print Date 01	Gen. Variant: SDS_US_GH /06/2022 SDS No.: BE63
	a cileble	
No additional information		
xtures Components		
Chemical name	CAS-No.	<u>Weight %</u>
Proprietary blend of polyolefin polymers	nic Mixture	95.0 - 100.0 %
Contains: Additives and sta	bilizers	
FIRST AID MEASURES		
General advice	: Take proper precautions t before attempting rescue	o ensure your own health and safe and providing first aid.
If inhaled	medical attention. In case of excessive inhal during heating of this mate Obtain medical attention.	ir. If signs/symptoms continue, get ation of fumes that may be genera erial, move the person to fresh air. essary give Cardio-Pulmonary
In case of skin contact	large amounts of water to Do not attempt to peel pol skin.	s the skin, immediately flush with cool the affected tissue and polym ymer from skin as this will remove ncy medical attention if burn is dea
In case of eye contact	: Flush eyes thoroughly with medical attention if discon	h water for several minutes and se nfort persists.
	minutes.	with cool running water for at least attempt to remove the material
	· Advarge beelth offects du	
If swallowed	. Adverse nearlin ellects du	e to ingestion are not anticipated.

(+) 18816996168 Ponciplastics.com SAFETY DATA SHEET lvondellbase Gen. Variant: SDS US GHS Hifax 7430P 38N Granite Gray Version 1.3 Revision Date 10/02/2019 Print Date 01/06/2022 SDS No.: BE6341 Notes to physician Symptoms Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Treatment Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing : None known. media Specific hazards during fire Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be fighting produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Special protective equipment Wear approved positive pressure self-contained breathing for fire-fighters apparatus and firefighter protective clothing. Further information Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out. 3 / 13

Hifax 7430P 38N Granite Gray Gen. Variant: SDS_US_Control SDS No.: B Wersion 1.3 Revision Date 10/02/2019 Print Date 01/06/2022 SDS No.: B ACCIDENTAL RELEASE MEASURES Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip merrgency responders with proper personal protect equipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surface. Equip merrgency responders with proper personal protect equipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sever system. Methods for containment / Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with gengineering practices. Reclaim where possible. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avdive dust designed or NFPA 654 to avdive acquired to signific model in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion		(+) 18816996168
Accidential and storage Precautions for safe handling Image: Solution of the solution. Solution of the solution. Handling and storage Precautions of the solution. Image: Solution of the solution of the solution of the solution. Solution of the solution of the solution. Advice on safe handling Image: Solution of the solution. Solution of the solution. Solution of the solution. Advice on safe handling Image: Solution of the solution. Image: Solution of the solution. Solution of the solution. Advice on safe handling Image: Solution of the solution. Image: Solution of the solution. Solution of the solution. Advice on safe handling Image: Solution of the solution. Image: Solution of the solution. Solution of the solution. Advice on safe handling Image: Solution of the solution. Image: Solution of the solution. Solution of the solution. Advice on safe handling Image: Solution of the solution. Image: Solution of the solution. Solution. Advice on safe handling Image: Solution of the solution. Image: Solution of the solution. Solution. Advice disclosed of or otheresolution	SAFETY DATA SHEET	Ponciplastics.com
ACCIDENTAL RELEASE MEASURES Personal precautions Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protec equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : On tand, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance with g engineering practices. Reclaim where possible. Handling and storage : Metrial si in a pellet form, if converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion. Electostatic charge may build during conveying or handling Equipment handling polymer should be conductive and		
Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfact with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system. Methods for containment / Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance with gengineering practices. Reclaim where possible. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and		
Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PEE) Avoid generating dust. Avoid generating dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system. Methods for containment / : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance with gengineering practices. Reclaim where possible. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 664 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion hazard.	ACCIDENTAL RELEASE MEAS	SURES
Methods for containment / On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance with gengineering practices. Reclaim where possible. Handling and storage Precautions for safe handling Advice on safe handling Advice on safe handling Static discharge (source) in a pollet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handlir	Personal precautions	 Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth
Methods for cleaning up vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance with g engineering practices. Reclaim where possible. Handling and storage Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and	Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handlin Equipment handling polymer should be conductive and		On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance wit applicable laws and regulations and in conformance with goo
 Advice on safe handling Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handlin Equipment handling polymer should be conductive and 	Handling and storage	
If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to av dust accumulation. Avoid generating dust; fine dust suspended in air and in th presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handlin Equipment handling polymer should be conductive and		-
4 / 13	Advice on safe handling	 If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust explosion Electrostatic charge may build during conveying or handling.
		4 / 13

(+) **18816996168**

Ponciplastics.com

		Poncipla	astics.com -		
SAFETY DATA S	HEET			lyonde	ellbasell
Hifax 7430P 38	N Granite	Grav		Gen. Variant:	SDS_US_GHS
	vision Date 10		Print Date 01/	06/2022	SDS No.: BE6341
Fire-fighting class Conditions for sa Requirements for s	: fe storage, inc	grounded Metal cont should be All electric codes and combustibl After hand water. When brin may develo section 10. Refer to N Dust Explo Handling c Polymer w	(earthed) and bo ainers involved i grounded and bo al equipment sho regulatory requir le dusts. ling, always was ging the material op may condens FPA 654, Standa osions from the N of Combustible P rill burn but does	nded. n the transfer of this onded. ould conform to app rements for areas h h hands thoroughly to processing temp e in the exhaust ver ard for the Preventio Aanufacturing, Proc articulate Solids, for not easily ignite.	s material licable electric handling with soap and beratures vapors ntilation. See on of Fire and essing, and
areas and containe		Use good and handlin should be Store away oxidizing a Keep conta	housekeeping pr ng. Process enc used to avoid ex y from excessive agents. ainer closed to p	ractices during stora losures and adequa cessive dust accum heat and away from revent contamination the build up of elect	te ventilation nulation. m strong on.
Specific end use(See Sectio	on 1.		
8. EXPOSURE CONTR Control parameters	OLS/PERSON	AL PROTE	CTION		
Ingredients with	workplace con	trol param	eters		
Occupational Exp	osure Limits				
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
			140		
		5	/ 13		

(+) 18816996168

onciplastics.com

SAFETY	DATA	Toncip

111 Gen. Variant: SDS_US_GHS Hifax 7430P 38N Granite Gray Revision Date 10/02/2019 Print Date 01/06/2022 SDS No.: BE6341

lyondellbasel

Materials that can	TWA	3 mg/m3	US (ACGIH)	
be formed when		respirable	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust		45 / 0		
Materials that can	TWA	15 mg/m3	US (OSHA)	
be formed when		total dust	2005	
handling this				
product: Non-				
specified (inert or nuisance) dust				
Materials that can	TWA	5 mg/m2	US (OSHA)	
be formed when	IVVA	5 mg/m3 respirable	2005	
handling this		respirable	2005	
product: Non-				
specified (inert or				
nuisance) dust				

Consult local authorities for acceptable exposure limits.

Exposure controls

Version 1.3

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators. 	
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.	
Eye and face protection	: Dust service goggles should be worn to prevent mechanical	
	6 / 13	

(+) 18816996168

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hifax 7430P 38N Gran Version 1.3 Revision Da	Ite GrayGen. Variant: SDS_US_GHSte 10/02/2019Print Date 01/06/2022SDS No.: BE634
	E 10/02/2015 Thin Date 51/00/2022 000
	injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
D. PHYSICAL AND CHEMICAL	
Appearance Color	: Pellets. : gray
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
	: No Data Available.
Lower explosion limit	 No Data Available. The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution.
	: The minimum explosive concentration (MEC) for polymer dus
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution.
Lower explosion limit	 The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution. Not applicable.
Lower explosion limit Upper explosion limit Flammability (solid, gas)	 The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite.
Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	 The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C
Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	 The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C
Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	 The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined
Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range	 The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C
Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range Boiling point/boiling range	 The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C Not applicable.

	(+) 18816996168 Ponciplastics.com
SAFETY DATA SHEET	lyondellbase
lifax 7430P 38N Gran	
ersion 1.3 Revision Date	e 10/02/2019 Print Date 01/06/2022 SDS No.: BE63
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
STABILITY AND REACTIVITY	(
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks o open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition	: Not expected to decompose under normal conditions.
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
. TOXICOLOGICAL INFORMA	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 13

	(+) 1881	6996168	
SAFETY DATA SHEET	Poncipla	stics.com	lvoodollbacoll
			lyondellbasell
Hifax 7430P 38N Granite		Drink Data 04/00	Gen. Variant: SDS_US_GHS
Version 1.3 Revision Date 7	10/02/2019	Print Date 01/06	/2022 SDS No.: BE6341
Respiratory or skin	: Not classifie	ed	
sensitization			
Chronic toxicity			
Component Name Titanium Dioxide	NTP	IARC 2B	OSHA Present
Carbon Black		2B 2B	Present
Carcinogenicity	: Not classifie	ed	
	Contains co	omponent(s) listed	by IARC as possibly
	carcinogeni	c to humans.	
			in a thermoplastic resin with conditions of use, transportation,
	and storage	9.	
Germ cell mutagenicity	: Not classifie	ed	
Democratica (assisted			
Reproductive toxicity Effects on fertility /	: Not classifie	od	
Effects on or via lactation	. NOL CIASSIN	50	
Effects on Development	: Not classifie	ed	
Target Organ Systemic Toxicant - Single exposure		nce or mixture is n ant, single exposu	ot classified as specific target re.
Target Organ Systemic	: The substa	nce or mixture is n	not classified as specific target
Toxicant - Repeated exposure	organ toxic	ant, repeated expo	osure.
Aspiration hazard	: Not applica	ble.	
12 Ecological information			
12. Ecological information			
Ecotoxicology Assessment			
Short-term (acute) aquatic hazard	: Not classifie	ed	
Long-term (chronic) aquatic hazard	: Not classifie	ed	
	9.	/ 13	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SAFETY DATA SHEET	lyondellbasell
Hifax 7430P 38N Granite	Grav Gen. Variant: SDS_US_GHS
Version 1.3 Revision Date 10	Clay
Persistence and degradability	
Biodegradability	Not expected to be biodegradable.
Bioaccumulative potential	
Bioaccumulation	This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	no data available
Other adverse effects	
Environmental fate and	This material is not volatile and insoluble in water.
Other information	
Additional ecological : information	Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations	
Waste treatment methods	
Product	All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible. This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
	10 / 13

(+) 18816996168

Ponciplastics.com

SAFETY DATA SHEET

Hifax 7430P 38N Granite Gray

Version 1.3

Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE6341

lyondellbase

Not regulated for transport

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

1333-86-4 Carbon Black

No components are subject to the Massachusetts Right to Know Act.

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

1333-86-4 Carbon Black

Other international regulations

11 / 13

 $(+)\,18816996168$

SAFETY DATA SHEET

Ponciplastics.com

Hifax 7430P 38N Granite Gray

Version 1.3

1.3 Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE6341

Iyondellbase

....

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

HMIS Classification

: Health Hazard: 0 Flammability: 1 Physical hazards: 0



12 / 13

