| Trade name:CAS Number::Chemical name:Synonyms:Identified uses:Identified uses:Prohibited uses:Prohibited uses:Equistar Chemicals, LPLyondellBasell Tower, Suite 3001221 McKinney St.P.O. Box 2583Houston Texas 77252-2583 | IO/02/2019 Print Date 01/06/2022 SDS No.: BE544 TANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING : Hifax CA1110/1GC BLK P23444 Mixture : Compounded polyolefin Orgonal devices : Polyolefin, Compounded polymer SDS No.: BE544 : Manufacture of plastic articles by injection molding, extrusion or other conversion process. : FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications Customer Service 888 777-0232 |
|--|---|
| Hifax CA1110/1GC BLK Version 1.2 Revision Date 1 I. IDENTIFICATION OF THE SUBST Trade name : CAS Number: : Chemical name : Synonyms : Identified uses : Prohibited uses : Prohibited uses : Prohibited uses : Multiple Stephone numbe | P23444 Gen. Variant: SDS_US_GHS 10/02/2019 Print Date 01/06/2022 SDS No.: BE544 TANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING : Hifax CA1110/1GC BLK P23444 : Mixture : Compounded polyolefin : Polyolefin, Compounded polymer : Manufacture of plastic articles by injection molding, extrusion or other conversion process. : FDA Class III medical devices; European class III medical devices; Applications involving permanent implantation into the body; Life-sustaining medical applications : Company Telephone Customer Service 888 777-0232 |
| Version 1.2 Revision Date 1 I. IDENTIFICATION OF THE SUBST Trade name : CAS Number: : Chemical name : Synonyms : Identified uses : Prohibited uses : Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone numbe | 10/02/2019 Print Date 01/06/2022 SDS No.: BE544 TANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING : Hifax CA1110/1GC BLK P23444 : Mixture : Compounded polyolefin : Polyolefin, Compounded polymer : Manufacture of plastic articles by injection molding, extrusion or other conversion process. : FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications : Company Telephone Customer Service 888 777-0232 |
| Version 1.2 Revision Date 1 I. IDENTIFICATION OF THE SUBST Trade name : CAS Number: : Chemical name : Synonyms : Identified uses : Prohibited uses : Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone numbe | IO/02/2019 Print Date 01/06/2022 SDS No.: BE544 TANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING : Hifax CA1110/1GC BLK P23444 Mixture : Compounded polyolefin Orgonal devices : Polyolefin, Compounded polymer SDS No.: BE544 : Manufacture of plastic articles by injection molding, extrusion or other conversion process. : FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications Customer Service 888 777-0232 |
| Trade name:CAS Number::Chemical name:Synonyms:Identified uses:Identified uses:Prohibited uses:Prohibited uses:Equistar Chemicals, LPLyondellBasell Tower, Suite 3001221 McKinney St.P.O. Box 2583Houston Texas 77252-2583 | Hifax CA1110/1GC BLK P23444 Mixture Compounded polyolefin Polyolefin, Compounded polymer Manufacture of plastic articles by injection molding, extrusion or other conversion process. FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications <u>Company Telephone</u> Customer Service 888 777-0232 |
| CAS Number: : : Chemical name : Synonyms : Identified uses : Prohibited uses : Prohi | Mixture Compounded polyolefin Polyolefin, Compounded polymer Manufacture of plastic articles by injection molding, extrusion or other conversion process. FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications <u>Company Telephone</u> Customer Service 888 777-0232 |
| Prohibited uses : <u>Company Address</u> Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 <u>Emergency telephone numbe</u> | or other conversion process. FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications <u>Company Telephone</u> Customer Service 888 777-0232 |
| Company Address Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone numbe | devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications <u>Company Telephone</u> Customer Service 888 777-0232 |
| Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone numbe | Customer Service 888 777-0232 |
| | |
| EQUISTAR 800-245-4532 E-mail address : Responsible/issuing person | r : product.safety@lyb.com |
| 2. HAZARDS IDENTIFICATION | |
| GHS Classification | |
| Combustible dust | |
| Label elements | |
| Signal word | : Warning |
| Hazard Statements | : If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air. |
| Other hazards | |
| | 1 / 13 |

| SAFETY DATA SHEET | (+) 18816996168 Ponciplastics.com | lvoodollbacoll | | |
|--|---|--|--|--|
| SAFETY DATA SHEET IVONCEIDASE Hifax CA1110/1GC BLK P23444 Gen. Variant: SDS_US_GH | | | | |
| Version 1.2 Revision Date 1 | | 6/2022 SDS No.: BE5448 | | |
| No additional information ava | | | | |
| Mixtures | | | | |
| Components | | | | |
| Chemical name | CAS-No. | Weight % | | |
| Proprietary blend of polyolefinic polymers | Mixture | 80.0 - 100.0 % | | |
| Contains: Additives, stabilizers | and fillers | | | |
| 4. FIRST AID MEASURES General advice | : Take proper precautions to before attempting rescue an | ensure your own health and safety nd providing first aid. | | |
| If inhaled | medical attention. In case of excessive inhalat | If signs/symptoms continue, get ion of fumes that may be generated ial, move the person to fresh air. ssary give Cardio-Pulmonary | | |
| In case of skin contact | If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. | | | |
| In case of eye contact | : Flush eyes thoroughly with water for several minutes and see medical attention if discomfort persists. | | | |
| | In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. | | | |
| If swallowed | : Adverse health effects due | to ingestion are not anticipated. | | |
| | 2 / 13 | | | |
| | | | | |

| | (+) 18816996168 |
|---|--|
| SAFETY DATA SHEET | Ponciplastics.com |
| | I [®] IIII I |
| Hifax CA1110/1GC BLK Version 1.2 Revision Date | 1 20444 |
| | |
| Notes to physician | |
| Symptoms | : Inhalation of process fumes and vapors may cause soreness i the nose and throat and coughing. |
| Hazards | : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. |
| Treatment | : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. |
| | |
| 5. FIRE-FIGHTING MEASURES | |
| Suitable extinguishing media | : SMALL FIRE: Use dry chemical, CO2, or water spray. |
| | : LARGE FIRES: Use water spray hose nozzles from a safe location. |
| Unsuitable extinguishing media | : None known. |
| Specific hazards during fire fighting | Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). |
| Special protective equipment for fire-fighters | : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. |
| Further information | Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. |
| | Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container.Always stay away from tanks engulfed in fire.Do not attempt to get on top of storage containers involved in fire. |
| | Cool storage containers with large volumes of water even afte fire is out. |
| | 3 / 13 |

| AFETY DATA SHEET IIfax CA1110/1GC BLK ersion 1.2 Revision Date | Ponciplastics.com yondelbase Gen. Variant: SDS_US_GHS |
|--|---|
| | Con Variant: SDS US CH |
| ersion 1.2 Revision Date | P23444 Gen. Valiant. 3D3_03_01 |
| | 10/02/2019 Print Date 01/06/2022 SDS No.: BE54 |
| | |
| ACCIDENTAL RELEASE MEASU | JRES |
| Personal precautions | Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. |
| Environmental precautions | : Do not flush into surface water or sanitary sewer system. |
| Methods for containment / Methods for cleaning up | On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with goo engineering practices. Reclaim where possible. |
| Handling and storage | |
| Precautions for safe handling | |
| Advice on safe handling | Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and |
| | 4 / 13 |
| | |

| | | (+) 188 | 16996168 | | | |
|--|--|--------------------------|-------------------|--|------------------|--|
| SAFETY DATA S | | Poncip1: | astics.com | lu a a da | | |
| SAILTI DATA S | | | | IYONGE | ellbasell | |
| Hifay CA1110/ | | 223444 | | Gen. Variant: | SDS_US_GHS | |
| Hifax CA1110/1GC BLK P23444Gen. Variant: SDS_US_GHSVersion 1.2Revision Date 10/02/2019Print Date 01/06/2022SDS No.: BE5448 | | | | | | |
| | | | | | | |
| | | | | | | |
| | grounded (earthed) and bonded. Metal containers involved in the transfer of this material | | | | | |
| | should be grounded and bonded. All electrical equipment should conform to applicable electri | | | | | |
| | codes and regulatory requirements for areas handling | | | | | |
| | combustible dusts. After handling, always wash hands thoroughly with soap ar | | | | | |
| | | water. When brin | aina the materia | al to processing temp | peratures vanors | |
| | | may develo | op may conden | se in the exhaust ver | | |
| | | section 10 Refer to N | | lard for the Preventio | n of Fire and | |
| | | Dust Explo | sions from the | Manufacturing, Proc Particulate Solids, for | essing, and | |
| Fire-fighting class | : | Polymer w | ill burn but does | s not easily ignite. | | |
| Conditions for safe storage, including any incompatibilities | | | | | | |
| | Requirements for storage areas and containersStore in a dry location. Use good housekeeping practices during storage, transferring | | | | | |
| areas and containe | ers | | | closures and adequa | | |
| | should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong | | | | | |
| | | oxidizing a | igents. | | - | |
| | | | | prevent contamination the build up of elect | | |
| | _ | | | | | |
| Specific end use(| | | | | | |
| | : | See Section | on 1. | | | |
| | | | | | | |
| | | | | | | |
| 8. EXPOSURE CONTR | OLS/PERSON | AL PROTE | CTION | | | |
| Control parameters | | | | | | |
| - | | | | | | |
| Ingredients with | - | itrol param | eters | | | |
| Occupational Exp | osure Limits | | | | | |
| Components | CAS-No. | Туре | Limit Value | Basis | Additional | |
| Materials that can | | TWA | 10 mg/m3 | Revision Date US (ACGIH) | Information | |
| be formed when | | | inhalable | 2005 | | |
| handling this product: Non- | | | | | | |
| specified (inert or nuisance) dust | | | | | | |
| | l | 1 | l | | L | |
| | | 5 | / 13 | | | |
| | | | | | | |
| | | | | | | |
| | | | | | | |

| (+) 18816996168 | (+) | 1881 | 6996168 |
|-----------------|-----|------|---------|
|-----------------|-----|------|---------|

Ponciplastics.com

| SAFETY | DATA | SHEET | |
|--------|------|-------|--|
| | | | |

Gen. Variant: SDS_US_GHS

lyondellbasel

Hifax CA1110/1GC BLK P23444 Version 1.2 Revision Date 10/02/2019

Print Date 01/06/2022

SDS No.: BE5448

| Materials that can | TWA | 3 mg/m3 | US (ACGIH) | |
|---------------------|-----|------------|------------|--|
| be formed when | | respirable | 2005 | |
| handling this | | | | |
| product: Non- | | | | |
| specified (inert or | | | | |
| nuisance) dust | | 1- 1- 1- 0 | | |
| Materials that can | TWA | 15 mg/m3 | US (OSHA) | |
| be formed when | | total dust | 2005 | |
| handling this | | | | |
| product: Non- | | | | |
| specified (inert or | | | | |
| nuisance) dust | | | | |
| Materials that can | TWA | 5 mg/m3 | US (OSHA) | |
| be formed when | | respirable | 2005 | |
| handling this | | | | |
| product: Non- | | | | |
| specified (inert or | | | | |
| nuisance) dust | | | | |

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

| Respiratory protection | : Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposu- limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certifie respirators. | ire |
|-------------------------|---|-----|
| Hand protection | : Wear gloves that provide thermal protection where there is potential for contact with heated material. | a |
| Eye and face protection | : Dust service goggles should be worn to prevent mechanica | al |
| | 6 / 13 | |
| | | |

(+) 18816996168

| | (+) 18810990108 | | | |
|-----------------------------|---|--|--|--|
| SAFETY DATA SHEET | Ponciplastics.com | | | |
| | الا القار (الم | | | |
| Hifax CA1110/1GC BLK | | | | |
| /ersion 1.2 Revision Date | 10/02/2019 Print Date 01/06/2022 SDS No.: BE54 | | | |
| | | | | |
| | injury or other irritation to eyes due to airborne particles which may result from handling this product. | | | |
| Skin and body protection | : Wear suitable protective clothing. | | | |
| Hygiene measures | Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. | | | |
| | Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse. | | | |
| | | | | |
| | | | | |
| PHYSICAL AND CHEMICAL PR | OPERTIES | | | |
| Appearance Color | : Pellets. : Black | | | |
| Odor | : Slight. | | | |
| Odor Threshold | : No value available. | | | |
| Flash point | : No Data Available. | | | |
| Lower explosion limit | : The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution. | | | |
| Upper explosion limit | : Not applicable. | | | |
| Flammability (solid, gas) | : Polymer will burn but does not easily ignite. | | | |
| Oxidizing properties | : Not considered an oxidizing agent. | | | |
| Autoignition temperature | : > 300 °C | | | |
| Decomposition temperature | : not determined | | | |
| Melting point/range | : 50 - 170 °C | | | |
| Boiling point/boiling range | : Not applicable. | | | |
| Vapor pressure | : Not applicable. | | | |
| Density | : <1 g/cm3 | | | |
| Water solubility | : Insoluble. | | | |
| | 7 / 13 | | | |

| | (+) 18816996168 Ponciplastics.com | | |
|--|--|--|--|
| SAFETY DATA SHEET | lyondellbase | | |
| lifew CA4440/4CC DL | | | |
| Hifax CA1110/1GC BL /ersion 1.2 Revision Date | | | |
| | | | |
| | | | |
| Partition coefficient: n- octanol/water | : No Data Available. | | |
| Viscosity, dynamic | : Not applicable. | | |
| Relative vapor density | : Not applicable. | | |
| Evaporation rate | : Not applicable. | | |
| Explosive properties | : No Data Available. | | |
| Other Information | : No additional information available. | | |
| | | | |
| 0. STABILITY AND REACTIVITY | (| | |
| Reactivity | : No known reactivity hazards. | | |
| Chemical stability | : Stable under normal conditions. | | |
| Hazardous reactions | : Will not occur. | | |
| Conditions to avoid | : Avoid contact with strong oxidizers, excessive heat, sparks or open flame. | | |
| Materials to avoid | : Material may be softened by some hydrocarbons. | | |
| Hazardous decomposition products | : Not expected to decompose under normal conditions. | | |
| Thermal decomposition | : Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed. | | |
| 1. TOXICOLOGICAL INFORMA | ΓΙΟΝ | | |
| Acute toxicity | | | |
| Acute oral toxicity | : Not classified | | |
| Acute inhalation toxicity | : Not classified | | |
| Acute dermal toxicity | : Not classified | | |
| | | | |
| Skin corrosion/irritation | : Not a skin irritant. | | |
| Serious eye damage/eye irritation | : Not an eye irritant. Mechanical irritation is possible. | | |
| | 8 / 13 | | |

| | (+) 188 | 16996168 | |
|--|----------------|--|---|
| SAFETY DATA SHEET | Poncipla | astics.com | lyondollbacoll |
| | | | lyondellbasell |
| Hifax CA1110/1GC BLK | P23444 | | Gen. Variant: SDS_US_GHS |
| Version 1.2 Revision Date | 0/02/2019 | Print Date 01/06/2 | 2022 SDS No.: BE5448 |
| | | | |
| | | | |
| Respiratory or skin | : Not classifi | ied | |
| sensitization | | | |
| Chronic toxicity | | | |
| Component Name | NTP | IARC | OSHA |
| Carbon Black | | 2B | Present |
| Carcinogenicity | : Not classif | ied | |
| | | omponent(s) listed b ic to humans. | y IARC as possibly |
| | This mater | ial is encapsulated ir | n a thermoplastic resin with |
| | and storag | | onditions of use, transportation, |
| | | | |
| Germ cell mutagenicity | : Not classif | ied | |
| | | | |
| Reproductive toxicity | | | |
| Effects on fertility / Effects on or via lactation | : Not classifi | ied | |
| Effects on Development | : Not classif | ied | |
| Target Organ Systemic Toxicant - Single exposure | | ance or mixture is no cant, single exposure | t classified as specific target |
| Target Organ Systemic Toxicant - Repeated exposure | | ance or mixture is no cant, repeated expos | t classified as specific target ure. |
| Aspiration hazard | : Not applica | able | |
| | | | |
| | | | |
| 12. Ecological information | | | |
| Ecotoxicology Assessment | | | |
| Short-term (acute) aquatic | : Not classifi | ed | |
| hazard Long-term (chronic) aquatic hazard | : Not classifi | ed | |
| | ٥ | / 13 | |
| | 9 | , 10 | |
| | | | |
| | | | |

| | (+) 18816996168 | | | |
|---|---|--|--|--|
| | Ponciplastics.com | | | |
| SAFETY DATA SHEET | lyondellbasell | | | |
| Hifor CA1110/1CC PLK | P23444 Gen. Variant: SDS_US_GHS | | | |
| Hifax CA1110/1GC BLK Version 1.2 Revision Date 1 | | | | |
| | | | | |
| | | | | |
| | | | | |
| Persistence and degradability | | | | |
| Biodegradability | Not expected to be biodegradable. | | | |
| Bioaccumulative potential | | | | |
| | | | | |
| Bioaccumulation | : This material is not expected to bioaccumulate. | | | |
| Mobility in soil | | | | |
| Mobility | : no data available | | | |
| MODINTy | | | | |
| Other adverse effects | | | | |
| Environmental fate and | This material is not volatile and insoluble in water. | | | |
| pathways | | | | |
| Other information | | | | |
| Additional ecological information | Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts. | | | |
| 13. Disposal considerations | | | | |
| Waste treatment methods | | | | |
| Product | All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible. | | | |
| | This material is classified as a Non-hazardous Material by RCRA. | | | |
| | | | | |
| | | | | |
| 14. TRANSPORT INFORMATION | | | | |
| | | | | |
| | | | | |
| 10 / 13 | | | | |
| | | | | |
| | | | | |
| | | | | |

| (+) 18816996168 |
|-----------------|
|-----------------|

Ponciplastics.com

Iyondellbase

Hifax CA1110/1GC BLK P23444

Version 1.2

Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE5448

Not regulated for transport

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

14807-96-6 Talc, Magnesium Silicate

1333-86-4 Carbon Black

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

| 14807-96-6 | Talc, Magnesium Silicate |
|------------|--------------------------|
| 1333-86-4 | Carbon Black |

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

11 / 13

 $(+)\,18816996168$

Ponciplastics.com

SAFETY DATA SHEET

Hifax CA1110/1GC BLK P23444

Version 1.2

Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE5448

lyondellbase

14807-96-6Talc, Magnesium Silicate1333-86-4Carbon Black

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

| Country/Region | Inventory | Status Description |
|--------------------------|-----------|--------------------------------|
| Australia | AICS | Compliant |
| Canada | DSL | Compliant |
| China | IECSC | Compliant |
| Europe | REACH | See REACH Compliance Statement |
| Japan | ENCS | Compliant |
| Korea | KECI | Compliant |
| New Zealand | NZIoC | Compliant |
| Philippines | PICCS | Compliant |
| United States of America | TSCA | Compliant |
| Taiwan | TCSCA | Compliant |

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

HMIS Classification

: Health Hazard: 0 Flammability: 1 Physical hazards: 0



12 / 13

