	(+) 18816996168			
AFETY DATA SHEET	Ponciplastics.com			
ALLI DATA SHELI	lyondellbase			
lifax CA387PC 183E	STEALTHGRAY Gen. Variant: SDS_US_GH			
	te 10/01/2019 Print Date 01/06/2022 SDS No.: BE9			
. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING				
Trade name CAS Number: Chemical name Synonyms	<ul> <li>Hifax CA387PC 183E STEALTH GRAY</li> <li>Mixture</li> <li>Compounded polyolefin</li> <li>Polyolefin, Compounded polymer</li> </ul>			
Identified uses	<ul> <li>Manufacture of plastic articles by injection molding, extrusion or other conversion process.</li> </ul>			
Prohibited uses	: FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications			
<u>Company Address</u> Equistar Chemicals, LP LyondellBasell Tower, Suite 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583				
Emergency telephone num EQUISTAR 800-245-4532	<u>ıber</u>			
E-mail address Responsible/issuing person	: product.safety@lyb.com			
HAZARDS IDENTIFICATION				
GHS Classification				
Combustible dust				
Label elements				
	: Warning			
Signal word	i frannig			
Signal word Hazard Statements	<ul> <li>If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.</li> </ul>			
-	<ul> <li>If small particles are generated during further processing, handling or by other means, may form combustible dust</li> </ul>			

No additional information available. COMPOSITION/INFORMATION ON INGREDIENTS Atures Components Chemical name CAS-No. Weight % Proprietary blend of polyolefinic Mixture 95.0 - 100.0 polymers Contains: Additives and stabilizers	
Instruction Control Link Honor Print Date 01/06/2022         SDS           No additional information available.            COMPOSITION/INFORMATION ON INGREDIENTS (tures)            Components            Contains:         Chemical name         CAS-No.           Veight %         95.0 - 100.0           polymers         95.0 - 100.0           Contains:         Additives and stabilizers   FIRST AID MEASURES General advice If inhaled If inhaled If inhaled If inhaled If inhaled If moteon contact If moteon warm, if necessary give Cardio-Pulm Resuscitation (CPR) In case of skin contact If moteon warm, if necessary give Cardio-Pulm Resuscitation (CPR) In case of skin contact If moteon material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this vision. Obtain immediate emergency medical attention if or extensive. In case of eye contact If no case of eye contact If no case of eye contact If in case of eye contact If is contact If in case of eye contact If is contact If in case of eye contact If is conta	base
No additional information available. COMPOSITION/INFORMATION ON INGREDIENTS ctures Components Chemical name CAS-No. Weight % Proprietary blend of polyolefinic Mixture 95.0 - 100.0 polymers Contains: Additives and stabilizers FIRST AID MEASURES General advice : Take proper precautions to ensure your own heal before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms co medical attention. In case of excessive inhalation of furmes that may during heating of this material, move the person t Obtain medical attention. Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR) In case of skin contact If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this v skin. Obtain immediate emergency medical attention if or extensive. In case of eye contact In case of eye c	S_US_G⊦
COMPOSITION/INFORMATION ON INGREDIENTS           Attures           Components <ul></ul>	No.: BE9
COMPOSITION/INFORMATION ON INGREDIENTS           Attures           Components <ul></ul>	
COMPOSITION/INFORMATION ON INGREDIENTS           Attures           Components <ul></ul>	
Chemical name         CAS-No.         Weight %           Proprietary blend of polyolefinic polymers         Mixture         95.0 - 100.0           Contains: Additives and stabilizers         Contains: Additives and stabilizers         Second Se	
Components         Chemical name       CAS-No.       Weight %         Proprietary blend of polyolefinic polymers       Mixture       95.0 - 100.0         Contains: Additives and stabilizers       Contains: Additives and stabilizers         FIRST AID MEASURES       General advice       : Take proper precautions to ensure your own heal before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms comedical attention. In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention. Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this to skin. Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minu- medical attention if discomfort persists.         In case of eye contact       : Flush eyes thoroughly with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
Chemical name         CAS-No.         Weight %           Proprietary blend of polyolefinic         Mixture         95.0 - 100.0           polymers         Ontains: Additives and stabilizers         Scotal         Scotal           FIRST AID MEASURES         General advice         : Take proper precautions to ensure your own heal before attempting rescue and providing first aid.           If inhaled         : Remove person to fresh air. If signs/symptoms comedical attention. In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention. Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)           In case of skin contact         : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this vision. Obtain immediate emergency medical attention if or extensive.           In case of eye contact         : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.           In case of eye contact         : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
Proprietary blend of polyolefinic       Mixture       95.0 - 100.0         polymers       Ontains: Additives and stabilizers         FIRST AID MEASURES       General advice       : Take proper precautions to ensure your own heal before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms comedical attention. In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention. Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this viskin. Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         In case of eye contact       : Flush eyes thoroughly with molten polymer: Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
polymers       Image: Contains: Additives and stabilizers         FIRST AID MEASURES       General advice       : Take proper precautions to ensure your own heal before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms comedical attention. In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention. Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this visit. Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
polymers       Contains: Additives and stabilizers         FIRST AID MEASURES       General advice       : Take proper precautions to ensure your own heal before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms comedical attention. In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention. Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately parage amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this vision. Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	%
FIRST AID MEASURES         General advice       : Take proper precautions to ensure your own heal before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms comedical attention. In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention. Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this vision. Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minum medical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
FIRST AID MEASURES         General advice       : Take proper precautions to ensure your own heal before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms comedical attention. In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention. Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this vision. Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minum medical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
General advice       : Take proper precautions to ensure your own heal before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms comedical attention. In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention. Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately targe amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this vision. Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
General advice       : Take proper precautions to ensure your own heal before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms comedical attention. In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention. Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this vision. Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
before attempting rescue and providing first aid.         If inhaled       : Remove person to fresh air. If signs/symptoms comedical attention. In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention. Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this vision. Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
If inhaled       : Remove person to fresh air. If signs/symptoms comedical attention.         In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention.         Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this vision.         Obtain immediate emergency medical attention if or extensive.       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes.         Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).       :	th and safe
medical attention.       In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention.         Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this vision.         Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes.         Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	in and said
medical attention.       In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention.         Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this vision.         Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes.         Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
In case of excessive inhalation of fumes that may during heating of this material, move the person to Obtain medical attention.         Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this viskin.         Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes.         Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	ontinue, ge
during heating of this material, move the person to Obtain medical attention.         Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this viskin.         Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes.         Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	he genera
Keep person warm, if necessary give Cardio-Pulm Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately arge amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this viskin.         Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes.         Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	•
In case of skin contact       : If molten material contacts the skin, immediately large amounts of water to cool the affected tissue Do not attempt to peel polymer from skin as this viskin. Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         : In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	0000
Iarge amounts of water to cool the affected tissue         Do not attempt to peel polymer from skin as this vision.         Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         : In case of eye contact with molten polymer:         : Continuously flush eye(s) with cool running water minutes.         Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	ionary
large amounts of water to cool the affected tissue         Do not attempt to peel polymer from skin as this vision.         Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         : In case of eye contact with molten polymer:         : Continuously flush eye(s) with cool running water minutes.         Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
Do not attempt to peel polymer from skin as this we skin.         Obtain immediate emergency medical attention if or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minumedical attention if discomfort persists.         : In case of eye contact with molten polymer:         Continuously flush eye(s) with cool running water minutes.         Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	lush with
<ul> <li>skin. Obtain immediate emergency medical attention if or extensive.</li> <li>In case of eye contact</li> <li>Flush eyes thoroughly with water for several minumedical attention if discomfort persists.</li> <li>In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).</li> </ul>	
or extensive. In case of eye contact : Flush eyes thoroughly with water for several minumedical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	viii ternove
<ul> <li>In case of eye contact</li> <li>Flush eyes thoroughly with water for several minumedical attention if discomfort persists.</li> <li>In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).</li> </ul>	burn is de
<ul> <li>medical attention if discomfort persists.</li> <li>In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes.</li> <li>Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).</li> </ul>	
<ul> <li>medical attention if discomfort persists.</li> <li>In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water minutes.</li> <li>Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).</li> </ul>	itos and sc
Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
Continuously flush eye(s) with cool running water minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	
minutes. Beyond flushing, DO NOT attempt to remove the adherent to the eye(s).	for at leas
adherent to the eye(s).	
	material
If swallowed : Adverse health effects due to ingestion are not ar	ticipated.
2 / 13	

	Ponciplastics.com
SAFETY DATA SHEET	lyondellbasel
Hifax CA387PC 183E ST	FAITHGRAY Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient.
5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	<ul> <li>Keep away from heat and sources of ignition.</li> <li>In case of fire hazardous decomposition products may be produced such as:</li> <li>Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).</li> </ul>
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	<ul> <li>Combustible particulate solid, will decompose under fire conditions.</li> <li>Calorific Value: 8000 - 11000 kcal/kg</li> <li>Fight fire from safe distance with hose lines or monitor nozzles Heat from fire may melt, decompose polymer, and generate flammable vapors.</li> <li>Move containers from fire area if it can be done without risk.</li> <li>Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire.</li> <li>Do not attempt to get on top of storage containers involved in fire.</li> <li>Cool storage containers with large volumes of water even after fire is out.</li> </ul>
	3 / 13

	(+) 18816996168
	Ponciplastics.com
AFETY DATA SHEET	lyondellbase
lifax CA387PC 183E S	Gen. Variant: SDS US GH
ersion 1.2 Revision Date	
ACCIDENTAL RELEASE MEAS	SURES
Personal precautions	: Equip responders with proper protection.
	Creates dangerous slipping hazard on any hard smooth
	surface. Equip emergency responders with proper personal protective
	equipment (PPE) Avoid generating dust.
	Avoid dispersal of dust in the air (i.e., clearing dust surfaces
	with compressed air). Potential combustible dust hazard.
	Polymer particles create slipping hazard on hard smooth
	surfaces.
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment /	: On land, sweep/shovel into suitable disposal containers or
Methods for cleaning up	vacuum using equipment which avoids ignition risk.
	On water, material is insoluble; collect and contain as any solid.
	All recovered material should be packaged, labeled,
	transported and disposed of or reclaimed in conformance wit applicable laws and regulations and in conformance with goo
	engineering practices. Reclaim where possible.
Handling and storage	
Precautions for safe handlin	-
Advice on safe handling	: Material is in a pellet form. If converted to small particles during further processing,
	handling, or by other means, may form combustible dust concentrations in air.
	Avoid dust accumulation in enclosed space.
	Use dust collection systems designed per NFPA 654 to avoid dust accumulation.
	Avoid generating dust; fine dust suspended in air and in the
	presence of an ignition source is a potential dust explosion hazard.
	Static discharge (spark), or other ignition sources, in high due environments may ignite the dust and result in a dust
	explosion Electrostatic charge may build during conveying or handling.
	Equipment handling polymer should be conductive and
	4 / 13

		Poncinl	astics.com				
SAFETY DATA S	HEET	i oneipi	astres.com	lyonde	ellbasell		
Hifax CA387PC	183F ST	Gen. Variant:	SDS_US_GHS				
	vision Date 10/			te 01/06/2022 SDS No.: BE9141			
grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.Fire-fighting class:Polymer will burn but does not easily ignite.Equipments for safe storage areas and containers:Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Processive dust accumulation. Store away from excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge.					s material blicable electric handling with soap and peratures vapors ntilation. See on of Fire and cessing, and r safe handling.		
Take measures to prevent the build up of electrostatic charge. Specific end use(s) : See Section 1.							
8. EXPOSURE CONTROLS/PERSONAL PROTECTION							
Control parameters Ingredients with v	workplace con	trol param	eters				
Occupational Exposure Limits							
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information		
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005			
			140				
5 / 13							

Ponciplastics.com

### SAFETY DATA SHEET

lyondellbasell

## Hifax CA387PC 183E STEALTH GRAY

Version 1.2 Revision Date

Revision Date 10/01/2019 Print Date 01/06/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE9141

Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

#### Exposure controls

#### Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

#### Personal protective equipment

Respiratory protection	<ul> <li>Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.</li> <li>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.</li> <li>Use appropriate respiratory protection where atmosphere exceeds recommended limits.</li> <li>Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.</li> </ul>
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

	(1)10010330100
AFETY DATA SHEET	Ponciplastics.com
	I I I I
lifax CA387PC 183E S ersion 1.2 Revision Date	
	10/01/2013 Thin Date 01/00/2022 000 No DE0
	injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	<ul> <li>Selection of appropriate personal protective equipment shoul be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.</li> <li>Use good personal hygiene practices.</li> <li>Wash hands before eating, drinking, smoking, or using toilet facilities.</li> <li>Take off contaminated clothing and wash before reuse.</li> </ul>
PHYSICAL AND CHEMICAL P Appearance	: Pellets.
Color	: gray
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
	: Not applicable.
Vapor pressure	
Vapor pressure Density	: <1 g/cm3
	: <1 g/cm3 : Insoluble.

(+) <b>18816996168</b>
------------------------

	(1)10010550100			
SAFETY DATA SHEET	Ponciplastics.com			
	I TI III			
Hifax CA387PC 183E S Version 1.2 Revision Date				
Partition coefficient: n-	: No Data Available.			
octanol/water Viscosity, dynamic	: Not applicable.			
Relative vapor density	: Not applicable.			
Evaporation rate	: Not applicable.			
Explosive properties	: No Data Available.			
Other Information	: No additional information available.			
0. STABILITY AND REACTIVITY	/			
Reactivity	: No known reactivity hazards.			
Chemical stability	: Stable under normal conditions.			
Hazardous reactions	: Will not occur.			
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.			
Materials to avoid	: Material may be softened by some hydrocarbons.			
Hazardous decomposition	: Not expected to decompose under normal conditions.			
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.			
1. TOXICOLOGICAL INFORMAT	ΓΙΟΝ			
Acute toxicity				
Acute oral toxicity	: Not classified			
Acute inhalation toxicity	: Not classified			
Acute dermal toxicity	: Not classified			
Skin corrosion/irritation	: Not a skin irritant.			
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.			
	8 / 13			

	(+) 1881	6996168			
SAFETY DATA SHEET	Poncipla	stics.com			
SAFELY DATA SHEET				yonde	llbasell
Hifax CA387PC 183E ST	EALTHG	RAY	(	Gen. Variant:	SDS_US_GHS
Version 1.2 Revision Date 10		Print Date 0	1/06/202	2 SE	OS No.: BE9141
Respiratory or skin sensitization	Not classifie	ed			
Chronic toxicity					
Component Name Titanium Dioxide	NTP	IARC 2B		OSHA Present	
Carbon Black		2B		Present	
- · · · ·			•		
Carcinogenicity	Not classifie	ed			
	Not classifie				
		omponent(s) lis	sted by 1	ARC as possil	oly
	This materia	al is encapsula			
		ase under norr	mal cond	litions of use, t	transportation,
	and storage				
Germ cell mutagenicity	: Not classifie	he			
Cerni cen matagementy					
Reproductive toxicity					
•	Not classifie	ed			
Effects on or via lactation					
Effects on Development	Not classifie	ed			
Townet Owners Sweternia			in motio		aifia taraat
Target Organ Systemic Toxicant - Single exposure		nce or mixture ant, single exp		assined as spo	echic target
Target Organ Systemic	. The substa	nce or mixture	is not c	lassified as sn	ecific target
Toxicant - Repeated		ant, repeated		•	come target
exposure					
Aspiration hazard	Not applicat	ole.			
12. Ecological information					
12. Leological mormation					
Ecotoxicology Assessment					
<b>``</b> , <b>`</b> , <b>`</b>	Not classifie	ed			
hazard Long-term (chronic)	: Not classifie	ed			
·	9,	/ 13			

	(+) 18816996168		
SAFETY DATA SHEET	Ponciplastics.com		
SALETT DATA SHEET	lyondellbasell		
Hifax CA387PC 183E ST	<b>EALTHGRAY</b> Gen. Variant: SDS_US_GHS		
Version 1.2 Revision Date 1	0/01/2019 Print Date 01/06/2022 SDS No.: BE9141		
aquatic hazard			
Persistence and degradability			
Biodegradability	: Not expected to be biodegradable.		
Bioaccumulative potential			
Bioaccumulation	: This material is not expected to bioaccumulate.		
Mobility in soil			
Mobility	: no data available		
Other adverse effects			
Environmental fate and pathways	: This material is not volatile and insoluble in water.		
Other information			
Additional ecological information	: Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.		
13. Disposal considerations			
Waste treatment methods			
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.		
	: This material is classified as a Non-hazardous Material by RCRA.		
14. TRANSPORT INFORMATION			
	10 / 13		

(+) <b>18816996168</b>	+)	1881	699	6168
------------------------	----	------	-----	------

Ponciplastics.com

## SAFETY DATA SHEET

- Iyondellbase

Hifax CA387PC 183E STEALTH GRAY

Version 1.2

Revision Date 10/01/2019 Print Date 01/06/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE9141

1/06/2022

Not regulated for transport

#### 15. REGULATORY INFORMATION

#### TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

#### Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

#### SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

#### SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

#### Combustible dust

#### SARA 313

This product contains no known chemicals regulated under SARA 313.

#### State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

1333-86-4 Carbon Black

No components are subject to the Massachusetts Right to Know Act.

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

1333-86-4 Carbon Black

11 / 13

 $(+)\,18816996168$ 

Ponciplastics.com

## SAFETY DATA SHEET

lyondellbasell

## Hifax CA387PC 183E STEALTH GRAY

Version 1.2

Revision Date 10/01/2019 Print Date 01/06/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE9141

#### Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Not Determined
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

#### REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.


#### **16. OTHER INFORMATION**

**HMIS Classification** 

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

: Health Hazard: 0 Flammability: 1 Physical hazards: 0



12 / 13

