	(+) 18	816996168			
	Poncip	<b>816996168</b> lastics.com			
SAFETY DATA SHEET according to Regulation (EC) No. 190	07/2006		lyondellbasell		
Hifax EP3080G			Gen. Variant: SDS_AT		
Version 1.4 Revision Date (	5/23/2020	Print Date 01	/07/2022 SDS No.: BE7996		
1. Identification of the substance/m	ixture and o	f the company/u	Indertaking		
1.1 Product identifier					
Trade name : Synonyms :	Copolymer	opylene copolym	ier, 1-Propene-Ethylene-		
Substance name : Substance No. :	1-Propene, 9010-79-1	Polymer with Eth	nene		
Chemical characterization :		ne copolymer			
1.2 Relevant identified uses of the	substance or	mixture and use	es advised against		
Identified uses :		e of plastic article version process.	es by injection molding, extrusion		
Prohibited uses :	devices; He Applications	alth Canada clas	es; European class III medical is IV Medical Devices; nent implantation into the body; cations		
1.3 Details of the supplier of the safety data sheet					
<b>Company</b> Basell Sales & Marketing Company Delftseplein 27E 3013 AA Rotterdam Netherlands		Registration nur NA	mber Telephone 31 (0) 10 275 55 00		
E-mail address : Responsible/issuing person	product.safety	@lyb.com			
1.4 Emergency telephone number					
Basell Sales & Marketing Company	B.V.		+32 3 575 1235		
Poison Center: Gesundheid Österreich GMBH AT: +43 1 406 43 43 24 hours all days					
		4/40			
		1 / 16			



according to Regulation (EC) No. 1907/2006

## Hifax EP3080G

Version 1.4

Print Date 01/07/2022

SDS No.: BE7996

lyondellbasell

Gen. Variant: SDS AT

#### 2. Hazards identification

### 2.1 Classification of the substance or mixture

### Classification (REGULATION (EC) No 1272/2008)

Revision Date 05/23/2020

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

### 2.2 Label elements

### Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

### 2.3 Other hazards

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

### 3. Composition/information on ingredients

#### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC) No 1272/2008)	<u>Weight %</u>
1-Propene, Polymer with Ethene	9010-79-1	Not Classified	98.0 - 100.0 %

Contains: Additives and stabilizers

#### 4. First aid measures

#### 4.1 Description of first-aid measures

General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.

If inhaled

: Remove person to fresh air. If signs/symptoms continue, get

 $(+)\,18816996168$ Ponciplastics.com

medical attention if discomfort persists.         :       In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       :       Adverse health effects due to ingestion are not anticipated.         2 Most important symptoms and effects, both acute and delayed       .         Symptoms       :       Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       :       Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         3 Indication of any immediate medical attention and special treatment needed Treatment       :         Fire-fighting measures       :				
medical attention.         In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air.         Obtain medical attention.         Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)         In case of skin contact       : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer.         Do not attempt to peel polymer from skin as this will remove the skin.       Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists.         In case of eye contact       : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes.         Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s).       Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.         2 Most important symptoms and effects, both acute and delayed       Symptoms         Symptoms       : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         3 Indication of any immediate medical attention and special treatment needed       Treatment of overexposure should be directed at the				
In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 2 Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient.				
Iarge amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and seel medical attention if discomfort persists.         : In case of eye contact       : Flush eyes thoroughly with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.         2 Most important symptoms and effects, both acute and delayed         Symptoms       : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         3 Indication of any immediate medical attention and special treatment needed         Treatment       : Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient.		In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary		
or extensive.         In case of eye contact       : Flush eyes thoroughly with water for several minutes and seed medical attention if discomfort persists.         : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       : Adverse health effects due to ingestion are not anticipated.         2 Most important symptoms and effects, both acute and delayed         Symptoms       : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         3 Indication of any immediate medical attention and special treatment needed         Treatment       : Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient.         Fire-fighting measures       :	In case of skin contact	large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin.		
medical attention if discomfort persists.         :       In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.         If swallowed       :       Adverse health effects due to ingestion are not anticipated.         2 Most important symptoms and effects, both acute and delayed       .         Symptoms       :       Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       :       Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         3 Indication of any immediate medical attention and special treatment needed       :         Treatment       :       Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient.				
Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. <b>2 Most important symptoms and effects, both acute and delayed</b> Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. <b>3 Indication of any immediate medical attention and special treatment needed</b> Treatment : Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient. <b>Fire-fighting measures</b>	In case of eye contact	: Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists.		
2 Most important symptoms and effects, both acute and delayed         Symptoms       : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         3 Indication of any immediate medical attention and special treatment needed         Treatment       : Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient.         Fire-fighting measures		Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s).		
Symptoms       : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.         Hazards       : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         3 Indication of any immediate medical attention and special treatment needed         Treatment       : Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient.         Fire-fighting measures	If swallowed	: Adverse health effects due to ingestion are not anticipated.		
Hazards       : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.         3 Indication of any immediate medical attention and special treatment needed         Treatment       : Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient.         Fire-fighting measures	2 Most important symptoms	and effects, both acute and delayed		
Molten polymer may cause thermal burns. 3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control o symptoms and the clinical condition of the patient. Fire-fighting measures	Symptoms			
Treatment : Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient. Fire-fighting measures	Hazards	•		
symptoms and the clinical condition of the patient.	3 Indication of any immediat	e medical attention and special treatment needed		
	Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.		
	Fire-fighting measures			
1 Extinguishing media	1 Extinguishing media			
3 / 16		3 / 16		

SAFETY DATA SHEET according to Regulation (EC) No. 1	(+) 18816996168 Ponciplastics.com
Hifax EP3080G Version 1.4 Revision Date	Gen. Variant: SDS_AT
Suitable extinguishing media	<ul> <li>SMALL FIRE: Use dry chemical, CO2, or water spray.</li> <li>LARGE FIRES:</li> </ul>
Unsuitable extinguishing media	Use water spray hose nozzles from a safe location. : None known.
5.2 Special hazards arising from	he substance or mixture
Specific hazards during fire fighting	<ul> <li>Keep away from heat and sources of ignition.</li> <li>In case of fire hazardous decomposition products may be produced such as:</li> <li>Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).</li> </ul>
5.3 Advice for firefighters	
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	<ul> <li>Combustible particulate solid, will decompose under fire conditions.</li> <li>Calorific Value: 8000 - 11000 kcal/kg</li> <li>Fight fire from safe distance with hose lines or monitor nozzles.</li> <li>Heat from fire may melt, decompose polymer, and generate flammable vapors.</li> <li>Move containers from fire area if it can be done without risk.</li> <li>Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container.</li> <li>Always stay away from tanks engulfed in fire.</li> <li>Do not attempt to get on top of storage containers involved in fire.</li> <li>Cool storage containers with large volumes of water even after fire is out.</li> </ul>
6. Accidental release measures	
6.1 Personal precautions, protect	ve equipment and emergency procedures
Personal precautions	: Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface.
	4 / 16

SAFETY DATA SHEET according to Regulation (EC) No. 190	(+) 18816996168 Ponciplastics.com
Hifax EP3080G	Gen. Variant: SDS_AT
Version 1.4 Revision Date 0	Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.
6.2 Environmental precautions Environmental precautions :	Do not flush into surface water or sanitary sewer system.
6.3 Methods and materials for conta	ainment and cleaning up
Methods for containment / : Methods for cleaning up	On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
7. Handling and storage	
7.1 Precautions for safe handling Advice on safe handling :	Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers involved in the transfer of this material
	5 / 16

	(+) 18	8816996168 plastics.com		
SAFETY DATA SHEET	Ponci	plastics.com	lvood	امالهمدمال
according to Regulation (EC) N	lo. 1907/2006		Iyunu	ellbasell
Hifax EP3080G Version 1.4 Revision	Date 05/23/2020	Print Date 01	Gen. Varian	t: SDS_AT SDS No.: BE7996
	Jale 03/23/2020	Finit Date of	10112022	303 NO.: DE7990
	All electric: codes and combustibl After handl water. When bring	regulatory require e dusts. ing, always wash ging the material t op may condense	ded. Id conform to appli ments for areas ha hands thoroughly o processing tempe in the exhaust vent	andling with soap and eratures vapors
Fire-fighting class	: Polymer w	ill burn but does n	ot easily ignite.	
7.2 Conditions for safe storag	e, including any	incompatibilities		
Requirements for storage areas and containers	and handlin should be Store away oxidizing a Keep conta	housekeeping prac ng. Process enclo used to avoid exco / from excessive h gents. ainer closed to pre	ctices during storag sures and adequate essive dust accume leat and away from event contamination he build up of electr	e ventilation ulation. a strong
7.3 Specific end use(s)	: See Sectio	n 1.2.		
8. Exposure controls/personal	protection			
8.1 Control parameters				
Ingredients with workpla	ce control param	eters		
Occupational Exposure L	imits.			
Components CAS	S-No. Type	Limit Value	Basis Revision Date	Additional Information
		6 / 16		



according to Regulation (EC) No. 1907/2006

Revision Date 05/23/2020

## Hifax EP3080G

Version 1.4

Print Date 01/07/2022

SDS No.: BE7996

lyondellbasell

Gen. Variant: SDS AT

Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		VA	10 mg/m3 inhalable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TV	VA	3 mg/m3 respirable	US (ACGIH) 2005	

Consult local authorities for acceptable exposure limits.

#### 8.2 Exposure controls

#### Engineering measures

Follow the recommendations in international standard NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

#### Personal protective equipment

Respiratory protection	<ul> <li>Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.</li> <li>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.</li> <li>Use appropriate respiratory protection where atmosphere exceeds recommended limits.</li> <li>Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.</li> </ul>
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
	7 / 16

	(+) <b>18816996168</b> Ponciplastics.com	
	Ponciplastics.com	
SAFETY DATA SHEET according to Regulation (EC) No. 1	1907/2006	lyondellbasell
Hifax EP3080G		Gen. Variant: SDS_AT
Version 1.4 Revision Date	e 05/23/2020 Print Date 01,	/07/2022 SDS No.: BE7996
Eye and face protection	: Dust service goggles should injury or other irritation to eye may result from handling this	s due to airborne particles which
Skin and body protection	: Wear suitable protective cloth	ning.
Hygiene measures	be based on an evaluation of of the protective equipment re performed, conditions presen hazards and/or potential haza during use. Use good personal hygiene p	t, duration of use, and the ards that may be encountered practices. rinking, smoking, or using toilet
Environmental exposure con	ntrols	
General advice	: See section 6.	
9. Physical and chemical propert 9.1 Information on basic physical		
Appearance	: Pellets.	
Color	: Translucent to white	
Odor	: Slight.	
Flash point	: No Data Available.	
Lower explosion limit	: The minimum explosive conc varies according to particle si	entration (MEC) for polymer dust ze distribution.
Upper explosion limit	: Not applicable.	
Flammability (solid, gas)	: Polymer will burn but does no	ot easily ignite.
Oxidizing properties	: Not considered an oxidizing a	agent.
Autoignition temperature	: > 300 °C	
	8 / 16	

SAFETY DATA SHEET according to Regulation (EC) No.	(+) 18816996168 Ponciplastics.com 1907/2006
Hifax EP3080G	Gen. Variant: SDS_AT
Version 1.4 Revision Dat	te 05/23/2020 Print Date 01/07/2022 SDS No.: BE7996
Decomposition temperature Melting point/range Boiling point/boiling range	<ul> <li>not determined</li> <li>50 - 170 °C</li> <li>Not applicable.</li> </ul>
Vapor pressure	: Not applicable.
Density	: <1 g/cm3
Water solubility	: Insoluble.
Partition coefficient: n-	: No Data Available.
octanol/water Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
9.2 Other information	. No additional information quallele
Other information	: No additional information available.
10. Stability and reactivity	
10.1 Reactivity	
No known reactivity hazards.	
10.2 Chemical stability	
Stable under normal condition	ıs.
10.3 Possibility of hazardous rea	actions
Hazardous reactions	: Will not occur.
10.4 Conditions to avoid	
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
	9 / 16

SAFETY DATA SHEET	(+) 18816996168 Ponciplastics.com
according to Regulation (EC) No.	1907/2006 Gen. Variant: SDS AT
Hifax EP3080G Version 1.4 Revision Dat	—
<ul> <li>10.5 Incompatible materials Materials to avoid</li> <li>10.6 Hazardous decomposition p Hazardous decomposition products Thermal decomposition</li> </ul>	<ul> <li>Material may be softened by some hydrocarbons.</li> <li>broducts</li> <li>Not expected to decompose under normal conditions.</li> <li>Note: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.</li> </ul>
<ul> <li>11. Toxicological information</li> <li>11.1 Information on toxicologica</li> <li>Acute toxicity</li> </ul>	effects
Acute oral toxicity	Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
Respiratory or skin sensitization	: Not classified
Chronic toxicity	
Carcinogenicity	: Not classified
	10 / 16

SAFETY DATA SHEET according to Regulation (EC) No. 7 Hifax EP3080G Version 1.4 Revision Date		Gen. Variant: SDS_AT 07/2022 SDS No.: BE7996
Germ cell mutagenicity	: Not classified	
<b>Reproductive toxicity</b> Effects on fertility / Effects on or via lactation Effects on Development	: Not classified : Not classified	
Target Organ Systemic Toxi	cant - Single exposure	
	: The substance or mixture is r organ toxicant, single exposu	not classified as specific target re.
Target Organ Systemic Toxi	cant - Repeated exposure	
	: The substance or mixture is r organ toxicant, repeated expo	· •
Aspiration hazard	: Not applicable.	
12. Ecological information		
12.1 Ecotoxicology Assessment		
Short-term (acute) aquatic	: Not classified	
hazard Long-term (chronic) aquatic hazard	: Not classified	
12.2 Persistence and degradability	ity	
Biodegradability	: Not expected to be biodegrad	able.
12.3 Bioaccumulative potential		
Bioaccumulation	: This material is not expected	to bioaccumulate.
	11 / 16	

SAFETY DATA SHEET	(+) 18816996168 Ponciplastics.com		
I I III II			
Hifax EP3080G Version 1.4 Revision Da	Gen. Variant: SDS_AT te 05/23/2020 Print Date 01/07/2022 SDS No.: BE7996		
12.4 Mobility in soil			
Mobility	: no data available		
12.5 Results of PBT and vPvB a	ssessment		
Result	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).		
12.6 Other adverse effects			
Environmental fate and pathways	: This material is not volatile and insoluble in water.		
12.7 Other information			
Additional ecological information	Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.		
13. Disposal considerations			
13.1 Waste treatment methods			
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.		
14. Transport information			
	12 / 16		



according to Regulation (EC) No. 1907/2006

Revision Date 05/23/2020

## Hifax EP3080G

Version 1.4

Print Date 01/07/2022

SDS No.: BE7996

lyondellbasell

Gen. Variant: SDS AT

Not regulated for transport

### 15. Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **REACh** status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

#### Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

Contact product.safety@lyb.com for additional global inventory information.

#### 15.2 Chemical safety assessment

No information available.



according to Regulation (EC) No. 1907/2006

### Hifax EP3080G

Version 1.4

Print Date 01/07/2022

SDS No.: BE7996

lvondellbasell

Gen. Variant: SDS\_AT

#### 16. OTHER INFORMATION

#### Material safety datasheet sections which have been updated:

Revision Date 05/23/2020

Revised Section(s): 15 Abbreviations and Acronyms

ACGIH - American Conference of Governmental Industrial Hygienists ACGIH BEIs - American Conference of Governmental Industrial Hygienists Biological Exposure Indices ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road AICS - Australian Inventory of Chemical Substances ASTM - American Society for Testing and Materials **BEL - Biological Exposure Limits** BTEX - Benzene, Toluene, Ethylbenzene, Xylenes CAS - Chemical Abstracts Service **CEFIC - European Chemical Industry Council** CLP - Classification Packaging and Labelling COC - Cleveland Open-Cup CS - Consumer Scenario DIN - Deutsches Institut für Normung DN(M)EL - Derived No (Minimal) Effect Level DSL - Canada Domestic Substance List EC - European Commission EC50 - Median Effective Concentration ECETOC - European Center on Ecotoxicology and Toxicology of Chemicals ECHA - European Chemicals Agency EL50 - Effective Loading fifty ELINCS - EHR-Lab Interoperability and Connectivity Specification ENCS - Japanese Existing and New Chemical Substances Inventory ERC - Environmental Release Category EUSES - European Union System for the Evaluation of Substances EWC - European Waste Code GHS - Globally Harmonized System of Classification and Labelling of Ch IARC - International Agency for Research on Cancer IATA - International Air Transport Association IC50 - Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG - International Maritime Dangerous Goods **IECSC** - Chinese Chemicals Inventory **IOELV - Indicative Occupational Exposure Limit Values** IP346 - Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables KECI - Korea Existing Chemicals Inventory Koc - Organic Carbon/Water Partition Coefficient



according to Regulation (EC) No. 1907/2006

## Hifax EP3080G

Version 1.4

Revision Date 05/23/2020 Print Date 01/07/2022

SDS No.: BE7996

lvondellbasel

Gen. Variant: SDS\_AT

LC50 - Lethal Concentration fifty LD50 - Lethal Dose fifty per cent. LL/EL/IL - Lethal Loading/Effective Loading/Inhibitory Loading LL50 - Lethal Loading fifty MAK Commission - Permanent Senate Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area MARPOL - International Convention for the Prevention of Pollution from Ships No. - Number NOEC/NOEL - No Observed Effect Concentration / No Observed Effect Level NZIoC - New Zealand Inventory of Chemicals OE\_HPV - Occupational Exposure - High Production Volume OECD - Organization for Economic Co-operation and Development **OEL - Occupational Exposure Limit** PBT - Persistent, Bio accumulative and Toxic PICCS - Philippine Inventory of Chemicals and Chemical Substances PNEC - Predicted No Effect Concentration PPE - Personal Protective Equipment PROC - Process Category QSAR - Quantitative Structure-Activity Relationship REACh - Registration Evaluation and Authorization of Chemicals RID - Regulations Relating to International Carriage of Dangerous Goods by Rail SDS - Safety Data Sheet SKIN\_DES - Skin Designation STEL - Short term exposure limit STP - Standard Temperature and Pressure TCSCA - Taiwan inventory of chemicals TGD - Technical Guidance Document TRA - Targeted Risk Assessment TSCA - US Toxic Substances Control Act TWA - Time-Weighted Average UN - United Nations vPvB - very Persistent and very Bioaccumulative WGK - German Water Endangerment Class

#### Disclaimer

Multiple legal entities and registration numbers may be displayed in Section 1. The Recipient shall refer to the shipping documents to identify the legal entity that supplied this product.

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.



according to Regulation (EC) No. 1907/2006

## Hifax EP3080G

Version 1.4

Revision Date 05/23/2020

Print Date 01/07/2022

SDS No.: BE7996

lvondellbasell

Gen. Variant: SDS AT

#### Disclaimer

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

#### Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

#### Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

#### End of Material Safety Data Sheet