	(+) 1	8816996168		
SAFETY DATA SHEET	Ponci	8816996168 plastics.com	luor	عطماللهمجمال
according to Regulation (EC) No. 190			i iyui	ndellbasell
Hifax EYC 361P G13063			Gen. Va	ariant: SDS_AT
Version 1.2 Revision Date 0)1/26/2022	Print Date 02	2/25/2022	SDS No.: BE8011
1. Identification of the substance/m	ixturo and	of the company/u	ndortaking	
		or the company/u	ndentaking	
1.1 Product identifier				
Trade name : Synonyms :		361P G13063 Compounded poly	mer	
Substance name :		led polyolefin		
1.2 Relevant identified uses of the	substance o	or mixture and us	es advised aç	yainst
Identified uses :		re of plastic article process.		molding, extrusion
Prohibited uses :	devices; H Applicatior	s III medical device lealth Canada clas ns involving permai ning medical applic	s IV Medical D nent implantat)evices;
1.3 Details of the supplier of the safe Company Basell Sales & Marketing Company Delftseplein 27E 3013 AA Rotterdam Netherlands E-mail address : Responsible/issuing person	B.V.	eet Registration nui NA ty@lyb.com		Felephone 31 (0) 10 275 55 00
1.4 Emergency telephone number				
Basell Sales & Marketing Company	B.V.		+3	32 3 575 1235
Poison Center: Gesundheid Österreich GMBH AT: +43 1 406 43 43 24 hours all days				
2. Hazards identification				
2.1 Classification of the substance	or mixture			
		1 / 16		
		1/10		

(+) 18816996168

Ponciplastics.com

according to Regulation (EC) No. 1907/2006

Hifax EYC 361P G13063

Version 1.2

Revision Date 01/26/2022

Print Date 02/25/2022

SDS No.: BE8011

lyondellbasell

Gen. Variant: SDS AT

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

2.3 Other hazards

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

3. Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC) No 1272/2008)	<u>Weight %</u>
Proprietary blend of polyolefinic polymers	Mixture		80.0 - 100.0 %

Contains: Additives, stabilizers and fillers

4. First aid measures

4.1 Description of first-aid measures

General advice	: Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.
If inhaled	 Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary
	2 / 16

 $(+)\,18816996168$

Ponciplastics.com



according to Regulation (EC) No. 1907/2006

Version 1.2 Revision Date 01/26/2022 Print Date 02/25/2022 SDS No.: BE8 Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 4.2 Most important symptoms and effects, both acute and delayed : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.	Hifax EYC 361P G1306	Gen. Variant: SDS_AT
In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 4.2 Most important symptoms and effects, both acute and delayed Symptoms Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.		
In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 4.2 Most important symptoms and effects, both acute and delayed Symptoms Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.		
Iarge amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 4.2 Most important symptoms and effects, both acute and delayed : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.		Resuscitation (CPR)
medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 4.2 Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.	In case of skin contact	large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep
Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. 4.2 Most important symptoms and effects, both acute and delayed Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.	In case of eye contact	
 4.2 Most important symptoms and effects, both acute and delayed Symptoms Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 		Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s).
Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.	If swallowed	: Adverse health effects due to ingestion are not anticipated.
 in the nose and throat and coughing. Hazards Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. 4.3 Indication of any immediate medical attention and special treatment needed Treatment Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 	.2 Most important symptoms an	d effects, both acute and delayed
4.3 Indication of any immediate medical attention and special treatment needed Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.	Symptoms	
Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.	Hazards	
symptoms and the clinical condition of the patient.	.3 Indication of any immediate n	nedical attention and special treatment needed
5. Fire-fighting measures	Treatment	
	. Fire-fighting measures	
5.1 Extinguishing media	1 Extinguishing media	
Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray.	Suitable extinguishing media	
: LARGE FIRES: Use water spray hose nozzles from a safe location.		
3 / 16		3 / 16

Hifax EYC 361P G13063

 $(+)\,18816996168$

Ponciplastics.com

according to Regulation (EC) No. 1907/2006

Gen. Variant: SDS_AT

Version 1.2

Revision Date 01/26/2022

Print Date 02/25/2022

SDS No.: BE8011

Unsuitable extinguishing media	: None known.
5.2 Special hazards arising from t	the substance or mixture
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
5.3 Advice for firefighters	
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
6. Accidental release measures	
6.1 Personal precautions, protect	ive equipment and emergency procedures
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth
	4 / 16
	4710

 $(+)\,18816996168$

Ponciplastics.com

according to Regulation (EC) No. 1907/2006

Hifax EYC 361P G13063

Version 1.2

Revision Date 01/26/2022

Gen. Variant: SDS_AT Print Date 02/25/2022

SDS No.: BE8011

	surfaces.
6.2 Environmental precautions	
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
6.3 Methods and materials for co	ntainment and cleaning up
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
7. Handling and storage	
7.1 Precautions for safe handling	

Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See
	5 / 16

(+) 18816996168

Ponciplastics.com

according to Regulation (EC) No. 1907/2006

lvondellbasell Gen. Variant: SDS AT Hifax EYC 361P G13063 Version 1.2 Revision Date 01/26/2022 Print Date 02/25/2022 SDS No.: BE8011 section 10. Fire-fighting class : Polymer will burn but does not easily ignite. 7.2 Conditions for safe storage, including any incompatibilities Requirements for storage : Store in a dry location. areas and containers Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. 7.3 Specific end use(s) : See Section 1.2. 8. Exposure controls/personal protection 8.1 Control parameters Ingredients with workplace control parameters

Occupational Exposure Limits

Components	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can		TWA	10 mg/m3	US (ACGIH)	
be formed when			inhalable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	3 mg/m3	US (ACGIH)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					

6/16



Ponciplastics.com

according to Regulation (EC) No. 1907/2006

Hifax EYC 361P G13063

Version 1.2

Revision Date 01/26/2022

Print Date 02/25/2022

SDS No.: BE8011

lyondellbasell

Gen. Variant: SDS AT

Consult local authorities for acceptable exposure limits.

8.2 Exposure controls

Engineering measures

Follow the recommendations in international standard NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet
	7 / 16

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
according to Regulation (EC) No. 1	
Hifax EYC 361P G13063	
Version 1.2 Revision Date	01/26/2022 Print Date 02/25/2022 SDS No.: BE8011
	facilities.
	Take off contaminated clothing and wash before reuse.
Environmental exposure cont	
General advice	: See section 6.
0. Dhurical and shamical proporti	
9. Physical and chemical propertie	
9.1 Information on basic physical	and chemical properties : pellets
Appearance	solid
Color	: black
Odor	: Slight.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: <1 g/cm3
Water solubility	: Insoluble.
Partition coefficient: n-	: No Data Available.
	8 / 16

(+) 18816996168

	(+) 18810990108			
SAFETY DATA SHEET	1907/2006 Iyondellbasell			
according to Regulation (EC) No. 7	1907/2006 Iyondenbasen			
Hifax EYC 361P G1306	3 Gen. Variant: SDS_AT			
Version 1.2 Revision Date	e 01/26/2022 Print Date 02/25/2022 SDS No.: BE8011			
octanol/water				
Viscosity, dynamic	: Not applicable.			
Relative vapor density	: Not applicable.			
Evaporation rate	: Not applicable.			
Explosive properties	: No Data Available.			
9.2 Other information				
Other information	: No additional information available.			
10. Stability and reactivity				
10.1 Reactivity				
No known reactivity hazards.				
10.2 Chemical stability				
Stable under normal conditions.				
10.3 Possibility of hazardous reactions				
Hazardous reactions	: Will not occur.			
10.4 Conditions to avoid				
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.			
10.5 Incompatible materials				
Materials to avoid	: Material may be softened by some hydrocarbons.			
10.6 Hazardous decomposition p	products			
Hazardous decomposition	: Not expected to decompose under normal conditions.			
products Thermal decomposition	: Note: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.			


	(+) 18816996168				
SAFETY DATA SHEET	1907/2006 Inciplastics.com				
according to Regulation (EC) No.					
Hifax EYC 361P G130					
Version 1.2 Revision Da	ate 01/26/2022 Print Date 02/25/2022 SDS No.: BE801				
·····					
11. Toxicological information 11.1 Information on toxicologica	al offects				
Acute toxicity					
Acute oral toxicity	:				
	Not classified				
Acute inhalation toxicity	: Not classified				
Acute dermal toxicity	: Not classified				
Skin corrosion/irritation	: Not a skin irritant.				
Serious eye damage/eye	: Not an eye irritant.				
irritation	Mechanical irritation is possible.				
Respiratory or skin sensitization	: Not classified				
Chronic toxicity					
Carainagoniaity	: Not classified				
Carcinogenicity					
Germ cell mutagenicity	: Not classified				
Reproductive toxicity					
Effects on fertility / Effects on or via lactation	: Not classified				
Effects on Development	: Not classified				
Target Organ Systemic Tox	icant - Single exposure				
	: The substance or mixture is not classified as specific target organ toxicant, single exposure.				
	10 / 16				

	(+) 1881699616	8			
SAFETY DATA SHEET	Ponciplastics.co				
according to Regulation (EC) No. 190	7/2006	🗂 lyondellbasell			
Hifax EYC 361P G13063 Gen. Variant: SDS_AT					
Version 1.2 Revision Date 01	/26/2022 Print Date	e 02/25/2022 SDS No.: BE8011			
Townet Owner Customic Towice	t Demosted everence				
Target Organ Systemic Toxican		is not classified as specific target			
	organ toxicant, repeated e				
Aspiration hazard :	Not applicable.				
12. Ecological information					
12.1 Ecotoxicology Assessment					
	Not classified				
hazard	Not classified				
aquatic hazard	Not classified				
12.2 Persistence and degradability					
Biodegradability :	Not expected to be biodeg	gradable.			
12.3 Bioaccumulative potential		5			
12.5 Divaccumulative potential					
Bioaccumulation :	This material is not expec	ted to bioaccumulate.			
12.4 Mobility in soil					
Mobility :	no data available				
12.5 Results of PBT and vPvB assessment					
Result :		ontains no components considered baccumulative and toxic (PBT) or			
	very persistent and very b				
12.6 Other adverse effects					
Environmental fate and :	This material is not volatile	e and insoluble in water.			
11 / 16					

	(+) 18816996168				
SAFETY DATA SHEET	(+) 18816996168 Ponciplastics.com	lvoodellbacell			
according to Regulation (EC) No. 19		lyondellbasell			
Hifax EYC 361P G13063 Gen. Variant: SDS_AT					
Version 1.2 Revision Date (25/2022 SDS No.: BE8011			
pathways					
12.7 Other information					
Additional ecological information	: Ecotoxicity is expected to be r solubility of polymers. No data available on this prod other wildlife may eat pellets v intestinal tracts.	luct. However, birds, fish and			
13. Disposal considerations					
13.1 Waste treatment methods					
Product		or reclaimed in conformance with as and in conformance with good			
14. Transport information					
Not regulated for transport					
15. Regulatory information					
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture					
REACh status If the product has been purchased registered in the European Union registered under REACh, in acco 1907/2006)	, we confirm that all substances				
	12 / 16				

 $(+)\,18816996168$

Ponciplastics.com



Hifax EYC 361P G13063

Version 1.2

Revision Date 01/26/2022

Print Date 02/25/2022

SDS No.: BE8011

lvondellbasell

Gen. Variant: SDS AT

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

Contact product.safety@lyb.com for additional global inventory information.

15.2 Chemical safety assessment

No information available.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 1 15 Abbreviations and Acronyms

ACGIH - American Conference of Governmental Industrial Hygienists

ACGIH_BEIs - American Conference of Governmental Industrial Hygienists_Biological Exposure Indices

ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road AICS - Australian Inventory of Chemical Substances

ASTM - American Society for Testing and Materials

BEL - Biological Exposure Limits

BTEX - Benzene, Toluene, Ethylbenzene, Xylenes

CAS - Chemical Abstracts Service

CEFIC - European Chemical Industry Council

13 / 16

(+) **18816996168**

Ponciplastics.com

according to Regulation (EC) No. 1907/2006

Hifax EYC 361P G13063

Version 1.2

Revision Date 01/26/2022

Print Date 02/25/2022

SDS No.: BE8011

lvondellbasell

Gen. Variant: SDS AT

CLP - Classification Packaging and Labelling COC - Cleveland Open-Cup CS - Consumer Scenario DIN - Deutsches Institut für Normuna DN(M)EL - Derived No (Minimal) Effect Level DSL - Canada Domestic Substance List EC - European Commission EC50 - Median Effective Concentration ECETOC - European Center on Ecotoxicology and Toxicology of Chemicals ECHA - European Chemicals Agency EL50 - Effective Loading fifty ELINCS - EHR-Lab Interoperability and Connectivity Specification ENCS - Japanese Existing and New Chemical Substances Inventory ERC - Environmental Release Category EUSES - European Union System for the Evaluation of Substances EWC - European Waste Code GHS - Globally Harmonized System of Classification and Labelling of Ch IARC - International Agency for Research on Cancer IATA - International Air Transport Association IC50 - Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG - International Maritime Dangerous Goods **IECSC - Chinese Chemicals Inventory IOELV - Indicative Occupational Exposure Limit Values** IP346 - Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables KECI - Korea Existing Chemicals Inventory KKDIK - Registration, evaluation, Authorization, and Restriction of Ch Koc - Organic Carbon/Water Partition Coefficient K-REACH - Korea - Registration, Evaluation, and Authorization of Chemicals LC50 - Lethal Concentration fifty LD50 - Lethal Dose fifty per cent. LL/EL/IL - Lethal Loading/Effective Loading/Inhibitory Loading LL50 - Lethal Loading fifty MAK Commission - Permanent Senate Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area MARPOL - International Convention for the Prevention of Pollution from Ships NDSL - Canada Non-Domestic Substance List No. - Number NOEC/NOEL - No Observed Effect Concentration / No Observed Effect Level NZIoC - New Zealand Inventory of Chemicals OE_HPV - Occupational Exposure - High Production Volume OECD - Organization for Economic Co-operation and Development OEL - Occupational Exposure Limit PBT - Persistent, Bio accumulative and Toxic PICCS - Philippine Inventory of Chemicals and Chemical Substances PNEC - Predicted No Effect Concentration **PPE - Personal Protective Equipment** 14 / 16

(+) 18816996168

Ponciplastics.com

according to Regulation (EC) No. 1907/2006

Hifax EYC 361P G13063

Version 1.2

Revision Date 01/26/2022

Print Date 02/25/2022

SDS No.: BE8011

lvondellbasel

Gen. Variant: SDS AT

PROC - Process Category QSAR - Quantitative Structure-Activity Relationship REACH - Registration Evaluation and Authorization of Chemicals RID - Regulations Relating to International Carriage of Dangerous Goods by Rail SDS - Safety Data Sheet SKIN_DES - Skin Designation STEL - Short term exposure limit STP - Standard Temperature and Pressure TCSCA - Taiwan inventory of chemicals TGD - Technical Guidance Document TRA - Targeted Risk Assessment TSCA - US Toxic Substances Control Act TWA - Time-Weighted Average UK REACH - United Kingdom - Registration, Evaluation, and Authorization of Chemicals **UN** - United Nations vPvB - very Persistent and very Bioaccumulative WGK - German Water Endangerment Class

Disclaimer

Multiple legal entities and registration numbers may be displayed in Section 1. The Recipient shall refer to the shipping documents to identify the legal entity that supplied this product.

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith

15 / 16

	(+) 18816996168				
SAFETY DATA SHEET	Ponciplastics.com	lvoodollbacoll			
according to Regulation (EC) No. 1907	/2006	lyondellbasell			
Hifax EYC 361P G13063		Gen. Variant: SDS_AT			
Version 1.2 Revision Date 01	/26/2022 Print Date 02	2/25/2022 SDS No.: BE8011			
effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.					
End	of Material Safety Data Sh	heet			
	16 / 16				