		(+) 188	316996168				
		U 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	astics.com				
SAFETY DATA SHEET					lyon	del	lbasel
					Con Va	iant: S	DS US GHS
Hifax PPU X9067HS Version 1.0 Revision Da			Print Date 1				S No.: BE144
		21/2013	Finit Date 1	2/23/20	19	50	5 NO DL 144
SECTION 1. PRODUCT AND C	ОМРА	NY IDENT	IFICATION				
Product name	:		J X9067HS UV	-7C45			
CAS Number:		Mixture					
Chemical Name	:		ded polyolefin , Compounded	nolymo	r		
Synonyms	•	Polyolelin	, Compounded	polyme	ſ		
Identified uses	:		ure of plastic ar conversion proce		injection	moldir	ng, extrusion
Prohibited uses	:	housings; and mech	cal parts; Train Seat belt syste anisms; Pedals and mechanism	ems and s (brake	mechani , gas , c	sms; B lutch);	rake systems Steering
Company	:	LyondellB 1221 McF P.O. Box	Chemicals, LP asell Tower, St Kinney St. 2583 Texas 77252-2				
Telephone	:	Customer Product S	Service 888 77 Safety 800 70	77-0232 00-0946			
Emergency telephone	:	-	EC USA 800-42 R 800-245-453				
E-mail address		product.s	afety@lyb.com				
SECTION 2. HAZARDS IDENTI	FICAT	ION					
GHS Classification							
OSHA Hazard Category:	· Com	bustible D	ust				
Label elements							
Signal Word		Warning					
Signal Word	•	wanning					
Hazard Statements	:	handling	particles are ge or by other mea tions in air.				
Other hazards							
No additional information	n availa	able.					
3. Composition/information or	1 inara	dients					
Mixtures	. mgi t						
			1 / 13				

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell
Hifax PPU X9067HS UV-7	7C45	Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date 04		3/2019 SDS No.: BE1440
In ave die née		
Ingredients Chemical Name	CAS-No.	Weight %
Proprietary blend of polyolefinic polymers	Mixture	95.0 - 100.0 %
Contains: Additives and stabilize	rs	
SECTION 4. FIRST AID MEASURES		
First aid procedures		
General advice :	Take proper precautions to e before attempting rescue and	ensure your own health and safety d providing first aid.
If inhaled :	medical attention.	If signs/symptoms continue, get
	fresh air.	this material, move the person to
	Obtain medical attention. Keep person warm, if necess Resuscitation (CPR)	sary give Cardio-Pulmonary
In case of skin contact :	If molten material contacts th large amounts of water to co- polymer.	
	the skin. Obtain immediate emergency	er from skin as this will remove / medical attention if burn is deep
	or extensive.	
In case of eye contact :	Flush eyes thoroughly with w medical attention if discomfor	vater for several minutes and seek rt persists.
	In case of eye contact with m Continuously flush eye(s) wit 15 minutes.	nolten polymer: h cool running water for at least
	Beyond flushing, DO NOT at adherent to the eye(s). Immediately seek medical at	
If swallowed :	Adverse health effects due to	pingestion are not anticipated.
Notes to physician		
Symptoms :	Inhalation of process fumes a in the nose and throat and co	and vapors may cause soreness oughing.
Hazards :	Dust contact with the eyes ca Molten polymer may cause th	an lead to mechanical irritation. hermal burns.
	2 / 13	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hifax PPU X9067HS UV	Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date	1040
Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
ECTION 5. FIRE-FIGHTING MEA	SURES
Flammable properties	
Autoignition temperature	: > 572 °F (300 °C)
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Fire fighting	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
Protective equipment and pr	ecautions for firefighters
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
	3 / 13
	0,10

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SAFELY DATA SHEET	lyondellbasell
Hifax PPU X9067HS UV-	7C45 Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date 04	
SECTION 6. ACCIDENTAL RELEAS	E MEASURES
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
SECTION 7. HANDLING AND STOR Handling	AGE
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water.
	4 / 13

SAFETY DATA SHEET Hifax PPU X9067HS UV-7	(+) 188169 Ponciplast 7 C45		Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date 04/		Print Date 12/23/20	SDS No.: BE1440
	section 10. Refer to NFPA Dust Explosion	A 654, Standard fo	he exhaust ventilation. See r the Prevention of Fire and acturing, Processing, and late Solids, for safe handling.
Storage			
Requirements for storage : areas and containers	and handling. should be use Store away fro oxidizing agen Keep containe	sekeeping practic Process enclosure d to avoid excess om excessive heat hts. er closed to preven	es during storage, transferring es and adequate ventilation ive dust accumulation. and away from strong t contamination. uild up of electrostatic charge.

8. Exposure controls/personal protection

Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

Ingredients	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can		TWA	10 mg/m3	US (ACGIH)	
be formed when			inhalable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	3 mg/m3	US (ACGIH)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	15 mg/m3	US (OSHA)	
be formed when			total dust	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	5 mg/m3	US (OSHA)	
be formed when			respirable	2005	
handling this			·		
product: Non-					
specified (inert or					
nuisance) dust					
,	I	1		1	
		5	/ 13		

5 / 13

(+) **18816996168**

SAFETY DATA SHEET

Ponciplastics.com

Hifax PPU X9067HS UV-7C45

Version 1.0

Revision Date 04/21/2015

Print Date 12/23/2019

Gen. Variant: SDS_US_GHS 19 SDS No.: BE1440

Iyondellbase

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
	6 / 13

$(+)\,18816996168$

Ponciplastics.com

Hifax PPU X9067HS UV-7C45

SAFETY DATA SHEET

Version 1.0 Revision Date 04/21/2015

Gen. Variant: SDS_US_GHS Print Date 12/23/2019 SDS No.: BE1440

Appearance	
Physical state	: Pellets.
Color	: dark gray
Odor	: Slight.
Safety data	
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer de varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 572 °F (300 °C)
Decomposition temperature	: not determined
рН	: Not applicable.
Melting point/range	: 122 - 338 °F (50 - 170 °C)
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: <1 g/cm3
Water solubility	: Insoluble.
Partition coefficient: n-	: No Data Available.
octanol/water Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Remarks - Other information	: No additional information available.

$(+)\,18816996168$

Ponciplastics.com

SAFETY DATA SHEET

Hifax PPU X9067HS UV-7C45

Version 1.0 Revision Date 04/21/2015

Gen. Variant: SDS_US_GHS Print Date 12/23/2019 SDS No.: BE1440

lyondellbasell

Reactivity	:	No known	reactivity hazards.		
·····	•				
Chemical stability	:	Stable und	er normal conditions.		
Conditions to avoid	:	Avoid conta open flame	-	ers, excessive heat, spa	
Materials to avoid	:	Material ma	ay be softened by so	me hydrocarbons.	
Hazardous decomposition products	:	: Not expected to decompose under normal conditions.			
Thermal decomposition	:	Carbon monoxide, olefinic and paraffinic compounds, trac amounts of organic acids, ketones, aldehydes and alcoho may be formed.			
Hazardous reactions	:	Will not occ	cur.		
TION 11. TOXICOLOGICAL		RMATION			
Acute toxicity					
Acute oral toxicity	:	Not classifi	ed		
Acute inhalation toxicity	:	Not classifi	ed		
Acute dermal toxicity	:	Not classifi	ed		
Skin corrosion/irritation	:	Not a skin	irritant.		
Serious eye damage/eye irritation	:	Not an eye Mechanica	irritant. I irritation is possible.		
Respiratory or skin sensitization	:	Not classifi	ed		
Chronic toxicity					
Component Name		NTP	IARC	OSHA	
Carbon Black			2B	Present	
Titanium Dioxide			2B	Present	
Carcinogenicity	:				
		Not classifi		APC as passibly	
			omponent(s) listed by ic to humans.	ARU as possibly	
		22.2.1.0901			

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hifax PPU X9067HS UV Version 1.0 Revision Date	
Version 1.0 Revision Date	3 04/21/2015 Pfint Date 12/23/2019 SDS No.: BE1440
	This material is encapsulated in a thermoplastic resin with limited release under normal conditions of use, transportation, and storage.
Germ cell mutagenicity	: Not classified
Reproductive toxicity	
Effects on fertility / Effects on or via lactation	: Not classified
Effects on Development	: Not classified
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Aspiration hazard	: Not applicable.
12. ECOLOGICAL INFORMATION	N
Ecotoxicology Assessment	
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Not classified
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
Bioaccumulative potential	
Bioaccumulation	: This material is not expected to bioaccumulate.
Mobility in soil	
Additional advice Environmental fate and pathways	: This material is not volatile and insoluble in water.
	9 / 13

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell
Hifax PPU X9067HS UV-7	7C45	Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date 04	1/21/2015 Print Date 1	2/23/2019 SDS No.: BE1440
Results of PBT and vPvB assessme Not applicable.	nt	
Other adverse effects		
Additional ecological : information	solubility of polymers. No data available on this	be minimal based on the low water product. However, birds, fish and lets which may obstruct their
SECTION 13. DISPOSAL CONSIDER	ATIONS	
Further information	transported and disposed	ould be packaged, labeled, d of or reclaimed in conformance with lations and in conformance with good eclaim where possible.
	This material is classified RCRA.	l as a Non-hazardous Material by

SECTION 14. TRANSPORT INFORMATION

Not regulated for transport

SECTION 15. REGULATORY INFORMATION

If identified components of this product are listed under the TSCA 12(b) Export Notification rule, they will be listed below.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN	Type of Toxicity				
		Carcinogen	Developmental	Repro-Male	Repro- Female	
Hexachlorobenzene	118-74-1	Х	Х			
		10 / 13	3			

(+) **18816996168**

Ponciplastics.com

SAFETY DATA SHEET

Hifax PPU X9067HS UV-7C45

Version 1.0 Revision Date 04/21/2015

Print Date 12/23/2019

Gen. Variant: SDS_US_GHS 19 SDS No.: BE1440

lyondellbase

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

14807-96-6	Talc,	Magnesium	Silicate

1333-86-4 Carbon Black

13463-67-7 Titanium Dioxide

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

- 14807-96-6 Talc, Magnesium Silicate
- 1333-86-4 Carbon Black

13463-67-7 Titanium Dioxide

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

14807-96-6 Talc, Magnesium Silicate

1333-86-4 Carbon Black

13463-67-7 Titanium Dioxide

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Not Determined


REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been preregistered or, where required under REACh, registered, and that we have the intention to proceed with their registration in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

SECTION 16. OTHER INFORMATION

Further information



(+) **18816996168**

SAFETY DATA SHEET

Ponciplastics.com

Hifax PPU X9067HS UV-7C45

Version 1.0

Revision Date 04/21/2015

Print Date 12/23/2019

SDS No.: BE1440

lyondellbase

Gen. Variant: SDS US GHS

Disclaimer

Luflexen, Lupolen, Metocene, Microthene, Moplen, Nexprene, Petrothene, Plexar, Pristene, Pro-Fax, Purell, Sequel, Softell, Starflex, Ultrathene, and Valtec are trademarks owned or used by the LyondellBasell family of companies.

Adsyl, Akoafloor, Akoalit, Alastian, Alathon, Avant, Dexflex, Flexathene, Hifax, Hostacom, Hostalen, Integrate, Koattro, Lucalen, Lupolen, Microthene, Moplen, Nexprene, Petrothene, Plexar, Pristene, Pro-Fax, Purell, Sequel, Softell, Starflex, and Ultrathene are registered in the U.S. Patent and Trademark Office.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.