	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell
Hifax RC 516N 2053		Gen. Variant: SDS JP
Version 1.0 Revision Date 20	21-11-05 Print Date 2	
1. IDENTIFICATION OF THE SUBSTA		
CAS Number: : Chemical name :	Hifax RC 516N 2053 Mixture Compounded polyolefin Polyolefin, Compounded po	lymer
	Manufacture of plastic articl or other conversion process	es by injection molding, extrusion s.
	devices; Health Canada cla	anent implantation into the body;
<u>Company Address</u> Basell Asia Pacific Ltd. 32/F, Dorset House Taikoo Place 979 King's Road Quarry Bay, Hong Kong	<u>Company Tel</u> Product Safety Switchboard product.safety	+852-2585-0120 +852-2577-3855
E-mail address : Responsible/issuing person	product.safety@lyb.com	
2. HAZARDS IDENTIFICATION		
GHS-Classification		
Not a hazardous substance or r	nixture according to the Glo	bally Harmonized System (GHS).
	nixture according to the Glo	bally Harmonized System (GHS).
Other hazards		
If small particles are generated combustible dust concentrations		andling or by other means, may form
3. COMPOSITION/INFORMATION ON Mixtures	INGREDIENTS	

r		(+) 18816996168				
SAFETY DATA SHEE	г	Ponciplastics.com	lyondellbasell			
Hifax RC 516N 2053	6	Gen. Variant: SDS_JP				
Version 1.0 Revision Date 2021-11-05 Print Date 2022-01-06 SDS No.: BE37						
Components	Components					
Chemical name	CAS-No	b. ENCS/ISHL number	<u>Weight %</u>			
Proprietary blend of polyolefinic polymers	Mixture	hambol	80.0 - 100.0 %			
Contains: Additives, sta	bilizers and	fillers				
4. FIRST AID MEASURES						
General advice		Take proper precautions to before attempting rescue a	o ensure your own health and safety and providing first aid.			
lf inhaled	r 	medical attention. In case of excessive inhala during heating of this mate Obtain medical attention.	r. If signs/symptoms continue, get ation of fumes that may be generated erial, move the person to fresh air. essary give Cardio-Pulmonary			
In case of skin contact	; [S (large amounts of water to Do not attempt to peel poly skin.	the skin, immediately flush with cool the affected tissue and polymer. mer from skin as this will remove the ncy medical attention if burn is deep			
In case of eye contact		Flush eyes thoroughly with medical attention if discom	water for several minutes and seek fort persists.			
	(r E a	 In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. 				
If swallowed	: 4	Adverse health effects due	e to ingestion are not anticipated.			
Notes to physician	Notes to physician					
Symptoms	: 1	Inhalation of process fume	s and vapors may cause soreness in			

SAFETY DATA SHEET	(+) 18816996168 Ponciplastics.com
Hifax RC 516N 2053	Gen. Variant: SDS_JP
Version 1.0 Revision Date	2021-11-05 Print Date 2022-01-06 SDS No.: BE3794
	the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
6. ACCIDENTAL RELEASE MEAS Personal precautions	URES : Equip responders with proper protection.

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell
Hifax RC 516N 2053		Gen. Variant: SDS_JP
Version 1.0 Revision Date 20	21-11-05 Print Date 20	022-01-06 SDS No.: BE3794
	surface. Equip emergency responde equipment (PPE) Avoid generating dust. Avoid dispersal of dust in th with compressed air). Potential combustible dust	y hazard on any hard smooth ers with proper personal protective ne air (i.e., clearing dust surfaces hazard. pping hazard on hard smooth
Environmental precautions :	Do not flush into surface wa	ater or sanitary sewer system.
Methods for cleaning up	vacuum using equipment wh On water, material is insolut solid. All recovered material shoul transported and disposed of	ble; collect and contain as any d be packaged, labeled, f or reclaimed in conformance with ons and in conformance with good
7. Handling and storage Precautions for safe handling		
-	Material is in a pellet form.	
	If converted to small particle handling, or by other means concentrations in air. Avoid dust accumulation in a Use dust collection systems dust accumulation. Avoid generating dust; fine a presence of an ignition sour hazard. Static discharge (spark), or environments may ignite the explosion Electrostatic charge may bu Equipment handling polyme grounded (earthed) and bor Metal containers involved in should be grounded and bor All electrical equipment shou codes and regulatory require combustible dusts.	a designed per NFPA 654 to avoid dust suspended in air and in the ce is a potential dust explosion other ignition sources, in high dust e dust and result in a dust ild during conveying or handling. In should be conductive and ided. I the transfer of this material inded. uld conform to applicable electric

		(.,10	816996168		
SAFETY DATA SI	HEET	Poncip	lastics.com	lyond	lellbase
lifax RC 516N 2	053			Gen. Varia	ant: SDS_JP
Version 1.0 Rev	vision Date 20	021-11-05	Print Date 20	022-01-06	SDS No.: BE37
		may develo section 10 Refer to N Dust Explo	pp may condense FPA 654, Standar psions from the M	to processing temp in the exhaust ver rd for the Preventic anufacturing, Proc articulate Solids, fo	ntilation. See on of Fire and essing, and
Conditions for saf	e storage, inc	luding any	v incompatibilitie	s	
Requirements for s areas and containe		Use good and handli should be Store away oxidizing a Keep cont	ng. Process enclo used to avoid exc y from excessive agents. ainer closed to pr	actices during stora osures and adequa cessive dust accun heat and away from event contamination he build up of elec	ite ventilation nulation. m strong on.
• ••• • • •					
Specific end use(s		See Section	on 1.		
EXPOSURE CONTRO	:				
EXPOSURE CONTRO	OLS/PERSON/	AL PROTE	CTION		
EXPOSURE CONTRO	OLS/PERSON/ workplace c	AL PROTE	CTION		
EXPOSURE CONTRO ontrol parameters Ingredients with	OLS/PERSON/ workplace c	AL PROTE	CTION	Basis	Additional
EXPOSURE CONTRO ontrol parameters Ingredients with Occupational Exp	OLS/PERSON/ workplace o osure Limits	AL PROTE	CTION	Basis Revision Date US (ACGIH) 2005	Additional Information

(+) 18816996168
Ponciplastics.com
Gen. Variant: SDS_JP
e 2021-11-05 Print Date 2022-01-06 SDS No.: BE3794
eptable exposure limits.
n NFPA 654 (as amended and adopted) for equipment used to handle osed systems, should be used whenever feasible to maintain criteria. When such controls are not feasible, or sufficient to achieve full g controls such as local exhaust ventilation should be used. Ing combustible dust from this material should be designed to either ng) or safely vent dust explosions per NFPA 654 tems (such as exhaust ducts, dust collectors, vessels, and processing manner to prevent the escape of dust into the work area (i.e., there is t).
ent
 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
: Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product.
: Wear suitable protective clothing.
 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hifax RC 516N 2053	Gen. Variant: SDS_JP
Version 1.0 Revision Date	e 2021-11-05 Print Date 2022-01-06 SDS No.: BE3794
9. PHYSICAL AND CHEMICAL PF	ROPERTIES
Appearance	: pellets
Color	solid : black
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: 1.01 g/cm3 at 23 °C
Water solubility	: Insoluble.
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.

10. STABILITY AND REACTIVITY

(+) 18816996168 Ponciplastics.com Iyondellbasell SAFETY DATA SHEET Hifax RC 516N 2053 Gen. Variant: SDS JP Version 1.0 Revision Date 2021-11-05 Print Date 2022-01-06 SDS No.: BE3794 Reactivity : No known reactivity hazards. Chemical stability : Stable under normal conditions. Hazardous reactions : Will not occur. Conditions to avoid : Avoid contact with strong oxidizers, excessive heat, sparks or open flame. Materials to avoid : Material may be softened by some hydrocarbons. Hazardous decomposition : Not expected to decompose under normal conditions. products Thermal decomposition : Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed. **11. TOXICOLOGICAL INFORMATION** Acute toxicity Acute oral toxicity : Not classified Acute inhalation toxicity : Not classified Acute dermal toxicity : Not classified Skin corrosion/irritation : Not a skin irritant. Serious eye damage/eye : Not an eye irritant. irritation Mechanical irritation is possible. Respiratory or skin : Not classified sensitization Chronic toxicity Carcinogenicity : Not classified Germ cell mutagenicity : Not classified

Reproductive toxicity

Effects on fertility /	:	Not classified
Effects on or via lactation		
Effects on Development	:	Not classified

r		(+) 18816996168	
SAFETY DATA SHEET		Ponciplastics.com	lyondellbasell
Hifax RC 516N 2053			Gen. Variant: SDS_JP
Version 1.0 Revision Date	20	21-11-05 Print Date 20	022-01-06 SDS No.: BE3794
Target Organ Systemic Toxicant - Single exposure Target Organ Systemic	:	organ toxicant, single expos The substance or mixture is	not classified as specific target
Toxicant - Repeated exposure		organ toxicant, repeated ex	posure.
Aspiration hazard	:	Not applicable.	
12. Ecological information			
Ecotoxicology Assessment			
Short-term (acute) aquatic	:	Not classified	
hazard Long-term (chronic) aquatic hazard	:	Not classified	
Persistence and degradability			
Biodegradability	:	Not expected to be biodegra	idable.
Bioaccumulative potential			
Bioaccumulation	:	This material is not expected	d to bioaccumulate.
Mobility in soil			
Mobility	:	no data available	
Other adverse effects			
Environmental fate and pathways	:	This material is not volatile a	and insoluble in water.
Other information			
Additional ecological information		solubility of polymers.	e minimal based on the low water oduct. However, birds, fish and s which may obstruct their

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell
Hifax RC 516N 2053		Gen. Variant: SDS_JP
Version 1.0 Revision Date 202	21-11-05 Print Date 20	022-01-06 SDS No.: BE3794
13. Disposal considerations		
Waste treatment methods		
		f or reclaimed in conformance with ons and in conformance with good
14. TRANSPORT INFORMATION		
Not regulated for transport		
15. REGULATORY INFORMATION		
Act on Confirmation, etc. of Releas Environment and Promotion of Imp		
None		
Industrial Safety and Health Law		
Dangerous Substances		
None		
Organia Calumat Dulas		
Organic Solvent Rules		
None		
Strong Mutagenic Chemical Subs	tances	
None		
 Substances Subject to be Notified 	Names	

	(+) 1881	6996168	
SAFETY DATA SHEET	Ponciplas	stics.com	lyondellbasell
Hifax RC 516N 2053			Gen. Variant: SDS_JP
Version 1.0 Revision Date 2	2021-11-05	Print Date 2	022-01-06 SDS No.: BE3794
<u>Component</u>	<u>CAS-I</u>	<u>No.</u>	
Carbon Black	1333-	86-4	>= 0.1 % weight
			•
Magnesium Stearate	557-0	4-0	>= 1 % weight
Substances Subject to be Indic	ated Names		
<u>Component</u>	<u>CAS-I</u>	<u>No.</u>	
Carbon Black	1333-	86-4	>= 1 % weight
Magnesium Stearate	557-0		>= 1 % weight
Chemical Substance Control Lav	V		
Poisonous and Deleterious Subs None Other international regulations Global Inventory Status The ingredients of this product are co exemptions. *Additional Explanatory Statu	mpliant with the	following che	
Country/Region	Inventory	Status De	escription
Australia	AICS	Compliant	-
Canada	DSL	Compliant	
China	IECSC	Compliant	
Europe	REACH		CH Compliance Statement
Japan	ENCS	Compliant	
Korea	KECI	Compliant	
New Zealand	NZloC	Compliant	
Philippines	PICCS	Compliant	
United States of America	TSCA	Compliant	
Toiwan	TOSOA	Compliant	

REACh status

Taiwan

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Compliant

TCSCA

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell
Hifax RC 516N 2053		Gen. Variant: SDS_JP
Version 1.0 Revision Date 20	021-11-05 Print Date 20	022-01-06 SDS No.: BE3794
Contact product.safety@lyb.com for a	dditional global inventory info	rmation.
16. OTHER INFORMATION		
Material safety datasheet section	ons which have been upda	ted:
Revised Section(s): 15 16		
	Disclaimer	
The document is designed to proprocessing, storage, transportation or quality specification, either exist fitness for any particular purpose their use and can be used safely. In addition to any prohibitions of further prohibit or restrict the salinformation, please contact a Lyat: https://www.lyondellbasell.com	ovide users general information on, disposal and release and press or implied, including an e. Users shall determine whe mand legally. use specifically noted in this e of its products into certain a ondellBasell representative of m/en/products-technology/pro-	does not constitute any warranty ny warranty of merchantability or ther the product is suitable for document, LyondellBasell may applications. For further r visit the LyondellBasell website
toxicological values, is expresse a period (.) as the decimal marke	d using a comma (,) to sepa	ysical and chemical properties and rate digits into groups of three and g/kg = 1 234,56 mg/kg.
LyondellBasell believes to be re effort to verify the accuracy of the	eliable. LyondellBasell and it he translation, but assume n red. Please refer to our web	nslated from English by a vendor is vendor have made a good-faith o liability or other responsibility for o site (www.lyondellbasell.com) for
Enc	l of Material Safety Data Sl	neet