	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SAFEIT DATA SHEET	lyondellbasell
Hifax TKC 805P 207D CH	HARCOAL Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date 1	
1. IDENTIFICATION OF THE SUBST	ANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name : CAS Number: :	Hifax TKC 805P 207D CHARCOAL Mixture
CAS Number Chemical name :	Compounded polyolefin
Synonyms :	Polyolefin, Compounded polymer, HX TKC 805P 207D
	CHARCOAL
Identified uses :	Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses :	FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications
Company Address	Company Telephone
Equistar Chemicals, LP LyondellBasell Tower, Suite 300	Customer Service 888 777-0232 product.safety@lyb.com
1221 McKinney St.	
P.O. Box 2583 Houston Texas 77252-2583	
Emergency telephone number EQUISTAR 800-245-4532	<u>r</u>
E-mail address : Responsible/issuing person	product.safety@lyb.com
2. HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
Other hazards	
	1 / 14

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell
Hifax TKC 805P 207D CI		Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date 1	0/02/2019 Print Date 01/06	5/2022 SDS No.: BE5519
No additional information ava	ilable.	
3. COMPOSITION/INFORMATION C	ON INGREDIENTS	
Mixtures		
Components Chemical name	CAS-No.	<u>Weight %</u>
Proprietary blend of polyolefinic	Mixture	50.0 - 80.0 %
polymers		
Contains: Additives, stabilizers	and miers	
4. FIRST AID MEASURES		
General advice	: Take proper precautions to before attempting rescue an	ensure your own health and safety d providing first aid.
lf inhaled	medical attention. In case of excessive inhalati	If signs/symptoms continue, get on of fumes that may be generated al, move the person to fresh air. sary give Cardio-Pulmonary
In case of skin contact	large amounts of water to co Do not attempt to peel polyn skin.	he skin, immediately flush with bol the affected tissue and polymer. ner from skin as this will remove the y medical attention if burn is deep
In case of eye contact	: Flush eyes thoroughly with medical attention if discomform	water for several minutes and seek ort persists.
	minutes.	th cool running water for at least 15 ttempt to remove the material
If swallowed	: Adverse health effects due t	o ingestion are not anticipated.
	2 / 14	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	I <sup>™</sup> I
Hifax TKC 805P 207D C Version 1.2 Revision Date	
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient.
5. FIRE-FIGHTING MEASURES Suitable extinguishing media	: SMALL FIRE: Use dry chemical. CO2. or water spray.
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	<ul> <li>Keep away from heat and sources of ignition.</li> <li>In case of fire hazardous decomposition products may be produced such as:</li> <li>Carbon monoxide, carbon dioxide and unburned hydrocarbon (smoke).</li> </ul>
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	<ul> <li>Combustible particulate solid, will decompose under fire conditions.</li> <li>Calorific Value: 8000 - 11000 kcal/kg</li> </ul>
	Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk.
	Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in
	fire. Cool storage containers with large volumes of water even after fire is out.
	3 / 14

Hifax TKC 805P 207D CHARCOAL Gen. Variant: SDS_US_G	SAFETY DATA SHEET     Yondel       Hifax TKC 805P 207D CHARCOAL     Gen. Variant: SI	DS_US_GHS
ACCIDENTAL RELEASE MEASURES       Personal precautions       Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air), Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.         Environmental precautions       : On tand, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids lightion risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed or reclaimed in conformance with ge engineering practices. Reclaim where possible.         Handling and storage       If Material is in a pellet form. If coverted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Avoid generating (bust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Stoid is on a poly other means, may form combustible dust concentrations in air. Avoid dust accumulation. Avoid generating (bust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high d environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling equipment handling polymer should be conductive and		
Personal precautions       : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid digenerating dust. Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.         Environmental precautions       : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance vi applicable laws and regulations and in conformance with ge engineering practices. Reclaim where possible.         Handling and storage       : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high d environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and		
Personal precautions       : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.         Environmental precautions       : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed for reclaimed in conformance via applicable laws and regulations and in conformance with ge engineering practices. Reclaim where possible.         Handling and storage       : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high d environments may ignite the dust and result in a dust explosion Electrosatic charge may build during conveying or handling Equipment handling polymer should be conductive and		
Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protect equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.       Environmental precautions     : Do not flush into surface water or sanitary sever system.       Methods for containment / Methods for cleaning up     : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance wit gr engineering practices. Reclaim where possible.       Handling and storage     : Material is in a pellet form. If converted to small panticles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high d environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and	. ACCIDENTAL RELEASE MEASURES	
Methods for containment / Methods for cleaning up       On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid.         All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with ge engineering practices. Reclaim where possible.         Handling and storage         Precautions for safe handling         Advice on safe handling         Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high d environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and	Creates dangerous slipping hazard on any hard s surface. Equip emergency responders with proper person equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing du with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard	al protective st surfaces
Methods for cleaning up       vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid.         All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance w applicable laws and regulations and in conformance with ge engineering practices. Reclaim where possible.         Handling and storage       Precautions for safe handling         Advice on safe handling       : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high di environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and	Environmental precautions : Do not flush into surface water or sanitary sewer	system.
Precautions for safe handling         Advice on safe handling         : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high d environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and	Methods for cleaning up Vacuum using equipment which avoids ignition ris On water, material is insoluble; collect and contain solid. All recovered material should be packaged, labele transported and disposed of or reclaimed in confor applicable laws and regulations and in conformance	k. n as any ed, rrmance with
<ul> <li>Advice on safe handling</li> <li>Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high d environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and</li> </ul>	Handling and storage	
If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avo dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high d environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and	-	
4 / 14	If converted to small particles during further proce handling, or by other means, may form combustible concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 6 dust accumulation. Avoid generating dust; fine dust suspended in air presence of an ignition source is a potential dust 6 hazard. Static discharge (spark), or other ignition sources environments may ignite the dust and result in a c explosion Electrostatic charge may build during conveying of	ole dust 654 to avoid and in the explosion , in high dus dust or handling.
	4 / 14	

(+) 18816996168

			10550100		
SAFETY DATA S	HEET	Poncip1	astics.com	lvood	ellbasel
Hifax TKC 805					: SDS_US_GHS
Version 1.2 Re	evision Date 10	0/02/2019	Print Date 0	1/06/2022	SDS No.: BE551
			(earthed) and b		
			grounded and	in the transfer of thi bonded.	s material
		All electric	al equipment s regulatory requ	hould conform to app uirements for areas	
		After hand water.	ling, always wa	sh hands thoroughly	·
			op may conden	al to processing tem use in the exhaust ve	
		Refer to N Dust Explo	FPA 654, Stan	dard for the Prevention Manufacturing, Proor Particulate Solids, for	cessing, and
Fire-fighting class	:	Polymer w	vill burn but doe	s not easily ignite.	
Conditions for sa	fe storage, in	cluding any	/ incompatibili	ties	
Requirements for s			dry location.		
areas and containe	ərs	and handli should be Store awa oxidizing a Keep cont	ng. Process en used to avoid e y from excessiv agents. ainer closed to	practices during stor closures and adequa excessive dust accur we heat and away fro prevent contamination t the build up of elect	ate ventilation nulation. m strong on.
Specific end use(					
	:	See Section	on 1.		
8. EXPOSURE CONTR	OLS/PERSON	IAL PROTE	CTION		
Control parameters					
-			- 1		
Ingredients with	workplace co	ntroi param	eters		
Occupational Exp	osure Limits				
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
handling this			minalable	2003	
product: Non- specified (inert or					
nuisance) dust					
		5	5 / 14		

# (+) **18816996168**

Ponciplastics.com

SAFETY DA	TA SHEET
-----------	----------

Iyondellbasell

### Hifax TKC 805P 207D CHARCOAL

Version 1.2 Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE5519

Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

#### Exposure controls

#### Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

#### Personal protective equipment

Respiratory protection	<ul> <li>Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.</li> <li>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.</li> <li>Use appropriate respiratory protection where atmosphere exceeds recommended limits.</li> <li>Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.</li> </ul>
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 14

# (+) 18816996168

	(+) 18816996168 Ponciplastics.com
SAFETY DATA SHEET	lyondellbase
	I <sup>™</sup> I
Hifax TKC 805P 207D Tersion 1.2 Revision Date	te 10/02/2019 Print Date 01/06/2022 SDS No.: BE5
	injury or other irritation to eyes due to airborne particles whic may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	<ul> <li>Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.</li> <li>Use good personal hygiene practices.</li> <li>Wash hands before eating, drinking, smoking, or using toilet facilities.</li> <li>Take off contaminated clothing and wash before reuse.</li> </ul>
Appearance	: Pellets.
Color	: Pellets. : dark gray
Appearance Color Odor	: Pellets. : dark gray : Slight.
Appearance Color Odor Odor Threshold	<ul> <li>Pellets.</li> <li>dark gray</li> <li>Slight.</li> <li>No value available.</li> </ul>
Appearance Color Odor Odor Threshold Flash point	<ul> <li>Pellets.</li> <li>dark gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer data and the second seco</li></ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit	<ul> <li>Pellets.</li> <li>dark gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer data varies according to particle size distribution.</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit	<ul> <li>Pellets.</li> <li>dark gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer de varies according to particle size distribution.</li> <li>Not applicable.</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas)	<ul> <li>Pellets.</li> <li>dark gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer de varies according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	<ul> <li>Pellets.</li> <li>dark gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer data varies according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	<ul> <li>Pellets.</li> <li>dark gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer data varies according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	<ul> <li>Pellets.</li> <li>dark gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer davaries according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> <li>not determined</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range	<ul> <li>Pellets.</li> <li>dark gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer de varies according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> <li>not determined</li> <li>50 - 170 °C</li> </ul>
Appearance ColorOdorOdor ThresholdFlash pointLower explosion limitUpper explosion limitFlammability (solid, gas)Oxidizing propertiesAutoignition temperatureDecomposition temperatureMelting point/rangeBoiling point/boiling range	<ul> <li>Pellets.</li> <li>dark gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer devaries according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> <li>not determined</li> <li>50 - 170 °C</li> <li>Not applicable.</li> </ul>

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hifax TKC 805P 207D CHVersion 1.2Revision Date 10	IAROOAL
Partition coefficient: n-	: No Data Available.
octanol/water Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
10. STABILITY AND REACTIVITY	
Reactivity	: No known reactivity hazards.
Chemical stability :	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition : products	: Not expected to decompose under normal conditions.
Thermal decomposition :	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
11. TOXICOLOGICAL INFORMATIO	 N
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye	: Not an eye irritant. Mechanical irritation is possible.
	8 / 14

	(+) 188	16996168	
SAFETY DATA SHEET	Poncip1a	stics.com	lvoodollbacoll
			lyondellbasell
Hifax TKC 805P 207D (			Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	10/02/2019	Print Date 01	1/06/2022 SDS No.: BE5519
Respiratory or skin sensitization	: Not classifi	ed	
Chronic toxicity			
Component Name	NTP	IARC	OSHA
Titanium Dioxide		2B	Present
Carbon Black		2B	Present
Carcinogenicity	: Not classifi	ed	
	Not classifi		sted by IARC as possibly
	carcinogeni	ic to humans.	
			ated in a thermoplastic resin with mal conditions of use, transportation,
	and storage		
Germ cell mutagenicity	: Not classifi	ed	
Reproductive toxicity			
Effects on fertility /	: Not classifi	ed	
Effects on or via lactation			
Effects on Development	: Not classifi	ed	
Target Organ Systemic	: The substa	ince or mixture	is not classified as specific target
Toxicant - Single exposure		ant, single exp	
Target Organ Systemic Toxicant - Repeated		ance or mixture ant, repeated	e is not classified as specific target
exposure	organ toxic		
Aspiration hazard	: Not applica	blo	
	. Not applied	DIC.	
12. Ecological information			
Ecotoxicology Assessment			
Short-term (acute) aquatic hazard	: Not classifie	ed	
Long-term (chronic)	: Not classifi		
	9	/ 14	

(+) 18816996168 Ponciplastics.com Hifax TKC 805P 207D CHARCOAL Version 1.2 Revision Date 10/02/2019 Print Date 01/06/2022 SDS No.: aquatic hazard Persistence and degradability Biodegradability : Not expected to be biodegradable. Bioaccumulative potential Bioaccumulation : This material is not expected to bioaccumulate. Mobility in soil	S_GHS
Hifax TKC 805P 207D CHARCOAL       Gen. Variant: SDS_UG         Version 1.2       Revision Date 10/02/2019       Print Date 01/06/2022       SDS No.:         aquatic hazard         Persistence and degradability         Biodegradability       : Not expected to be biodegradable.         Bioaccumulative potential         Bioaccumulation       : This material is not expected to bioaccumulate.	S_GHS
Version 1.2       Revision Date 10/02/2019       Print Date 01/06/2022       SDS No.:         aquatic hazard         Persistence and degradability         Biodegradability       : Not expected to be biodegradable.         Bioaccumulative potential         Bioaccumulation       : This material is not expected to bioaccumulate.	_
Version 1.2       Revision Date 10/02/2019       Print Date 01/06/2022       SDS No.:         aquatic hazard         Persistence and degradability         Biodegradability       : Not expected to be biodegradable.         Bioaccumulative potential         Bioaccumulation       : This material is not expected to bioaccumulate.	_
Persistence and degradability         Biodegradability       : Not expected to be biodegradable.         Bioaccumulative potential         Bioaccumulation       : This material is not expected to bioaccumulate.	
Biodegradability       : Not expected to be biodegradable.         Bioaccumulative potential       : This material is not expected to bioaccumulate.	
Bioaccumulative potential Bioaccumulation : This material is not expected to bioaccumulate.	
<b>Bioaccumulation</b> : This material is not expected to bioaccumulate.	
Mobility in soil	
Mobility : no data available	
Other adverse effects	
Environmental fate and : This material is not volatile and insoluble in water. pathways	
Other information	
Additional ecological information: Ecotoxicity is expected to be minimal based on the low solubility of polymers. No data available on this product. However, birds, fish other wildlife may eat pellets which may obstruct their intestinal tracts.	
13. Disposal considerations	
Waste treatment methods	
Product : All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance wit engineering practices. Reclaim where possible. Recycle if possible.	h good
: This material is classified as a Non-hazardous Material RCRA.	by
14. TRANSPORT INFORMATION	
10 / 14	

(+) 18816996168
-----------------

Ponciplastics.com

### SAFETY DATA SHEET

# Hifax TKC 805P 207D CHARCOAL

Version 1.2

Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS US GHS SDS No.: BE5519

Iyondellbase

Not regulated for transport

#### **15. REGULATORY INFORMATION**

#### TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

#### Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

#### SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

#### SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

#### Combustible dust

#### **SARA 313**

This product contains no known chemicals regulated under SARA 313.

#### State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN	Type of Toxicity			
		Carcinogen	Developmental	Repro-Male	Repro- Female
Lead	7439-92-1	Х	Х	Х	Х
Cadmium	7440-43-9	Х	Х	Х	
Chromium	7440-47-3	Х			
Arsenic	7440-38-2	Х			
Nickel	7440-02-0	X			
Mercury	7439-97-6		X		

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

11 / 14

	(+)]	1881	6996	5168
--	------	------	------	------

Ponciplastics.com

## SAFETY DATA SHEET

Hifax TKC 805P 207D CHARCOAL Revision Date 10/02/2019

Version 1.2

Print Date 01/06/2022

Gen. Variant: SDS US GHS

Iyondellbase

SDS No.: BE5519

Talc, Magnesium Silicate 14807-96-6 1333-86-4 Carbon Black

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

14807-96-6 Talc, Magnesium Silicate

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

14807-96-6 Talc, Magnesium Silicate 1333-86-4 Carbon Black

#### Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.


Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Not Compliant*
China	IECSC	Not Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Not Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

#### REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

12 / 14



	(+) 18816996168					
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell				
Hifax TKC 805P 207D C		Gen. Variant: SDS_US_GHS				
Version 1.2 Revision Date 1	10/02/2019 Print Date 0	1/06/2022 SDS No.: BE5519				
LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.						
End	d of Material Safety Data S	Sheet				