	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	I I III I
Hifax TRC 103P 11BK Version 1.0 Revision Da	Ate 04/21/2015 Print Date 12/23/2019 SDS No.: BE101
SECTION 1. PRODUCT AND C	OMPANY IDENTIFICATION
Product name CAS Number:	: Hifax TRC 103P 11BK02 BLACK Mixture
Chemical Name	: Compounded polyolefin
Synonyms	: Polyolefin, Compounded polymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: Aeronautical parts; Train transportation parts; Air bag unit housings; Seat belt systems and mechanisms; Brake systems and mechanisms; Pedals (brake , gas , clutch); Steering systems and mechanisms; Medical applications use
Company	 Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583
Telephone	: Customer Service 888 777-0232 Product Safety 800 700-0946
Emergency telephone	: CHEMTREC USA 800-424-9300 EQUISTAR 800-245-4532
E-mail address	product.safety@lyb.com
SECTION 2. HAZARDS IDENTI	FICATION
GHS Classification	
OSHA Hazard Category:	Combustible Dust
Label elements	
Signal Word	: Warning
Hazard Statements	 If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
Other hazards	
No additional information	available.
B. Composition/information on	ingredients
	1 / 13
	. ,

	(+) 18816996168					
SAFETY DATA SHEET	Ponciplastics.com	<u> </u>				
SAFEIY DAIA SHEEI		lyondellbasell				
Hifax TRC 103P 11BK02 BLACK Gen. Variant: SDS_US_GHS						
Ingredients						
Chemical Name	CAS-No.	Weight %				
Proprietary blend of polyolefinic polymers	Mixture	50.0 - 80.0 %				
Contains: Additives, stabilizers a	and fillers					
SECTION 4. FIRST AID MEASURES						
First aid procedures						
General advice	: Take proper precautions to before attempting rescue a	o ensure your own health and safety and providing first aid.				
If inhaled	 Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) 					
In case of skin contact	 If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. 					
In case of eye contact	: Flush eyes thoroughly with medical attention if discom	water for several minutes and seek fort persists.				
	In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.					
If swallowed	: Adverse health effects due to ingestion are not anticipated.					
Notes to physician						
Symptoms	: Inhalation of process fumes in the nose and throat and	s and vapors may cause soreness coughing.				
Hazards	: Dust contact with the eyes Molten polymer may cause	can lead to mechanical irritation. thermal burns.				
	2 / 13					

	(+) 18816996168 Ponciplastics.com
SAFETY DATA SHEET	lyondellbase
Hifax TRC 103P 11BK0 ersion 1.0 Revision Date	
Treatment	: Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient.
ECTION 5. FIRE-FIGHTING MEA	SURES
Flammable properties	
Autoignition temperature	: > 572 °F (300 °C)
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Fire fighting	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
Protective equipment and pr	ecautions for firefighters
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
	3 / 13

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SAFEIY DAIA SHEEI	lyondellbasell
Hifax TRC 103P 11BK02	BLACK Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date 0	
SECTION 6. ACCIDENTAL RELEAS	E MEASURES
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
SECTION 7. HANDLING AND STOP	RAGE
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors
	4 / 13

SAFETY DATA SHEET	(+) 18816996168 Ponciplastics.com	
Hifax TRC 103P 11BK02	BLACK	Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date 0	4/21/2015 Print Date	12/23/2019 SDS No.: BE1015
	section 10. Refer to NFPA 654, Star Dust Explosions from th	ense in the exhaust ventilation. See ndard for the Prevention of Fire and le Manufacturing, Processing, and e Particulate Solids, for safe handling.
Storage		
Requirements for storage areas and containers	and handling. Process e should be used to avoid Store away from excess oxidizing agents. Keep container closed to	practices during storage, transferring enclosures and adequate ventilation excessive dust accumulation. sive heat and away from strong o prevent contamination. nt the build up of electrostatic charge.

8. Exposure controls/personal protection

Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

		T			
Ingredients	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can		TWA	10 mg/m3	US (ACGIH)	
be formed when			inhalable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	3 mg/m3	US (ACGIH)	
be formed when			respirable	2005	
handling this			•		
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	15 mg/m3	US (OSHA)	
be formed when			total dust	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	5 mg/m3	US (OSHA)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
,				1	
		5	/ 13		

 $(+)\,18816996168$

SAFETY DATA SHEET

Ponciplastics.com

Hifax TRC 103P 11BK02 BLACK

Version 1.0 Revision Date 04/21/2015

Print Date 12/23/2019

Gen. Variant: SDS_US_GHS 19 SDS No.: BE1015

Iyondellbase

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
	6 / 13

(+) 18816996168

AFETY DATA SHEET	lyondellbase
ifax TRC 103P 11BK	
ersion 1.0 Revision Date	e 04/21/2015 Print Date 12/23/2019 SDS No.: BE1
CTION 9. PHYSICAL AND CH	EMICAL PROPERTIES
Appearance	
Physical state	: Pellets.
Color	: Black
Odor	: Slight.
Safety data	
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 572 °F (300 °C)
Decomposition temperature	: not determined
pH	: Not applicable.
Melting point/range	: 122 - 338 °F (50 - 170 °C)
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: >1 g/cm3
Water solubility	: Insoluble.
Partition coefficient: n-	: No Data Available.
octanol/water Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Remarks - Other information	: No additional information available.
	7 / 13

(+) 18816996168

		10000100			
SAFETY DATA SHEET	Poncip1a	stics.com		vooda	Ilhacoll
SAFETY DATA SHEET					
Hifax TRC 103P 11BK0					SDS_US_GHS
Version 1.0 Revision Date	04/21/2015	Print Date 1	2/23/2019	S	DS No.: BE1015
SECTION 10. STABILITY AND REA	ACTIVITY				
Reactivity	: No known	reactivity haza	rds.		
Chemical stability	: Stable und	er normal cond	ditions.		
Conditions to avoid	: Avoid conta open flame	-	oxidizers	, excessive ł	neat, sparks or
Materials to avoid	: Material ma	ay be softened	by some	hydrocarbor	IS.
Hazardous decomposition products	: Not expect	ed to decompo	ose under	normal cond	litions.
Thermal decomposition	amounts of	Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.			
Hazardous reactions	: Will not occ	our.			
Acute toxicity	NI (1				
Acute oral toxicity	: Not classified				
Acute inhalation toxicity	: Not classified				
Acute dermal toxicity	: Not classifi	: Not classified			
Skin corrosion/irritation	: Not a skin irritant.				
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.				
Respiratory or skin sensitization	: Not classifi	ed			
Chronic toxicity					
Component Name	NTP	IARC		OSHA	
Carbon Black		2B		Present]
Carcinogenicity	carcinogen	ed omponent(s) li c to humans. al is encapsula	-		-
	8	/ 13			

	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics.com			
	lyondellbasel			
Hifax TRC 103P 11BK0 Version 1.0 Revision Date	Hifax TRC 103P 11BK02 BLACK Gen. Variant: SDS_US_GHS			
Version 1.0 Revision Date	04/21/2015 Print Date 12/23/2019 SDS No.: BE101			
	limited release under normal conditions of use, transportation, and storage.			
Germ cell mutagenicity	: Not classified			
Reproductive toxicity				
Effects on fertility / Effects on or via lactation	: Not classified			
Effects on Development	: Not classified			
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.			
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.			
Aspiration hazard	: Not applicable.			
12. ECOLOGICAL INFORMATION				
Ecotoxicology Assessment				
Acute aquatic toxicity	: Not classified			
Chronic aquatic toxicity	: Not classified			
Persistence and degradability				
Biodegradability	: Not expected to be biodegradable.			
Bioaccumulative potential				
Bioaccumulation	: This material is not expected to bioaccumulate.			
Mobility in soil				
Additional advice Environmental fate and pathways	: This material is not volatile and insoluble in water.			
Results of PBT and vPvB assess	nent			
	9 / 13			
	9/13			

SAFETY DATA SHEET Hifax TRC 103P 11BK02	(+) 18816996168 Ponciplastics.com BLACK	Gen. Variant: SDS_US_GHS
Version 1.0 Revision Date 04	4/21/2015 Print Date 12	2/23/2019 SDS No.: BE1015
Not applicable. Other adverse effects Additional ecological information	solubility of polymers. No data available on this	be minimal based on the low water product. However, birds, fish and ets which may obstruct their
SECTION 13. DISPOSAL CONSIDER	RATIONS	
Further information	applicable laws and regula engineering practices. Re Recycle if possible.	of or reclaimed in conformance with ations and in conformance with good

SECTION 14. TRANSPORT INFORMATION

Not regulated for transport

SECTION 15. REGULATORY INFORMATION

If identified components of this product are listed under the TSCA 12(b) Export Notification rule, they will be listed below.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material is not known to contain a chemical substance known to the State of California to cause cancer, reproductive, or developmental toxicity under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and CommunityRight to Know Act:14807-96-6Talc, Magnesium Silicate1333-86-4Carbon Black

This product contains the following chemicals regulated by Massachusetts' Right to Know Law: 14807-96-6 Talc, Magnesium Silicate

(+) 18816996168

SAFETY DATA SHEET

Ponciplastics.com



Hifax TRC 103P 11BK02 BLACK Revision Date 04/21/2015

Version 1.0

Print Date 12/23/2019

Gen. Variant: SDS US GHS SDS No.: BE1015

1333-86-4 Carbon Black

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act: 14807-96-6 Talc, Magnesium Silicate

1333-86-4 Carbon Black

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Not Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Not Determined

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been preregistered or, where required under REACh, registered, and that we have the intention to proceed with their registration in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.


SECTION 16. OTHER INFORMATION

Further information

HMIS Classification

: Health Hazard: 0 Flammability: 1 Physical hazards: 0





 $(+)\,18816996168$

Ponciplastics.com

SAFETY DATA SHEET

Hifax TRC 103P 11BK02 BLACK

Version 1.0

Revision Date 04/21/2015

Print Date 12/23/2019

Gen. Variant: SDS_US_GHS 19 SDS No.: BE1015

Iyondellbasel

Disclaimer

Plexar, Pristene, Pro-Fax, Purell, Sequel, Softell, Starflex, and Ultrathene are registered in the U.S. Patent and Trademark Office.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.