	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics.com	luce de llbe e e ll		
according to GB/T 16483-2008, GB/T	17519-2013	lyondellbasell		
Hifax TRC 134P C6 C12594		Gen. Variant: SDS_CN		
Version 1.0 Revision Date 20	21-12-01 Print Date 20	022-01-06 SDS No.: BE9293		
1. IDENTIFICATION OF THE SUBSTA	NCE/MIXTURE AND OF TH	E COMPANY/UNDERTAKING		
	Hifax TRC 134P C6 C12594	l l		
	Mixture Compounded polyolefin			
Synonyms :	Polyolefin, Compounded po	lymer		
	Manufacture of plastic articl or other conversion process	es by injection molding, extrusion		
	devices; Health Canada cla	anent implantation into the body;		
Company AddressCompany TelephoneBasell Advanced Polyolefins (Suzhou) Co.Product Safety +852-2585-0120Ltd.Tel : +86- 512-6283690036, Fangda Street, Suzhou Industrial Park Suzhou, Jiangsu, ChinaProduct Safety +852-2585-0120				
E-mail address : product.safety@lyb.com Responsible/issuing person				
2. HAZARDS IDENTIFICATION				
Emergency Overview				
If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air. At process temperatures irritating fumes may be produced. Molten polymer may cause thermal burns. Slipping hazard if spilled on hard smooth walking surface. The material can accumulate static charges which could be a source of ignition.				
GHS-Classification				
Not a hazardous substance or mixture according to the Globally Harmonized System (GHS).				
GHS-Labeling				
Not a hazardous substance or mixture according to the Globally Harmonized System (GHS).				
Physical-chemical, Health, Environmental Hazard Description				

	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics.com	luce de lles e e ll		
according to GB/T 16483-2008, GB	/T 17519-2013	lyondellbasell		
Hifax TRC 134P C6 C125	94	Gen. Variant: SDS_CN		
Version 1.0 Revision Date	2021-12-01 Print Date 20	022-01-06 SDS No.: BE9293		
Health hazards				
Eyes:	Mechanical irritation is po	ssible.		
Ingestion:	Ingestion not a likely route	e of exposure.		
Inhalation:	in the nose and throat and polymer dust typically exh they are reasonably contr	Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. "Nuisance dust" such as polymer dust typically exhibit no significant health effect when they are reasonably controlled. Exposure to high concentrations of dust may cause slight irritation by mechanical action.		
Skin:	Molten polymer may caus	se thermal burns.		
Other hazards				
Outer hazarda				
No additional information ava	ilable.			
B. COMPOSITION/INFORMATION C	ON INGREDIENTS			
Mixtures				
Components	·			
Chemical name	CAS-No.	<u>Weight %</u>		
Proprietary blend of polyolefinic polymers	Mixture	50.0 - 80.0 %		
Contains: Additives, stabilizers	and fillers			
I. FIRST AID MEASURES				
General advice	: Take proper precautions to before attempting rescue a	ensure your own health and safety nd providing first aid.		
If inhaled	Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)			

	(+) 18816996168	
SAFETY DATA SHEET according to GB/T 16483-2008, GE Hifax TRC 134P C6 C125	Ponciplastics.com 3/T 17519–2013	Gen. Variant: SDS CN
Version 1.0 Revision Date		
	Do not attempt to peel poly skin.	cool the affected tissue and polymer. mer from skin as this will remove the cy medical attention if burn is deep
In case of eye contact	: Flush eyes thoroughly with medical attention if discom	water for several minutes and seek fort persists.
	minutes.	vith cool running water for at least 15 attempt to remove the material
If swallowed	: Adverse health effects due	to ingestion are not anticipated.
Notes to physician		
Symptoms	: Inhalation of process fumes the nose and throat and cc	s and vapors may cause soreness in ughing.
Hazards	: Dust contact with the eyes Molten polymer may cause	can lead to mechanical irritation. thermal burns.
Treatment	: Treatment of overexposure symptoms and the clinical	should be directed at the control of condition of the patient.
5. FIRE-FIGHTING MEASURES		
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or	water spray.
	: LARGE FIRES: Use water spray hose nozz	les from a safe location.
Unsuitable extinguishing media	: None known.	
Specific hazards during fire fighting	produced such as:	sources of ignition. ecomposition products may be dioxide and unburned hydrocarbons

	(+) 18816996168	
SAFETY DATA SHEET according to GB/T 16483-2008, GB/T	Ponciplastics.com	lyondellbasell
Hifax TRC 134P C6 C1259		Gen. Variant: SDS_CN
Version 1.0 Revision Date 20	021-12-01 Print Date 2	022-01-06 SDS No.: BE9293
Special protective equipment : for fire-fighters	Wear approved positive pro apparatus and firefighter p	essure self-contained breathing rotective clothing.
Further information :	conditions. Calorific Value: 8000 - 110 Fight fire from safe distance Heat from fire may melt, de flammable vapors. Move containers from fire a Evacuate immediately in the container pressure relief de Always stay away from tan Do not attempt to get on to fire.	e with hose lines or monitor nozzles. ecompose polymer, and generate area if it can be done without risk. he event of opening of storage evices or discoloration of container.
6. ACCIDENTAL RELEASE MEASUR Personal precautions :	Equip responders with prop Creates dangerous slipping surface. Equip emergency responde equipment (PPE) Avoid generating dust. Avoid dispersal of dust in t with compressed air). Potential combustible dust	g hazard on any hard smooth ers with proper personal protective he air (i.e., clearing dust surfaces
Environmental precautions :	Do not flush into surface w	ater or sanitary sewer system.
Methods for containment / : Methods for cleaning up	vacuum using equipment w On water, material is insolu solid. All recovered material shou transported and disposed o	ble; collect and contain as any ld be packaged, labeled, f or reclaimed in conformance with ons and in conformance with good

	(+) 18816996168	
SAFETY DATA SHEET ccording to GB/T 16483-2008, GB	Ponciplastics.com /T 17519-2013	lyondellbasell
Hifax TRC 134P C6 C125	Gen. Variant: SDS CN	
Version 1.0 Revision Date		
		522 01 00 505 110 BE/2/3
Handling and storage		
Precautions for safe handling		
Advice on safe handling	 concentrations in air. Avoid dust accumulation in e Use dust collection systems dust accumulation. Avoid generating dust; fine o presence of an ignition sourch hazard. Static discharge (spark), or e environments may ignite the explosion Electrostatic charge may bu Equipment handling polyme grounded (earthed) and bon Metal containers involved in should be grounded and bon All electrical equipment shou codes and regulatory require combustible dusts. After handling, always wash water. When bringing the material f may develop may condense section 10. Refer to NFPA 654, Standar Dust Explosions from the Material 	, may form combustible dust enclosed space. a designed per NFPA 654 to avoid dust suspended in air and in the ce is a potential dust explosion other ignition sources, in high dust e dust and result in a dust ild during conveying or handling. r should be conductive and ided. the transfer of this material nded. uld conform to applicable electric
Conditions for sofe storage in	oluding ony incompatibilitie	-
Conditions for safe storage, in Requirements for storage areas and containers	 Store in a dry location. Use good housekeeping pra and handling. Process enclo should be used to avoid exc Store away from excessive oxidizing agents. Keep container closed to pre 	actices during storage, transferring osures and adequate ventilation cessive dust accumulation. heat and away from strong
Specific end use(s)		
	: See Section 1.	

SAFETY DATA SHEET

(+) **18816996168** Ponciplastics.com

according to GB/T 16483-2008, GB/T 17519-2013

Hifax TRC 134P C6 C12594

Version 1.0 Revision Date 2021-12-01 Print Date 2022-01-06

Gen. Variant: SDS_CN

lyondellbasell

SDS No.: BE9293

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

Components	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can		TWA	10 mg/m3	US (ACGIH)	
be formed when			inhalable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					
Materials that can		TWA	3 mg/m3	US (ACGIH)	
be formed when			respirable	2005	
handling this					
product: Non-					
specified (inert or					
nuisance) dust					

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
	Use appropriate respiratory protection where atmosphere exceeds recommended limits.
	Where workers could be exposed to dust concentrations

(+) 18816996168

Ponciplastics.com

SAFETY DATA SHEET according to GB/T 16483-2008, GB/T 17519-2013



Hifax TRC 134P C6 C12594 Gen. Variant: SDS CN Version 1.0 Revision Date 2021-12-01 Print Date 2022-01-06 SDS No.: BE9293 above the exposure limit they must use appropriate certified respirators. Hand protection : Wear gloves that provide thermal protection where there is a potential for contact with heated material. Eye and face protection : Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product. : Wear suitable protective clothing. Skin and body protection Hygiene measures : Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities.

Take off contaminated clothing and wash before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Color	: pellets solid : black
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C

(+) 18816996168 Ponciplastics.com lyondellbasell SAFETY DATA SHEET according to GB/T 16483-2008, GB/T 17519-2013 Hifax TRC 134P C6 C12594 Gen. Variant: SDS CN Revision Date 2021-12-01 Print Date 2022-01-06 SDS No.: BE9293 Version 1.0 Boiling point/boiling range : Not applicable. Vapor pressure : Not applicable. Density > 1 g/cm3 • Water solubility : Insoluble. Partition coefficient: n-: No Data Available. octanol/water Viscosity, dynamic : Not applicable. Relative vapor density : Not applicable. Evaporation rate : Not applicable. Explosive properties : No Data Available. Other Information : No additional information available. **10. STABILITY AND REACTIVITY** Reactivity : No known reactivity hazards. Chemical stability : Stable under normal conditions. Hazardous reactions : Will not occur. Conditions to avoid : Avoid contact with strong oxidizers, excessive heat, sparks or open flame. Materials to avoid : Material may be softened by some hydrocarbons. : Not expected to decompose under normal conditions. Hazardous decomposition products Thermal decomposition : Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed. **11. TOXICOLOGICAL INFORMATION** Acute toxicity : Not classified Acute oral toxicity Acute inhalation toxicity : Not classified Acute dermal toxicity : Not classified

	(+) 18816996168		
SAFETY DATA SHEET according to GB/T 16483-2008, G	BB/T 17519-2013		
Hifax TRC 134P C6 C12 Version 1.0 Revision Date		SDS_CN No.: BE9293	
Skin corrosion/irritation	: Not a skin irritant.	INU BE9293	
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.		
Respiratory or skin sensitization	: Not classified		
Chronic toxicity			
Carcinogenicity	: Not classified		
Germ cell mutagenicity	: Not classified		
Reproductive toxicity			
Effects on fertility / Effects on or via lactation	: Not classified		
Effects on Development	: Not classified		
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific organ toxicant, single exposure.	; target	
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is not classified as specific organ toxicant, repeated exposure.	; target	
Aspiration hazard	: Not applicable.		
12. Ecological information			
Ecotoxicology Assessment			
Short-term (acute) aquatic	: Not classified		
hazard Long-term (chronic) aquatic hazard	: Not classified		
Persistence and degradability			

	(+) 18816996168				
SAFETY DATA SHEET	Ponciplastics.com	lvoodollbacoll			
according to GB/T 16483-2008, GB/	/T 17519-2013	lyondellbasell			
Hifax TRC 134P C6 C12594 Gen. Variant: SDS_CN					
Version 1.0 Revision Date 2	2021-12-01 Print Date 20	022-01-06 SDS No.: BE9293			
Biodegradability	: Not expected to be biodegra	adable.			
Bioaccumulative potential					
Bioaccumulation	: This material is not expecte	d to bioaccumulate.			
Mobility in soil					
Mobility	: no data available				
Other adverse effects					
Environmental fate and pathways	: This material is not volatile a	and insoluble in water.			
Other information					
Additional ecological information	Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.				
13. Disposal considerations					
Waste treatment methods					
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.				
14. TRANSPORT INFORMATION					
Not regulated for transport					
15. REGULATORY INFORMATION					
Other international regulations					
Global Inventory Status					

SAFETY DATA SHEET

(+) **18816996168** Ponciplastics.com

according to GB/T 16483-2008, GB/T 17519-2013

Hifax TRC 134P C6 C12594

Revision Date 2021-12-01 Print Date 2022-01-06

Gen. Variant: SDS_CN

lyondellbasell

SDS No.: BE9293

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Not Determined
Philippines	PICCS	Not Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

Version 1.0

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

First Edition

Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

	(+) 18816996168 Ponciplastics.com	
SAFETY DATA SHEET according to GB/T 16483-2008, GB/T		J lyondellbasell
Hifax TRC 134P C6 C12594		Gen. Variant: SDS_CN
Version 1.0 Revision Date 20	21-12-01 Print Date 2	2022-01-06 SDS No.: BE9293

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet