	(+) 18816996168
	Ponciplastics.com
SAFETY DATA SHEET	lyondellbase
	I 2637 Gen. Variant: SDS_US_GHS
Hifax TRC 228P NA C ⁻ Version 1.1 Revision Dat	e 10/01/2019 Print Date 01/06/2022 SDS No.: BE1574
. IDENTIFICATION OF THE SU	BSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name	: Hifax TRC 228P NA C12637
CAS Number: Chemical name	: Mixture : Compounded polyolefin
Synonyms	: Polyolefin, Compounded polymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion
	or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical
	devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body;
	Life-sustaining medical applications
<u>Company Address</u> Equistar Chemicals, LP	Company Telephone Customer Service 888 777-0232
LyondellBasell Tower, Suite	
1221 McKinney St. P.O. Box 2583	
Houston Texas 77252-2583	
Emergency telephone num	ber
EQUISTAR 800-245-4532	
E-mail address	: product.safety@lyb.com
Responsible/issuing person	
2. HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing, handling or by other means, may form combustible dust
	concentrations in air.
Other hazards	
	1 / 14

		(+) 18816996168	
In case of skin contact If moltane is of skin contact If in case of eye contact If moltane is of skin contact If is wallowed If moltane is of skin contact If is wallowed If moltane is of skin contact	AFETY DATA SHEET	Ponciplastics.com	lvondellbase
ersion 1.1 Revision Date 10/01/2019 Print Date 01/06/2022 SDS No.: BE1 No additional information available. COMPOSITION/INFORMATION ON INGREDIENTS xtures Components	lifax TRC 228P NA C1	2637	Gen. Variant: SDS_US_GH
COMPOSITION/INFORMATION ON INGREDIENTS xtures Components Chemical name CAS-No. Weight % Proprietary blend of polyolefinic Mixture 80.0 - 100.0 % contains: Additives, stabilizers and fillers FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and sa before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, g medical attention. In case of excessive inhalation of fumes that may be gene during heating of this material, move the person to fresh ai Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuctation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and poly Do not attempt to peel polymer from skin as this will remov skin. Obtain immediate emergency medical attention if burn is do or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and a medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with water for several minutes and a medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with water for several minutes and a medical attention if discomfort persists.			/06/2022 SDS No.: BE15
COMPOSITION/INFORMATION ON INGREDIENTS xtures Components Chemical name CAS-No. Weight % Proprietary blend of polyolefinic Mixture 80.0 - 100.0 % Contains: Additives, stabilizers and fillers FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and sa before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, g medical attention. In case of excessive inhalation of fumes that may be gene during heating of this material, move the person to fresh ai Obtain medical attention. In case of excessive inhalation of fumes that may be gene during heating of this material, move the person to fresh ai Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and poly Do not attempt to peel polymer from skin as this will remov skin. Obtain immediate emergency medical attention if burn is do or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and a medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with water for several minutes and a diverent to the eye(s). Immediately seek medical attention. Be			
xtures Components Proprietary blend of polyolefinic polymers Mixture 80.0 - 100.0 % Contains: Additives, stabilizers and fillers FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and set before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, g medical attention. In case of excessive inhalation of fumes that may be gene during heating of this material, move the person to fresh ai Obtain medical attention. In case of skin contact In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and poly Do not attempt to peel polymer from skin as this will remov skin. Obtain immediate emergency medical attention if burn is d or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and s medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with cool running water for at lear minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated	No additional information a	vailable.	
Components Image: Construct of polyolefinic of polymers Mixture 80.0 - 100.0 % Contains: Additives, stabilizers and fillers Contains: Additives, stabilizers and fillers FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and sea before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, gemedical attention. In case of excessive inhalation of fumes that may be gene during heating of this material, move the person to fresh ai Obtain medical attention. In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and poly Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is do or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seminutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated	COMPOSITION/INFORMATION	ON INGREDIENTS	
Chemical name CAS-No. Weight % Proprietary blend of polyolefinic Mixture 80.0 - 100.0 % polymers Contains: Additives, stabilizers and fillers FIRST AID MEASURES General advice			
polymers		CAS-No.	Weight %
Contains: Additives, stabilizers and fillers FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and se before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, g medical attention. In case of excessive inhalation of fumes that may be gene during heating of this material, move the person to fresh ai Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and poly Do not attempt to peel polymer from skin as this will remov skin. Obtain immediate emergency medical attention if burn is d or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and a medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with molten polymer: Continuously flush eye(s) with cool running water for at learninutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated		c Mixture	80.0 - 100.0 %
FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and sabefore attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, gmedical attention. In case of excessive inhalation of fumes that may be gene during heating of this material, move the person to fresh ai Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and poly Do not attempt to peel polymer from skin as this will removiskin. Obtain immediate emergency medical attention if burn is do or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and similatention. In case of eye contact : Flush eyes thoroughly with water for several minutes and similatention. In case of eye contact : Flush eyes thoroughly with molten polymer: Continuously flush eye(s) with cool running water for at leadminutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated	polymers		
General advice : Take proper precautions to ensure your own health and sate before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, genedical attention. In case of excessive inhalation of fumes that may be geneduring heating of this material, move the person to fresh air. Obtain medical attention. In case of excessive inhalation of fumes that may be geneduring heating of this material, move the person to fresh air. Obtain medical attention. Neep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and poly Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is do or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and semedical attention if discomfort persists. : In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at lear minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated	Contains: Additives, stabilizer	s and fillers	
General advice : Take proper precautions to ensure your own health and sate before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, genedical attention. In case of excessive inhalation of fumes that may be geneduring heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and poly Do not attempt to peel polymer from skin as this will remove skin. Obtain immediate emergency medical attention if burn is do or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and se medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at lear minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated			
If inhaled : Remove person to fresh air. If signs/symptoms continue, g medical attention. In case of excessive inhalation of fumes that may be gene during heating of this material, move the person to fresh ai Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and poly Do not attempt to peel polymer from skin as this will remov skin. Obtain immediate emergency medical attention if burn is do or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and a medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at lea minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated	FIRST AID MEASURES		
medical attention. In case of excessive inhalation of fumes that may be gene during heating of this material, move the person to fresh at Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and poly Do not attempt to peel polymer from skin as this will remov skin. Obtain immediate emergency medical attention if burn is d or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and s medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at lear minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated	General advice		-
Iarge amounts of water to cool the affected tissue and poly Do not attempt to peel polymer from skin as this will removiskin. Obtain immediate emergency medical attention if burn is dor extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and simedical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at lear minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated	lf inhaled	medical attention. In case of excessive inhal during heating of this mat Obtain medical attention. Keep person warm, if nec	ation of fumes that may be genera erial, move the person to fresh air.
medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at lear minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated	In case of skin contact	large amounts of water to Do not attempt to peel po skin. Obtain immediate emerge	cool the affected tissue and polym lymer from skin as this will remove
Continuously flush eye(s) with cool running water for at lead minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated	In case of eye contact		
· · ·		Continuously flush eye(s) minutes. Beyond flushing, DO NOT adherent to the eye(s).	with cool running water for at leas
2 / 14	If swallowed	: Adverse health effects du	e to ingestion are not anticipated.
		2 / 14	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	I I III
Hifax TRC 228P NA C12 /ersion 1.1 Revision Date	
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control symptoms and the clinical condition of the patient.
FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbor (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved ir fire. Cool storage containers with large volumes of water even aft fire is out.
	3 / 14

SAFETY DATA SHEET Penciplastics, con Hifax TRC 228P NA C12637 Ext. Variant: SDE 0.6 Version 1.1 Revision Date 10/01/2013 Print Date 01/06/2023 SDE No. 16 ACCIDENTAL RELEASE MEASURES Equip presponders with proper protection. Creates dangerous sipping hazard on any hard smootl surface. Equip emergency responders with proper personal prot equipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surf with compressed air). Potential combustible dust hazard. Potential combustible dust hazard. Methods for containment / Methods for cleaning up In land, sweep/shovel into suitable disposal contain as a solid. Methods for cleaning up In land, sweep/shovel into suitable disposal contain as a solid. Methods for cleaning up In land, sweep/shovel into suitable disposal contain as a solid. Methods for cleaning up In land, sweep/shovel into suitable disposal contain as a solid. Methods for cleaning up In land, sweep/shovel into suitable disposal contain as a solid. Methods for cleaning up In land, sweep/shovel into suitable disposal contain as a solid. Methods for cleaning up In converted to small particles during further processing, handing, or by other means, may form combustible dus concentrations and in conformance wit engineering practices. Reclaim where possible: * Handling and storage Methods for cleaning up Advid dus accumulation in enclosed space. Use d					16996168			
Accidential and storage Print Date 10/07/2019 Print Date 01/06/2022 SDS No.: I Advice on safe handling : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smootl surface. Equip emergency responders with proper personal prot equipment (PPE) Avoid generating dust. Avoid generating dust. Avoid generating dust. Avoid generating dust. Avoid generating dust. Potential combustible dust hazard. Polymer particles create slipping hazard on hard smoot surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system acuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as a solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance wit engineering practices. Reclaim where possible. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dus concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and in presence of an ignition source is a potential dust explosion Electrostatic charge may build during conveying or hand Equipment handling polymer should be conductive and	3Se	lellb	ronde	ľ	astics.com	Poncipl	ATA SHEET	AFETY DAT
Personal precautions Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal prot equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surf with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smoot surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as a solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance wit engineering practices. Reclaim where possible. Handling and storage Metrial is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dus concentrations in air. Avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in presence of an ignition source is a potential dust explos hazard. Static discharge (spark), or other ignition sources, in hig environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or hance Equipment handling polymer should be conductive and equipment handling polymer should be conductive and					Print Date			
Personal precautions Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal prot equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surf with compressed of the attent of the attent of the attent of the attent Polymer particles create slipping hazard on hard smoot surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as at solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance wit engineering practices. Reclaim where possible. Handling and storage Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dus concentrations in air. Avoid dust accumulation. Avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in presence of an ignition source is a potential dust explos hazard. Static clischarge (spark), or other ignition sources, in hig environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or hance Equipment handling polymer should be conductive and								
Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protequipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfwith compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system vacuum using equipment which avoids ignition risk. Methods for cleaning up : On land, sweep/shovel into suitable disposal containers vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as a solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance wite engineering practices. Reclaim where possible. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dus concentrations in air. Avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in presence of an ignition source is a potential dust explos hazard. Avoid generating dust; fine dust suspended in air and in presence of an ignition source is a potential dust explos hazard. Static discharge (spark), or other ignition sources, in hig environments may ignite the dust and result in a dust explosion						SURES	. RELEASE MEASU	ACCIDENTAL
Methods for containment / On land, sweep/shovel into suitable disposal containers vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as an solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance wite engineering practices. Reclaim where possible. Handling and storage Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dus concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and in presence of an ignition source is a potential dust explos hazard. Static discharge (spark), or other ignition sources, in hig environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or hand Equipment handling polymer should be conductive and	otective Irfaces	personal pr	on any ha proper pers e., clearing	ing hazar nders with n the air (st hazard	angerous slip ergency respo t (PPE) erating dust. persal of dust pressed air). combustible c	Creates of surface. Equip en equipmer Avoid ge Avoid dis with com Potential Polymer	ecautions	Personal prec
Methods for cleaning up vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as ar solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance applicable laws and regulations and in conformance with engineering practices. Reclaim where possible. Handling and storage Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dus concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and in presence of an ignition source is a potential dust explos hazard. Static discharge (spark), or other ignition sources, in hig environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or hanc Equipment handling polymer should be conductive and	em.	sewer syst	anitary sev	water or	sh into surfac	: Do not flu	tal precautions	Environmenta
Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dus concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and in presence of an ignition source is a potential dust explos hazard. Static discharge (spark), or other ignition sources, in hig environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or hand Equipment handling polymer should be conductive and	any nce witl	ion risk. contain as labeled, conformai prmance w	ids ignition ect and cor ckaged, lak aimed in co l in conform	which av oluble; co ould be p l of or rec ations ar	sing equipmer material is ins ed material s d and dispose laws and reg	vacuum u On water, solid. All recove transporte applicable		
Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dus concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and in presence of an ignition source is a potential dust explos hazard. Static discharge (spark), or other ignition sources, in hig environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or hand Equipment handling polymer should be conductive and							d storage	Handling and s
If converted to small particles during further processing, handling, or by other means, may form combustible dus concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and in presence of an ignition source is a potential dust explos hazard. Static discharge (spark), or other ignition sources, in hig environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or hand Equipment handling polymer should be conductive and						ng	is for safe handling	Precautions
4 / 14	ist o avoid in the osion igh dus ndling.	IFPA 654 f IFPA 654 f in air and dust explo purces, in h in a dust ying or ha	orm combus d space. ed per NFP spended in potential du nition sourc nd result in g conveying	cles durir ins, may in enclos ms desig ue dust su purce is a or other in the dust a build dur	d to small par or by other me ions in air. collection syst nulation. erating dust; f of an ignition s harge (spark) hts may ignite tic charge ma	If converter handling, concentra Avoid dus Use dust dust accu Avoid gen presence hazard. Static disc environme explosion Electrosta	afe handling	Advice on saf
					/ 14	4		

(+) 18816996168

		(+)100	10990108		
SAFETY DATA S		Poncip1	astics.com		
SALLII DATA S				Iyonae	ellbasel
Hifax TRC 228F	NA C126	637		Gen. Variant:	SDS_US_GHS
	vision Date 10		Print Date 0	1/06/2022 S	DS No.: BE1574
Fire-fighting class Conditions for saf Requirements for s areas and containe	e storage, in torage	grounded Metal cont should be All electric codes and combustib After hand water. When brin may develous section 10 Refer to N Dust Exploi Handling co Polymer w cluding any Store in a Use good and handli should be Store away oxidizing a Keep cont	(earthed) and b ainers involved grounded and al equipment s regulatory required le dusts. ling, always wa ging the materi- op may conden FPA 654, Stand bions from the of Combustible rill burn but doe r incompatibili dry location. housekeeping ng. Process en used to avoid e y from excessiva agents. ainer closed to	bonded. in the transfer of this bonded. hould conform to app uirements for areas h ish hands thoroughly al to processing temp ise in the exhaust ve dard for the Preventic Manufacturing, Proc Particulate Solids, fo s not easily ignite.	s material blicable electric handling with soap and beratures vapors ntilation. See on of Fire and esssing, and r safe handling. age, transferring the ventilation hulation. m strong
Specific end use(s	-	See Section	on 1.		
3. EXPOSURE CONTR Control parameters Ingredients with v Occupational Exp	vorkplace co	ntrol param			
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
		5	/ 14		

 $(+)\,18816996168$

Ponciplastics.com

lyondellbasell

Hifax TRC 22	8PNA	C12637
Version 1.1	Revision	Date 10/01/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE15744

Materials that can	TW	· · · · · · · · · · · · · · · · · · ·	US (ACGIH)	
be formed when handling this		respirable	2005	
product: Non-				
specified (inert or				
nuisance) dust				
Materials that can	TW	A 15 mg/m3	US (OSHA)	
be formed when		total dust	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust				
Materials that can	TW	0	US (OSHA)	
be formed when		respirable	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust				

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	:	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	:	Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	:	Dust service goggles should be worn to prevent mechanical
		6 / 14

(+) 18816996168

Version 1.1 Revision Date 10/01/2019 Print Date 01/06/2022 SDS No.: BE19 injury or other irritation to eyes due to airborne particles white may result from handling this product. injury or other irritation to eyes due to airborne particles white may result from handling this product. Skin and body protection : Wear suitable protective clothing. Hygiene measures : Selection of appropriate personal protective equipment shot be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toile facilities. Take off contaminated clothing and wash before reuse.		(+) 18810990108	
Hifax TRC 228P NA C12637 Gen. Variant: SDS. US, Gi Version 1.1 Revision Date 10/01/2019 Print Date 01/06/2022 SDS No :: BE11 injury or other irritation to eyes due to airborne particles white may result from handling this product. Skin and body protection :: Wear suitable protective clothing. Hygiene measures : Selection of appropriate personal protective equipment shot becard on an evaluation of the performance characteristic of the protectine equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using tolle facilities. Take off contaminated clothing and wash before reuse. Pellets. Color : Slight. Odor : Slight. Odor : No value available. Flash point : No bata Available. Elash point : No tapplicable. Upper explosion limit : Not applicable. Flammability (solid, gas) : Polymer will burn but does not easily ignite. Oxidizing properties : Not considered an axidizing agent. Autoignition temperature : y 300 °C Decomposition temperature : not determined Metting point/range	SAFETY DATA SHEET	Ponciplastics.com	lugadallbaca
Version 1.1 Revision Date 10/01/2019 Print Date 01/06/2022 SDS No.: BE14 injury or other irritation to eyes due to airbome particles while may result from handling this product. Skin and body protection : Wear suitable protective clothing. Hygiene measures : Selection of appropriate personal protective equipment shot be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Version 1.1 Wear Suitable Protective eating, drinking, smoking, or using toile facilities. . Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toile facilities. Take off contaminated clothing and wash before reuse. PHYSICAL AND CHEMICAL PROPERTIES Appearance : Pellets. Color : Black Odor Odor : Slight. Odor Odor : No value available. Lower explosion limit Lower explosion limit : No tapplicable. Flammability (solid, gas) : Polymer will burn but does not easily ignite. Oxidizing properties : Not considered an oxidizing agent. Autoignition temperature : not determined Melting point/range : S0 - 170 °C<			iyondelibase
injury or other irritation to eyes due to airborne particles whi may result from handling this product. Skin and body protection : Wear suitable protective clothing. Hygiene measures : Selection of appropriate personal protective equipment sho be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toile facilities. Take off contaminated clothing and wash before reuse. PHYSICAL AND CHEMICAL PROPERTIES Appearance : Pellets. Color : Black Odor : Slight. Odor Threshold : No value available. Flash point : No Data Available. Lower explosion limit : No pata Available. Flammability (solid, gas) : Polymer will burn but does not easily ignite. Oxidizing properties : Not considered an oxidizing agent. Autoignition temperature : > 300 °C Decomposition temperature : not determined Melting point/boiling range : Not applicable. Vapor pressure : Not applicable.			Gen. Variant: SDS_US_GH
may result from handling this product. Skin and body protection : Wear suitable protective clothing. Hygiene measures : Selection of appropriate personal protective equipment shot be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. PHYSICAL AND CHEMICAL PROPERTIES Appearance : Pellets. Color : Black Odor : Slight. Odor Threshold : No value available. Flash point : No taplicable. Icover explosion limit : The minimum explosive concentration (MEC) for polymer d varies according to particle size distribution. Upper explosion limit : Not applicable. Flammability (solid, gas) : Polymer will burn but does not easily ignite. Oxidizing properties : Not considered an oxidizing agent. Autoignition temperature : s00 °C Decomposition temperature : not determined Metting point/boiling range : 50 - 170 °C Boiling point/boiling range : Not applicable.	Version 1.1 Revision Date	10/01/2019 Print Date 0	01/06/2022 SDS No.: BE15
may result from handling this product. Skin and body protection : Wear suitable protective clothing. Hygiene measures : Selection of appropriate personal protective equipment shot be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toile facilities. Take off contaminated clothing and wash before reuse. Take off contaminated clothing and wash before reuse. PHYSICAL AND CHEMICAL PROPERTIES Appearance : Pellets. Color : Black Odor Odor : Slight. Odor Threshold : No value available. Flash point : No taplicable. Eacerding to particle size distribution. Upper explosion limit : Not applicable. Flammability (solid, gas) : Polymer will burn but does not easily ignite. Oxidizing properties : Not considered an oxidizing agent. Autoignition temperature : s000 °C Decomposition temperature : not determined Melting point/boiling range : 50 - 170 °C Boiling point/boiling range : Not applicable. <			
Hygiene measures : Selection of appropriate personal protective equipment shot be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toile facilities. Take off contaminated clothing and wash before reuse. PHYSICAL AND CHEMICAL PROPERTIES Appearance : Pellets. Color : Black Odor : Slight. Odor : Slight. Odor : No value available. Flash point : No Data Available. Lower explosion limit : The minimum explosive concentration (MEC) for polymer d varies according to particle size distribution. Upper explosion limit : Not applicable. Flammability (solid, gas) : Polymer will burn but does not easily ignite. Oxidizing properties : Not considered an oxidizing agent. Autoignition temperature : not determined Metting point/range : 50 - 170 °C Boiling point/boiling range : Not applicable. Vapor pressure : Not applicable.			
be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toile facilities. Take off contaminated clothing and wash before reuse. Appearance : Color : Black Odor : Odor : Slight. Odor : Odor : Slight. Odor : No value available. Lower explosion limit : No value available. Lower explosion limit : Not applicable. Flammability (solid, gas) : Polymer will burn but does not easily ignite. Oxidizing properties : Not considered an oxidizing agent. Autoignition temperature : Polymer will burn but does not easily ignite. Oxidizing point/range<	Skin and body protection	: Wear suitable protective	clothing.
facilities. Take off contaminated clothing and wash before reuse. PHYSICAL AND CHEMICAL PROPERTIES Appearance : Pellets. Color : Black Odor : Slight. Odor Threshold : No value available. Flash point : No Data Available. Lower explosion limit : The minimum explosive concentration (MEC) for polymer divaries according to particle size distribution. Upper explosion limit : Not applicable. Flammability (solid, gas) : Polymer will burn but does not easily ignite. Oxidizing properties : Not considered an oxidizing agent. Autoignition temperature : not determined Melting point/range : 50 - 170 °C Boiling point/boiling range : Not applicable. Vapor pressure : Not applicable.	Hygiene measures	be based on an evaluation of the protective equipment performed, conditions pro- hazards and/or potential during use. Use good personal hygie	n of the performance characteristics ent relative to the task(s) to be esent, duration of use, and the hazards that may be encountered ene practices.
PHYSICAL AND CHEMICAL PROFERTIES Appearance : Pellets. Color : Black Odor : Slight. Odor Threshold : No value available. Flash point : No Data Available. Lower explosion limit : The minimum explosive concentration (MEC) for polymer divaries according to particle size distribution. Upper explosion limit : Not applicable. Flammability (solid, gas) : Polymer will burn but does not easily ignite. Oxidizing properties : Not considered an oxidizing agent. Autoignition temperature : > 300 °C Decomposition temperature : 50 - 170 °C Boiling point/boiling range : Not applicable. Vapor pressure : Not applicable.		facilities.	
Appearance Color: Pellets. : BlackOdor: Slight.Odor Threshold: No value available.Flash point: No Data Available.Lower explosion limit: The minimum explosive concentration (MEC) for polymer divaries according to particle size distribution.Upper explosion limit: Not applicable.Flammability (solid, gas): Not considered an oxidizing agent.Autoignition temperature: Not considered an oxidizing agent.Metting point/range: So - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.		Take on containinated of	othing and wash before reuse.
Appearance Color: Pellets. : BlackOdor: Slight.Odor Threshold: No value available.Flash point: No Data Available.Lower explosion limit: The minimum explosive concentration (MEC) for polymer divaries according to particle size distribution.Upper explosion limit: Not applicable.Flammability (solid, gas): Not considered an oxidizing agent.Autoignition temperature: Not considered an oxidizing agent.Melting point/range: So - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.			
Appearance Color: Pellets. : BlackOdor: Slight.Odor Threshold: No value available.Flash point: No Data Available.Lower explosion limit: The minimum explosive concentration (MEC) for polymer divaries according to particle size distribution.Upper explosion limit: Not applicable.Flammability (solid, gas): Not considered an oxidizing agent.Autoignition temperature: Not considered an oxidizing agent.Melting point/range: So - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.	PHYSICAL AND CHEMICAL P	ROPERTIES	
Odor: Slight.Odor Threshold: No value available.Flash point: No Data Available.Lower explosion limit: The minimum explosive concentration (MEC) for polymer of varies according to particle size distribution.Upper explosion limit: Not applicable.Flammability (solid, gas): Polymer will burn but does not easily ignite.Oxidizing properties: Not considered an oxidizing agent.Autoignition temperature: >300 °CDecomposition temperature: 50 - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.			
Odor Threshold: No value available.Flash point: No Data Available.Lower explosion limit: The minimum explosive concentration (MEC) for polymer diverse according to particle size distribution.Upper explosion limit: Not applicable.Flammability (solid, gas): Polymer will burn but does not easily ignite.Oxidizing properties: Not considered an oxidizing agent.Autoignition temperature: > 300 °CDecomposition temperature: 50 - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.	Color	: Black	
Flash point: No Data Available.Lower explosion limit: The minimum explosive concentration (MEC) for polymer of varies according to particle size distribution.Upper explosion limit: Not applicable.Flammability (solid, gas): Polymer will burn but does not easily ignite.Oxidizing properties: Not considered an oxidizing agent.Autoignition temperature: > 300 °CDecomposition temperature: for - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.	Odor	: Slight.	
Lower explosion limit: The minimum explosive concentration (MEC) for polymer divaries according to particle size distribution.Upper explosion limit: Not applicable.Flammability (solid, gas): Polymer will burn but does not easily ignite.Oxidizing properties: Not considered an oxidizing agent.Autoignition temperature: > 300 °CDecomposition temperature: not determinedMelting point/range: 50 - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.	Odor Threshold	: No value available.	
Varies according to particle size distribution.Upper explosion limit: Not applicable.Flammability (solid, gas): Polymer will burn but does not easily ignite.Oxidizing properties: Not considered an oxidizing agent.Autoignition temperature: > 300 °CDecomposition temperature: not determinedMelting point/range: 50 - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.	Flash point	: No Data Available.	
Flammability (solid, gas): Polymer will burn but does not easily ignite.Oxidizing properties: Not considered an oxidizing agent.Autoignition temperature: > 300 °CDecomposition temperature: not determinedMelting point/range: 50 - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.	Lower explosion limit		
Oxidizing properties: Not considered an oxidizing agent.Autoignition temperature: > 300 °CDecomposition temperature: not determinedMelting point/range: 50 - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.	Upper explosion limit	: Not applicable.	
Autoignition temperature: > 300 °CDecomposition temperature: not determinedMelting point/range: 50 - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.	Flammability (solid, gas)	: Polymer will burn but do	es not easily ignite.
Decomposition temperature: not determinedMelting point/range: 50 - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.	Oxidizing properties	: Not considered an oxidiz	zing agent.
Melting point/range: 50 - 170 °CBoiling point/boiling range: Not applicable.Vapor pressure: Not applicable.	Autoignition temperature	: > 300 °C	
Boiling point/boiling range: Not applicable.Vapor pressure: Not applicable.	Decomposition temperature	: not determined	
Vapor pressure : Not applicable.	Melting point/range	: 50 - 170 °C	
	Boiling point/boiling range	: Not applicable.	
Density : < 1 g/cm3	Vapor pressure	: Not applicable.	
	Density	: <1 g/cm3	
Water solubility : Insoluble.	Water solubility	: Insoluble.	

	(+) 18816996168 Ponciplastics.com
SAFETY DATA SHEET	lyondellbase
Hifax TRC 228P NA C1	
Version 1.1 Revision Date	e 10/01/2019 Print Date 01/06/2022 SDS No.: BE157
Partition coefficient: n-	: No Data Available.
octanol/water Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
0. STABILITY AND REACTIVITY	(
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition	: Not expected to decompose under normal conditions.
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
1. TOXICOLOGICAL INFORMA	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
-	
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 14

	(+) 18	816996168	
SAFETY DATA SHEET	Poncip	lastics.com	lvoodollbacoll
			lyondellbasell
Hifax TRC 228P NA C12		Drint Data 01/06/2	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	10/01/2019	Print Date 01/06/2	022 SDS No.: BE15744
Respiratory or skin sensitization	: Not class	sified	
Chronic toxicity			
Component Name	NTP	IARC	OSHA
Carbon Black		2B	Present
Carcinogenicity	: Not class	sified	
		component(s) listed b	y IARC as possibly
	This mate		a thermoplastic resin with
	limited re and stora		onditions of use, transportation,
Germ cell mutagenicity	: Not class	sified	
Reproductive toxicity			
Effects on fertility / Effects on or via lactation	: Not class	sified	
Effects on Development	: Not class	sified	
Target Organ Systemic Toxicant - Single exposure		stance or mixture is not kicant, single exposure	t classified as specific target
Target Organ Systemic Toxicant - Repeated exposure		stance or mixture is not kicant, repeated expos	t classified as specific target ure.
Aspiration hazard	: Not appli	aabla	
12. Ecological information			
Ecotoxicology Assessment			
Short-term (acute) aquatic	: Not class	ified	
hazard Long-term (chronic) aquatic hazard	: Not class	ified	
		9 / 14	
L			

	(+) 18816996168
	Ponciplastics.com
SAFETY DATA SHEET	lyondellbasell
Hifax TRC 228P NA C120	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date 10	
Devoistance and desvedability	
Persistence and degradability	
Biodegradability	Not expected to be biodegradable.
Bioaccumulative potential	
Bioaccumulation	This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	no data available
Other adverse effects	
Environmental fate and	This material is not volatile and insoluble in water.
pathways	
Other information	
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations	
Waste treatment methods	
Product	All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
	10 / 14

	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell		
Hifax TRC 228P NA C12	2637	Gen. Variant: SDS_US_GHS		
Version 1.1 Revision Date	10/01/2019 Print Date 01/06/2	2022 SDS No.: BE15744		
Not regulated for transport				
15. REGULATORY INFORMATION				
TSCA 12b				
The following substance(s) is/are si	ubject to TSCA 12(b) export notifica	tion requirements:		
Component	CASRN	Section		
Octamethylcyclotetrasiloxane	556-67-2			
Significant New Use Rules (SNUR) No substances are subject to a Significant New Use Rule.				
SARA 302/304				
This product contains no known che	emicals regulated under SARA 302	/304.		
SARA 311/312				
Based upon available information, t hazards according to Section 311 &		wing health and/or physical		
Combustible dust				
SARA 313				
This product contains no known chemicals regulated under SARA 313.				
State Reporting				
This material does not contain lister birth defects, or other reproductive 65 State Drinking Water and Toxic However, LyondellBasell has not te	harm that would require warning un Enforcement Act.	der the California Proposition		

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

14807-96-6Talc, Magnesium Silicate1333-86-4Carbon Black


This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

14807-96-6 Talc, Magnesium Silicate

11 / 14

			(+) 188169		
SAFE	TY DAT	A SHEET	Ponciplasti	CS. COM	lyondellbasell
Hifax	TRC 2	28P NA C126	37		Gen. Variant: SDS_US_GHS
Versior	n 1.1	Revision Date 10/	/01/2019 Pr	int Date 0 ⁻	1/06/2022 SDS No.: BE15744
1333-86	6-4	Carbon Black			
This pro	duct contai	ins the following che	micals regulated	by Penns	sylvania's Right to Know Act:
14807-9 1333-86		Talc, Magnesium S Carbon Black	ilicate		
Other in	nternationa	al regulations			
Global Inventory Status The ingredients of this product are compliant with the following chemical inventory requirements or exemptions. *Additional Explanatory Status Statements follow the table, as necessary.					
	Country/	Region	Inventory	Status	Description
	Australia		AICS	Complia	
	Canada		DSL	Complia	
	China		IECSC	Complia	
	Europe		REACH	See RE	ACH Compliance Statement
	Japan		ENCS	Complia	ant
	Korea		KECI	Complia	ant
	New Zeal		NZIoC	Complia	ant
	Philippine		PICCS	Complia	ant
	United St	ates of America	TSCA	Complia	
	Taiwan		TCSCA	Complia	ant
REACh status If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)					
Contact product.safety@lyb.com for additional global inventory information.					

16. OTHER INFORMATION		
	et sections which have been up	dated:
Revised Section(s): 15	16	
HMIS Classification	: Health Hazard: 0 Flammability: 1	0 1 0
	12 / 14	



SAFETY DATA SHEET	(+) 18816996168 Ponciplastics.com	
Hifax TRC 228P NA C126	37	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date 10/	/01/2019 Print Date 0	01/06/2022 SDS No.: BE15744

14 / 14