Ponciplastics.com Gen. Variant: SDS_US 10/01/2019 Print Date 01/06/2022 SDS No.: TANCE/MIXTURE AND OF THE COMPANY/UNDERTAKIN : Hifax TYC 1168P 1 RXF : Mixture : Compounded polyolefin : Polyolefin, Compounded polymer	6_GF <u>BE1</u>
Gen. Variant: SDS_US Gen. Variant: SDS_US SDS No.: TANCE/MIXTURE AND OF THE COMPANY/UNDERTAKIN Hifax TYC 1168P 1 RXF Mixture Compounded polyolefin Polyolefin, Compounded polymer	6_GF <u>BE1</u>
10/01/2019 Print Date 01/06/2022 SDS No.: TANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING : Hifax TYC 1168P 1 RXF : Mixture : Compounded polyolefin : Polyolefin, Compounded polymer	BE1
TANCE/MIXTURE AND OF THE COMPANY/UNDERTAKIN : Hifax TYC 1168P 1 RXF : Mixture : Compounded polyolefin : Polyolefin, Compounded polymer	
 Hifax TYC 1168P 1 RXF Mixture Compounded polyolefin Polyolefin, Compounded polymer 	NG
 Hifax TYC 1168P 1 RXF Mixture Compounded polyolefin Polyolefin, Compounded polymer 	NG
 Mixture Compounded polyolefin Polyolefin, Compounded polymer 	
Compounded polyolefinPolyolefin, Compounded polymer	
: Polyolefin, Compounded polymer	
: Manufacture of plastic articles by injection molding, extru	Isior
or other conversion process.	10101
: FDA Class III medical devices; European class III medical	al
	odv.
Life-sustaining medical applications	Juy,
Company Telephone	
Customer Service 888 777-0232	
0 product.safety@lyb.com	
: Warning	
-	na
handling or by other means, may form combustible dust concentrations in air.	ıg,
1 / 14	
e	 FDA Class III medical devices; European class III medica devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the belief of the sustaining medical applications Company Telephone Customer Service 888 777-0232 product.safety@lyb.com product.safety@lyb.com product.safety@lyb.com i product.safety@lyb.com i f small particles are generated during further processin handling or by other means, may form combustible dust concentrations in air.

<section-header> SAFETY DATA SHEET Exercised MATERY DATA SHEET Exercised MATERY CALL Revision Date 1001/2019 Print Date 01/06/2022 Six Nr.: BE198 Materia Call Revision Date 1001/2019 Print Date 01/06/2022 Six Nr.: BE198 Acaditional information available. CALL Revision Date 1001/2019 Print Date 01/06/2022 Six Nr.: BE198 Composition Composition Composition Nr.: BE198 Nr.: BE198 Propriotary Duend of polyolefinic divisure 80.0 - 100.0 % Nr.: BE198 Printing Strain St</section-header>		(+) 18816996168	
Hiftax TYC 1168P 1 RXF Gen. Variant: SDS US GHS Version 1.1 Revision Date 10/01/2019 Print Date 01/06/2022 SDS No.: BE188 No additional information available. SCOMPOSITION/INFORMATION ON INGREDIENTS Status Accomponents Components Status 80.0 - 100.0 % Proprietary blend of polyolefinic Mixture 80.0 - 100.0 % Status Joint Contains: Additives, stabilizers and fillers Contains: Additives, stabilizers and fillers If inhaled : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Neage person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If motion material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with cool running wat	SAFETY DATA SHEET	Ponciplastics.com	lvoodollbacoll
Version 1.1 Revision Date 10/01/2019 Print Date 01/06/2022 SDS No.: BE198 No additional information available.			
No additional information available. 3: COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components Proprietary blend of polyolefinic Mixture Boot Contains: Additives, stabilizers and fillers Contains: Additives, stabilizers and fillers Contains: Additives Ceneral advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : In case of eye contact : In case of eye contact : : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush			
A. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components 	Version 1.1 Revision Date 1	10/01/2019 Print Date 01/00	5/2022 SDS No.: BE1985
A COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components 			
Alixtures Components 	No additional information ava	illable.	
Components Image: Chemical name CAS-No. Weight % Proprietary blend of polyolefinic Mixture 80.0 - 100.0 % polymers 80.0 - 100.0 % Solution of the solutis and solutis of the solution of the solution of the so	. COMPOSITION/INFORMATION	ON INGREDIENTS	
Chemical name CAS-No. Weight % Proprietary blend of polyolefinic Mixture 80.0 - 100.0 % Contains: Additives, stabilizers and fillers Contains: Additives, stabilizers and fillers FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : Flush eyes (so with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.			
polymers	-	CAS-No.	Weight %
Contains: Additives, stabilizers and fillers FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	Proprietary blend of polyolefinic	Mixture	80.0 - 100.0 %
FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with molten polymer: Continuously flush eye(s) with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	polymers		
General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Neep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	Contains: Additives, stabilizers	and fillers	
General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.			
If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	FIRST AID MEASURES		
medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	General advice		
Iarge amounts of water to cool the affected tissue and polymer Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. : In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	lf inhaled	medical attention. In case of excessive inhalated during heating of this materi Obtain medical attention. Keep person warm, if neces	ion of fumes that may be generated al, move the person to fresh air.
medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	In case of skin contact	large amounts of water to co Do not attempt to peel polyr skin. Obtain immediate emergeno	ool the affected tissue and polymer ner from skin as this will remove th
Continuously flush eye(s) with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	In case of eye contact		
		Continuously flush eye(s) wi minutes. Beyond flushing, DO NOT a adherent to the eye(s).	ith cool running water for at least 1
2 / 14	If swallowed	: Adverse health effects due	to ingestion are not anticipated.
		2 / 14	

SAFETY DATA SHEET	Ponciplastics.com
Lifey TVC 1160D 1 DVE	Iyondenbase
Hifax TYC 1168P 1 RXF	
Version 1.1 Revision Date	10/01/2019 Print Date 01/06/2022 SDS No.: BE198
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as:
	Carbon monoxide, carbon dioxide and unburned hydrocarbon (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	: Combustible particulate solid, will decompose under fire conditions.
	Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors.
	Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container
	Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire.
	Cool storage containers with large volumes of water even after fire is out.
	3 / 14

	(+) 18816996168 Ponciplastics.com
SAFETY DATA SHEET	lyondellbase
Hifax TYC 1168P 1 RXF (ersion 1.1 Revision Date	
ACCIDENTAL RELEASE MEAS	SURES
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with goo engineering practices. Reclaim where possible.
Handling and storage	
Precautions for safe handlin	-
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and
	4 / 14

		(+) 188	16996168		
SAFETY DATA S		Poncip1	astics.com	luce ed	
OAILII DAIA O				iyona	ellbasell
Hifax TYC 1168	3P1RXF			Gen. Variant	t: SDS_US_GHS
Version 1.1 Re	evision Date 10	/01/2019	Print Date 0	1/06/2022	SDS No.: BE1989
		Metal cont should be All electric codes and combustib After hand water. When brin may develous section 10 Refer to N Dust Exploi Handling co	grounded and al equipment s regulatory required le dusts. ling, always wa ging the materi op may conden FPA 654, Stando osions from the of Combustible	in the transfer of the bonded. hould conform to ap- uirements for areas ash hands thoroughly al to processing tem ase in the exhaust ver- dard for the Preventi- Manufacturing, Pro- Particulate Solids, for	plicable electric handling / with soap and peratures vapors entilation. See on of Fire and cessing, and
Fire-fighting class	:	Polymer w	ill burn but doe	s not easily ignite.	
Conditions for sa	fe storage, ind	cluding any	/ incompatibili	ties	
Requirements for s areas and containe Specific end use(s	ers	Use good and handli should be Store away oxidizing a Keep cont	ng. Process en used to avoid e y from excessiv agents. ainer closed to	practices during stor aclosures and adequa excessive dust accur ve heat and away fro prevent contaminati t the build up of elec	ate ventilation mulation. om strong on.
	:	See Section	on 1.		
8. EXPOSURE CONTR Control parameters		_			
Ingredients with	-	trol param	eters		
Occupational Exp	osure Limits				
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
		5	5/14		
		5	/ 14		

1.1	-	0	0		C	0	0	C		C	0
(+)		8	Ø	L	b	9	9	b	L	b	8
		_	-	-	-	_	-	-	_	-	-

Ponciplastics.com

Hifax TYC 1168P 1 RXF

Revision Date 10/01/2019

SAFETY DATA SHEET

Version 1.1

lyondellbasell

Gen. Variant: SDS_US_GHS Print Date 01/06/2022 SDS No.: BE1989

Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 14

(+) 18816996168

	lyondellbase
injury or other irritation to may result from handling Skin and body protection : Wear suitable protective of be based on an evaluation of the protective equipme performed, conditions prehazards and/or potential during use. Use good personal hygie Wash hands before eating facilities. Take off contaminated closes 9. PHYSICAL AND CHEMICAL PROPERTIES Appearance : Pellets. Color : Black Odor : Slight. Odor : No value available. Flash point : No Data Available. Lower explosion limit : The minimum explosive varies according to partic Upper explosion limit : Not applicable. Flammability (solid, gas) : Polymer will burn but doe	F Gen. Variant: SDS_US_GH
ersion 1.1 Revision Date	e 10/01/2019 Print Date 01/06/2022 SDS No.: BE1
	injury or other irritation to eyes due to airborne particles whic may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet
Appearance	: Pellets.
Odor Threshold	-
Flash point	. NO Dala Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution.
Lower explosion limit Upper explosion limit Flammability (solid, gas)	 The minimum explosive concentration (MEC) for polymer duvaries according to particle size distribution. Not applicable.
Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	 The minimum explosive concentration (MEC) for polymer devaries according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent.
Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	 The minimum explosive concentration (MEC) for polymer duvaries according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C
Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	 The minimum explosive concentration (MEC) for polymer duvaries according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined
Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range	 The minimum explosive concentration (MEC) for polymer duvaries according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C
Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range Boiling point/boiling range	 The minimum explosive concentration (MEC) for polymer duvaries according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C Not applicable.
Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range Boiling point/boiling range Vapor pressure	 The minimum explosive concentration (MEC) for polymer duvaries according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C Not applicable. Not applicable.

	(+) 18816996168
AFETY DATA SHEET	Ponciplastics.com
lifax TYC 1168P 1 RX ersion 1.1 Revision Date	
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
STABILITY AND REACTIVITY	(
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks o open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition	: Not expected to decompose under normal conditions.
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
. TOXICOLOGICAL INFORMA	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 14

		6996168		
SAFETY DATA SHEET	Poncip1a	stics.com	lyondellbas	:0
			Iyondenbas	
lifax TYC 1168P 1 RXI			Gen. Variant: SDS_US_	
ersion 1.1 Revision Date	10/01/2019	Print Date 01/06/2	2022 SDS No.: B	E19
Respiratory or skin sensitization	: Not classifi	ed		
Chronic toxicity				
Component Name	NTP	IARC	OSHA	
Carbon Black Titanium Dioxide		2B 2B	Present Present	
L		1	11000111	
Carcinogenicity	: Not classifie	ed		
	Not classifi			
		omponent(s) listed l c to humans.	by IARC as possibly	
			n a thermoplastic resin with	I
			onditions of use, transportat	tion
	and storage) .		
Corres call mutagoniaitu	: Not classifi	ad		
Germ cell mutagenicity	. NOL CIASSIII	ea		
Reproductive toxicity				
Effects on fertility /	: Not classifi	od		
Effects on or via lactation	. Not oldsom			
Effects on Development	: Not classifi	ed		
Target Organ Systemic	: The substa	nce or mixture is no	ot classified as specific targe	et
Toxicant - Single exposure		ant, single exposure		
Target Organ Systemic	: The substa	nce or mixture is no	ot classified as specific targe	et
Toxicant - Repeated	organ toxic	ant, repeated expos	sure.	
exposure				
Aspiration hazard	: Not applica	hle		
Aspiration hazaru	. Not applica	DIE.		
. Ecological information				
Ecotoxicology Assessment				
Short-term (acute) aquatic hazard	: Not classifie	ed		
hazard Long-term (chronic)	: Not classifie	ed		
	9	/ 14		

	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics.com			
Hifax TYC 1168P 1 RXF Version 1.1 Revision Date				
aquatic hazard				
Persistence and degradability				
Biodegradability	: Not expected to be biodegradable.			
Bioaccumulative potential				
Bioaccumulation	: This material is not expected to bioaccumulate.			
Mobility in soil				
Mobility	: no data available			
Other adverse effects				
Environmental fate and pathways	: This material is not volatile and insoluble in water.			
Other information				
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts. 			
13. Disposal considerations				
Waste treatment methods				
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.			
	: This material is classified as a Non-hazardous Material by RCRA.			
14. TRANSPORT INFORMATION				
	10 / 14			

(+) 18816996168

Ponciplastics.com

Hifax TYC 1168P 1 RXF

SAFETY DATA SHEET

Version 1.1

Revision Date 10/01/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE1989

yondellbase

Not regulated for transport

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN	Type of Toxicity			
		Carcinogen	Developmental	Repro-Male	Repro- Female
Mercury	7439-97-6		Х		
Lead	7439-92-1	Х	Х	Х	Х
Nickel	7440-02-0	Х			
Cadmium	7440-43-9	Х	Х	Х	
Chromium	7440-47-3	Х			
Arsenic	7440-38-2	Х			

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

11 / 14

(+) 18816996168

Ponciplastics.com

Hifax TYC 1168P 1 RXF

SAFETY DATA SHEET

Version 1.1

Revision Date 10/01/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE1989

yondellbase

14807-96-6	Talc, Magnesium Silicate
1333-86-4	Carbon Black

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

14807-96-6 Talc, Magnesium Silicate

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

14807-96-6Talc, Magnesium Silicate1333-86-4Carbon Black

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.


Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Not Determined
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Not Determined
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

12 / 14



	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics.com	1 1 111 11		
SAFETY DATA SHEET		lyondellbasell		
Hifax TYC 1168P 1 RXF		Gen. Variant: SDS_US_GHS		
Version 1.1 Revision Date 10	0/01/2019 Print Date 0			
LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.				
End	of Material Safety Data S	sheet		