	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SAFELI DALA SHEEL	lyondellbasel
Hifax TYC 1168P 598F	ANTHRACITE Gen. Variant: SDS_US_GHS
Version 1.4 Revision Date	10/01/2019 Print Date 01/06/2022 SDS No.: BE148
. IDENTIFICATION OF THE SUB	STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name	: Hifax TYC 1168P 598F ANTHRACITE
CAS Number: Chemical name	: Mixture : Compounded polyolefin
Synonyms	: Polyolefin, Compounded polymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical
	devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body;
	Life-sustaining medical applications
Company Address	Company Telephone
Equistar Chemicals, LP LyondellBasell Tower, Suite 3	Customer Service 888 777-0232 00 product.safety@lyb.com
1221 McKinney St.	product.salety eryb.com
P.O. Box 2583 Houston Texas 77252-2583	
Emergency telephone numb	<u>per</u>
EQUISTAR 800-245-4532	
E-mail address	: product.safety@lyb.com
Responsible/issuing person	
2. HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing,
	handling or by other means, may form combustible dust concentrations in air.
Other hazards	
	1 / 14
	1 / 14

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lvoodollbacoll
		lyondellbasell
Hifax TYC 1168P 598F A		Gen. Variant: SDS_US_GHS
Version 1.4 Revision Date 10	0/01/2019 Print Date 01/06	5/2022 SDS No.: BE1482
No additional information avai	lable.	
3. COMPOSITION/INFORMATION O	N INGREDIENTS	
Mixtures		
Components		
Chemical name	CAS-No.	<u>Weight %</u>
Proprietary blend of polyolefinic polymers	Mixture	80.0 - 100.0 %
Contains: Additives, stabilizers a	and fillers	
4. FIRST AID MEASURES		
	. Taka propar procestions to	analyze your own health and actaty
General advice	before attempting rescue an	ensure your own health and safety d providing first aid.
If inhaled	medical attention.	If signs/symptoms continue, get
		on of fumes that may be generated al, move the person to fresh air.
	Obtain medical attention. Keep person warm, if neces	sary give Cardio-Pulmonary
	Resuscitation (CPR)	
In case of skin contact	: If molten material contacts t	he skin, immediately flush with
		ool the affected tissue and polymer. ner from skin as this will remove the
	skin. Obtain immediate emergenc	y medical attention if burn is deep
	or extensive.	,
In case of eye contact	: Flush eyes thoroughly with	water for several minutes and seek
	medical attention if discomfo	
	: In case of eye contact with r Continuously flush eye(s) wi	nolten polymer: th cool running water for at least 15
	minutes.	ttempt to remove the material
	adherent to the eye(s).	
	Immediately seek medical a	
If swallowed	Adverse health effects due t	o ingestion are not anticipated.
	2 / 14	
	<u>۲</u> /۱ ۹	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	lyondellbasell
Hifax TYC 1168P 598F A	
Version 1.4 Revision Date 1	0/01/2019 Print Date 01/06/2022 SDS No.: BE1482
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing	: None known.
media Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
	3 / 14

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	lyondellbase
Hifax TYC 1168P 598F	ANTHRACITE Gen. Variant: SDS_US_GH
/ersion 1.4 Revision Date	a 10/01/2019 Print Date 01/06/2022 SDS No.: BE1
ACCIDENTAL RELEASE MEAS	SURES
Personal precautions	: Equip responders with proper protection.
	Creates dangerous slipping hazard on any hard smooth surface.
	Equip emergency responders with proper personal protective
	equipment (PPE) Avoid generating dust.
	Avoid dispersal of dust in the air (i.e., clearing dust surfaces
	with compressed air). Potential combustible dust hazard.
	Polymer particles create slipping hazard on hard smooth surfaces.
	Sunaces.
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment /	: On land, sweep/shovel into suitable disposal containers or
Methods for cleaning up	vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any
	solid.
	All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance wit
	applicable laws and regulations and in conformance with goo engineering practices. Reclaim where possible.
	engineering practices. Reclaim where possible.
Handling and storage	
Precautions for safe handlin	ng
Advice on safe handling	: Material is in a pellet form. If converted to small particles during further processing,
	handling, or by other means, may form combustible dust
	concentrations in air. Avoid dust accumulation in enclosed space.
	Use dust collection systems designed per NFPA 654 to avoid
	dust accumulation. Avoid generating dust; fine dust suspended in air and in the
	presence of an ignition source is a potential dust explosion
	hazard. Static discharge (spark), or other ignition sources, in high du
	environments may ignite the dust and result in a dust
	explosion Electrostatic charge may build during conveying or handling.
	Equipment handling polymer should be conductive and
	4 / 14

(+) 18816996168

<section-header><section-header><section-header><section-header><section-header><text><text><text><text><text><text><text><text><text><text><text><text><text><text></text></text></text></text></text></text></text></text></text></text></text></text></text></text></section-header></section-header></section-header></section-header></section-header>			(+) 100	10990108		
Pridax TYC1163P 598FANTHRACIDE Gen. Variant: SDS_US_CHM Version 1.4 Revision Date 10/01/201 Print Date 01/06/2022 Gen. Variant: SDS_US_CHM Version 1.4 Revision Date 10/01/2013 Print Date 01/06/2022 SDS No: BE14 Version 1.4 Revision Date 10/01/2013 Print Date 01/06/2022 SDS No: BE14 Version 1.4 Media containers involved in the transfer of this material should be grounded and bonded. Metal containers involved in the transfer of this material should be devisita. All electricial equipitment should conform to applicable electric codes and regulatory requirements for areas handling. Aff Headtricial equipitment should conform to applicable electric codes and regulatory requirements for areas handling. Refer to NFPA 654, Standard for the Prevention of Fire and Duste. Were. Were in Marching. Process enclosures and adequate versitation should be used to avoid excessive dust accumulation. Store away from excessive lost accumulation. Store away from exce	SAFETY DATA SH	EET	Poncipla	astics.com	lyoada	
Prevaluation Revision Date 10/01/2019 Print Date 01/06/2022 SDS No.: BE14 grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities areas and containers : Store in a dry location. Use good housekeep out accountation. Store away from excessive heat and away from strong oxidizing agents. Regulate container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge specific end use(s) EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters See Section 1. Explosional Exposure Limits bare of CAS-No. Type Limit Value Basis Additional Information Information Materials that can be formed wine handling this product: Non- orginacie dust TWA 10 mg/m3 US (ACGH)					Iyunue	ling26
grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Mandlacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage : Store in a dry location. areas and containers : Store in a dry location. use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION Dortrol parameters Ingredients with workplace control parameters Occupational Exposure Limi	lifax TYC 1168F	• 598F Al	NTHRAC			SDS_US_GHS
Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should contorn to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Mandlacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive dust accumulation. Take measures to prevent the build up of electrostatic charge ordinary and handling. Process ine dust accumulation. Take measures to prevent the build up of electrostatic charge storage. Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ordigenet with workplace control parameters Ordigenet with workplace control parameters Ordigenet with workplace control parameter	Version 1.4 Revis	ion Date 10	/01/2019	Print Date 01	1/06/2022 5	SDS No.: BE148
Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Mandfacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers Store in a dry location. Use good housekkeeping practices during storage, transferring and handling. Process enclosures and adequate ventition should be used to avoid excessive dust accumulation. Store away from excessive dust accumulation. Take measures to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Oruponents CAS-No. Type Limit Value Basis Additional Information Materials that can be formed when handing this product: Non-specified (inert or nuisance) dust US (ACGH) Information						
should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with scap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage : Store in a dry location. areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling, Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge oxidizing fagents. Keep container closed to prevent build up of electrostatic charge : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION information ontrol parameters information Ingredients with workplace control parameters Occupational Exposure Limits Compone						
All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with scap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage : Store in a dry location. areas and containers : Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation. Store away from excessive dust accumulation. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION to the material stat can be formed when handing this product: Non- specified (inert or nuisance) dust Materials that can be formed when handing this product: Non- specified (inert or nuisance) dust 10 mg/m3 Materials that can be formed when handing this product: Non- specified (inert or nuisance) dust 10 mg/m3						s material
After handling, always wash hands thoroughly with soap and water. When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing. Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components Additional Information inhalable Materials that can be done when handling this product: Non-specified (inert or nuisance) dust TWA 10 mg/m3 US (ACGIH) inhalable			All electrica codes and	al equipment sh regulatory requ	hould conform to app	
When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10. Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage areas and containers : Store in a dry location. use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Information Materials that can TWA 10 mg/m3 US (ACGiH) Information madding this TWA 10 mg/m3 US (ACGiH) Information			After handl		sh hands thoroughly	with soap and
Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling. Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits 10 mg/m3 US (ACGIH) 2005 Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust TWA 10 mg/m3 US (ACGIH) 2005			When bring may develo	op may conden		
Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Information be formed when handling this product: Non-specified (net or nuisance) dust			Refer to NF Dust Explo	FPA 654, Standosions from the	Manufacturing, Proce	essing, and
Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Revision Date Information handling this rows 2005	Fire-fighting class	:	-			Suid handg.
areas and containers Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits CaS-No. Type Limit Value Basis Additional Information Materials that can be formed when handling this product: Non-specified (inert or nuisance) dust TWA 10 mg/m3 US (ACGIH) product: Non-specified (inert or nuisance) dust inhalable 2005 Additional	Conditions for safe	storage, in	cluding any	, incompatibili	ties	
and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge Specific end use(s) EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Information Materials that can TWA 10 mg/m3 US (ACGIH) be formed when handling this product: Non-specified (inert or nuisance) dust	Requirements for sto	orage :	Store in a d	dry location.		
Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits 	areas and containers		and handlir should be Store away oxidizing a Keep conta	ng. Process en used to avoid e y from excessiv agents. ainer closed to	closures and adequa excessive dust accum we heat and away from prevent contaminatio	te ventilation nulation. n strong n.
EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Information Materials that can TWA 10 mg/m3 US (ACGIH) 2005 Additional Information be formed when Inhalable 2005 Inhalable 2005 Information specified (inert or nuisance) dust Information Inhalable 2005 Information	Specific end use(s)					
Ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Information Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust TWA 10 mg/m3 inhalable US (ACGIH) 2005		:	See Sectio	on 1.		
Control parameters Ingredients with workplace control parameters Occupational Exposure Limits Limit Value Basis Additional Components CAS-No. Type Limit Value Basis Additional Materials that can TWA 10 mg/m3 US (ACGIH) Information be formed when TWA 10 mg/m3 US (ACGIH) Information product: Non- specified (inert or nuisance) dust Information Information	FXPOSURE CONTROL	S/PERSON				
Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Materials that can TWA 10 mg/m3 US (ACGIH) Information be formed when TWA 10 mg/m3 US (ACGIH) 2005 Information specified (inert or Information Information Information Information						
Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Additional Materials that can TWA 10 mg/m3 US (ACGIH) Information be formed when Information Inhalable 2005 Information product: Non- Information Inhalable Information specified (inert or nuisance) dust Information Information Information		orkolace cor	ntrol param	eters		
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dustTWA10 mg/m3 inhalableUS (ACGIH) 2005		-	-	••••		
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	Components	CAS-No.	Туре	Limit Value		
be formed when handling this product: Non- specified (inert or nuisance) dust	Materials that can		TWA	10 mg/m3		Information
nuisance) dust	handling this product: Non-			-	· · · ·	
5 / 14						
5 / 14						
			5	/ 14		

(+) **18816996168**

Ponciplastics.com

SAFETY DATA SHEET	
-------------------	--

lyondellbasell

Hifax TYC 11	168P 598F ANT HRAC	ITE
Version 1.4	Revision Date 10/01/2019	Print

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE1482

Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators. 	
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.	
Eye and face protection	: Dust service goggles should be worn to prevent mechanical	
	6 / 14	

(+) 18816996168

	Depainlactics com
AFETY DATA SHEET	Ponciplastics.com
ifax TYC 1168P 598F ersion 1.4 Revision Date	
	injury or other irritation to eyes due to airborne particles whic may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
PHYSICAL AND CHEMICAL P Appearance Color	: Pellets.
Appearance Color	: Pellets. : gray
Appearance Color Odor	: Pellets. : gray : Slight.
Appearance Color Odor Odor Threshold	 Pellets. gray Slight. No value available.
Appearance Color Odor Odor Threshold Flash point	 Pellets. gray Slight. No value available. No Data Available.
Appearance Color Odor Odor Threshold	 Pellets. gray Slight. No value available.
Appearance Color Odor Odor Threshold Flash point	 Pellets. gray Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer due
Appearance Color Odor Odor Threshold Flash point Lower explosion limit	 Pellets. gray Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer day varies according to particle size distribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit	 Pellets. gray Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer data varies according to particle size distribution. Not applicable.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas)	 Pellets. gray Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer da varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	 Pellets. gray Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	 Pellets. gray Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C
Appearance ColorOdorOdor ThresholdFlash pointLower explosion limitUpper explosion limitFlammability (solid, gas)Oxidizing propertiesAutoignition temperatureDecomposition temperature	 Pellets. gray Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined
Appearance ColorOdorOdor ThresholdFlash pointLower explosion limitUpper explosion limitFlammability (solid, gas)Oxidizing propertiesAutoignition temperatureDecomposition temperatureMelting point/range	 Pellets. gray Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C
Appearance ColorOdorOdor ThresholdFlash pointLower explosion limitUpper explosion limitFlammability (solid, gas)Oxidizing propertiesAutoignition temperatureDecomposition temperatureMelting point/rangeBoiling point/boiling range	 Pellets. gray Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer data varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C Not applicable.

(+)	18816996168

AFETY DATA SHEET	Ponciplastics.com
AFEIT DATA SHEET	lyondellbas
ifax TYC 1168P 598F	ANTHRACITE Gen. Variant: SDS_US_G
ersion 1.4 Revision Date	e 10/01/2019 Print Date 01/06/2022 SDS No.: BE
	. Na Data Augilabla
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
STABILITY AND REACTIVITY	(
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition	: Not expected to decompose under normal conditions.
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
TOXICOLOGICAL INFORMA	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 14

	(+) 188	16996168			
SAFETY DATA SHEET	Poncipla	stics.com	lyondellbasell		
			Iyunuenbasen		
Hifax TYC 1168P 598F ANT HRACITE Gen. Variant: SDS_US_GHS					
Version 1.4 Revision Date	10/01/2019	Print Date 01	1/06/2022 SDS No.: BE1482		
Respiratory or skin : Not classified sensitization					
Chronic toxicity					
Component Name	NTP	IARC	OSHA		
Carbon Black Titanium Dioxide		2B 2B	Present Present		
Carcinogenicity	: Not classifi	ed			
	Not classifi				
	Contains c	omponent(s) lis	sted by IARC as possibly		
		ic to humans. al is encapsula	ted in a thermoplastic resin with		
		ase under norn	nal conditions of use, transportation,		
	and storage	5.			
Germ cell mutagenicity	: Not classifi	ed			
Reproductive toxicity					
Effects on fertility /	: Not classified				
Effects on or via lactation					
Effects on Development	: Not classifi	ed			
Target Organ Systemic	: The substa	ance or mixture	is not classified as specific target		
Toxicant - Single exposure		ant, single exp			
Target Organ Systemic Toxicant - Repeated		ance or mixture ant, repeated	is not classified as specific target		
exposure	organ toxic	ani, repeated t	exposure.		
Aspiration hazard	: Not applica	ble.			
12. Ecological information					
Ecotoxicology Assessment					
Short-term (acute) aquatic	: Not classifi	ed			
hazard Long-term (chronic)	: Not classifi	ed			
	9	/ 14			

	(+) 18816996168				
SAFETY DATA SHEET	Ponciplastics.com				
SAFETY DATA SHEET	lyondellbasell				
Hifax TYC 1168P 598F A	NTHRACITE Gen. Variant: SDS_US_GHS				
Version 1.4 Revision Date 1					
aquatic hazard					
Persistence and degradability					
Biodegradability	: Not expected to be biodegradable.				
Bioaccumulative potential					
Bioaccumulation	: This material is not expected to bioaccumulate.				
Mobility in soil					
Mobility	: no data available				
Other adverse effects					
Environmental fate and pathways	: This material is not volatile and insoluble in water.				
Other information					
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts. 				
13. Disposal considerations					
Waste treatment methods					
Product	All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.				
	: This material is classified as a Non-hazardous Material by RCRA.				
14. TRANSPORT INFORMATION					
	10 / 14				

(+)	1881	6996	168
()	1001	0000	100

Ponciplastics.com

Iyondellbase

Hifax TYC 1168P 598F ANTHRACITE

Version 1.4

Revision Date 10/01/2019 Print Date 01/06/2022

Gen. Variant: SDS_US_GHS SDS No.: BE1482

Not regulated for transport

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN	Type of Tox	icity		
		Carcinogen	Developmental	Repro-Male	Repro- Female
Chromium	7440-47-3	Х			
Cadmium	7440-43-9	Х	Х	Х	
Nickel	7440-02-0	Х			
Mercury	7439-97-6		Х		
Lead	7439-92-1	X	X	X	Х
Arsenic	7440-38-2	X			

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

11 / 14

(+) 18816996168

Ponciplastics.com

SAFETY DATA SHEET

Hifax TYC 1168P 598F ANTHRACITE

Version 1.4

Revision Date 10/01/2019 Print Date 01/06/2022

.... Gen. Variant: SDS US GHS

Iyondellbase

SDS No.: BE1482

Talc, Magnesium Silicate 14807-96-6 Carbon Black 1333-86-4

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

14807-96-6 Talc, Magnesium Silicate

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

14807-96-6	Talc, Magnesium Silicate
1333-86-4	Carbon Black
557-05-1	Zinc Stearate

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.


Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

12 / 14



	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell		
Iyuluelibaseli				
Hifax TYC 1168P 598F ANTHRACITEGen. Variant: SDS_US_GHSVersion 1.4Revision Date 10/01/2019Print Date 01/06/2022SDS No.: BE1482				
LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.				
End	of Material Safety Data S	heet		
	14 / 14			