	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SAFETT DATA SHEET	lyondellbase
Hifax TYC 1168P VOL	CANOGRAY Gen. Variant: SDS_US_GH
Version 1.1 Revision Date	
IDENTIFICATION OF THE SUE	3STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name	: Hifax TYC 1168P VOLCANO GRAY
CAS Number:	: Mixture
Chemical name Synonyms	<ul><li>Compounded polyolefin</li><li>Polyolefin, Compounded polymer</li></ul>
	. Polyolenn, Compounded polymen
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical
	devices; Health Canada class IV Medical Devices;
	Applications involving permanent implantation into the body; Life-sustaining medical applications
Company Address	Company Telephone
Equistar Chemicals, LP	Customer Service 888 777-0232
LyondellBasell Tower, Suite 3	300 product.safety@lyb.com
1221 McKinney St.	
P.O. Box 2583 Houston Texas 77252-2583	
Emergency telephone num EQUISTAR 800-245-4532	<u>ber</u>
E-mail address	: product.safety@lyb.com
Responsible/issuing person	
HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing,
	handling or by other means, may form combustible dust concentrations in air.
Other hazards	
	1 / 14

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell
Hifax TYC 1168P VOLCAVersion 1.1Revision Date 1		Gen. Variant: SDS_US_GHS 6/2022 SDS No.: BE4983
No additional information ava		
3. COMPOSITION/INFORMATION C Mixtures	IN INGREDIENTS	
Components		
Chemical name	CAS-No.	<u>Weight %</u>
Proprietary blend of polyolefinic polymers	Mixture	80.0 - 100.0 %
Contains: Additives and stabiliz	ers	
4. FIRST AID MEASURES		
General advice	: Take proper precautions to before attempting rescue an	ensure your own health and safety Id providing first aid.
If inhaled	medical attention. In case of excessive inhalati	If signs/symptoms continue, get ion of fumes that may be generated al, move the person to fresh air. sary give Cardio-Pulmonary
In case of skin contact	large amounts of water to co Do not attempt to peel polyn skin.	he skin, immediately flush with ool the affected tissue and polymer. ner from skin as this will remove the ey medical attention if burn is deep
In case of eye contact	: Flush eyes thoroughly with medical attention if discomform	water for several minutes and seek ort persists.
	minutes.	ith cool running water for at least 15
If swallowed	: Adverse health effects due t	to ingestion are not anticipated.
	2 / 14	

	(+) 18816996168		
SAFETY DATA SHEET	Ponciplastics.com		
Hifax TYC 1168P VOLCANO GRAYGen. Variant: SDS_US_GHSVersion 1.1Revision Date 10/02/2019Print Date 01/06/2022SDS No.: BE498			
Notes to physician			
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.		
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.		
Treatment	: Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient.		
FIRE-FIGHTING MEASURES			
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.		
	: LARGE FIRES: Use water spray hose nozzles from a safe location.		
Unsuitable extinguishing media	: None known.		
Specific hazards during fire fighting	<ul> <li>Keep away from heat and sources of ignition.</li> <li>In case of fire hazardous decomposition products may be produced such as:</li> <li>Carbon monoxide, carbon dioxide and unburned hydrocarbon (smoke).</li> </ul>		
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.		
Further information	<ul> <li>Combustible particulate solid, will decompose under fire conditions.</li> <li>Calorific Value: 8000 - 11000 kcal/kg</li> <li>Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors.</li> <li>Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire.</li> <li>Do not attempt to get on top of storage containers involved in fire.</li> <li>Cool storage containers with large volumes of water even after the storage containers of the storage containers with large volumes of the storage containers of the storage containers with large volumes of the storage container of the storage containers with large volumes of the storage container of the storage containers with large volumes of the storage container of the storage containers with large volumes of the storage containers of the storage containers of the storage containers of the storage containers with large volumes of the storage containers of</li></ul>		
	fire is out.		
	3 / 14		

SAFETY DATA SHEET					
/ersion 1.1       Revision Date 10/02/2019       Print Date 01/06/2022       SDS No.         ACCIDENTAL RELEASE MEASURES       Personal precautions       : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smoc surface. Equip emergency responders with proper personal pre equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust su with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smo surfaces.         Environmental precautions       : On land, sweep/shovel into suitable disposal container vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as solid. All recovered material should be packaged, labeled, transported and disposed or reclaimed in conformana applicable laws and regulations and in conformane w engineering practices. Reclaim where possible.         Handling and storage       : Material is in a pellet form. If converted to small particles during further processing handling, or by other means, may form combustible du concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 t dust accumulation. Avoid generating dust; fine dust suspended in air and presence of an lignition source is a potential dust explosion Electrostatic charge (spark), or other ignition sources, in h environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or hat Equipment handling polymer should be conductive and equipment					
Personal precautions       : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smoc surface. Equip emergency responders with proper personal pri- equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust su with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smo- surfaces.         Environmental precautions       : On land, sweep/shovel into suitable disposal container vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance w engineering practices. Reclaim where possible.         Handling and storage       : Material is in a pellet form. If converted to small particles during further processing handling, or by other means, may form combustible du concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and presence of an ignition source is a potential dust explo hazard. Static discharge (spark), or other ignition sources, in h environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or hat Equipment handling polymer should be conductive and Equipment handling polymer should					
Personal precautions       : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smoc surface. Equip emergency responders with proper personal pri- equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust su with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smo- surfaces.         Environmental precautions       : On land, sweep/shovel into suitable disposal container vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance w engineering practices. Reclaim where possible.         Handling and storage       : Material is in a pellet form. If converted to small particles during further processing handling, or by other means, may form combustible du concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and presence of an ignition source is a potential dust explo hazard. Static discharge (spark), or other ignition sources, in h environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or han Equipment handling polymer should be conductive and Equipment handling polymere should					
Creates dangerous slipping hazard on any hard smoc surface. Equip emergency responders with proper personal pr equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust su with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smo surfaces. Environmental precautions : Do not flush into surface water or sanitary sever syst Methods for containment / Methods for cleaning up Con land, sweep/shovel into suitable disposal container vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as solid. All recovered material is insoluble; collect and contain as applicable laws and regulations and in conformance w engineering practices. Reclaim where possible. Material is in a pellet form. If converted to small particles during further processing handling, or by other means, may form combustible du concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and presence of an ignition source is a potential dust explo hazard. Static discharge (spark), or other ignition sources, in h environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or hat Equipment handling polymer should be conductive and					
Methods for containment /       : On land, sweep/shovel into suitable disposal container vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as solid.         All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conforman applicable laws and regulations and in conformance w engineering practices. Reclaim where possible.         Handling and storage       Precautions for safe handling         Advice on safe handling       : Material is in a pellet form. If converted to small particles during further processing handling, or by other means, may form combustible du concentrations in air.         Avoid dust accumulation.       Avoid dust accumulation.         Avoid generating dust; fine dust suspended in air and presence of an ignition source is a potential dust explohazard.         Static discharge (spark), or other ignition sources, in h environments may ignite the dust and result in a dust explosion	protective surfaces				
Methods for cleaning up       vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as isolid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance we engineering practices. Reclaim where possible.         Handling and storage       Precautions for safe handling         Advice on safe handling       : Material is in a pellet form. If converted to small particles during further processing handling, or by other means, may form combustible du concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 tr dust accumulation. Avoid generating dust; fine dust suspended in air and presence of an ignition source is a potential dust explohazard. Static discharge (spark), or other ignition sources, in h environments may ignite the dust and result in a dust explosion	vstem.				
Precautions for safe handling         Advice on safe handling         :       Material is in a pellet form. If converted to small particles during further processing handling, or by other means, may form combustible du concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and presence of an ignition source is a potential dust exploi hazard. Static discharge (spark), or other ignition sources, in h environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or har Equipment handling polymer should be conductive and	as any nance with				
<ul> <li>Advice on safe handling</li> <li>Material is in a pellet form. If converted to small particles during further processing handling, or by other means, may form combustible du concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and presence of an ignition source is a potential dust explo- hazard. Static discharge (spark), or other ignition sources, in h environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or har Equipment handling polymer should be conductive and</li> </ul>					
If converted to small particles during further processing handling, or by other means, may form combustible du concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to dust accumulation. Avoid generating dust; fine dust suspended in air and presence of an ignition source is a potential dust explo hazard. Static discharge (spark), or other ignition sources, in h environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or har Equipment handling polymer should be conductive and					
4 / 14	dust 4 to avoid nd in the plosion n high dus st handling.				

		(+) 188	16996168		
SAFETY DATA SI	HEET	Poncip1:	astics.com	lvonde	ellbasell
				<b>1 1</b>	111 11
Hifax TYC 1168				SDS_US_GHS	
Version 1.1 Rev	vision Date 10	/02/2019	Print Date 01	/06/2022	SDS No.: BE4983
		grounded	(earthed) and bo	onded.	
				n the transfer of this	s material
		All electric	regulatory requi	onded. ould conform to app rements for areas h	
				h hands thoroughly	with soap and
		may develo	op may condens	I to processing temp e in the exhaust ver	
			FPA 654, Standa	ard for the Preventio Manufacturing, Proc	
				articulate Solids, for	
Fire-fighting class	:	Polymer w	ill burn but does	not easily ignite.	
Conditions for saf	e storage, inc	luding any	incompatibiliti	es	
Requirements for s areas and container	-	Use good and handli should be Store away oxidizing a	ng. Process enc used to avoid ex y from excessive igents.	ractices during stora losures and adequa cessive dust accum heat and away fror prevent contaminatio	te ventilation nulation. n strong
		•		the build up of elect	
Specific end use(s	)				
	:	See Section	on 1.		
8. EXPOSURE CONTRO	DLS/PERSON	AL PROTE	CTION		
Control parameters					
Ingredients with w	vorkplace con	trol param	eters		
Occupational Exp	osure Limits				
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when handling this product: Non-		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
specified (inert or nuisance) dust					

## $(+)\,18816996168$

Ponciplastics.com

Gen. Variant: SDS US GHS

### Hifax TYC 1168P VOLCANO GRAY

Version 1.1 Revision Date 10/02/2019

Print Date 01/06/2022

SDS No.: BE4983

Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

#### Exposure controls

#### Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

#### Personal protective equipment

Respiratory protection	<ul> <li>Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.</li> <li>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.</li> <li>Use appropriate respiratory protection where atmosphere exceeds recommended limits.</li> <li>Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.</li> </ul>
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 14

# (+) 18816996168

AFETY DATA SHEET	Ponciplastics.com
ifax TYC 1168P VOL	
ersion 1.1 Revision Dat	te 10/02/2019 Print Date 01/06/2022 SDS No.: BE4
	injury or other irritation to eyes due to airborne particles whic may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	<ul> <li>Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.</li> <li>Use good personal hygiene practices.</li> <li>Wash hands before eating, drinking, smoking, or using toilet facilities.</li> <li>Take off contaminated clothing and wash before reuse.</li> </ul>
PHYSICAL AND CHEMICAL F Appearance Color	: Pellets.
Appearance	
Appearance Color	: Pellets. : gray
Appearance Color Odor	: Pellets. : gray : Slight.
Appearance Color Odor Odor Threshold	: Pellets. : gray : Slight. : No value available.
Appearance Color Odor Odor Threshold Flash point	<ul> <li>Pellets.</li> <li>gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer due</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit	<ul> <li>Pellets.</li> <li>gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer devaries according to particle size distribution.</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit	<ul> <li>Pellets.</li> <li>gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer de varies according to particle size distribution.</li> <li>Not applicable.</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas)	<ul> <li>Pellets.</li> <li>gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer de varies according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	<ul> <li>Pellets.</li> <li>gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer de varies according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> <li>Not considered an oxidizing agent.</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	<ul> <li>Pellets.</li> <li>gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer devaries according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	<ul> <li>Pellets.</li> <li>gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer devaries according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> <li>not determined</li> </ul>
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range	<ul> <li>Pellets.</li> <li>gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer de varies according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> <li>not determined</li> <li>50 - 170 °C</li> </ul>
Appearance ColorOdorOdor ThresholdFlash pointLower explosion limitUpper explosion limitFlammability (solid, gas)Oxidizing propertiesAutoignition temperatureDecomposition temperatureMelting point/rangeBoiling point/boiling range	<ul> <li>Pellets.</li> <li>gray</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration (MEC) for polymer devaries according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily ignite.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> <li>not determined</li> <li>50 - 170 °C</li> <li>Not applicable.</li> </ul>

	(+) 18816996168 Ponciplastics.com
AFETY DATA SHEET	Iyondellbase
lifax TYC 1168P VOL	CANOGRAY Gen. Variant: SDS_US_GH
ersion 1.1 Revision Dat	
Partition coefficient: n-	: No Data Available.
octanol/water Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
STABILITY AND REACTIVITY	
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks o open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition	: Not expected to decompose under normal conditions.
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
. TOXICOLOGICAL INFORMA	τιον
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 14

		816996168		
SAFETY DATA SHEET	Poncip	lastics.com	lyondellbasell	
	Hifax TYC 1168P VOLCANO GRAYGen. Variant: SDS_US_GHSVersion 1.1Revision Date 10/02/2019Print Date 01/06/2022SDS No.: BE4983			
	0/02/2010			
Respiratory or skin sensitization	: Not class	sified		
Chronic toxicity				
Component Name	NTP	IARC	OSHA	
Carbon Black		2B	Present	
Carcinogenicity	: Not class	sified		
		component(s) listed b enic to humans.	y IARC as possibly	
	This mat	terial is encapsulated ir	n a thermoplastic resin with onditions of use, transportation,	
	and stor			
Germ cell mutagenicity	: Not class	sified		
Gerni Ceri mutagenicity	. Not class	Silieu		
Denneductive terrisity				
<b>Reproductive toxicity</b> Effects on fertility /	: Not class	sified		
Effects on or via lactation				
Effects on Development	: Not class	sified		
Target Organ Systemic	· The sub	stance or mixture is no	t classified as specific target	
Toxicant - Single exposure		xicant, single exposure		
Target Organ Systemic Toxicant - Repeated		stance or mixture is no xicant, repeated expos	t classified as specific target	
exposure	organ to	Alcani, repeated expos	uie.	
Assistion becaud	. Not over	i a chuir		
Aspiration hazard	: Not appli			
12. Ecological information				
Ecotoxicology Assessment				
Short-term (acute) aquatic hazard	: Not class	sified		
Long-term (chronic) aquatic hazard	: Not class	sified		
		9 / 14		

	(+) 18816996168			
	Ponciplastics.com			
SAFETY DATA SHEET	lyondellbasell			
	I I II II			
Hifax TYC 1168P VOLCA Version 1.1 Revision Date 10				
Persistence and degradability				
Biodegradability	Not expected to be biodegradable.			
Bioaccumulative potential				
Bioaccumulation	This material is not expected to bioaccumulate.			
Mobility in soil				
Mobility	no data available			
Other adverse effects				
Environmental fate and pathways	This material is not volatile and insoluble in water.			
Other information				
	Factovisity is expected to be minimal based on the law water			
Additional ecological information	Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.			
13. Disposal considerations				
Waste treatment methods				
Product	All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.			
	This material is classified as a Non-hazardous Material by RCRA.			
14. TRANSPORT INFORMATION				
	10 / 14			

(1)10010330100	(+)	1881	6996168
----------------	-----	------	---------

Ponciplastics.com

### SAFETY DATA SHEET

## Iyondellbase Hifax TYC 1168P VOLCANO GRAY

Version 1.1

Revision Date 10/02/2019

.... Gen. Variant: SDS US GHS SDS No.: BE4983

Print Date 01/06/2022

Not regulated for transport

#### **15. REGULATORY INFORMATION**

#### TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

#### Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

#### SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

#### SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

#### **SARA 313**

This product contains no known chemicals regulated under SARA 313.

#### State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN Type of Toxicity				
		Carcinogen	Developmental	Repro-Male	Repro- Female
Lead	7439-92-1	Х	Х	Х	Х
Chromium	7440-47-3	Х			
Cadmium	7440-43-9	Х	Х	Х	
Nickel	7440-02-0	Х			
Arsenic	7440-38-2	Х			
Mercury	7439-97-6		Х		
Hexachlorobenzene	118-74-1	Х	Х		

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

11 / 14

(+) 18816996168	(+)	1881	699	61	68
-----------------	-----	------	-----	----	----

Ponciplastics.com

Hifax TYC 1168P VOLCANO GRAY Revision Date 10/02/2019

Version 1.1

Print Date 01/06/2022

Gen. Variant: SDS US GHS SDS No.: BE4983

....

vondellbas

14807-96-6 Talc, Magnesium Silicate Carbon Black 1333-86-4

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

14807-96-6 Talc, Magnesium Silicate 1333-86-4 Carbon Black

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

14807-96-6	Talc, Magnesium Silicate
1333-86-4	Carbon Black

#### Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.


Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

#### REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

12 / 14



	(+) 18816996168					
SAFETY DATA SHEET	Ponciplastics.com	hundellbacell				
		lyondellbasell				
Hifax TYC 1168P VOLCA		Gen. Variant: SDS_US_GHS				
Version 1.1 Revision Date 10	/02/2019 Print Date 0	1/06/2022 SDS No.: BE4983				
LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.						
End	of Material Safety Data S	heet				