	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SAFEIY DAIA SHEEI	lyondellbase
Hifax TYC 773X ACH	BLK Gen. Variant: SDS_US_GHS
	Date 10/02/2019 Print Date 01/06/2022 SDS No.: BE556
1. IDENTIFICATION OF THE S	SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name	: Hifax TYC 773X ACH BLK
CAS Number: Chemical name	: Mixture : Compounded polyolefin
Synonyms	: Polyolefin, Compounded polymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical
	devices; Health Canada class IV Medical Devices;
	Applications involving permanent implantation into the body; Life-sustaining medical applications
Company Address	Company Telephone
Equistar Chemicals, LP	Customer Service 888 777-0232
LyondellBasell Tower, Sui 1221 McKinney St.	te 300 product.safety@lyb.com
P.O. Box 2583	
Houston Texas 77252-25	83
Emergency telephone nu	
EQUISTAR 800-245-4532	
E-mail address	: product.safety@lyb.com
Responsible/issuing persor	١
. HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing,
	handling or by other means, may form combustible dust concentrations in air.
Other hazards	
	1 / 14

	(+) 18816996168	
AFETY DATA SHEET	Ponciplastics.com	lyondellbasel
lifax TYC 773X ACH E ersion 1.2 Revision Date		Gen. Variant: SDS_US_GHS 06/2022 SDS No.: BE556
No additional information	available.	
COMPOSITION/INFORMATION	I ON INGREDIENTS	
Components		
Chemical name	CAS-No.	Weight %
Proprietary blend of polyolefini polymers	c Mixture	80.0 - 100.0 %
Contains: Additives, stabilize	rs and fillers	
FIRST AID MEASURES		
General advice	· Take proper precautions to	ensure your own health and safety
	before attempting rescue a	
If inhaled	: Remove person to fresh ai	r. If signs/symptoms continue, get
	medical attention.	tion of fumes that may be generate
		rial, move the person to fresh air.
		ssary give Cardio-Pulmonary
In case of skin contact	large amounts of water to	the skin, immediately flush with cool the affected tissue and polymer
	skin.	mer from skin as this will remove th
	Obtain immediate emerger or extensive.	cy medical attention if burn is deep
In case of eye contact	: Flush eves thoroughly with	water for several minutes and seel
	medical attention if discom	
	: In case of eye contact with Continuously flush eye(s)	molten polymer: vith cool running water for at least 1
	minutes.	attempt to remove the material
	adherent to the eye(s). Immediately seek medical	
If swallowed	· Adverse health effects due	to ingestion are not anticipated.
		to ingestion are not anticipated.

	(+) 18816996168
SAFETY DATA SHEET Hifax TYC 773X ACH B	Ponciplastics.com yondelbase Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient.
FIRE-FIGHTING MEASURES Suitable extinguishing media	: SMALL FIRE:
	Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbon (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
	3 / 14

Hifax TYC 773X ACH BLK Gen. Variant: SDS_US_GI Version 1.2 Revision Date 10/02/2019 Print Date 01/06/2022 SDS No.: BEF 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PEE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system. Methods for containment / Methods for cleaning up : On land, sweep/showel into suitable disposal containers or vacuum using equipment which avoids ignition nisk. On water, material shouldbe collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with go engineering practices. Reclaim where possible. 7. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handing, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation. Avoid dust accumulation. Bettorestatic charge (spark), or other ignition sources, in high du environments. may ignite the dust and result in a dust explosion bazard.		(+) 18816996168
Hifax TYC 773X ACH BLK Gen. Variant: SDS_US_GI Version 1.2 Revision Date 10/02/2019 Print Date 01/06/2022 SDS No.: BER 6. ACCIDENTAL RELEASE MEASURES Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protectin equipment (PFE) Avoid generating dust. Avoid depresail of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system. Methods for cleaning up : On land, sweep/showel into suitable disposal containers or vacuum using equipment which axoids ignition nsk. On water, material should be packaged, labeled, transported and disposed of or reclaimed in conformance with go engineering practices. Reclaim where possible. 7. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation. Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation. Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid generating dust; fine dust suspended	SAFETY DATA SHEET	Iyondellbasel
ACCIDENTAL RELEASE MEASURES Personal precautions Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protectin equipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air), Poternital combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions C on land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with go engineering practices. Reclaim where possible. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoi dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust axplosion		K Gen. Variant: SDS_US_GHS
Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : Do not flush into surface water or sanitary sewer system. Methods for containment / Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with go engineering practices. Reclaim where possible. 7. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust supended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high di ervironments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and	Version 1.2 Revision Date 10	0/02/2019 Print Date 01/06/2022 SDS No.: BE556
Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protectiv equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with go engineering practices. Reclaim where possible. 7. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed pr NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust supended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high di environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling, Equipment handling polymer should be conductive and		
Personal precautions : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid digenerating dust. Avoid digenerating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with go engineering practices. Reclaim where possible. 7. Handling and storage : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed pr NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust supended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high di environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling, Equipment handling polymer should be conductive and	ACCIDENTAL DELEASE MEASU	DES
 Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protectine quipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. Environmental precautions Do not flush into surface water or sanitary sewer system. Methods for containment / Methods for cleaning up On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with go engineering practices. Reclaim where possible. Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid dust accumulation source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high di environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handing, Equipment handling polymer should be conductive and 		
Methods for containment / Methods for cleaning up : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with go engineering practices. Reclaim where possible. 7. Handling and storage Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling.	Personal precautions	 Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth
Methods for cleaning up vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with go engineering practices. Reclaim where possible. 7. Handling and storage Precautions for safe handling Advice on safe handling If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and	Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Precautions for safe handling Advice on safe handling : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and		 vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good
 Advice on safe handling Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high due nvironments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and 	7. Handling and storage	
If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoi dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and	Precautions for safe handling	
	Advice on safe handling	If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and
4 / 14		4 / 14

 $(+)\,18816996168$

Ponciplastics.com

		Poncipla	astics.com -			
SAFETY DATA S				1 I	ellbasell	
Hifax TYC 773)	(ACH BL	κ		Gen. Variant:	SDS_US_GHS	
Version 1.2 Re	vision Date 10/	/02/2019	Print Date 01	/06/2022	SDS No.: BE5565	
Fire-fighting class		Metal cont should be All electric codes and combustibl After hand water. When brin may develo section 10. Refer to N Dust Explo Handling co Polymer w	grounded and b al equipment sh regulatory requi le dusts. ling, always was ging the materia op may condens FPA 654, Stand osions from the I of Combustible F rill burn but does	in the transfer of this onded. ould conform to app irements for areas h sh hands thoroughly I to processing temp se in the exhaust ver ard for the Preventio Manufacturing, Proc Particulate Solids, for not easily ignite.	licable electric andling with soap and peratures vapors ntilation. See n of Fire and essing, and	
Conditions for sa	fe storage, inc	luding any	[,] incompatibilit	ies		
	 Requirements for storage areas and containers Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. 					
Specific end use(,	See Sectio	on 1.			
8. EXPOSURE CONTR Control parameters	OLS/PERSON/	AL PROTE	CTION			
Ingredients with	workplace con	trol param	eters			
Occupational Exposure Limits						
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005		
	5 / 14					

(+)	1881	699	6168
(1)	1001	055	0100

SAFETY	DATA	SHEET	

lyondellbasell

Hifax TYC 773X ACH BLK

Version 1.2 Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE5565

Materials that can	TWA	3 mg/m3	US (ACGIH)	
be formed when		respirable	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust				
Materials that can	TWA	15 mg/m3	US (OSHA)	
be formed when		total dust	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust				
Materials that can	TWA	5 mg/m3	US (OSHA)	
be formed when		respirable	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust				

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 14

(+) 18816996168

	Ponciplastics.com	
AFETY DATA SHEET		Iyondellbase
lifax TYC 773X ACH B	RI K	Gen. Variant: SDS_US_GH
ersion 1.2 Revision Date		01/06/2022 SDS No.: BE5
	injury or other irritation t may result from handling	o eyes due to airborne particles whicl this product.
Skin and body protection	: Wear suitable protective	clothing.
Hygiene measures	be based on an evaluation of the protective equipmed performed, conditions performed, conditions performed, conditions per hazards and/or potential during use. Use good personal hygi Wash hands before eating facilities.	personal protective equipment shoul on of the performance characteristics ent relative to the task(s) to be resent, duration of use, and the hazards that may be encountered ene practices. ng, drinking, smoking, or using toilet clothing and wash before reuse.
PHYSICAL AND CHEMICAL P	ROPERTIES	
PHYSICAL AND CHEMICAL P Appearance Color	ROPERTIES : Pellets. : Black	
Appearance	: Pellets.	
Appearance Color	: Pellets. : Black	
Appearance Color Odor	: Pellets. : Black : Slight.	
Appearance Color Odor Odor Threshold	 Pellets. Black Slight. No value available. No Data Available. 	
Appearance Color Odor Odor Threshold Flash point	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive 	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive varies according to part 	icle size distribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive varies according to part Not applicable. 	ticle size distribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas)	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive varies according to part Not applicable. Polymer will burn but determined to part 	ticle size distribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive varies according to part Not applicable. Polymer will burn but det Not considered an oxid 	ticle size distribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive varies according to part Not applicable. Polymer will burn but designed in the oxid antication oxid in the oxid in the oxid oxid in the oxid oxid oxid oxid oxid oxid oxid oxid	ticle size distribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive varies according to part Not applicable. Polymer will burn but det Not considered an oxid > 300 °C not determined 	ticle size distribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	 Pellets. Black Slight. No value available. No Data Available. No Data Available. The minimum explosive varies according to part Not applicable. Polymer will burn but determined > 300 °C not determined 50 - 170 °C 	ticle size distribution.
Appearance ColorOdorOdor ThresholdFlash pointLower explosion limitUpper explosion limitFlammability (solid, gas)Oxidizing propertiesAutoignition temperatureDecomposition temperatureMelting point/rangeBoiling point/boiling range	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive varies according to part Not applicable. Polymer will burn but deserver and an oxid > 300 °C not determined 50 - 170 °C Not applicable. 	pes not easily ignite.

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hifax TYC 773X ACH E Version 1.2 Revision Date	
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
10. STABILITY AND REACTIVITY	, ,
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition products	: Not expected to decompose under normal conditions.
Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
11. TOXICOLOGICAL INFORMAT	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 14

	(+) 188	16996168	
SAFETY DATA SHEET	Poncip1	astics.com	lyondellbasell
Hifax TYC 773X ACH BI Version 1.2 Revision Date		Print Date 01/06/2	Gen. Variant: SDS_US_GHS 022 SDS No.: BE5565
		a .	
Respiratory or skin sensitization	: Not classi	fied	
Chronic toxicity			
Component Name	NTP	IARC	OSHA
Carbon Black		2B	Present
Carcinogenicity	: Not classi	fied	
	Not classi Contains d	fied component(s) listed b	y IARC as possibly
		nic to humans. rial is encapsulated ir	n a thermoplastic resin with
	limited released and storage		onditions of use, transportation,
		-	
Germ cell mutagenicity	: Not classi	fied	
Reproductive toxicity			
Effects on fertility / Effects on or via lactation	: Not classi	fied	
Effects on Development	: Not classi	fied	
Target Organ Systemic Toxicant - Single exposure		ance or mixture is no cant, single exposure	t classified as specific target
Target Organ Systemic			t classified as specific target
Toxicant - Repeated exposure	organ toxi	cant, repeated expos	ure.
Aspiration hazard	: Not applic	able.	
12. Ecological information			
Ecotoxicology Assessment			
Short-term (acute) aquatic	: Not classif	fied	
hazard Long-term (chronic) aquatic hazard	: Not classif	fied	
	ç	9 / 14	

	(+) 18816996168		
SAFETY DATA SHEET	Ponciplastics.com		
Hifax TYC 773X ACH BL			
Version 1.2 Revision Date 10	D/02/2019 Print Date 01/06/2022 SDS No.: BE5565		
Persistence and degradability			
Biodegradability	Not expected to be biodegradable.		
Bioaccumulative potential			
Bioaccumulation	This material is not expected to bioaccumulate.		
Mobility in soil			
Mobility	: no data available		
Other adverse effects			
Environmental fate and pathways	This material is not volatile and insoluble in water.		
Other information			
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts. 		
13. Disposal considerations			
Waste treatment methods Product	All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.		
	This material is classified as a Non-hazardous Material by RCRA.		
14. TRANSPORT INFORMATION			
	10 / 14		

(+)18816996168	(+)	1881	6996168
----------------	-----	------	---------

Hifax TYC 773X ACH BLK

SAFETY DATA SHEET

Version 1.2

Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS US GHS SDS No.: BE5565

Iyondellbase

Not regulated for transport

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN	Type of Tox	icity		
		Carcinogen	Developmental	Repro-Male	Repro-
					Female
Lead	7439-92-1	Х	Х	Х	Х
Cadmium	7440-43-9	Х	Х	Х	
Chromium	7440-47-3	Х			
Arsenic	7440-38-2	Х			
Nickel	7440-02-0	X			
Mercury	7439-97-6		Х		

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

11 / 14

(+) 18816996168

Hifax TYC 773X ACH BLK

SAFETY DATA SHEET

Version 1.2

Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE5565

yondellbase

14807-96-6Talc, Magnesium Silicate1333-86-4Carbon Black

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

14807-96-6Talc, Magnesium Silicate1333-86-4Carbon Black

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

14807-96-6	Talc, Magnesium Silicate
1333-86-4	Carbon Black

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.


Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Not Compliant*
China	IECSC	Not Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Not Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

12 / 14



(+)	18816996168
(' '	10010330100

Hifax TYC 773X	ACH BLK
----------------	----------------

SAFETY DATA SHEET

Version 1.2

Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS SDS No.: BE5565

Iyondellbasel

LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet