Prohibited uses : FDA Class III medical device devices; Health Canada cla Applications involving perm Life-sustaining medical app Company Address : Company Tele	THE COMPANY/UNDERTAKING olymer eles by injection molding, extrusion s. ces; European class III medical ass IV Medical Devices; hanent implantation into the body; blications phone ce 888 777-0232
Image: Section 1.2 Revision Date 10/01/2019 Print Date 01/1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE SUBSTANCE SUBSTANCE AND OF THE SUBSTANCE SUBSTANCE AND OF THE SUBSTAN	Gen. Variant: SDS_US_GH Gen. Variant: SDS_US_GH O6/2022 SDS No.: BE144§ CHE COMPANY/UNDERTAKING olymer eles by injection molding, extrusion s. ces; European class III medical ass IV Medical Devices; nanent implantation into the body; olications
ersion 1.2 Revision Date 10/01/2019 Print Date 01/ IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF T Trade name : Hifax TYC1123X BLACK CAS Number: : Mixture Chemical name : Compounded polyolefin Synonyms : Polyolefin, Compounded polyolefin Identified uses : Manufacture of plastic artic or other conversion proces Prohibited uses : FDA Class III medical devid devices; Health Canada cla Applications involving perm Life-sustaining medical app Company Address : FDA Class III medical devid devices; Health Canada cla Applications involving perm Life-sustaining medical app Company Address : FDA Class III medical devid devices; Health Canada cla Applications involving perm Life-sustaining medical app Company Address : FDA Class III medical devid devices; Health Canada cla Applications involving perm Life-sustaining medical app Quistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Company Tele Customer Servic product.safety@ E-mail address : product.safety@lyb.com Responsible/issuing person : product.safety@lyb.com HAZARDS IDE	206/2022 SDS No.: BE1449 THE COMPANY/UNDERTAKING olymer eles by injection molding, extrusion s. ces; European class III medical ass IV Medical Devices; hanent implantation into the body; blications phone ce 888 777-0232
IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF T Trade name : Hifax TYC1123X BLACK CAS Number: : Mixture Chemical name : Compounded polyolefin Synonyms : Polyolefin, Compounded pr Identified uses : Manufacture of plastic artic or other conversion proces Prohibited uses : FDA Class III medical device devices; Health Canada cla Applications involving perm Life-sustaining medical app Company Address Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification	THE COMPANY/UNDERTAKING olymer eles by injection molding, extrusion s. ces; European class III medical ass IV Medical Devices; hanent implantation into the body; blications phone ce 888 777-0232
Trade name : Hifax TYC1123X BLACK CAS Number: : Mixture Chemical name : Compounded polyolefin Synonyms : Polyolefin, Compounded polyolefin Identified uses : Manufacture of plastic artice or other conversion proces Prohibited uses : FDA Class III medical devic devices; Health Canada cla Applications involving perm Life-sustaining medical app Company Address Equistar Chemicals, LP Customer Service product.safety@ LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Ermergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person : product.safety@lyb.com HAZARDS IDENTIFICATION GHS Classification	olymer eles by injection molding, extrusion s. ces; European class III medical ass IV Medical Devices; nanent implantation into the body; plications phone ce 888 777-0232
Trade name : Hifax TYC1123X BLACK CAS Number: : Mixture Chemical name : Compounded polyolefin Synonyms : Polyolefin, Compounded polyolefin Identified uses : Manufacture of plastic artice or other conversion proces Prohibited uses : FDA Class III medical devic devices; Health Canada cla Applications involving perm Life-sustaining medical app Company Address Equistar Chemicals, LP Customer Service product.safety@ LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person : product.safety@lyb.com HAZARDS IDENTIFICATION GHS Classification	olymer eles by injection molding, extrusion s. ces; European class III medical ass IV Medical Devices; nanent implantation into the body; plications phone ce 888 777-0232
CAS Number: : Mixture Chemical name : Compounded polyolefin Synonyms : Polyolefin, Compounded polyolefin Identified uses : Manufacture of plastic artic or other conversion process Prohibited uses : FDA Class III medical devic devices; Health Canada cla Applications involving perm Life-sustaining medical app Company Address Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification	eles by injection molding, extrusion s. ces; European class III medical ass IV Medical Devices; nanent implantation into the body; plications phone ce 888 777-0232
Chemical name : Compounded polyolefin Synonyms : Polyolefin, Compounded polyolefin Identified uses : Manufacture of plastic artic or other conversion process Prohibited uses : FDA Class III medical devic devices; Health Canada cla Applications involving perm Life-sustaining medical app Company Address : FDA Class III medical devic devices; Health Canada cla Applications involving perm Life-sustaining medical app Company Address : Company Tele Customer Servic product.safety@ LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Company Tele Customer Servic product.safety@ Emergency telephone number EQUISTAR 800-245-4532 : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification : product.safety@lyb.com	eles by injection molding, extrusion s. ces; European class III medical ass IV Medical Devices; nanent implantation into the body; plications phone ce 888 777-0232
Synonyms : Polyolefin, Compounded problematic article or other conversion process Identified uses : Manufacture of plastic article or other conversion process Prohibited uses : FDA Class III medical device devices; Health Canada cla Applications involving permulife-sustaining medical approximations involving permulifie-sustaining medical approximations involving permulifie-sustaining medical approximations involving permulifie-sustaining medical approximations involving permulifie-sustaining medical approximations involves involving permulifie-sustaining medical approximations involves invo	eles by injection molding, extrusion s. ces; European class III medical ass IV Medical Devices; nanent implantation into the body; plications phone ce 888 777-0232
Identified uses : Manufacture of plastic articles or other conversion process Prohibited uses : FDA Class III medical device devices; Health Canada cla Applications involving permulife-sustaining medical app Company Address : FDA Class III medical device devices; Health Canada cla Applications involving permulife-sustaining medical app Company Address : FDA Class III medical device devices; Health Canada cla Applications involving permulife-sustaining medical app LyondellBasell Tower, Suite 300 : Ecustomer Service product.safety@ LyondellBasell Tower, Suite 300 : product.safety@ 1221 McKinney St. P.O. Box 2583 Eustomer Service product.safety@ Houston Texas 77252-2583 : product.safety@ E-mail address : product.safety@lyb.com Responsible/issuing person : product.safety@lyb.com HAZARDS IDENTIFICATION GHS Classification	eles by injection molding, extrusion s. ces; European class III medical ass IV Medical Devices; nanent implantation into the body; plications phone ce 888 777-0232
Prohibited uses : FDA Class III medical devic devices; Health Canada cla Applications involving perm Life-sustaining medical approximations involving perm Life-sustaining medical approximation involving perm Life-sustaining medical approximation involving p	ces; European class III medical ass IV Medical Devices; nanent implantation into the body; blications phone ce 888 777-0232
devices; Health Canada cla Applications involving perm Life-sustaining medical app Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Energency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification	ass IV Medical Devices; nanent implantation into the body; plications phone ce 888 777-0232
Life-sustaining medical app Company Address Equistar Chemicals, LP LyondellBasell Tower, Suite 300 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification	plications phone ce 888 777-0232
Company Address Company Tele Equistar Chemicals, LP Customer Service LyondellBasell Tower, Suite 300 product.safety@ 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Freegency telephone number EQUISTAR 800-245-4532 E-mail address E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification GHS Classification	phone ce 888 777-0232
Equistar Chemicals, LP Customer Service LyondellBasell Tower, Suite 300 product.safety@ 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Houston Texas 77252-2583 Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification GHS Classification	ce 888 777-0232
LyondellBasell Tower, Suite 300 product.safety@ 1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification	
1221 McKinney St. P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification	alyb.com
P.O. Box 2583 Houston Texas 77252-2583 Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification	
Emergency telephone number EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification	
EQUISTAR 800-245-4532 E-mail address : product.safety@lyb.com Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification	
E-mail address Responsible/issuing person : product.safety@lyb.com HAZARDS IDENTIFICATION GHS Classification	
Responsible/issuing person HAZARDS IDENTIFICATION GHS Classification	
HAZARDS IDENTIFICATION GHS Classification	
GHS Classification	
GHS Classification	
Combustible dust	
Label elements	
Signal word : Warning	
	erated during further processing,
handling or by other means concentrations in air.	s, may form combustible dust
Other hazards	
1 / 14	
1 / 14	

AFETY DATA SHEET	Ponciplastics.com	
		lyondellbasel
lifax TYC1123X BLAC	К	Gen. Variant: SDS_US_GHS
ersion 1.2 Revision Date		06/2022 SDS No.: BE14495
No additional information a	vailable.	
COMPOSITION/INFORMATION xtures	ON INGREDIENTS	
Components		
Chemical name	CAS-No.	Weight %
Proprietary blend of polyolefinion polymers	: Mixture	80.0 - 100.0 %
Contains: Additives, stabilizer	s and fillers	
FIRST AID MEASURES		
General advice	: Take proper precautions to before attempting rescue a	ensure your own health and safety nd providing first aid.
If inhaled	medical attention. In case of excessive inhala during heating of this mater Obtain medical attention.	tion of fumes that may be generate rial, move the person to fresh air. ssary give Cardio-Pulmonary
In case of skin contact	large amounts of water to c Do not attempt to peel poly skin.	the skin, immediately flush with ool the affected tissue and polyme mer from skin as this will remove th cy medical attention if burn is deep
In case of eye contact	: Flush eyes thoroughly with water for several minutes and see medical attention if discomfort persists.	
	 In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. 	
If swallowed	: Adverse health effects due	to ingestion are not anticipated.
	2 / 14	

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	
Hifax TYC1123X BLACKGen. Variant:SDS_US_GHSVersion 1.2Revision Date 10/01/2019Print Date 01/06/2022SDS No.:BE14495		
Notes to physician		
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.	
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.	
Treatment	: Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient.	
. FIRE-FIGHTING MEASURES		
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.	
	: LARGE FIRES: Use water spray hose nozzles from a safe location.	
Unsuitable extinguishing media	: None known.	
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbon (smoke). 	
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.	
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out. 	
	3 / 14	

	(+) 18816996168	
AFETY DATA SHEET	Ponciplastics.com	
Iifax TYC1123X BLACKGen. Variant: SDS_US_GHersion 1.2Revision Date 10/01/2019Print Date 01/06/2022SDS No.: BE144		
ACCIDENTAL RELEASE MEAS	SURES	
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces. 	
Environmental precautions	: Do not flush into surface water or sanitary sewer system.	
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with goo engineering practices. Reclaim where possible. 	
Additional advice	: See Section 15: Regulatory Information.	
Handling and storage		
Precautions for safe handlin	ıg	
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust 	
	4 / 14	

Ponciplastics.com

SAFETY DATA SH	EET	1 one ipit	Istics.com	lyonde	ellbasell
Hifax TYC1123X	BLACK			Gen. Variant:	SDS_US_GHS
	sion Date 10/	/01/2019	Print Date 01/0	06/2022 SD	S No.: BE144950
		Equipment grounded (Metal conta should be All electrica codes and combustibl After handl water. When bring may develo section 10. Refer to NI Dust Explo	handling polyme (earthed) and bor ainers involved ir grounded and bo al equipment sho regulatory require le dusts. ling, always wash ging the material op may condense FPA 654, Standa psions from the M	n the transfer of this	ctive and s material licable electric handling with soap and beratures vapors ntilation. See n of Fire and essing, and
Fire-fighting class	:	Polymer w	ill burn but does	not easily ignite.	
Conditions for safe	storage, inc	luding any	incompatibilitie	es	
Requirements for sto areas and containers		Use good I and handlin should be Store away oxidizing a Keep conta	ng. Process encloused to avoid exc from excessive gents. ainer closed to pr	actices during stora osures and adequa cessive dust accum heat and away fror revent contaminatio the build up of elect	te ventilation nulation. m strong on.
Specific end use(s)					
	:	See Sectio	ın 1.		
8. EXPOSURE CONTROL Control parameters	_S/PERSON/	AL PROTE	CTION		
Ingredients with wo	orkolace con	trol param	eters		
Occupational Expos	-				
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
		5	/ 14		

Ponciplastics.com

SAFETY DATA SHEET

Hifax TYC1123X BLACK

Revision Date 10/01/2019 Version 1.2

Print Date 01/06/2022

Gen. Variant: SDS US GHS SDS No.: BE144950

Iyondellbasel 111

Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and

processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified
	6 / 14

AFETY DATA SHEET	Ponciplastics.com	
	I I III	
Hifax TYC1123X BLACK Gen. Variant: SDS_US_GH /ersion 1.2 Revision Date 10/01/2019 Print Date 01/06/2022 SDS No.: BE1449		
	respirators.	
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.	
Eye and face protection	: Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles whice may result from handling this product.	
Skin and body protection	: Wear suitable protective clothing.	
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse. 	
PHYSICAL AND CHEMICAL P Appearance Color		
Appearance	ROPERTIES : Pellets.	
Appearance Color	ROPERTIES : Pellets. : Black	
Appearance Color Odor	ROPERTIES : Pellets. : Black : Slight.	
Appearance Color Odor Odor Threshold	ROPERTIES : Pellets. : Black : Slight. : No value available.	
Appearance Color Odor Odor Threshold Flash point	ROPERTIES : Pellets. : Black : Slight. : No value available. : No Data Available. : The minimum explosive concentration (MEC) for polymer d	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit	ROPERTIES : Pellets. : Black : Slight. : No value available. : No Data Available. : The minimum explosive concentration (MEC) for polymer d varies according to particle size distribution.	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit	ROPERTIES Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer d varies according to particle size distribution. Not applicable.	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas)	ROPERTIES Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer d varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite.	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	ROPERTIES	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	ROPERTIES : Pellets. : Black : Slight. : No value available. : No Data Available. : The minimum explosive concentration (MEC) for polymer d varies according to particle size distribution. : Not applicable. : Not applicable. : Polymer will burn but does not easily ignite. : Not considered an oxidizing agent. : > 300 °C	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	ROPERTIES : Pellets. : Black : Slight. : No value available. : No Data Available. : No Data Available. : The minimum explosive concentration (MEC) for polymer d varies according to particle size distribution. : Not applicable. : Not applicable. : Not considered an oxidizing agent. : > 300 °C : not determined	

(+)	18816996168
()	10010000100

	(+) 18816996168
SAFETY DATA SHEET Hifax TYC1123X BLACK	
Version 1.2 Revision Date 1	0/01/2019 Print Date 01/06/2022 SDS No.: BE144950
Vapor pressure	: Not applicable.
Relative density	: > 1 (Water = 1)
Density	: > 1 g/cm3
Water solubility	: Insoluble.
Partition coefficient: n- octanol/water Viscosity, dynamic	No Data Available.Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
10. STABILITY AND REACTIVITY	
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition products	: Not expected to decompose under normal conditions.
	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
11. TOXICOLOGICAL INFORMATIO	 N
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified

8 / 14

	(+) 18816996168 Ponciplastics.com	
FETY DATA SHEET	L ly	n. Variant: SDS_US_GI
sion 1.2 Revision Date		SDS No.: BE14
Acute dermal toxicity	: Not classified	
Skin corrosion/irritation	: Not a skin irritant.	
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.	
Respiratory or skin sensitization	: Not classified	
Chronic toxicity		
Component Name	NTP IARC	OSHA
Carbon Black	2B	Present
	Contains component(s) listed by IAF carcinogenic to humans. This material is encapsulated in a th limited release under normal condition	ermoplastic resin with
	and storage.	ons of use, transportatio
Germ cell mutagenicity		ons of use, transportatio
Germ cell mutagenicity Reproductive toxicity	and storage.	ons of use, transportatio
	and storage.	ons of use, transportatio
Reproductive toxicity Effects on fertility /	and storage. : Not classified	ons of use, transportatio
Reproductive toxicity Effects on fertility / Effects on or via lactation	and storage. Not classified Not classified	
Reproductive toxicity Effects on fertility / Effects on or via lactation Effects on Development Target Organ Systemic	 and storage. Not classified Not classified Not classified The substance or mixture is not classified 	sified as specific target
Reproductive toxicity Effects on fertility / Effects on or via lactation Effects on Development Target Organ Systemic Toxicant - Single exposure Target Organ Systemic Toxicant - Repeated	 and storage. Not classified Not classified Not classified The substance or mixture is not class organ toxicant, single exposure. The substance or mixture is not class 	sified as specific target

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	
Hifax TYC1123X BLACI		
12. Ecological information		
Ecotoxicology Assessment		
Short-term (acute) aquatic hazard	: Not classified	
Long-term (chronic) aquatic hazard	: Not classified	
Persistence and degradability		
Biodegradability	: Not expected to be biodegradable.	
Bioaccumulative potential		
Bioaccumulation	: This material is not expected to bioaccumulate.	
Mobility in soil		
Mobility	no data available	
Other adverse effects		
Environmental fate and pathways	: This material is not volatile and insoluble in water.	
Other information		
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts. 	
13. Disposal considerations		
Waste treatment methods		
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.	
	: This material is classified as a Non-hazardous Material by RCRA.	
	10 / 14	

(+) 18816996168	+)]	881	6996	168
-----------------	-----	-----	------	-----

Ponciplastics.com

lyoi	ndell	base

Hifax TYC1123X BLACK

SAFETY DATA SHEET

Version 1.2

Revision Date 10/01/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE144950

14. TRANSPORT INFORMATION

Not regulated for transport

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN	Type of Tox	icity		
		Carcinogen	Developmental	Repro-Male	Repro- Female
Lead	7439-92-1	Х	Х	Х	Х
Chromium	7440-47-3	Х			
		11 / 14	1		

Ponciplastics.com

SAFETY DATA SHEET

Hifax TYC1123X BLACK Version 1.

Gen. Variant: SDS US GHS

Iyondellbase

.2	Revision	Date	10/01/2019

Print Date 01/06/2022

SDS No.:	BE144950

....

Cadmium	7440-43-9	Х	Х	Х	
Nickel	7440-02-0	Х			
Arsenic	7440-38-2	Х			
Mercury	7439-97-6		Х		

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

14807-96-6	Talc, Magnesium Silicate
546-93-0	Magnesium Carbonate
1333-86-4	Carbon Black

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

14807-96-6	Talc, Magnesium Silicate
546-93-0	Magnesium Carbonate

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

14807-96-6	Talc, Magnesium Silicate
1333-86-4	Carbon Black

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics.com			
SAFETT DATA SHEET		lyondellbasell		
Hifax TYC1123X BLACK		Gen. Variant: SDS_US_GHS		
Version 1.2 Revision Date 10	/01/2019 Print Date 01/06	5/2022 SDS No.: BE144950		
Contact product.safety@lyb.com for a	dditional global inventory inforn	nation.		
16. OTHER INFORMATION				
Material safety datasheet section	ons which have been update	ed:		
Revised Section(s): 15 16				
	Health Hazard: 0 Flammability: 1 Physical hazards: 0	0 1 0		
	Health Hazard: 0 Fire Hazard: 1 Instability: 0			
Further information HMIS rating scale (0 = minimal han NFPA rating scale (0 = minimal han				
	. ,			
	Disclaimer			
Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.				
In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.				
Numerical Data Presentation				
	13 / 14			

	(+) 18816996168 Ponciplastics.com	
DATA SHEET	roncipiastics.com	lyondellbasel
		Gen. Variant: SDS US GHS

Hifax TYC1123X BLACK

Version 1.2

SAFETY

Revision Date 10/01/2019

Print Date 01/06/2022

SDS No.: BE144950

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet