	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SAFETT DATA SHEET	lyondellbasel
Hifax TYC1175PG01	BLACK Gen. Variant: SDS_US_GHS
	te 10/01/2019 Print Date 01/06/2022 SDS No.: BE126
I. IDENTIFICATION OF THE SU	BSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name	: Hifax TYC1175P G01 BLACK
CAS Number: Chemical name	: Mixture : Compounded polyolefin
Synonyms	: Polyolefin, Compounded polymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices;
	Applications involving permanent implantation into the body; Life-sustaining medical applications
Company Address	Company Telephone
Equistar Chemicals, LP LyondellBasell Tower, Suite	Customer Service 888 777-0232300product.safety@lyb.com
1221 McKinney St. P.O. Box 2583	
Houston Texas 77252-2583	3
Emergency telephone nun EQUISTAR 800-245-4532	<u>ıber</u>
E-mail address Responsible/issuing person	: product.safety@lyb.com
2. HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
Other hazards	
	1 / 14

	(+) 18816996168 Ponciplastics.com	
AFETY DATA SHEET	Tonerprastres.com	lyondellbase
lifax TYC1175P G01 ersion 1.2 Revision Da	BLACK ate 10/01/2019 Print Date 01/	Gen. Variant: SDS_US_GH 06/2022 SDS No.: BE12
No additional information		
xtures Components		
Chemical name	CAS-No.	Weight %
Proprietary blend of polyolefi polymers	nic Mixture	50.0 - 80.0 %
Contains: Additives, stabiliz	ers and fillers	
FIRST AID MEASURES General advice	: Take proper precautions to before attempting rescue a	o ensure your own health and safe and providing first aid.
If inhaled	medical attention. In case of excessive inhale during heating of this mate Obtain medical attention.	ir. If signs/symptoms continue, get ation of fumes that may be genera erial, move the person to fresh air. essary give Cardio-Pulmonary
In case of skin contact	large amounts of water to Do not attempt to peel pol skin.	the skin, immediately flush with cool the affected tissue and polym ymer from skin as this will remove ncy medical attention if burn is dea
In case of eye contact	: Flush eyes thoroughly with medical attention if discon	n water for several minutes and senfort persists.
	minutes.	with cool running water for at leas attempt to remove the material
If swallowed	: Adverse health effects due	e to ingestion are not anticipated.

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hifax TYC1175PG01 B	
Version 1.2 Revision Date	10/01/2019 Print Date 01/06/2022 SDS No.: BE1269
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	: Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons
	(smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles Heat from fire may melt, decompose polymer, and generate flammable vapors.
	Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in
	fire. Cool storage containers with large volumes of water even after fire is out.
	3 / 14

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hifax TYC1175P G01 B Version 1.2 Revision Date	
Version 1.2 Revision Date	10/01/2019 Fillit Date 01/00/2022 3D3 No DE 12
. ACCIDENTAL RELEASE MEAS	SURES
Personal precautions	: Equip responders with proper protection.
	Creates dangerous slipping hazard on any hard smooth surface.
	Equip emergency responders with proper personal protective equipment (PPE)
	Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces
	with compressed air). Potential combustible dust hazard.
	Polymer particles create slipping hazard on hard smooth
	surfaces.
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment /	: On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk.
Methods for cleaning up	On water, material is insoluble; collect and contain as any
	solid. All recovered material should be packaged, labeled,
	transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good
	engineering practices. Reclaim where possible.
Handling and storage	
Precautions for safe handlin	-
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust
	concentrations in air. Avoid dust accumulation in enclosed space.
	Use dust collection systems designed per NFPA 654 to avoid dust accumulation.
	Avoid generating dust; fine dust suspended in air and in the
	presence of an ignition source is a potential dust explosion hazard.
	Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust
	explosion Electrostatic charge may build during conveying or handling.
	Equipment handling polymer should be conductive and
	4 / 14

(+) 18816996168

			10550100		
SAFETY DATA S	HEET	Poncipl	astics.com	lvood	ellbasell
Hifax TYC1175					SDS_US_GHS
Version 1.2 Re	evision Date 10	/01/2019	Print Date 0	1/06/2022	SDS No.: BE1269
		grounded	(earthed) and b	oonded.	
				in the transfer of this	s material
			grounded and al equipment s	hould conform to app	licable electric
		codes and combustib	• • •	uirements for areas h	andling
		After hand		ash hands thoroughly	with soap and
		water. When brin	aina the materi	al to processing temp	peratures vapors
		may develo	op may conden	ise in the exhaust ver	
		section 10 Refer to N		dard for the Preventic	n of Fire and
		Dust Explo	osions from the	Manufacturing, Proc Particulate Solids, for	essing, and
Fire-fighting class	:	Polymer w	vill burn but doe	s not easily ignite.	
Conditions for sa	fe storage, in	cluding any	, incompatibili	ties	
Requirements for s			dry location.		
areas and containe	ers			practices during stora aclosures and adequa	
				excessive dust accun	
		oxidizing a		ve heat and away from	IT STIOL
				prevent contamination the build up of election of the build up of election of the build up of election of the build up of the	
Specific end use(s)				
	-	See Section	on 1.		
B. EXPOSURE CONTR	OLS/PERSON	AL PROTE	CTION		
Control parameters					
Ingredients with	workplace cor	trol param	otors		
•	-		CICIS		
Occupational Exp	osure Limits				
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can		TWA	10 mg/m3	US (ACGIH)	Information
be formed when handling this			inhalable	2005	
product: Non-					
specified (inert or nuisance) dust					
	1	1	1	1	1
		5	/ 14		

(+)	1881	699616	8
			1

			Poncip1;	astics.com		
	SAFETY DATA S	SHEET	T OHOTPIC	istres. com	lyond	ellbasell
					1	111 11
	Hifax TYC117	5PG01BL	ACK		Gen. Variant	: SDS_US_GHS
1		evision Date 10		Print Date 01/	/06/2022	SDS No.: BE1269
1				Thin Date of	00,2022	00011011 021200
	Materials that can		TWA	3 mg/m3	US (ACGIH)	
	be formed when			respirable	2005	
	handling this					
	product: Non-					
	specified (inert or					
	nuisance) dust					
	Materials that can		TWA	15 mg/m3	US (OSHA)	
	be formed when			total dust	2005	
	handling this					
	product: Non-					
	specified (inert or					
	nuisance) dust					
	Materials that can		TWA	5 mg/m3	US (OSHA)	
	be formed when			respirable	2005	
	handling this					
	product: Non-					
	specified (inert or					
	nuisance) dust					

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 14

(+) 18816996168

AFETY DATA SHEET	Ponciplastics.com
lifax TYC1175P G01 E ersion 1.2 Revision Dat	BLACK Gen. Variant: SDS_US_GH te 10/01/2019 Print Date 01/06/2022 SDS No.: BE1
	injury or other irritation to eyes due to airborne particles whic may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse.
PHYSICAL AND CHEMICAL F Appearance	: Pellets.
Appearance Color	: Pellets. : Black
Appearance Color Odor	: Pellets. : Black : Slight.
Appearance Color Odor Odor Threshold	: Pellets. : Black : Slight. : No value available.
Appearance Color Odor Odor Threshold Flash point	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer due
Appearance Color Odor Odor Threshold Flash point Lower explosion limit	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer data varies according to particle size distribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dayaries according to particle size distribution. Not applicable.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas)	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer da varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dayaries according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range Boiling point/boiling range	 Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C Not applicable.

	(+) 18816996168		
SAFETY DATA SHEET	Ponciplastics.com		
Hifax TYC1175P G01 E /ersion 1.2 Revision Date			
	$\frac{10}{01}$ 10/01/2019 Finit Date 01/00/2022 SDS No DE 12		
Partition coefficient: n- octanol/water	: No Data Available.		
Viscosity, dynamic	: Not applicable.		
Relative vapor density	: Not applicable.		
Evaporation rate	: Not applicable.		
Explosive properties	: No Data Available.		
Other Information	: No additional information available.		
0. STABILITY AND REACTIVITY	,		
Reactivity	: No known reactivity hazards.		
Chemical stability	: Stable under normal conditions.		
Hazardous reactions	: Will not occur.		
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.		
Materials to avoid	: Material may be softened by some hydrocarbons.		
Hazardous decomposition	: Not expected to decompose under normal conditions.		
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.		
1. TOXICOLOGICAL INFORMAT	ΓΙΟΝ		
Acute toxicity			
Acute oral toxicity	: Not classified		
Acute inhalation toxicity	: Not classified		
Acute dermal toxicity	: Not classified		
Skin corrosion/irritation	: Not a skin irritant.		
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.		
	8 / 14		

	(+) 18	816996168	
SAFETY DATA SHEET	Poncip	lastics.com	lyondellbasell
Hifax TYC1175P G01 B Version 1.2 Revision Date		Print Date 01/06/20	Gen. Variant: SDS_US_GHS 22 SDS No.: BE1269
	10/01/2019		22 3D3 NO DE 1209
Respiratory or skin sensitization	: Not class	ified	
Chronic toxicity			
Component Name	NTP	IARC	OSHA
Carbon Black		2B	Present
Carcinogenicity	: Not class	ified	
	Not class Contains	ified component(s) listed by	ARC as possibly
	carcinoge	enic to humans.	a thermoplastic resin with
		lease under normal cor	nditions of use, transportation,
		.90.	
Germ cell mutagenicity	: Not class	ified	
Reproductive toxicity			
Effects on fertility / Effects on or via lactation	: Not class	ified	
Effects on Development	: Not class	ified	
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is not classified as specific target organ toxicant, single exposure.		
Target Organ Systemic			classified as specific target
Toxicant - Repeated exposure	organ tox	kicant, repeated exposu	ie.
Activation bound	. Net englis		
Aspiration hazard	: Not applie	capie.	
12. Ecological information			
Ecotoxicology Assessment			
Short-term (acute) aquatic hazard	: Not class	ified	
Long-term (chronic) aquatic hazard	: Not class	ified	
		9 / 14	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics. com
Hifax TYC1175P G01 BLVersion 1.2Revision Date 1	
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
Bioaccumulative potential	
Bioaccumulation	: This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	: no data available
Other adverse effects	
Environmental fate and pathways	: This material is not volatile and insoluble in water.
Other information	
Additional ecological information	: Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations	
Waste treatment methods	
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	: This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
	10 / 14

Ponciplastics.com	

SAFETY DATA SHEET

Hifax TYC1175PG01 BLACK

Version 1.2

Revision Date 10/01/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE1269

ondellbase

Not regulated for transport

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN	Type of Toxicity			
		Carcinogen	Developmental	Repro-Male	Repro-
					Female
Mercury	7439-97-6		Х		
Lead	7439-92-1	Х	Х	Х	Х
Arsenic	7440-38-2	Х			
Nickel	7440-02-0	Х			
Chromium	7440-47-3	Х			
Cadmium	7440-43-9	Х	X	X	

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

11 / 14

(+)	1881	699	6168
(')	1001	055	0010

Ponciplastics.com

SAFETY DATA SHEET

Hifax TYC1175P G01 BLACK

Version 1.2

Revision Date 10/01/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE1269

lyondellbase

14807-96-6Talc, Magnesium Silicate1333-86-4Carbon Black

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

14807-96-6 Talc, Magnesium Silicate

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

14807-96-6Talc, Magnesium Silicate1333-86-4Carbon Black

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant


REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

12 / 14



	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell
Hifax TYC1175PG01 BL	ACK	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date 10		/06/2022 SDS No.: BE1269
End	of Material Safety Data SI	heet