	(-	+) 18816996168 nciplastics.com				
SAFETY DATA S		nciplastics.com	lyondellbasell			
Hifax X M2 U1		Drint Data 01	Gen. Variant: SDS_AT			
Version 1.4	Revision Date 04/15/20	Print Date 01	/06/2022 SDS No.: BE3279			
1. Identification of the	e substance/mixture	and of the company/u	ndertaking			
1.1 Product identifier			·			
Trade name	: Hifax	X M2 U16 C11544				
Synonyms Substance name		lefin, Compounded poly ounded polyolefin	/mer			
		ice or mixture and us	es advised against			
Identified uses			s by injection molding, extrusion			
		er conversion process.				
Prohibited uses			s; European class III medical			
	Applic		nent implantation into the body;			
	Life-S	ustaining medical applic	ations			
1.3 Details of the sup	nliar of the safaty da	ta shaat				
	pher of the safety da		-			
	eting Company B.V.	Registration nur NA	nber Telephone 31 (0) 10 275 55 00			
Delftseplein 27E 3013 AA Rotterdam						
Netherlands						
E-mail address		.safety@lyb.com				
Responsible/issuing	person					
1.4 Emergency telep	hone number					
Basell Sales & Mark	eting Company B.V.		+32 3 575 1235			
Poison Center:						
Gesundheid Österre AT: +43 1 406 43 43						
24 hours all days						
2. Hazards identificat	tion					
2.1 Classification of t		turo				
		1 / 16				
1						



according to Regulation (EC) No. 1907/2006

Hifax X M2 U16 C11544

Version 1.4

Print Date 01/06/2022

SDS No.: BE3279

lyondellbasell

Gen. Variant: SDS AT

Classification (REGULATION (EC) No 1272/2008)

Revision Date 04/15/2020

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

2.2 Label elements

Labeling (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture according to Regulation (EC) No 1272/2008.

2.3 Other hazards

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT) or very persistent and very bioaccumulative (vPvB).

3. Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification (REGULATION (EC) No 1272/2008)	Weight %
Proprietary blend of polyolefinic polymers	Mixture	Not Classified	50.0 - 80.0 %

Contains: Additives, stabilizers and fillers

4. First aid measures


4.1 Description of first-aid measures

General advice	: Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid.
lf inhaled	 Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air.
	2 / 16



SAFETY DATA SHEET according to Regulation (EC) No.	1907/2006 Isotoplastics.com
Hifax X M2 U16 C11544	Gen. Variant: SDS_AT
Version 1.4 Revision Date	e 04/15/2020 Print Date 01/06/2022 SDS No.: BE32
	Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR)
In case of skin contact	 If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive.
In case of eye contact	: Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists.
	 In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.
If swallowed	: Adverse health effects due to ingestion are not anticipated.
	nd effects, both acute and delayed
Symptoms	: Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
3 Indication of any immediate i	medical attention and special treatment needed
Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
. Fire-fighting measures	
.1 Extinguishing media	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	3 / 16

SAFETY DATA SHEET	(+) 18816996168 Ponciplastics.com
according to Regulation (EC) No. 1	907/2006 lyondellbasell
Hifax X M2 U16 C11544	
Version 1.4 Revision Date	04/15/2020 Print Date 01/06/2022 SDS No.: BE3279
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media 5.2 Special hazards arising from t	: None known.
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
5.3 Advice for firefighters	
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out.
6. Accidental release measures	
	ive equipment and emergency procedures
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust.
	4 / 16



Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Beclaim where possible
	engineering practices. Reclaim where possible.

7. Handling and storage

7.1 Precautions for safe handling	
Advice on safe handling :	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling
	5 / 16

			(+) 18	816996168		
	SAFETY DATA SH			lastics.com	lyond	ellbasell
	Hifax X M2 U16 C	C11544 ision Date 04/	/15/2020	Print Date 01	Gen. Varian /06/2022	t: SDS_AT SDS No.: BE3279
			combustible After handlir water. When bring	e dusts. ng, always wash l ing the material to	hands thoroughly v p processing tempe in the exhaust vent	with soap and eratures <i>v</i> apors
	Fire-fighting class	: 1	Polymer wil	I burn but does no	ot easily ignite.	
7.	.2 Conditions for safe s	storage, inclu	iding any i	ncompatibilities		
	 Requirements for storage areas and containers Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge. 				e ventilation ulation. strong	
7.	.3 Specific end use(s)					
	: See Section 1.2.					
	. Exposure controls/per .1 Control parameters Ingredients with wo Occupational Expos	orkplace contr sure Limits	rol parame			
	Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information

	Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
be ha pi si	aterials that can e formed when andling this roduct: Non- becified (inert or uisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	

6 / 16



according to Regulation (EC) No. 1907/2006

Hifax X M2 U16 C11544

Version 1.4

Revision Date 04/15/2020

Print Date 01/06/2022

SDS No.: BE3279

lyondellbasell

Gen. Variant: SDS AT

Materials that can	TWA	3 mg/m3	US (ACGIH)	
be formed when		respirable	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust				

Consult local authorities for acceptable exposure limits.

8.2 Exposure controls

Engineering measures

Follow the recommendations in international standard NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection :	Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection :	Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection :	Dust service goggles should be worn to prevent mechanical injury or other irritation to eyes due to airborne particles which may result from handling this product.
Skin and body protection :	Wear suitable protective clothing.
	7 / 16

	(+) 18816996168		
	(+) 18816996168 Ponciplastics.com		
SAFETY DATA SHEET according to Regulation (EC) No. 1	1907/2006	lyondellbasell	
Hifax X M2 U16 C11544	Gen. Variant: SDS_AT		
Version 1.4 Revision Date			
	· Solaction of appropriate para	anal protoctive, equipment should	
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse. 		
Environmental exposure con			
General advice	: See section 6.		
9. Physical and chemical propert 9.1 Information on basic physical			
Appearance	: Pellets.		
Color	: Black		
Odor	: Slight.		
Flash point	: No Data Available.		
Lower explosion limit	: The minimum explosive conc varies according to particle si	entration (MEC) for polymer dust ze distribution.	
Upper explosion limit	: Not applicable.		
Flammability (solid, gas)	: Polymer will burn but does no	ot easily ignite.	
Oxidizing properties	: Not considered an oxidizing a	agent.	
Autoignition temperature	: > 300 °C		
Decomposition temperature	: not determined		
Melting point/range	: 50 - 170 °C		
Boiling point/boiling range	: Not applicable.		
	8 / 16		



according to Regulation (EC) No. 1907/2006

Hifax X M2 U16 C11544

Version 1.4

Revision Date 04/15/2020

Print Date 01/06/2022

SDS No.: BE3279

Gen. Variant: SDS_AT

Vapor pressure	: Not applicable.			
Density	: > 1 g/cm3			
Water solubility	: Insoluble.			
Partition coefficient: n-	: No Data Available.			
octanol/water Viscosity, dynamic	: Not applicable.			
Relative vapor density	: Not applicable.			
Evaporation rate	: Not applicable.			
Explosive properties	: No Data Available.			
9.2 Other information				
Other information	: No additional information available.			
10. Stability and reactivity 10.1 Reactivity				
No known reactivity hazards.				
10.2 Chemical stability				
Stable under normal condition	IS.			
10.3 Possibility of hazardous reactions				
Hazardous reactions	: Will not occur.			
10.4 Conditions to avoid				
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.			
10.5 Incompatible materials				
Materials to avoid	: Material may be softened by some hydrocarbons.			
10.6 Hazardous decomposition products				
9 / 16				

SAFETY DATA SHEET	(+) 18816996168 Ponciplastics.com 1907/2006				
1 111 11					
Hifax X M2 U16 C1154 Version 1.4 Revision Date	4 Gen. Variant: SDS_AT :e 04/15/2020 Print Date 01/06/2022 SDS No.: BE3279				
Hazardous decomposition products Thermal decomposition	 Not expected to decompose under normal conditions. Note: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed. 				
11. Toxicological information	l offorto				
11.1 Information on toxicologica Acute toxicity					
Acute oral toxicity	: Not classified				
Acute inhalation toxicity	: Not classified				
Acute dermal toxicity	: Not classified				
Skin corrosion/irritation	: Not a skin irritant.				
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.				
Respiratory or skin sensitization	: Not classified				
Chronic toxicity					
Carcinogenicity	: Not classified				
Germ cell mutagenicity	: Not classified				
Reproductive toxicity					
Effects on fertility / Effects on or via lactation	: Not classified				
	10 / 16				

	(+) 18816996168 Ponciplastics.com					
SAFETY DATA SHEET according to Regulation (EC) No.		lyondellbasell				
Hifax X M2 U16 C11544 Gen. Variant: SDS_AT						
Version 1.4 Revision Date	e 04/15/2020 Print Date 01/	06/2022 SDS No.: BE3279				
Effects on Development	: Not classified					
Target Organ Systemic Toxi						
	: The substance or mixture is not classified as specific target organ toxicant, single exposure.					
Target Organ Systemic Toxi	cant - Repeated exposure					
	: The substance or mixture is n organ toxicant, repeated expo	· · ·				
Aspiration hazard	: Not applicable.					
12. Ecological information						
12.1 Ecotoxicology Assessment						
Short-term (acute) aquatic hazard	: Not classified					
Long-term (chronic) aquatic hazard	: Not classified					
12.2 Persistence and degradabil	ity					
Biodegradability	: Not expected to be biodegrada	able.				
12.3 Bioaccumulative potential						
Bioaccumulation	: This material is not expected t	to bioaccumulate.				
12.4 Mobility in soil						
Mobility	: no data available					
12.5 Results of PBT and vPvB assessment						
	11 / 16					

	(+) 18816996168 Ponciplastics.com					
SAFETY DATA SHEET according to Regulation (EC) No. 1		lyondellbasell				
Hifax X M2 U16 C11544 Gen. Variant: SDS_AT						
Version 1.4 Revision Date		/06/2022 SDS No.: BE3279				
Result	: This substance/mixture conta to be either persistent, bioaco very persistent and very bioa	cumulative and toxic (PBT) or				
12.6 Other adverse effects						
Environmental fate and pathways	: This material is not volatile and insoluble in water.					
12.7 Other information						
Additional ecological information	solubility of polymers.	minimal based on the low water duct. However, birds, fish and which may obstruct their				
13. Disposal considerations						
13.1 Waste treatment methods						
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.					
14. Transport information						
Not regulated for transport						
15. Regulatory information						
15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture						
	12 / 16					



according to Regulation (EC) No. 1907/2006

Hifax X M2 U16 C11544

Version 1.4

Revision Date 04/15/2020

Print Date 01/06/2022

SDS No.: BE3279

lyondellbasell

Gen. Variant: SDS AT

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Not Compliant
Canada	DSL	Not Compliant
China	IECSC	Not Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Not Compliant
Korea	KECI	Not Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Not Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Not Compliant

Contact product.safety@lyb.com for additional global inventory information.

15.2 Chemical safety assessment

No information available.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 Abbreviations and Acronyms

13 / 16



according to Regulation (EC) No. 1907/2006

Hifax X M2 U16 C11544

Version 1.4

Revision Date 04/15/2020

Print Date 01/06/2022

SDS No.: BE3279

lyondellbasell

Gen. Variant: SDS AT

ACGIH - American Conference of Governmental Industrial Hygienists ACGIH BEIs - American Conference of Governmental Industrial Hygienists Biological Exposure Indices ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road AICS - Australian Inventory of Chemical Substances ASTM - American Society for Testing and Materials **BEL - Biological Exposure Limits** BTEX - Benzene, Toluene, Ethylbenzene, Xylenes CAS - Chemical Abstracts Service **CEFIC - European Chemical Industry Council** CLP - Classification Packaging and Labelling COC - Cleveland Open-Cup CS - Consumer Scenario DIN - Deutsches Institut für Normung DN(M)EL - Derived No (Minimal) Effect Level DSL - Canada Domestic Substance List EC - European Commission EC50 - Median Effective Concentration ECETOC - European Center on Ecotoxicology and Toxicology of Chemicals ECHA - European Chemicals Agency EL50 - Effective Loading fifty ELINCS - EHR-Lab Interoperability and Connectivity Specification ENCS - Japanese Existing and New Chemical Substances Inventory ERC - Environmental Release Category EUSES - European Union System for the Evaluation of Substances EWC - European Waste Code GHS - Globally Harmonized System of Classification and Labelling of Ch IARC - International Agency for Research on Cancer IATA - International Air Transport Association IC50 - Inhibitory Concentration fifty IL50 = Inhibitory Level fifty IMDG - International Maritime Dangerous Goods **IECSC - Chinese Chemicals Inventory** IOELV - Indicative Occupational Exposure Limit Values IP346 - Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables KECI - Korea Existing Chemicals Inventory Koc - Organic Carbon/Water Partition Coefficient LC50 - Lethal Concentration fifty LD50 - Lethal Dose fifty per cent. LL/EL/IL - Lethal Loading/Effective Loading/Inhibitory Loading LL50 - Lethal Loading fifty MAK Commission - Permanent Senate Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area MARPOL - International Convention for the Prevention of Pollution from Ships No. - Number NOEC/NOEL - No Observed Effect Concentration / No Observed Effect Level 14 / 16



according to Regulation (EC) No. 1907/2006

Hifax X M2 U16 C11544

Version 1.4

Revision Date 04/15/2020

Print Date 01/06/2022

SDS No.: BE3279

lvondellbasel

Gen. Variant: SDS_AT

NZIoC - New Zealand Inventory of Chemicals OE_HPV - Occupational Exposure - High Production Volume OECD - Organization for Economic Co-operation and Development **OEL - Occupational Exposure Limit** PBT - Persistent, Bio accumulative and Toxic PICCS - Philippine Inventory of Chemicals and Chemical Substances PNEC - Predicted No Effect Concentration PPE - Personal Protective Equipment **PROC** - Process Category QSAR - Quantitative Structure-Activity Relationship REACh - Registration Evaluation and Authorization of Chemicals RID - Regulations Relating to International Carriage of Dangerous Goods by Rail SDS - Safety Data Sheet SKIN_DES - Skin Designation STEL - Short term exposure limit STP - Standard Temperature and Pressure TCSCA - Taiwan inventory of chemicals TGD - Technical Guidance Document TRA - Targeted Risk Assessment TSCA - US Toxic Substances Control Act TWA - Time-Weighted Average **UN - United Nations** vPvB - very Persistent and very Bioaccumulative WGK - German Water Endangerment Class

Disclaimer

Multiple legal entities and registration numbers may be displayed in Section 1. The Recipient shall refer to the shipping documents to identify the legal entity that supplied this product.

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

15 / 16



according to Regulation (EC) No. 1907/2006

Hifax X M2 U16 C11544

Version 1.4

Revision Date 04/15/2020

Print Date 01/06/2022

SDS No.: BE3279

lyondellbasell

Gen. Variant: SDS AT

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet