	(+) 18816996168	
	Ponciplastics.com	_
SAFETY DATA SHEET	lyondellbas	e
Hostacom 65F5-4 NA	RI Gen. Variant: SDS_US_G	SHS
Version 1.2 Revision Da		
1. IDENTIFICATION OF THE SU	STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING	i
Trade name	: Hostacom 65F5-4 NATRL	
CAS Number:	: Mixture	
Chemical name	Compounded polyolefinPolyolefin, Compounded polymer	
Synonyms	: Polyolelin, Compounded polymer	
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.	on
Prohibited uses	: FDA Class III medical devices; European class III medical	
	devices; Health Canada class IV Medical Devices;	
	Applications involving permanent implantation into the body Life-sustaining medical applications	/;
<u>Company Address</u> Equistar Chemicals, LP	Company Telephone Customer Service 888 777-0232	
LyondellBasell Tower, Suite		
1221 McKinney St.		
P.O. Box 2583		
Houston Texas 77252-258		
Emergency telephone nur	<u>ber</u>	
EQUISTAR 800-245-4532		
E-mail address	: product.safety@lyb.com	
Responsible/issuing person		
. HAZARDS IDENTIFICATION		
GHS Classification		
Combustible dust		
Label elements		
Signal word	: Warning	
Hazard Statements	: If small particles are generated during further processing,	,
	handling or by other means, may form combustible dust concentrations in air.	
Other hazards		
	1 / 13	

	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics.com	lvoodollbacoll		
		lyondellbasell		
Hostacom 65F5-4 NATRL Gen. Variant: SDS_US_GHS				
Version 1.2 Revision Date 1	0/02/2019 Print Date 01/06	S/2022 SDS No.: BE5272		
No additional information avai	lable.			
3. COMPOSITION/INFORMATION O	N INGREDIENTS			
Mixtures				
Components Chemical name	CAS-No.	Woight 9/		
		<u>Weight %</u>		
Proprietary blend of polyolefinic polymers	Mixture	50.0 - 80.0 %		
Contains: Additives, stabilizers a	and fillers	_		
4. FIRST AID MEASURES				
General advice	· Take proper precautions to	ensure your own health and safety		
	before attempting rescue an			
If inhaled	· Domour porcon to fresh air	If signs/symptoms continue, get		
	medical attention.			
	during heating of this materi	on of fumes that may be generated al, move the person to fresh air.		
	Obtain medical attention. Keep person warm, if neces	sary give Cardio-Pulmonary		
	Resuscitation (CPR)			
In case of skin contact		he skin, immediately flush with		
		ool the affected tissue and polymer. ner from skin as this will remove the		
	skin. Obtain immediate emergenc	y medical attention if burn is deep		
	or extensive.			
In case of eye contact	: Flush eyes thoroughly with v	water for several minutes and seek		
	medical attention if discomfo			
	: In case of eye contact with r Continuously flush eye(s) wi	nolten polymer: th cool running water for at least 15		
	minutes.	ttempt to remove the material		
	adherent to the eye(s). Immediately seek medical a			
If swallowed	Adverse health effects due t	o ingestion are not anticipated.		
	2 / 13			

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	
OALETT DATA ONEET		Indellbase
Hostacom 65F5-4 NAT	L Gen.	Variant: SDS_US_GH
Version 1.2 Revision Date		SDS No.: BE52
Notes to physician		
Symptoms	: Inhalation of process fumes and vapo the nose and throat and coughing.	rs may cause soreness
Hazards	: Dust contact with the eyes can lead to Molten polymer may cause thermal be	
Treatment	: Treatment of overexposure should be symptoms and the clinical condition of	
FIRE-FIGHTING MEASURES		
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spra	у.
	: LARGE FIRES: Use water spray hose nozzles from a	safe location.
Unsuitable extinguishing media	: None known.	
Specific hazards during fire fighting	: Keep away from heat and sources of In case of fire hazardous decompositi produced such as: Carbon monoxide, carbon dioxide and	on products may be
	(smoke).	
Special protective equipment for fire-fighters	: Wear approved positive pressure self apparatus and firefighter protective cl	
Further information	: Combustible particulate solid, will dec conditions.	ompose under fire
	Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose Heat from fire may melt, decompose flammable vapors.	
	Move containers from fire area if it ca Evacuate immediately in the event of container pressure relief devices or di	opening of storage scoloration of containe
	Always stay away from tanks engulated Do not attempt to get on top of storag fire. Cool storage containers with large vol	e containers involved i
	fire is out.	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hostacom 65F5-4 NATE Version 1.2 Revision Date	
6. ACCIDENTAL RELEASE MEASU	URES
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
. Handling and storage	
Precautions for safe handling	3
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and
	4 / 13

 $(+)\,18816996168$

Ponciplastics.com

		Poncip1a	astics.com -		
SAFETY DATA S	HEE I			1 1	ellbasel
Hostacom 65F	5-4 NATRL	-		Gen. Variant:	SDS_US_GHS
Version 1.2 Re	vision Date 10/	/02/2019	Print Date 01/	06/2022	SDS No.: BE5272
		Metal cont should be All electric codes and combustibl After handl water. When bring may develo section 10. Refer to NI Dust Explo Handling o	grounded and be regulatory requi le dusts. ling, always was ging the material op may condens FPA 654, Standa osions from the M of Combustible P	n the transfer of this onded. ould conform to app rements for areas h h hands thoroughly to processing temp e in the exhaust ver ard for the Preventio Manufacturing, Proc articulate Solids, for	licable electric andling with soap and peratures vapors ntilation. See n of Fire and essing, and
Fire-fighting class				not easily ignite.	
Conditions for sa	fe storage, inc	luding any	incompatibiliti	es	
Requirements for s areas and containe		Use good and handlin should be Store away oxidizing a Keep conta	ng. Process enc used to avoid ex y from excessive gents. ainer closed to p	ractices during stora losures and adequa cessive dust accum heat and away fror revent contamination the build up of elect	te ventilation nulation. m strong m.
Specific end use(See Sectio	on 1.		
B. EXPOSURE CONTR	OLS/PERSON/	AL PROTE	CTION		
Control parameters	workplace.con	trol param	eters		
Ingredients with workplace control parameters Occupational Exposure Limits					
Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
		5	/ 13		

$(+)\,18816996168$

Ponciplastics.com

Gen. Variant: SDS US GHS

Hostacom 65	F5-4 NATRL
Version 1.2	Revision Date 10/02/2019

Print Date 01/06/2022

SDS_US_GHS SDS_US_GHS

Materials that can be formed when	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
handling this		respirable	2005	
product: Non-				
specified (inert or				
nuisance) dust				
Materials that can	TWA	15 mg/m3	US (OSHA)	
be formed when		total dust	2005	
handling this				
product: Non-				
specified (inert or				
nuisance) dust		E ma/m2		
Materials that can be formed when	TWA	5 mg/m3 respirable	US (OSHA) 2005	
handling this		respirable	2005	
product: Non-				
specified (inert or				
nuisance) dust				

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

	(+) 188		
SAFETY DATA SHEET	Poncipl	astics.com	lyondellbase
			1 1 11
Hostacom 65F5-4 NAT Version 1.2 Revision Date		Drint Date ()	Gen. Variant: SDS_US_GH
ersion 1.2 Revision Date	3 10/02/2013	Print Date 0	1/06/2022 SDS No.: BE5
		ther irritation to t from handling	eyes due to airborne particles which this product.
Skin and body protection	: Wear suita	able protective	clothing.
Hygiene measures	be based of of the prote performed, hazards an during use Use good Wash hand facilities.	on an evaluation ective equipme , conditions pre nd/or potential e. personal hygie ds before eatin	personal protective equipment shoul n of the performance characteristics ent relative to the task(s) to be esent, duration of use, and the hazards that may be encountered ne practices. g, drinking, smoking, or using toilet othing and wash before reuse.
PHYSICAL AND CHEMICAL P Appearance	: Pellets.		
Color	: Transluce	nt to white	
Odor	: Slight.		
Odor Odor Threshold	: Slight. : No value a	available.	
	-		
Odor Threshold	: No value a : No Data / : The minin	Available. num explosive	concentration (MEC) for polymer du cle size distribution.
Odor Threshold Flash point	: No value a : No Data / : The minin	Available. num explosive cording to partic	
Odor Threshold Flash point Lower explosion limit	 No value a No Data A The minin varies acc Not applic 	Available. num explosive cording to partic cable.	
Odor Threshold Flash point Lower explosion limit Upper explosion limit	 No value a No Data A The minin varies acc Not applic Polymer value 	Available. num explosive cording to partic cable.	cle size distribution. es not easily ignite.
Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas)	 No value a No Data A The minin varies acc Not applic Polymer value 	Available. num explosive cording to partic cable. will burn but doe	cle size distribution. es not easily ignite.
Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	 No value a No Data A The minin varies acc Not applic Polymer v Not consid 	Available. num explosive cording to partic cable. will burn but doe dered an oxidiz	cle size distribution. es not easily ignite.
Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	 No value a No Data A The minin varies acc Not applic Polymer v Not consident > 300 °C 	Available. num explosive cording to partic cable. will burn but doe dered an oxidiz nined	cle size distribution. es not easily ignite.
Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	 No value a No Data A The minin varies acc Not applic Polymer v Not consid > 300 °C not determination 	Available. num explosive cording to partic cable. will burn but doe dered an oxidiz nined °C	cle size distribution. es not easily ignite.
Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range	 No value a No Data A The minin varies acc Not applic Polymer v Not consid > 300 °C not determ 50 - 170 	Available. num explosive cording to partic cable. will burn but doe dered an oxidiz nined °C cable.	cle size distribution. es not easily ignite.
Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range Boiling point/boiling range	 No value a No Data A The minin varies accord Not application Polymer value Not considered > 300 °C not determant 50 - 170 Not application 	Available. num explosive cording to partic cable. will burn but doe dered an oxidiz nined °C cable. cable.	cle size distribution. es not easily ignite.

$(+)\,18816996168$

Ponciplastics.com

SAFETY	DATA	SHEET	

Hostacom 65F5-4 NATRL

lyondellbasell Gen. Variant: SDS_US_GHS Version 1.2 Revision Date 10/02/2019 Print Date 01/06/2022 SDS No.: BE5272

Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.

10. STABILITY AND REACTIVITY

Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition	: Not expected to decompose under normal conditions.
Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 13

	(+) 18816996168				
SAFETY DATA SHEET	Ponciplastics.com				
Iyulluelluasell					
Hostacom 65F5-4 NATRLGen. Variant: SDS_US_GHSVersion 1.2Revision Date 10/02/2019Print Date 01/06/2022SDS No.: BE5272					
Respiratory or skin sensitization	: Not classified				
Chronic toxicity					
Carcinogenicity	: Not classified				
	Not listed by IARC, NTP, OSHA or EPA.				
Germ cell mutagenicity	: Not classified				
Reproductive toxicity					
Effects on fertility / Effects on or via lactation	: Not classified				
Effects on Development	: Not classified				
Target Organ Systemic Toxicant - Single exposure	 The substance or mixture is not classified as specific target organ toxicant, single exposure. 				
Target Organ Systemic Toxicant - Repeated	The substance or mixture is not classified as specific target organ toxicant, repeated exposure.				
exposure					
Aspiration hazard	: Not applicable.				
12. Ecological information					
Ecotoxicology Assessment Short-term (acute) aquatic	: Not classified				
hazard Long-term (chronic)	: Not classified				
aquatic hazard					
Persistence and degradability					
Biodegradability	: Not expected to be biodegradable.				
9 / 13					

	(+) 18816996168				
SAFETY DATA SHEET	Ponciplastics.com	luce de llbe e e ll			
SALETT DATA SHEET		lyondellbasell			
Hostacom 65F5-4 NATR	l .	Gen. Variant: SDS_US_GHS			
Version 1.2 Revision Date 10		1/06/2022 SDS No.: BE5272			
Bioaccumulative potential					
Bioaccumulation	: This material is not expected to bioaccumulate.				
Mobility in soil					
Mobility	no data available				
Other adverse effects					
Environmental fate and pathways	: This material is not volatile and insoluble in water.				
Other information					
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts. 				
13. Disposal considerations Waste treatment methods					
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.				
	This material is classified RCRA.	as a Non-hazardous Material by			
14. TRANSPORT INFORMATION					
Not regulated for transport					
15. REGULATORY INFORMATION					
	10 / 13				

SAFETY DATA SHEET

Ponciplastics.com

Hostacom 65F5-4 NATRL Revision Date 10/02/2019

Version 1.2

Print Date 01/06/2022

Gen. Variant: SDS US GHS SDS No.: BE5272

Iyondellbase

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

Calcium Carbonate 1317-65-3

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

1317-65-3 Calcium Carbonate

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

1317-65-3 Calcium Carbonate

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

11 / 13

(+) 18816996168

Ponciplastics.com

SAFETY DATA SHEET

Hostacom 65F5-4 NATRL

Version 1.2

Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE5272

lyondellbase

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Not Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Not Determined

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

HMIS Classification	: Health Hazard: 0 Flammability: 1 Physical hazards: 0	0 1 0
NFPA Classification	: Health Hazard: 0 Fire Hazard: 1 Instability: 0	
Further information		
	12 / 13	

Ponciplastics.com SAFETY DATA SHEET

iyondelibase

Hostacom 65F5-4 NATRL

Version 1.2

Revision Date 10/02/2019

Print Date 01/06/2022

.... Gen. Variant: SDS US GHS

SDS No.: BE5272

HMIS rating scale (0 = minimal hazard; 4 = severe hazard) NFPA rating scale (0 = minimal hazard; 4 = severe hazard)

Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet