	(+) 18816996168		
SAFETY DATA SHEET	Ponciplastics.com		
SAFELY DATA SHEET	lyondellbase		
Hostacom CA199AC E	Gen. Variant: SDS_US_GH		
Version 1.2 Revision Date			
1. IDENTIFICATION OF THE SU	STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING		
Trade name	: Hostacom CA199AC BLK		
CAS Number: Chemical name	: Mixture : Compounded polyolefin		
Synonyms	: Polyolefin, Compounded polymer		
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.		
Durch in Stand August			
Prohibited uses	: FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices;		
	Applications involving permanent implantation into the body;		
	Life-sustaining medical applications		
Company Address	Company Telephone		
Equistar Chemicals, LP	Customer Service 888 777-0232		
LyondellBasell Tower, Suite	300 product.safety@lyb.com		
1221 McKinney St. P.O. Box 2583			
Houston Texas 77252-2583			
Emergency telephone num	ber		
EQUISTAR 800-245-4532			
E-mail address	: product.safety@lyb.com		
Responsible/issuing person	on		
. HAZARDS IDENTIFICATION			
<b>GHS</b> Classification			
Combustible dust			
Label elements			
Signal word	: Warning		
Hazard Statements	: If small particles are generated during further processing,		
	handling or by other means, may form combustible dust concentrations in air.		
Other hazards			
	1 / 13		

	(+) 18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lvoodollbacol
		lyondellbasel
Hostacom CA199AC BL	.К	Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date	10/02/2019 Print Date 01/0	6/2022 SDS No.: BE528
No additional information av	ailable.	
. COMPOSITION/INFORMATION	ON INGREDIENTS	
lixtures		
Components		
Chemical name	CAS-No.	Weight %
Proprietary blend of polyolefinic polymers	Mixture	98.0 - 100.0 %
Contains: Additives and stabiliz	zers	
FIRST AID MEASURES		
General advice	· Take proper precautions to	ensure your own health and safety
	before attempting rescue ar	
If inhaled	· Remove person to fresh air	If signs/symptoms continue, get
	medical attention.	ion of fumes that may be generate
		al, move the person to fresh air.
	Keep person warm, if neces Resuscitation (CPR)	sary give Cardio-Pulmonary
	Resuscitation (CFR)	
In case of skin contact		he skin, immediately flush with
	Do not attempt to peel polyr	ool the affected tissue and polymer ner from skin as this will remove th
		y medical attention if burn is deep
	or extensive.	
In case of eye contact		water for several minutes and seel
	medical attention if discomfo	ort persists.
	: In case of eye contact with Continuously flush eye(s) w	molten polymer: ith cool running water for at least 1
	minutes.	attempt to remove the material
	adherent to the eye(s). Immediately seek medical a	
If owned and	. Adverse health effects due .	to increation are not entirinated
If swallowed	. Auverse nearm ellects due	to ingestion are not anticipated.
	2 / 13	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hostacom CA199AC BL	<b>_K</b> Gen. Variant: SDS_US_GHS
/ersion 1.2 Revision Date	10/02/2019 Print Date 01/06/2022 SDS No.: BE528
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient.
FIRE-FIGHTING MEASURES	: SMALL FIRE:
	<ul><li>Use dry chemical, CO2, or water spray.</li><li>LARGE FIRES: Use water spray hose nozzles from a safe location.</li></ul>
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	<ul> <li>Keep away from heat and sources of ignition.</li> <li>In case of fire hazardous decomposition products may be produced such as:</li> <li>Carbon monoxide, carbon dioxide and unburned hydrocarbon (smoke).</li> </ul>
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	<ul> <li>Combustible particulate solid, will decompose under fire conditions.</li> <li>Calorific Value: 8000 - 11000 kcal/kg</li> <li>Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors.</li> <li>Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire.</li> <li>Do not attempt to get on top of storage containers involved in fire.</li> <li>Cool storage containers with large volumes of water even after fire is out.</li> </ul>

Accident of the second seco		(+) 18816996168
Accident of the second state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Accident and state 10/02/2019         Accident and state 10/02/2019         Print Date 01/06/2022         SDS No.: BE5           Methods for cleaning up         Interventile is in suble and state 10/02/2019         Accide and containes or vaccumusing equipment which avoids i	SAFETY DATA SHEET	Iyondellbase
ACCIDENTAL RELEASE MEASURES         Personal precautions       : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protectiv equipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.         Environmental precautions       : Do not flush into surface water or sanitary sewer system.         Methods for containment / Methods for cleaning up       : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid.         All recovered material should be packaged, labeled, transported and disposed for reclaimed in conformance with goo engineering practices. Reclaim where possible.         Handling and storage       : Material is in a pellet form. Hi converted to small particles during further processing, handling, or by other means, may form combustible dust concerntrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion		
Personal precautions       Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protectiv equipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.         Environmental precautions       : Do not flush into surface water or sanitary sewer system.         Methods for containment / Methods for containment / Methods for cleaning up       : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with goo engineering practices. Reclaim where possible.         Handling and storage       : Precautions for safe handling Advice on safe handling         Advice on safe handling       : Material is in a pellet form. If converted to small particles during further processing, handing, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling, Equipment handling polymer should be conductive and	Version 1.2 Revision Date	10/02/2019 Print Date 01/06/2022 SDS No.: BE52
Personal precautions       Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protectiv equipment (PPE) Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.         Environmental precautions       : Do not flush into surface water or sanitary sewer system.         Methods for containment / Methods for containment / Methods for cleaning up       : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with goo engineering practices. Reclaim where possible.         Handling and storage       : Precautions for safe handling Advice on safe handling         Advice on safe handling       : Material is in a pellet form. If converted to small particles during further processing, handing, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling, Equipment handling polymer should be conductive and		
Creates dangerous slipping hazard on any hard smooth surface.         Equip emergency responders with proper personal protective equipment (PPE)         Avoid generating dust.         Avoid generating dust.         Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).         Potential combustible dust hazard.         Polymer particles create slipping hazard on hard smooth surfaces.         Environmental precautions       : Do not flush into surface water or sanitary sewer system.         Methods for containment /       : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk.         On water, material is insoluble; collect and contain as any soild.       All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance wit applicable laws and regulations and in conformance wit applicable laws and regulations and in conformance wit gor engineering practices. Reclaim where possible.         Handling and storage       : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion hazard.	ACCIDENTAL RELEASE MEAS	JURES
Methods for containment / Methods for cleaning up       : On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with god engineering practices. Reclaim where possible.         Handling and storage       Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation. Avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and	Personal precautions	<ul> <li>Creates dangerous slipping hazard on any hard smooth surface.</li> <li>Equip emergency responders with proper personal protective equipment (PPE)</li> <li>Avoid generating dust.</li> <li>Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air).</li> <li>Potential combustible dust hazard.</li> <li>Polymer particles create slipping hazard on hard smooth</li> </ul>
Methods for cleaning up       vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid.         All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with god engineering practices. Reclaim where possible.         Handling and storage       Precautions for safe handling         Advice on safe handling       : Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and	Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Precautions for safe handling         Advice on safe handling         :       Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and		vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good
<ul> <li>Advice on safe handling</li> <li>Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and</li> </ul>	Handling and storage	
If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high du environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and		-
4 / 13	Advice on safe handling	<ul> <li>If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air.</li> <li>Avoid dust accumulation in enclosed space.</li> <li>Use dust collection systems designed per NFPA 654 to avoid dust accumulation.</li> <li>Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard.</li> <li>Static discharge (spark), or other ignition sources, in high dust explosion</li> <li>Electrostatic charge may build during conveying or handling.</li> </ul>
		4 / 13

		(+) 188	16996168			
		Poncipla	astics.com			
SAFETY DATA S	HEET			lyonde	ellbasell	
Hostacom CA199AC BLK Gen. Variant: SDS_US_GR						
			Print Date 0			
	Version 1.2       Revision Date 10/02/2019       Print Date 01/06/2022       SDS No.: BE52         grounded (earthed) and bonded.       Metal containers involved in the transfer of this material should be grounded and bonded.       All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts.         After handling, always wash hands thoroughly with soap and water.       When bringing the material to processing temperatures vapor may develop may condense in the exhaust ventilation. See section 10.					
				Manufacturing, Proc Particulate Solids, for		
Fire-fighting class	:	Polymer w	ill burn but doe	s not easily ignite.		
Conditions for sat	ie storage, inc	luding any	incompatibili	ties		
	<ul> <li>Requirements for storage areas and containers</li> <li>Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge.</li> </ul>				te ventilation nulation. m strong m.	
Specific end use(s	5)					
	:	See Section	on 1.			
8. EXPOSURE CONTR	OLS/PERSON	AL PROTE	CTION			
Control parameters						
Ingredients with v	Ingredients with workplace control parameters					
Occupational Exposure Limits						
Components Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	CAS-No.	Type TWA	Limit Value 10 mg/m3 inhalable	Basis Revision Date US (ACGIH) 2005	Additional Information	
		l				
		5	/ 13			

(+)	1881	69961	68
( )		00001	

Ponciplastics.com

SAFETY	DATA	SHEET

Iyondellbasell

# Hostacom CA199AC BLK

Version 1.2 Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE5285

Materials that can be formed when handling this product: Non- specified (inert or	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
nuisance) dust Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

#### Exposure controls

#### Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

#### Personal protective equipment

Respiratory protection	<ul> <li>Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.</li> <li>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.</li> <li>Use appropriate respiratory protection where atmosphere exceeds recommended limits.</li> <li>Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.</li> </ul>
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 13

(+) 18816996168

AFETY DATA SHEET	Ponciplastics.com	ondellbase
	I Y	
lostacom CA199AC B		. Variant: SDS_US_GH
ersion 1.2 Revision Date	10/02/2019 Print Date 01/06/2022	SDS No.: BE52
	injury or other irritation to eyes due to may result from handling this product	
Skin and body protection	: Wear suitable protective clothing.	
Hygiene measures	<ul> <li>Selection of appropriate personal probe based on an evaluation of the performed, conditions present, durati hazards and/or potential hazards tha during use.</li> <li>Use good personal hygiene practices Wash hands before eating, drinking, facilities.</li> <li>Take off contaminated clothing and wash hands</li> </ul>	formance characteristics o the task(s) to be on of use, and the t may be encountered s. smoking, or using toilet
PHYSICAL AND CHEMICAL P Appearance Color	: Pellets.	
Appearance	: Pellets. : Black	
Appearance Color	: Pellets.	
Appearance Color Odor	: Pellets. : Black : Slight.	
Appearance Color Odor Odor Threshold	<ul><li>Pellets.</li><li>Black</li><li>Slight.</li><li>No value available.</li></ul>	
Appearance Color Odor Odor Threshold Flash point	<ul> <li>Pellets.</li> <li>Black</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration</li> </ul>	
Appearance Color Odor Odor Threshold Flash point Lower explosion limit	<ul> <li>Pellets.</li> <li>Black</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration varies according to particle size distributed</li> </ul>	ribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit	<ul> <li>Pellets.</li> <li>Black</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration varies according to particle size districts</li> <li>Not applicable.</li> </ul>	ribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas)	<ul> <li>Pellets.</li> <li>Black</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration varies according to particle size distributions.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily</li> </ul>	ribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	<ul> <li>Pellets.</li> <li>Black</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration varies according to particle size distributions and the second seco</li></ul>	ribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	<ul> <li>Pellets.</li> <li>Black</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration varies according to particle size distributions.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> </ul>	ribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	<ul> <li>Pellets.</li> <li>Black</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration varies according to particle size distributions are according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> <li>not determined</li> </ul>	ribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	<ul> <li>Pellets.</li> <li>Black</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration varies according to particle size distributions according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> <li>not determined</li> <li>50 - 170 °C</li> </ul>	ribution.
Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range Boiling point/boiling range	<ul> <li>Pellets.</li> <li>Black</li> <li>Slight.</li> <li>No value available.</li> <li>No Data Available.</li> <li>The minimum explosive concentration varies according to particle size distributions according to particle size distribution.</li> <li>Not applicable.</li> <li>Polymer will burn but does not easily.</li> <li>Not considered an oxidizing agent.</li> <li>&gt; 300 °C</li> <li>not determined</li> <li>50 - 170 °C</li> <li>Not applicable.</li> </ul>	ribution.

	(+) 18816996168
AFETY DATA SHEET	Ponciplastics.com
lostacom CA199AC E	
ersion 1.2 Revision Date	e 10/02/2019 Print Date 01/06/2022 SDS No.: BE52
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
STABILITY AND REACTIVITY	(
Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks o open flame.
Materials to avoid	: Material may be softened by some hydrocarbons.
Hazardous decomposition	: Not expected to decompose under normal conditions.
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
. TOXICOLOGICAL INFORMA	ΓΙΟΝ
Acute toxicity	
Acute oral toxicity	: Not classified
Acute inhalation toxicity	: Not classified
Acute dermal toxicity	: Not classified
Skin corrosion/irritation	: Not a skin irritant.
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.
	8 / 13

	(+) 188	16996168	
SAFETY DATA SHEET	Poncip1	astics.com	lyondellbasell
Hostacom CA199AC B Version 1.2 Revision Date		Print Date 01/06/2	Gen. Variant: SDS_US_GHS 022 SDS No.: BE5285
Respiratory or skin sensitization	: Not classi	fied	
Chronic toxicity			
Component Name Carbon Black	NTP	IARC 2B	OSHA Present
Carcinogenicity	: Not classi	fied	
	carcinoger This mate	component(s) listed b nic to humans. rial is encapsulated ir ease under normal co	y IARC as possibly a thermoplastic resin with anditions of use, transportation,
Germ cell mutagenicity	: Not classi	fied	
Reproductive toxicity			
Effects on fertility / Effects on or via lactation	: Not classi	fied	
Effects on Development	: Not classi	fied	
Target Organ Systemic Toxicant - Single exposure		ance or mixture is not cant, single exposure	t classified as specific target
Target Organ Systemic Toxicant - Repeated exposure		ance or mixture is not cant, repeated expos	t classified as specific target ure.
Aspiration hazard	: Not applic	able.	
12. Ecological information			
Ecotoxicology Assessment			
Short-term (acute) aquatic hazard	: Not classi	fied	
Long-term (chronic) aquatic hazard	: Not classi	fied	
	ę	9 / 13	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics. com
Hostacom CA199AC BL Version 1.2 Revision Date 1	
Version 1.2 Revision Date 1	0/02/2019 Print Date 01/06/2022 SDS No.: BE5285
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
Bioaccumulative potential	
Bioaccumulation	: This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	: no data available
Other adverse effects	
Environmental fate and pathways	: This material is not volatile and insoluble in water.
Other information	
Additional ecological information	: Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations	
Waste treatment methods	
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	: This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
	10 / 13

(+) <b>18816996168</b>	
------------------------	--

Ponciplastics.com

# SAFETY DATA SHEET

# Hostacom CA199AC BLK

Version 1.2

Revision Date 10/02/2019

Print Date 01/06/2022

Gen. Variant: SDS\_US\_GHS

lyondellbase 

SDS No.: BE5285

Not regulated for transport

## **15. REGULATORY INFORMATION**

## TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

## Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

#### SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

## SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

#### **SARA 313**

This product contains no known chemicals regulated under SARA 313.

#### State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

1333-86-4 Carbon Black

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

1333-86-4 Carbon Black

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

1333-86-4 Carbon Black

11 / 13

(+) 18816996168		68	1	6	9	9	6	1	8	8	1	(+)	(
-----------------	--	----	---	---	---	---	---	---	---	---	---	-----	---

## SAFETY DATA SHEET

Ponciplastics.com

# Hostacom CA199AC BLK

Version 1.2

Revision Date 10/02/2019

Print Date 01/06/2022

SDS No.: BE5285

Gen. Variant: SDS US GHS

557-05-1 Zinc Stearate

#### Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

#### REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.


#### **16. OTHER INFORMATION**

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

HMIS Classification

: Health Hazard: 0 Flammability: 1 Physical hazards: 0



12 / 13

