	(+)18816996168	
SAFETY DATA SHEET	Ponciplastics.com	lyondellbasell
Hostacom DKG728P ZSF	P DEEP GRY	Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date 12	2/19/2017 Print Date 12	2/23/2019 SDS No.: BE5294
1. IDENTIFICATION OF THE SUBST	ANCE/MIXTURE AND OF	THE COMPANY/UNDERTAKING
Trade name :	Hostacom DKG728P ZSF	P DEEP GRY
CAS Number: : Chemical name :	Mixture	
Synonyms :	Compounded polyolefin Polyolefin, Compounded	polymer
Cynonyms .		polymen
Identified uses :	Manufacture of plastic art or other conversion proce	icles by injection molding, extrusion ss.
Prohibited uses :	devices; Health Canada c	manent implantation into the body;
<u>Company Address</u> Equistar Chemicals, LP	Customer Sen	<u>ephone</u> vice 888 777-0232
LyondellBasell Tower, Suite 300		
1221 McKinney St.	1	
P.O. Box 2583		
Houston Texas 77252-2583		
Emergency telephone number EQUISTAR 800-245-4532		
E-mail address : Responsible/issuing person	product.safety@lyb.com	
2. HAZARDS IDENTIFICATION		
GHS Classification		
OSHA Hazard Category: Con	nbustible Dust	
Label elements		
Signal word :	Warning	
Hazard Statements :		nerated during further processing,
nazaru Statements .		ns, may form combustible dust
Other hazards		
No additional information avail		
	1 / 14	

SAFETY DATA SHEET Subject of the system		(+) 18816996168	
Hostacom DKG728P ZSP DEEP GRY Gen. Variant: SDS_US_GHS Version 1.1 Revision Date 12/19/2017 Print Date 12/23/2019 SDS No.: BE5294 3. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Ingredients Contains: Additives, stabilizers and fillers Contains: Additives, stabilizers and fillers Contains: Additives, stabilizers and fillers General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of varies to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with water for attempt to remove the material admetion. In case of eye contact : Flush eyes thoroughly with water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention.	SAFETY DATA SHEET	Ponciplastics.com	lvoodollbacoll
Version 1.1 Revision Date 12/19/2017 Print Date 12/23/2019 SDS No.: BE5294 3. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Ingredients Ingredients Chemical name CAS-No. Weight % polymers Contains: Additives, stabilizers and fillers FIRST AID MEASURES General advice Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Otain medical attention. In case of skin contact If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Otbian immediate emergency medical attention if burn is deep or extensive. In case of eye contact Flush eyes thoroughly with water for several minutes and seek medical attention for genesits. In case of eye contact Flush eyes thoroughly with water for several minutes and seek medical attention. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s), immediately seek medical attention. Merese health effects due to ingestion are not anticipated. <th></th> <th></th> <th></th>			
3. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Ingredients Proprietary blend of polyolefinic polymers: Contains: Additives, stabilizers and fillers 4. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person run; if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. in case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health e			
Mixtures Ingredients Chemical name CAS-No. Weight % Solo - 80.0 %<th>Version 1.1 Revision Date 1.</th><th>2/19/2017 Pfint Date 12</th><th>2/23/2019 SDS NO BE5294</th>	Version 1.1 Revision Date 1.	2/19/2017 Pfint Date 12	2/23/2019 SDS NO BE5294
Mixtures Ingredients Chemical name CAS-No. Weight % Solo - 80.0 %<th></th><th></th><th></th>			
Mixtures Ingredients Chemical name CAS-No. Weight % Solo - 80.0 %<th></th><th></th><th></th>			
Chemical name CAS-No. Weight % Proprietary blend of polyolefinic Mixture 50.0 - 80.0 % polymers Contains: Additives, stabilizers and fillers Contains: Additives, stabilizers and fillers 4. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with iarge amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s), with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.			
Proprietary blend of polyolefinic Mixture 50.0 - 80.0 % contains: Additives, stabilizers and fillers A. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of turnes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with col running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	Ingredients		
polymers Contains: Additives, stabilizers and fillers 4. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	Chemical name	CAS-No.	Weight %
4. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.		Mixture	50.0 - 80.0 %
General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	Contains: Additives, stabilizers a	and fillers	
General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.			
If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	4. FIRST AID MEASURES		
If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	General advice	: Take proper precautions	to ensure your own health and safety
In case of skin contact If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due			
Iarge amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	If inhaled	medical attention. In case of excessive inha during heating of this ma Obtain medical attention. Keep person warm, if new	lation of fumes that may be generated terial, move the person to fresh air.
medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	In case of skin contact	large amounts of water to Do not attempt to peel po skin. Obtain immediate emerge	o cool the affected tissue and polymer. Olymer from skin as this will remove the
Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	In case of eye contact		
		Continuously flush eye(s) minutes. Beyond flushing, DO NO adherent to the eye(s).) with cool running water for at least 15 T attempt to remove the material
2 / 14	If swallowed	Adverse health effects du	ue to ingestion are not anticipated.
		2 / 14	

(+) 18816996168 Ponciplastics.com SAFETY DATA SHEET Iyondellbase Gen. Variant: SDS US GHS Hostacom DKG728P ZSP DEEP GRY Version 1.1 Revision Date 12/19/2017 Print Date 12/23/2019 SDS No.: BE5294 Notes to physician Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. LARGE FIRES: Use water spray hose nozzles from a safe location. Unsuitable extinguishing : None known. media Specific hazards during fire Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be fighting produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). Special protective equipment Wear approved positive pressure self-contained breathing for fire-fighters apparatus and firefighter protective clothing. Further information Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. Cool storage containers with large volumes of water even after fire is out. 3/14

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hostacom DKG728P Z Version 1.1 Revision Date	
. ACCIDENTAL RELEASE MEAS	SURES
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
Handling and storage	
Precautions for safe handlin	ng
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dus environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and grounded (earthed) and bonded.
	4 / 14

 $(+)\,18816996168$

Ponciplastics.com

SAFETY DATA SHEET	Ponciplastics. com
	lyondellbasell
Hostacom DKG728P Z	SPDFFPGRY Gen. Variant: SDS_US_GHS
Version 1.1 Revision Date	
	Metal containers involved in the transfer of this material
	should be grounded and bonded. All electrical equipment should conform to applicable electric
	codes and regulatory requirements for areas handling combustible dusts.
	After handling, always wash hands thoroughly with soap and water.
	When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10.
	Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.
	Handling of Compustible Fatticulate Solius, for sale Handling.
Fire-fighting class	: Polymer will burn but does not easily ignite.
Conditions for safe storage,	including any incompatibilities
Requirements for storage areas and containers	 Store in a dry location. Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic charge.
Specific end use(s)	
	: See Section 1.
8. EXPOSURE CONTROLS/PERS	ONAL PROTECTION
Control parameters	

Ingredients with workplace control parameters

Occupational Exposure Limits

Ingredients	CAS-No.	Туре	Limit Value	Basis	Additional
				Revision Date	Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	

Ponciplastics.com

lyondellbasell

	Hostacom	DKG728P	ZSP DEEP GRY
--	----------	---------	---------------------

Version 1.1 Revision Date 12/19/2017

Print Date 12/23/2019

Gen. Variant: SDS_US_GHS 19 SDS No.: BE5294

Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	ngineering controls to keep commended exposure lim /hen workers are facing co mit they must use appropria se appropriate respiratory kceeds recommended limi /here workers could be ex	its. Incentrations above the exposure ate certified respirators. protection where atmosphere
Hand protection	ear gloves that provide th btential for contact with he	ermal protection where there is a ated material.
Eye and face protection	ust service goggles should	be worn to prevent mechanical
	6 / 14	

	lyondellbase	
ostacom DKG728P Z		
ersion 1.1 Revision Date	2 12/19/2017 Print Date 12/23/2019 SDS No.: BE5	
	injury or other irritation to eyes due to airborne particles which may result from handling this product.	
Skin and body protection	: Wear suitable protective clothing.	
Hygiene measures	 Selection of appropriate personal protective equipment shoul be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse. 	
PHYSICAL AND CHEMICAL PI Appearance Color	ROPERTIES : Pellets. : Grey.	
Odor	: Slight.	
	•	
Odor Threshold	: No value available.	
Odor Threshold Flash point	: No value available. : No Data Available.	
	: No Data Available.	
Flash point	 No Data Available. The minimum explosive concentration (MEC) for polymer du 	
Flash point Lower explosion limit	 No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. 	
Flash point Lower explosion limit Upper explosion limit	 No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. 	
Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas)	 No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. 	
Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	 No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. 	
Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	 No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C 	
Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	 No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 	
Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range	 No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C 	
Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range Boiling point/boiling range	 No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C Not applicable. 	

	(+) 18816996168		
SAFETY DATA SHEET	Ponciplastics.com		
Hostacom DKG728P Z			
/ersion 1.1 Revision Date	e 12/19/2017 Print Date 12/23/2019 SDS No.: BE52		
Partition coefficient: n-	: No Data Available.		
octanol/water Viscosity, dynamic	: Not applicable.		
Relative vapor density	: Not applicable.		
Evaporation rate	: Not applicable.		
Explosive properties	: No Data Available.		
Other Information	: No additional information available.		
D. STABILITY AND REACTIVITY	(
Reactivity	: No known reactivity hazards.		
Chemical stability	: Stable under normal conditions.		
Hazardous reactions	: Will not occur.		
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.		
Materials to avoid	: Material may be softened by some hydrocarbons.		
Hazardous decomposition products	: Not expected to decompose under normal conditions.		
Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.		
1. TOXICOLOGICAL INFORMA	ΤΙΟΝ		
Acute toxicity			
Acute oral toxicity	: Not classified		
Acute inhalation toxicity	: Not classified		
Acute dermal toxicity	: Not classified		
Skin corrosion/irritation	: Not a skin irritant.		
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.		
	8 / 14		

	(+) 188	816996168	
	Poncipi	lastics.com	1 1 111
AFETY DATA SHEET			lyondellbase
		CDV	Gen. Variant: SDS_US_G
ostacom DKG728P Z ersion 1.1 Revision Date		Print Date 12/	
Respiratory or skin sensitization	: Not class	ified	
Chronic toxicity			
Component Name	NTP	IARC	OSHA
Titanium Dioxide Carbon Black		2B 2B	Present Present
		20	Flesell
Carcinogenicity	: Not class	ified	
Germ cell mutagenicity	This mate	lease under norma ge.	ed in a thermoplastic resin with al conditions of use, transportatio
Reproductive toxicity Effects on fertility / Effects on or via lactation	: Not class	ified	
Effects on Development	: Not class	ified	
Target Organ Systemic Toxicant - Single exposure		tance or mixture is icant, single expo	s not classified as specific target sure.
Target Organ Systemic Toxicant - Repeated exposure		tance or mixture is icant, repeated ex	s not classified as specific target xposure.
Aspiration hazard	: Not applic	cable.	
ECOLOGICAL INFORMATION	1		
Ecotoxicology Assessment			
Acute aquatic toxicity	: Not class	ified	
		9 / 14	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hostacom DKG728P Z Version 1.1 Revision Date	
Chronic aquatic toxicity	: Not classified
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
Bioaccumulative potential	
Bioaccumulation	: This material is not expected to bioaccumulate.
Mobility in soil	
Additional advice Environmental fate and pathways	: This material is not volatile and insoluble in water.
Results of PBT and vPvB assessr	nent
Not applicable.	
Other adverse effects	
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations	
Waste treatment methods	
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	: This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
	10 / 14

Ponciplastics.com

SAFETY DATA SHEET

lyondellbase

Gen. Variant: SDS US GHS

Version 1.1

Hostacom DKG728P ZSP DEEP GRY Revision Date 12/19/2017

Print Date 12/23/2019

SDS No.: BE5294

Not regulated for transport

15. REGULATORY INFORMATION

If identified components of this product are listed under the TSCA 12(b) Export Notification rule, they will be listed below.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Physical Hazards

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material is not known to contain a chemical substance known to the State of California to cause cancer, reproductive, or developmental toxicity under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

1333-86-4 Carbon Black

No components are subject to the Massachusetts Right to Know Act.

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

1333-86-4 Carbon Black

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Australia AICS Compliant	Inventory Status Description	Inventory	Country/Region
	AICS Compliant	AICS	Australia
11 / 14	11 / 14	11	
		••	

(+)	18816996168

Ponciplastics.com

SAFETY	DATA	SHEET
--------	------	-------

vondellbase

Hostacom DKG728P ZSP DEEP GRY Revision Date 12/19/2017

Version 1.1

Print Date 12/23/2019

Gen. Variant: SDS_US_GHS SDS No.: BE5294

Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Not Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been preregistered or, where required under REACh, registered, and that we have the intention to proceed with their registration in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION Material safety datasheet sections which have been updated: Revised Section(s): 1 15 16 December 14 2017 **HMIS Classification** : Health Hazard: 0 Flammability: 1 1 0 Physical hazards: 0 **NFPA Classification** : Health Hazard: 0 Fire Hazard: 1 1 Instability: 0 0 0 **Further information** HMIS rating scale (0 = minimal hazard; 4 = severe hazard) NFPA rating scale (0 = minimal hazard; 4 = severe hazard) 12 / 14

Ponciplastics.com

SAFETY DATA SHEET

lyondellbase

Version 1.1

Hostacom DKG728P ZSP DEEP GRY Revision Date 12/19/2017

Print Date 12/23/2019

Gen. Variant: SDS US GHS SDS No.: BE5294

Disclaimer

This document is generated for the purpose of distributing health, safety, and environmental data.

Information is correct to the best of our knowledge at the date of the SDS publication.

It is not a specification sheet nor should any displayed data be construed as a specification. Before using a product sold by a company of the LyondellBasell family of companies, users should make their own independent determination that the product is suitable for the intended use and can be used safely and legally.

SELLER MAKES NO WARRANTY; EXPRESS OR IMPLIED (INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY WARRANTY) OTHER THAN AS SEPARATELY AGREED TO BY THE PARTIES IN A CONTRACT.

Users should review the applicable Safety Data Sheet before handling the product. This product(s) may not be used in the manufacture of any of the following, without prior written approval by Seller for each specific product and application:

(i) U.S. FDA Class I or II Medical Devices; Health Canada Class I, II or III Medical Devices; European Union Class I or II Medical Devices;

(ii) film, overwrap and/or product packaging that is considered a part or component of one of the aforementioned medical devices:

(iii) packaging in direct contact with a pharmaceutical active ingredient and/or dosage form that is intended for inhalation, injection, intravenous, nasal, ophthalmic (eye), digestive, or topical (skin) administration;

(iv) tobacco related products and applications, electronic cigarettes and similar devices. (v) safety components in automotive applications, for example: air bags, air bag unit housings and covers, seat belt mechanisms, brake systems, pedals and pedal supports, steering systems.

The product(s) may not be used in:

(i) U.S. FDA Class III Medical Devices; Health Canada Class IV Medical Devices; European Class III Medical Devices;

(ii) applications involving permanent implantation into the body;

(iii) life-sustaining medical applications.

All references to U.S. FDA, Health Canada, and European Union regulations include another country's equivalent regulatory classification.

In addition to the above, LyondellBasell may further prohibit or restrict the use of its products in certain applications. For further information, please contact a LyondellBasell representative.

Adflex, Adstif, Adsyl, Akoafloor, Akoalit, Alastian, Alathon, Aquathene, Avant, Catalloy, Clyrell, Dexflex, Flexathene, Hifax, Hipolyene, Histif, Hostacom, Hostalen, Indure, Integrate, Koattro, Lucalen, Luflexen, Lupolen, Metocene, Microthene, Moplen, Nexprene, Petrothene, Plexar, Pristene, Pro-Fax, Purell, Sequel, SJS, Softell, Starflex, Ultrathene, and Valtec are trademarks owned or used by the LyondellBasell family of companies.

Adsyl, Akoafloor, Akoalit, Alastian, Alathon, Avant, Dexflex, Flexathene, Hifax, Hostacom, Hostalen, Integrate, Koattro, Lucalen, Lupolen, Microthene, Moplen, Nexprene, Petrothene, Plexar, Pristene, Pro-Fax, Purell, Sequel, Softell, Starflex, and Ultrathene are registered in the U.S. Patent and Trademark Office.

Product Information

(+) 18816996168 Ponciplastics.com

SAFETY DATA SHEET

Iyondellbase

Gen. Variant: SDS US GHS

Hostacom DKG728P ZSP DEEP GRY Revision Date 12/19/2017

Version 1.1

Print Date 12/23/2019

SDS No.: BE5294

Product Information

HMIS rating scale (0 = minimal hazard; 4 = severe hazard) NFPA rating scale (0 = minimal hazard; 4 = severe hazard)

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet