	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	lyondellbase
Hostacom EKC 330N Y /ersion 1.2 Revision Date	
	10/02/2019 Find Date 01/00/2022 3DS No.: BES
IDENTIFICATION OF THE SUB	STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name	: Hostacom EKC 330N Y20 PEARLGRAU
CAS Number: Chemical name	: Mixture : Compounded polyolefin
Synonyms	: Polyolefin, Compounded polymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical
	devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body;
	Life-sustaining medical applications
Company Address	Company Talanhana
<u>Company Address</u> Equistar Chemicals, LP	Company Telephone Customer Service 888 777-0232
LyondellBasell Tower, Suite 3	
1221 McKinney St.	
P.O. Box 2583	
Houston Texas 77252-2583	
Emergency telephone numb EQUISTAR 800-245-4532	<u>per</u>
E-mail address	: product.safety@lyb.com
Responsible/issuing person	
HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing,
	handling or by other means, may form combustible dust concentrations in air.
Other hazards	
	1 / 14

	(+) 18816996168		
AFETY DATA SHEET	Ponciplastics.com	lyondellbase	
		Iyunuenbast	
ostacom EKC 330N Y2		Gen. Variant: SDS_US_G	
rsion 1.2 Revision Date	10/02/2019 Print Date 0	1/06/2022 SDS No.: BES	
No additional information ava	ailable.		
COMPOSITION/INFORMATION (JN INGREDIENTS		
Components			
Chemical name	CAS-No.	Weight %	
Proprietary blend of polyolefinic	Mixture	50.0 - 80.0 %	
polymers			
Contains: Additives, stabilizers	and fillers		
IRST AID MEASURES			
General advice	: Take proper precautions before attempting rescue	to ensure your own health and saf	
	belore attempting recould		
If inhaled	: Remove person to fresh	air. If signs/symptoms continue, ge	
	medical attention.	alation of fumes that may be genera	
	during heating of this ma	terial, move the person to fresh air	
	Obtain medical attention. Keep person warm, if ne	cessary give Cardio-Pulmonary	
	Resuscitation (CPR)		
In case of skin contact	: If molten material contac	ts the skin, immediately flush with	
	large amounts of water to	o cool the affected tissue and polyr	
	skin.	olymer from skin as this will remove	
	Obtain immediate emerge or extensive.	ency medical attention if burn is de	
In case of eye contact	: Flush eyes thoroughly with water for several minutes and se		
	medical attention if disco		
	: In case of eye contact wi Continuously flush eye(s	th molten polymer:) with cool running water for at leas	
	minutes.		
	adherent to the eye(s).	T attempt to remove the material	
	Immediately seek medica	al attention.	
If swallowed	: Adverse health effects de	ue to ingestion are not anticipated.	
	2 / 14		

	Ponciplastics.com			
SAFETY DATA SHEET	lyondellbas			
Hostacom EKC 330N Y20 PEARLGRAU Gen. Variant: SDS_US_GH				
Version 1.2 Revision Date	10/02/2019 Print Date 01/06/2022 SDS No.: BE			
Notes to physician				
Symptoms	: Inhalation of process fumes and vapors may cause sorene the nose and throat and coughing.			
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.			
Treatment	: Treatment of overexposure should be directed at the contr symptoms and the clinical condition of the patient.			
FIRE-FIGHTING MEASURES Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.			
	: LARGE FIRES: Use water spray hose nozzles from a safe location.			
Unsuitable extinguishing	: None known.			
media				
media Specific hazards during fire fighting	: Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as:			
Specific hazards during fire	In case of fire hazardous decomposition products may be			
Specific hazards during fire	In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocark			
Specific hazards during fire fighting Special protective equipment	 In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocart (smoke). Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Combustible particulate solid, will decompose under fire conditions. 			
Specific hazards during fire fighting Special protective equipment for fire-fighters	 In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocart (smoke). Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat flammable vapors. 			
Specific hazards during fire fighting Special protective equipment for fire-fighters	 In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocark (smoke). Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat flammable vapors. Move containers from fire area if it can be done without ris Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container 			
Specific hazards during fire fighting Special protective equipment for fire-fighters	 In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocark (smoke). Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat flammable vapors. Move containers from fire area if it can be done without ris Evacuate immediately in the event of opening of storage 			
Specific hazards during fire fighting Special protective equipment for fire-fighters	 In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocart (smoke). Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor noz Heat from fire may melt, decompose polymer, and generat flammable vapors. Move containers from fire area if it can be done without ris Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of contain Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved fire. 			

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	Iyunuendas
Hostacom EKC 330N Y	
Version 1.2 Revision Date	10/02/2019 Print Date 01/06/2022 SDS No.: BE
. ACCIDENTAL RELEASE MEAS	URES
Personal precautions	: Equip responders with proper protection.
	Creates dangerous slipping hazard on any hard smooth surface.
	Equip emergency responders with proper personal protect equipment (PPE)
	Avoid generating dust.
	Avoid dispersal of dust in the air (i.e., clearing dust surface with compressed air).
	Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth
	surfaces.
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment /	: On land, sweep/shovel into suitable disposal containers or
Methods for cleaning up	vacuum using equipment which avoids ignition risk.
	On water, material is insoluble; collect and contain as any solid.
	All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance v
	applicable laws and regulations and in conformance with ge engineering practices. Reclaim where possible.
7. Handling and storage	
Precautions for safe handlin	g
Advice on safe handling	: Material is in a pellet form. If converted to small particles during further processing,
	handling, or by other means, may form combustible dust
	concentrations in air. Avoid dust accumulation in enclosed space.
	Use dust collection systems designed per NFPA 654 to avo dust accumulation.
	Avoid generating dust; fine dust suspended in air and in the
	presence of an ignition source is a potential dust explosion hazard.
	Static discharge (spark), or other ignition sources, in high c
	environments may ignite the dust and result in a dust explosion
	Electrostatic charge may build during conveying or handling Equipment handling polymer should be conductive and
	4 / 14

			10000100			
SAFETY DATA SH	HEET	Poncip1:	astics.com	lvood	ellbasel	
				I yond		
Hostacom EKC					SDS_US_GHS	
Version 1.2 Rev	ision Date 10)/02/2019	Print Date 0	1/06/2022	SDS No.: BE530	
			(earthed) and b			
	Metal containers involved in the transfer of this material should be grounded and bonded.					
		codes and	All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts.			
		After hand water.	ling, always wa	ash hands thoroughly		
			op may conder	al to processing tem use in the exhaust ve		
		Refer to N	FPA 654, Stan	dard for the Preventic Manufacturing, Proc		
				Particulate Solids, fo		
Fire-fighting class	:	Polymer w	ill burn but doe	s not easily ignite.		
Conditions for safe	e storage, in	cluding any	, incompatibili	ties		
Requirements for st areas and container			dry location.	practices during stor	age transferring	
areas and containers Use good housekeeping practices during storage, trans and handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic of			ate ventilation nulation. m strong on.			
Specific end use(s		See Section	on 1.			
8. EXPOSURE CONTRO	DLS/PERSON	IAL PROTE	CTION			
Control parameters						
Ingredients with w	orkplace co	ntrol param	eters			
Occupational Expo	osure Limits					
Components	CAS-No.	Туре	Limit Value	Basis	Additional	
Materials that can		TWA	10 mg/m3	Revision Date US (ACGIH)	Information	
be formed when handling this product: Non-			inhalable	2005		
specified (inert or nuisance) dust						
		5	/ 14			

Ponciplastics.com

SAFETY DATA SHEET

lyondellbasell

Hostacom EKC 330N Y20 PEARLGRAU

Version 1.2 F

Revision Date 10/02/2019 Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE5305

Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TW/	A 3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TW	A 15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	A 5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 14

	Ponciplastics.com			
SAFETY DATA SHEET	lyondellbasel			
Hostacom EKC 330N Y				
Version 1.2 Revision Date				
	injury or other irritation to eyes due to airborne particles which may result from handling this product.			
Skin and body protection	: Wear suitable protective clothing.			
Hygiene measures	 Wear suitable protective clothing. Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse. 			
PHYSICAL AND CHEMICAL PI	ROPERTIES			
Appearance	: Pellets.			
Color	: Grey.			
Color	: Grey.			
Color Odor	: Grey. : Slight.			
Color Odor Odor Threshold	: Grey.: Slight.: No value available.			
Color Odor Odor Threshold Flash point	 Grey. Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dust 			
Color Odor Odor Threshold Flash point Lower explosion limit	 Grey. Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution. 			
Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit	 Grey. Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution. Not applicable. 			
Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas)	 Grey. Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. 			
Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties	 Grey. Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. 			
Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature	 Grey. Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C 			
Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature	 Grey. Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 			
Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range	 Grey. Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C 			
Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range Boiling point/boiling range	 Grey. Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C Not applicable. 			

(+)	18	81	69	961	68

AFETY DATA SHEET	Ponciplastics.com			
ostacom EKC 330N				
ersion 1.2 Revision Date	e 10/02/2019 Print Date 01/06/2022 SDS No.: BE			
Partition coefficient: n- octanol/water	: No Data Available.			
Viscosity, dynamic	: Not applicable.			
Relative vapor density	: Not applicable.			
Evaporation rate	: Not applicable.			
Explosive properties	: No Data Available.			
Other Information	: No additional information available.			
STABILITY AND REACTIVITY	(
Reactivity	: No known reactivity hazards.			
Chemical stability	: Stable under normal conditions.			
Hazardous reactions	: Will not occur.			
Conditions to avoid				
	: Avoid contact with strong oxidizers, excessive heat, sparks o open flame.			
Materials to avoid	: Material may be softened by some hydrocarbons.			
Hazardous decomposition	: Not expected to decompose under normal conditions.			
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.			
TOXICOLOGICAL INFORMAT	TION			
Acute toxicity				
Acute oral toxicity	: Not classified			
Acute inhalation toxicity	: Not classified			
Acute dermal toxicity	: Not classified			
Skin corrosion/irritation	: Not a skin irritant.			
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.			
	8 / 14			

		816996168	
SAFETY DATA SHEET	Poncip	lastics.com	lyondellbasell
Hostacom EKC 330N Y Version 1.2 Revision Date		LGRAU Print Date 01/06/	Gen. Variant: SDS_US_GHS 2022 SDS No.: BE5305
Respiratory or skin sensitization	: Not class	sified	
Chronic toxicity			
Component Name	NTP	IARC	OSHA
Titanium Dioxide		2B	Present
Carcinogenicity	: Not class	sified	
	Not class		hy IAPC on possibly
	carcinoge	component(s) listed enic to humans.	
	limited re	lease under normal c	in a thermoplastic resin with conditions of use, transportation,
	and stora	age.	
Germ cell mutagenicity	: Not class	sified	
Reproductive toxicity			
Effects on fertility / Effects on or via lactation	: Not class	sified	
Effects on Development	: Not class	sified	
Target Organ Systemic Toxicant - Single exposure		stance or mixture is no kicant, single exposur	ot classified as specific target e.
Target Organ Systemic	C		ot classified as specific target
Toxicant - Repeated exposure		kicant, repeated expo	
Aspiration hazard	: Not appli	cable.	
12. Ecological information			
Ecotoxicology Assessment			
Short-term (acute) aquatic	: Not class	sified	
hazard Long-term (chronic)	: Not class	sified	
aquatic hazard		9 / 14	
		5/14	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SALETT DATA SHEET	lyondellbasell
Hostacom EKC 330N Y2	OPEARLGRAU Gen. Variant: SDS_US_GHS
Version 1.2 Revision Date 10	0/02/2019 Print Date 01/06/2022 SDS No.: BE5305
Persistence and degradability	
Biodegradability	Not expected to be biodegradable.
Bioaccumulative potential	
Bioaccumulation	This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	no data available
Other adverse effects	
Environmental fate and pathways	This material is not volatile and insoluble in water.
Other information	
Additional ecological information	Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations	
Waste treatment methods	
	All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
	10 / 14

(+)	1881	69961	68
(.)	1001	05501	00

Ponciplastics.com

SAFETY DATA SHEET

Iyondellbase

Hostacom EKC 330N Y20 PEARLGRAU Version 1.2 Revision Date 10/02/2019

Gen. Variant: SDS US GHS SDS No.: BE5305

Print Date 01/06/2022

Not regulated for transport

15. REGULATORY INFORMATION

TSCA 12b

The following substance(s) is/are subject to TSCA 12(b) export notification requirements:

Component	CASRN	Section		
Octamethylcyclotetrasiloxane	556-67-2			
Octamethylcyclotetrasiloxane	556-67-2	Section 4		

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN	Type of Toxicity							
		Carcinogen	Developmental	Repro-Male	Repro- Female				
Hexachlorobenzene	118-74-1	Х	Х						
Lead	7439-92-1	Х	Х	Х	Х				
Cadmium	7440-43-9	Х	Х	Х					
Chromium	7440-47-3	Х							
Arsenic	7440-38-2	Х							
11 / 14									

Ponciplastics.com

SAFETY DA	TA SHEET
-----------	----------

lyondellbasell

Hostacom EKC 330N Y20 PEARLGRAUGeVersion 1.2Revision Date 10/02/2019Print Date 01/06/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE5305

					i		
Nickel	7440-02-0	X					
Mercury	7439-97-6		Х				
This product of	ntaina tha fallowing abor	niagla regulato		Worker and C	o roo roo unitu (
Right to Know	ontains the following cher	nicals regulate	ed by new Jerseys		ommunity		
14807-96-6	Talc, Magnesium Sil	icate					
13463-67-7	Titanium Dioxide						
This product co	ontains the following cher	nicals regulate	ed by Massachuse	tts' Right to Kno	w Law:		
14807-96-6	Talc, Magnesium Silicate						
13463-67-7	Titanium Dioxide						
This product co	ontains the following cher	nicals regulate	ed by Pennsylvania	's Right to Know	v Act:		
4 4007 00 0		4 -					
14807-96-6	Talc, Magnesium Sil	Icate					
13463-67-7	Titanium Dioxide						
557-05-1	Zinc Stearate						

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.


Country/Region	Inventory	Status Description				
Australia	AICS	Compliant				
Canada	DSL	Compliant				
China	IECSC	Compliant				
Europe	REACH	See REACH Compliance Statement				
Japan	ENCS	Compliant				
Korea	KECI	Compliant				
New Zealand	NZIoC	Compliant				
Philippines	PICCS	Compliant				
United States of America	TSCA	Compliant				
Taiwan	TCSCA	Compliant				

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

12 / 14



(+)	15	28	1	6	9	9	6	1	6	8
(1)	10	0	1	υ	J	J	υ	1	υ	0

Ponciplastics.com

SAFETY DATA SHEET

Iyondellbase

Version 1.2

Hostacom EKC 330N Y20 PEARLGRAU Revision Date 10/02/2019 Print Date 01/06/2022

Gen. Variant: SDS_US_GHS

SDS No.: BE5305

a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet