	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
SAFELY DATA SHEET	lyondellbasell
Hostacom X M2 T12 3	56036 Gen. Variant: SDS_US_GHS
	te 10/01/2019 Print Date 01/07/2022 SDS No.: BE7592
1. IDENTIFICATION OF THE SU	BSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name	: Hostacom X M2 T12 356036
CAS Number: Chemical name	: Mixture : Compounded polyolefin
Synonyms	: Polyolefin, Compounded polymer
Identified uses	<ul> <li>Manufacture of plastic articles by injection molding, extrusion or other conversion process.</li> </ul>
De-Likitad upon	
Prohibited uses	: FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications
Company Address	Company Telephone
Equistar Chemicals, LP	Customer Service 888 777-0232
LyondellBasell Tower, Suite 1221 McKinney St.	300 product.safety@lyb.com
P.O. Box 2583	
Houston Texas 77252-2583	,
Emergency telephone num EQUISTAR 800-245-4532	<u>ıber</u>
E-mail address Responsible/issuing person	: product.safety@lyb.com
2. HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.
Other hazards	
	1 / 14

	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics.com			
SAFETT DATA SHEET		lyondellbasell		
Hostacom X M2 T12 356	036	Gen. Variant: SDS_US_GHS		
Version 1.3 Revision Date 1		7/2022 SDS No.: BE7592		
No additional information ava	ilable.			
3. COMPOSITION/INFORMATION C	JN INGREDIEN IS			
Components				
Chemical name	CAS-No.	Weight %		
Proprietary blend of polyolefinic polymers	Mixture	50.0 - 80.0 %		
Contains: Additives, stabilizers	and fillers	·		
4. FIRST AID MEASURES				
General advice	: Take proper precautions to before attempting rescue ar	ensure your own health and safety nd providing first aid.		
If inhaled	medical attention. In case of excessive inhalat during heating of this mater Obtain medical attention.	If signs/symptoms continue, get ion of fumes that may be generated ial, move the person to fresh air. ssary give Cardio-Pulmonary		
In case of skin contact	<ul> <li>If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polyme Do not attempt to peel polymer from skin as this will remove the skin.</li> <li>Obtain immediate emergency medical attention if burn is deep or extensive.</li> </ul>			
In case of eye contact	: Flush eyes thoroughly with medical attention if discomf	water for several minutes and seek ort persists.		
	<ul> <li>In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at lear minutes.</li> <li>Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s).</li> <li>Immediately seek medical attention.</li> </ul>			
If swallowed	: Adverse health effects due	to ingestion are not anticipated.		
	2 / 14			

	Ponciplastics.com
SAFETY DATA SHEET	lyondellbase
Hostacom X M2 T12 35	
Version 1.3 Revision Date	10/01/2019 Print Date 01/07/2022 SDS No.: BE75
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.
5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	<ul> <li>Keep away from heat and sources of ignition.</li> <li>In case of fire hazardous decomposition products may be produced such as:</li> <li>Carbon monoxide, carbon dioxide and unburned hydrocarbon (smoke).</li> </ul>
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	<ul> <li>Combustible particulate solid, will decompose under fire conditions.</li> <li>Calorific Value: 8000 - 11000 kcal/kg</li> <li>Fight fire from safe distance with hose lines or monitor nozzle</li> </ul>
	Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk.
	Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire.
	Cool storage containers with large volumes of water even after
	fire is out.

	(+) 18816996168				
SAFETY DATA SHEET	Ponciplastics.com				
Hostacom X M2 T12 356 Version 1.3 Revision Date 1					
	0/01/2019 Fillit Date 01/01/2022 3D3 No.: DE 739				
6. ACCIDENTAL RELEASE MEASU	IRES				
Personal precautions	: Equip responders with proper protection.				
	Creates dangerous slipping hazard on any hard smooth surface.				
	Equip emergency responders with proper personal protective equipment (PPE)				
	Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces				
	with compressed air). Potential combustible dust hazard.				
	Polymer particles create slipping hazard on hard smooth				
	surfaces.				
Environmental precautions	: Do not flush into surface water or sanitary sewer system.				
Methods for containment /	On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk.				
Methods for cleaning up	On water, material is insoluble; collect and contain as any				
	solid. All recovered material should be packaged, labeled,				
	transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good				
	engineering practices. Reclaim where possible.				
7. Handling and storage					
Precautions for safe handling					
Advice on safe handling	: Material is in a pellet form. If converted to small particles during further processing,				
	handling, or by other means, may form combustible dust concentrations in air.				
	Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid				
	dust accumulation.				
	Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion				
	hazard. Static discharge (spark), or other ignition sources, in high dust				
	environments may ignite the dust and result in a dust explosion				
	Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and				
	4 / 14				

		(+)100	10990100			
SAFETY DATA SI	HEET	Poncip1:	astics.com	lyood		
			iyunut	lyondellbasell		
Hostacom X M2	T12356	036		Gen. Variant:	SDS_US_GHS	
Version 1.3 Rev	ision Date 10	)/01/2019	Print Date 07	1/07/2022	SDS No.: BE759	
Fire-fighting class <b>Conditions for saf</b> Requirements for so areas and contained	e <b>storage, in</b> torage :	Metal cont should be All electric codes and combustib After hand water. When brin may develous section 10 Refer to N Dust Explous Handling of Polymer w <b>cluding any</b> Store in a Use good and handli should be Store away oxidizing a	grounded and I al equipment sl regulatory requ le dusts. ling, always wa ging the materia op may conden FPA 654, Stand osions from the of Combustible rill burn but does r <b>incompatibili</b> dry location. housekeeping p ng. Process en used to avoid e y from excessiv agents.	in the transfer of this bonded. hould conform to app uirements for areas h sh hands thoroughly al to processing temp se in the exhaust ver dard for the Preventic Manufacturing, Proc Particulate Solids, for s not easily ignite. <b>ties</b> practices during stora closures and adequa excessive dust accum <i>v</i> e heat and away from	dicable electric handling with soap and beratures vapors ntilation. See on of Fire and ressing, and r safe handling. age, transferring the ventilation hulation. m strong	
Specific end use(s			sures to prevent	prevent contaminatic the build up of elec		
EXPOSURE CONTRO Control parameters Ingredients with w Occupational Expo	vorkplace co	ntrol param				
Components	CAS-No.	Туре	Limit Value	Basis	Additional	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	Revision Date US (ACGIH) 2005	Information	
			1 4 4			
		5	/ 14			

Ponciplastics.com

Gen. Variant: SDS US GHS

Hostacom X	M2T12356036
Version 1.3	Revision Date 10/01/2019

Print Date 01/07/2022

SDS No.: BE7592

Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	15 mg/m3 total dust	US (OSHA) 2005	
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	5 mg/m3 respirable	US (OSHA) 2005	

Consult local authorities for acceptable exposure limits.

#### Exposure controls

#### Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

### Personal protective equipment

Respiratory protection	<ul> <li>Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits.</li> <li>When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.</li> <li>Use appropriate respiratory protection where atmosphere exceeds recommended limits.</li> <li>Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators.</li> </ul>
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.
Eye and face protection	: Dust service goggles should be worn to prevent mechanical
	6 / 14

	(+) 18816996168			
SAFETY DATA SHEET	Ponciplastics.com			
	III_III			
Hostacom X M2 T12 3 Version 1.3 Revision Date				
	injury or other irritation to eyes due to airborne particles which may result from handling this product.			
Skin and body protection	: Wear suitable protective clothing.			
Hygiene measures	<ul> <li>Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use.</li> <li>Use good personal hygiene practices.</li> <li>Wash hands before eating, drinking, smoking, or using toilet facilities.</li> <li>Take off contaminated clothing and wash before reuse.</li> </ul>			
. PHYSICAL AND CHEMICAL P				
Appearance Color	: Pellets. : gray			
Odor	: Slight.			
Odor Threshold	: No value available.			
Flash point	: No Data Available.			
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dus varies according to particle size distribution.			
Upper explosion limit	: Not applicable.			
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.			
Oxidizing properties	: Not considered an oxidizing agent.			
	. Not considered an oxidizing agent.			
Autoignition temperature	: > 300 °C			
Autoignition temperature Decomposition temperature				
	: > 300 °C			
Decomposition temperature	: > 300 °C : not determined			
Decomposition temperature Melting point/range	<ul> <li>: &gt; 300 °C</li> <li>: not determined</li> <li>: 50 - 170 °C</li> </ul>			
Decomposition temperature Melting point/range Boiling point/boiling range	<ul> <li>&gt; 300 °C</li> <li>: not determined</li> <li>: 50 - 170 °C</li> <li>: Not applicable.</li> </ul>			

	Ponciplastics.com				
SAFETY DATA SHEET	lyondellbase				
lostacom X M2 T12 3	56036 Gen. Variant: SDS_US_GF				
ersion 1.3 Revision Date					
Partition coefficient: n- octanol/water	: No Data Available.				
Viscosity, dynamic	: Not applicable.				
Relative vapor density	: Not applicable.				
Evaporation rate	: Not applicable.				
Explosive properties	: No Data Available.				
Other Information	: No additional information available.				
. STABILITY AND REACTIVITY	,				
Reactivity	: No known reactivity hazards.				
Chemical stability	: Stable under normal conditions.				
Hazardous reactions	: Will not occur.				
Conditions to avoid	: Avoid contact with strong oxidizers, excessive heat, sparks or open flame.				
Materials to avoid	: Material may be softened by some hydrocarbons.				
Hazardous decomposition	: Not expected to decompose under normal conditions.				
products Thermal decomposition	: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.				
. TOXICOLOGICAL INFORMAT	ΓΙΟΝ				
Acute toxicity					
Acute oral toxicity	: Not classified				
Acute inhalation toxicity	: Not classified				
Acute dermal toxicity	: Not classified				
Skin corrosion/irritation	: Not a skin irritant.				
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possible.				
	8 / 14				

			(+) 1881	6996168			
SAFE	SAFETY DATA SHEET			Ponciplastics.com		lyondellbasell	
				<b></b>	1 111	11	
Host Version	acom X M2 T1 n 1.3 Revision			Print Date 0 <sup>7</sup>		en. Variant: SDS SDS N	S_US_GHS lo.: BE7592
		Dato 10		T IIII Date o			
	spiratory or skin nsitization	:	Not classifie	ed			
Ch	ronic toxicity						
	Component Name		NTP	IARC		OSHA	]
	Titanium Dioxide Silica, Crystalline -	known	as a human	2B		Present	-
	Quartz		cinogen	1		Present	_
	Carbon Black			2B		Present	
Ca	rcinogenicity	:	Not classifie	ed			
				mponent(s) lis	sted by IAI	RC as possibly	
			This materia	al is encapsula		nermoplastic res ions of use, trans	
			and storage				sponation,
	u						
Ge	rm cell mutagenicity	:	Not classifie	ð			
_							
	productive toxicity		Not classifie	od.			
	ects on fertility / ects on or via lactation			eu			
Effe	Effects on Development : Not classified						
Та	Townet Owner Systemic					c target	
Target Organ Systemic: The substance or mixture is not classified as specific targToxicant - Single exposureorgan toxicant, single exposure.					o talgot		
Target Organ Systemic: The substance or mixture is not classified as specific targeToxicant - Repeatedorgan toxicant, repeated exposure.					c target		
	posure		organ toxica	ant, repeated t	exposule.		
•				-1-			
AS	piration hazard		Not applicat	Jie.			
12. Eco	logical information						
Ecoto	oxicology Assessmer	t					
	ort-term (acute) aqua zard	atic :	Not classifie	ed			
			9 /	′ 14			
L							

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Hostacom X M2 T12 3	
Version 1.3 Revision Date	e 10/01/2019 Print Date 01/07/2022 SDS No.: BE759
Long-term (chronic) aquatic hazard	: Not classified
Persistence and degradability	,
Biodegradability	: Not expected to be biodegradable.
Bioaccumulative potential	
Bioaccumulation	: This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	: no data available
Other adverse effects	
Environmental fate and pathways	: This material is not volatile and insoluble in water.
Other information	
Additional ecological information	<ul> <li>Ecotoxicity is expected to be minimal based on the low water solubility of polymers.</li> <li>No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.</li> </ul>
13. Disposal considerations	
Waste treatment methods	
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	: This material is classified as a Non-hazardous Material by RCRA.
	10 / 14

(+)	1881	6996	5168
(.)	1001	0000	00100

Ponciplastics.com

# SAFETY DATA SHEET

# Hostacom X M2 T12 356036

Version 1.3

Revision Date 10/01/2019

Print Date 01/07/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE7592

Iyondellbase

# **14. TRANSPORT INFORMATION**

Not regulated for transport

# 15. REGULATORY INFORMATION

#### TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

#### Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

#### SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

#### SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

# Combustible dust

#### **SARA 313**

This product contains no known chemicals regulated under SARA 313.

#### State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN	Type of Toxicity			
		Carcinogen	Developmental	Repro-Male	Repro- Female
Lead	7439-92-1	Х	Х	Х	Х
Arsenic	7440-38-2	Х			
Chromium	7440-47-3	Х			
Nickel	7440-02-0	Х			
Cadmium	7440-43-9	Х	Х	Х	
Mercury	7439-97-6		Х		
11 / 14					

(+)	18	81	69	9	61	68
-----	----	----	----	---	----	----

Ponciplastics.com

# SAFETY DATA SHEET

# Hostacom X M2 T12 356036

Version 1.3 Revision Date 10/01/2019 Print Date 01/07/2022

Gen. Variant: SDS US GHS

....

lyondellbase

SDS No.: BE7592

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

14807-96-6	Talc, Magnesium Silicate
------------	--------------------------

13463-67-7 Т	Titanium	Dioxide
--------------	----------	---------

14808-60-7 Silica, Crystalline - Quartz

1333-86-4 Carbon Black

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

14807-96-6	Talc, Magnesium Silicate
13463-67-7	Titanium Dioxide
14808-60-7	Silica, Crystalline - Quartz

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

14807-96-6	Talc, Magnesium Silicate
13463-67-7	Titanium Dioxide
1333-86-4	Carbon Black
1344-28-1	Aluminum oxide

### Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

### REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

SAFETY DATA SHEET	Poncip1a		
		stics.com	lyondellbasell
			I I III II
Hostacom X M2 T12 3 Version 1.3 Revision Date		Print Date 0	Gen. Variant: SDS_US_GHS 1/07/2022 SDS No.: BE7592
	10/01/2010		
Contact product.safety@lyb.com fe	or additional glol	oal inventory ir	nformation.
16. OTHER INFORMATION			
Material safety datasheet se	ections which l	nave been upo	dated:
Revised Section(s): 15 16			
HMIS Classification	: Health Hazar		
	Flammability Physical haz		
NFPA Classification	: Health Haza	-d- 0	
	Fire Hazard:		
	Instability: 0		
Further information			·
HMIS rating scale (0 = minima	al hazard <sup>.</sup> 4 = se	evere hazard)	
NFPA rating scale (0 = minim			
Information in this document		sclaimer	knowledge at the date of publication
The document is designed to	o provide users	general inform	knowledge at the date of publication. ation for safe handling, use, and does not constitute any warranty
or quality specification, eithe	er express or imp	lied, including	any warranty of merchantability or hether the product is suitable for
their use and can be used s			
In addition to any prohibition further prohibit or restrict the			his document, LyondellBasell may
	a LyondellBasell	representative	or visit the LyondellBasell website
			vned or used by the LyondellBasell
	13	/ 14	

 $(+)\,18816996168$ 

# SAFETY DATA SHEET

Ponciplastics.com

# Hostacom X M2 T12 356036

Version 1.3

Revision Date 10/01/2019

Print Date 01/07/2022

Gen. Variant: SDS\_US\_GHS 22 SDS No.: BE7592

lyondellbase

### Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

# Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

# End of Material Safety Data Sheet