yondellbasell | III | Gen. Variant: SDS AU

# Moplen HP400L

Version 1.4 Revision Date 2019-09-27 Print Date 2022-01-05 SDS No.: BE8578

## 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade name : Moplen HP400L CAS Number: : 9003-07-0

Chemical characterization : Polypropylene Homopolymer

Chemical name : Polypropylene

Synonyms : 1-Propene, homopolymer, PP

Identified uses : Manufacture of plastic articles by injection molding, extrusion

or other conversion process.

Prohibited uses : FDA Class III medical devices; European class III medical

devices; Health Canada class IV Medical Devices;

Applications involving permanent implantation into the body;

Life-sustaining medical applications

**Company Address** 

LyondellBasell Australia Pty. Ltd. Level 4, 650 Chapel Street South Yarra Vic 3141

Australia

Company Telephone

+61 (3) 9829 9455 product.safety@lyb.com

#### **Emergency telephone number**

1800 816 854 (AUSTRALIA ONLY)

E-mail address : product.safety@lyb.com

Responsible/issuing person

# 2. HAZARDS IDENTIFICATION

#### **GHS-Classification**

Not classified as hazardous according to criteria of Worksafe Australia.

# **GHS-Labeling**

Not classified as hazardous according to criteria of Worksafe Australia.

#### Other hazards

If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air.

yondellbasell Gen. Variant: SDS AU

# Moplen HP400L

Version 1.4 Revision Date 2019-09-27 Print Date 2022-01-05 SDS No.: BE8578

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Substances

#### Components

Chemical name	CAS-No. EC-No.	Weight %	Component Type
Polypropylene	9003-07-0	> 99.5 %	

Contains: Stabilizers

#### 4. FIRST AID MEASURES

General advice : Take proper precautions to ensure your own health and safety

before attempting rescue and providing first aid.

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air.

Obtain medical attention.

Keep person warm, if necessary give Cardio-Pulmonary

Resuscitation (CPR)

In case of skin contact : If molten material contacts the skin, immediately flush with

large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the

skin.

Obtain immediate emergency medical attention if burn is deep

or extensive.

In case of eye contact : Flush eyes thoroughly with water for several minutes and seek

medical attention if discomfort persists.

: In case of eye contact with molten polymer:

Continuously flush eye(s) with cool running water for at least 15

minutes.

Beyond flushing, DO NOT attempt to remove the material

adherent to the eye(s).

Immediately seek medical attention.

If swallowed : Adverse health effects due to ingestion are not anticipated.

Notes to physician

# SAFETY DATA SHEET

lyondellbasell

Moplen HP400L

Revision Date 2019-09-27

Print Date 2022-01-05

Gen. Variant: SDS\_AU
-05 SDS No.: BE8578

**Symptoms** 

Version 1.4

: Inhalation of process fumes and vapors may cause soreness in

the nose and throat and coughing.

Hazards : Dust contact with the eyes can lead to mechanical irritation.

Molten polymer may cause thermal burns.

Treatment : Treatment of overexposure should be directed at the control of

symptoms and the clinical condition of the patient.

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media :

: SMALL FIRE:

Use dry chemical, CO2, or water spray.

: LARGE FIRES:

Use water spray hose nozzles from a safe location.

Unsuitable extinguishing

media

. .

Specific hazards during fire

fighting

: None known.

: Keep away from heat and sources of ignition.

In case of fire hazardous decomposition products may be

produced such as:

Carbon monoxide, carbon dioxide and unburned hydrocarbons

(smoke).

: The formation of hydrocarbons and aldehydes are possible in the initial stages of a fire (especially in between 400 C and 700

nic initial stages of a life (especially in between 400 o and

C)

Special protective equipment

for fire-fighters

: Wear approved positive pressure self-contained breathing

apparatus and firefighter protective clothing.

Further information : Combustible particulate solid, will decompose under fire

conditions.

Calorific Value: 8000 - 11000 kcal/kg

Fight fire from safe distance with hose lines or monitor nozzles. Heat from fire may melt, decompose polymer, and generate

flammable vapors.

Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container.

Always stay away from tanks engulfed in fire.

Do not attempt to get on top of storage containers involved in

fire.

Cool storage containers with large volumes of water even after

fire is out.

## SAFETY DATA SHEET

yondellbasell Gen. Variant: SDS AU

# Moplen HP400L

Version 1.4 Revision Date 2019-09-27 Print Date 2022-01-05 SDS No.: BE8578

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Equip responders with proper protection.

Creates dangerous slipping hazard on any hard smooth

surface.

Equip emergency responders with proper personal protective

equipment (PPE)
Avoid generating dust.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Potential combustible dust hazard.

Polymer particles create slipping hazard on hard smooth

surfaces.

Environmental precautions : Do not flush into surface water or sanitary sewer system.

Methods for containment / Methods for cleaning up

: On land, sweep/shovel into suitable disposal containers or

vacuum using equipment which avoids ignition risk.

On water, material is insoluble; collect and contain as any

solid.

All recovered material should be packaged, labeled,

transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good

engineering practices. Reclaim where possible.

#### 7. Handling and storage

## Precautions for safe handling

Advice on safe handling : Material is in a pellet form.

If converted to small particles during further processing, handling, or by other means, may form combustible dust

concentrations in air.

Avoid dust accumulation in enclosed space.

Use dust collection systems designed per NFPA 654 to avoid

dust accumulation.

Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion

hazard.

Static discharge (spark), or other ignition sources, in high dust

environments may ignite the dust and result in a dust

explosion

Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and

grounded (earthed) and bonded.

lyondellbasell

Gen. Variant: SDS AU

Moplen HP400L

Version 1.4 Revision Date 2019-09-27

Print Date 2022-01-05

SDS No.: BE8578

Metal containers involved in the transfer of this material should be grounded and bonded.

All electrical equipment should conform to applicable electric codes and regulatory requirements for areas handling combustible dusts.

After handling, always wash hands thoroughly with soap and water

When bringing the material to processing temperatures vapors may develop may condense in the exhaust ventilation. See section 10.

Refer to NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids, for safe handling.

## Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store in a dry location.

Use good housekeeping practices during storage, transferring and handling. Process enclosures and adequate ventilation should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong

oxidizing agents.

Keep container closed to prevent contamination.

Take measures to prevent the build up of electrostatic charge.

Specific end use(s)

: See Section 1.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## Control parameters

## Ingredients with workplace control parameters

# **Occupational Exposure Limits**

Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	

lyono	del	lba	35	el	
1		Ш			

Moplen HP400L	Gen.	Variant:	SDS_AU
---------------	------	----------	--------

Version 1.4 Revision Date 2019-09-27 Print Date 2022-01-05 SDS No.: BE8578

Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust	TWA	3 mg/m3 respirable	US (ACGIH) 2005	
---	-----	-----------------------	--------------------	--

Consult local authorities for acceptable exposure limits.

## **Exposure controls**

#### **Engineering measures**

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is

no leakage from the equipment).

#### Personal protective equipment

Respiratory protection : Use process enclosures, local exhaust ventilation, or other

engineering controls to keep airborne levels below

recommended exposure limits.

When workers are facing concentrations above the exposure

limit they must use appropriate certified respirators.

Use appropriate respiratory protection where atmosphere

exceeds recommended limits.

Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified

respirators.

Hand protection : Wear gloves that provide thermal protection where there is a

potential for contact with heated material.

Eye and face protection : Dust service goggles should be worn to prevent mechanical

injury or other irritation to eyes due to airborne particles which

may result from handling this product.

Skin and body protection : Wear suitable protective clothing.

Hygiene measures : Selection of appropriate personal protective equipment should

be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered

during use.

# SAFETY DATA SHEET

yondellbasell Gen. Variant: SDS AU

Moplen HP400L

Version 1.4

Revision Date 2019-09-27

Print Date 2022-01-05

SDS No.: BE8578

Use good personal hygiene practices.

Wash hands before eating, drinking, smoking, or using toilet

facilities.

Take off contaminated clothing and wash before reuse.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Pellets.

Color : Translucent to white

Odor : Slight.

Odor Threshold : No value available.

Flash point : No Data Available.

Lower explosion limit : The minimum explosive concentration (MEC) for polymer dust

varies according to particle size distribution.

Upper explosion limit : Not applicable.

Flammability (solid, gas) : Polymer will burn but does not easily ignite.

Oxidizing properties : Not considered an oxidizing agent.

Autoignition temperature : > 300 °C

Decomposition temperature : not determined

Melting point/range : 50 - 170 °C

Boiling point/boiling range : Not applicable.

Vapor pressure : Not applicable.

Density : <1 g/cm3

Water solubility : Insoluble.

Partition coefficient: n-

octanol/water

: No Data Available.

Viscosity, dynamic : Not applicable.

Relative vapor density : Not applicable.

Evaporation rate : Not applicable.

Explosive properties : No Data Available.

# SAFETY DATA SHEET

lyondellbasell

Gen. Variant: SDS AU

Moplen HP400L

Version 1.4 Revision Date 2019-09-27

Print Date 2022-01-05

SDS No.: BE8578

Other Information : No additional information available.

10. STABILITY AND REACTIVITY

Reactivity : No known reactivity hazards.

Chemical stability : Stable under normal conditions.

Hazardous reactions : Will not occur.

Conditions to avoid : Avoid contact with strong oxidizers, excessive heat, sparks or

open flame.

Materials to avoid : Material may be softened by some hydrocarbons.

Hazardous decomposition

Thermal decomposition

products

: Not expected to decompose under normal conditions.

: Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols

may be formed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Acute oral toxicity : Not classified

Acute inhalation toxicity : Not classified

Acute dermal toxicity : Not classified

**Skin corrosion/irritation** : Not a skin irritant.

Serious eye damage/eye

irritation

: Not an eye irritant.

Mechanical irritation is possible.

Respiratory or skin

sensitization

: Not classified

Chronic toxicity

Carcinogenicity : Not classified

Not classified

# SAFETY DATA SHEET

lyondellbasell

Gen. Variant: SDS AU

Moplen HP400L

Version 1.4

Revision Date 2019-09-27

Print Date 2022-01-05

SDS No.: BE8578

Not listed by IARC, NTP, OSHA or EPA.

Germ cell mutagenicity : Not classified

Reproductive toxicity

Effects on fertility /

Effects on or via lactation

: Not classified

Effects on Development : Not classified

Target Organ Systemic Toxicant - Single exposure

: The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Target Organ Systemic Toxicant - Repeated

exposure

: The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

**Aspiration hazard** : Not applicable.

## 12. Ecological information

**Ecotoxicology Assessment** 

Short-term (acute) aquatic

hazard

Long-term (chronic)

aquatic hazard

: Not classified

: Not classified

Persistence and degradability

**Biodegradability** : Not expected to be biodegradable.

Bioaccumulative potential

**Bioaccumulation** : This material is not expected to bioaccumulate.

Mobility in soil

**Mobility** : no data available

Other adverse effects

# SAFETY DATA SHEET

Moplen HP400L

Revision Date 2019-09-27

Gen. Variant: SDS AU Print Date 2022-01-05

SDS No.: BE8578

**Environmental fate and** 

pathways

Version 1.4

: This material is not volatile and insoluble in water.

Other information

Additional ecological

information

: Ecotoxicity is expected to be minimal based on the low water

solubility of polymers.

No data available on this product. However, birds, fish and

other wildlife may eat pellets which may obstruct their

intestinal tracts.

## 13. Disposal considerations

#### Waste treatment methods

Product : All recovered material should be packaged, labeled,

> transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good

engineering practices. Reclaim where possible.

Recycle if possible.

#### 14. TRANSPORT INFORMATION

Not regulated for transport

## 15. REGULATORY INFORMATION

## Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant

#### SAFETY DATA SHEET

yondellbasell Gen. Variant: SDS AU

# Moplen HP400L

Version 1.4 Revision Date 2019-09-27 Print Date 2022-01-05 SDS No.: BE8578

Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

#### REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that the chemical substance in this product has been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

#### 16. OTHER INFORMATION

# Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

#### Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

#### Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

#### Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

# SAFETY DATA SHEET

lyondellbasell

Moplen HP400L Gen. Variant: SDS\_AU

Version 1.4 Revision Date 2019-09-27 Print Date 2022-01-05 SDS No.: BE8578

**End of Material Safety Data Sheet**