	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
ALLIT DATA SHELT	lyondellbase
Sequel 2392 SP NH16	Gen. Variant: SDS_US_GH
Version 1.2 Revision Da	ate 10/02/2019 Print Date 01/07/2022 SDS No.: BE6
IDENTIFICATION OF THE SU	JBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING
Trade name	: Sequel 2392 SP NH167L
CAS Number:	: Mixture
Chemical name	Compounded polyolefinPolyolefin, Compounded polymer
Synonyms	: Polyolelin, Compounded polymer
Identified uses	: Manufacture of plastic articles by injection molding, extrusion or other conversion process.
Prohibited uses	: FDA Class III medical devices; European class III medical
	devices; Health Canada class IV Medical Devices;
	Applications involving permanent implantation into the body;
	Life-sustaining medical applications
<u>Company Address</u>	Company Telephone
Equistar Chemicals, LP	Company Telephone Customer Service 888 777-0232
LyondellBasell Tower, Suite	
1221 McKinney St.	
P.O. Box 2583	
Houston Texas 77252-258	13
Emergency telephone nu EQUISTAR 800-245-4532	mber
EQUISTAR 000-245-4552	
E-mail address	: product.safety@lyb.com
Responsible/issuing person	
HAZARDS IDENTIFICATION	
GHS Classification	
Combustible dust	
Label elements	
Signal word	: Warning
Hazard Statements	: If small particles are generated during further processing,
	handling or by other means, may form combustible dust
	concentrations in air.
Other hazards	
	1 / 14
	1 / 14

SAFETY DATA SHEET Seque 2392 SP NH167L Ser. Variant: SDS_US_GHS Seque 2392 SP NH167L Ser. Variant: SDS_US_GHS Version 1.2 Revision Date 10/02/2019 Pint Date 01/07/2022 SDS No: BEGES A additional information available. SCOMPOSITIONINFORMATION ON INGREDIENTS Marrian Signal Strands Son Son Strands SOS No: BEGES Marrian Signal Strands Son Son Strands Son Son Strands Scomponents Son Son Strands Son Son Strands Arrian Strands Son Son Strands Son Son Strands Son Son Strands Son Son Strands Son Son Strands Contains: Additives, stabilizers and fillers Son		(+) 18816996168	
Sequel 2392 SP NH167L Gen. Variani: SDS. U.S. Gelds Version 1.2 Revision Date 10/02/201 Print Date 01/07/202 SDS No: BE666 No additional information available. SCOMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components Components Chemical name CAS-No. Weight 26 Contains: Additives, stabilizers and fillers 80.0 - 100.0 % State proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. In case of skin contact : In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : Flush eyes horoughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : Flush eyes horoughly with m	SAFETY DATA SHEET	Ponciplastics.com	
Version 1.2 Revision Date 10/02/2019 Print Date 01/07/2022 SDS No.: BE6155 No additional information available. Image: Composition and the composition of the composition of the composition of polyolefinic in the composition of polyoners in the composition of polyoners in the composition of the composition of the composition of the composition of polyoners in the composition of the compositio	SAFETT DATA SHEET		lyondelibaseli
Version 1.2 Revision Date 10/02/2019 Print Date 01/07/2022 SDS No.: BE6158 No additional information available. 3. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components Contains: Additional of polyolefinic Mixture 90.0 - 100.0 % Contains: Additives, stabilizers and fillers 90.0 - 100.0 % Contains: A. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomtort persists. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attentin if discomtort persists.<	Sequel 2392 SP NH167L	_	Gen. Variant: SDS_US_GHS
3. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components Chemical name CAS-No. Veight % Poprietary blend of polyolefinic Mixture Ontains: Additives, stabilizers and fillers A. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. :: In case of eye contact :: In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipate			7/2022 SDS No.: BE6158
3. COMPOSITION/INFORMATION ON INGREDIENTS Mixtures Components Chemical name CAS-No. Veight % 90.0 - 100.0 % Contains: Additives, stabilizers and fillers Contains: Additives, stabilizers and fillers A. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention. If discomfort persists. : In case of eye contact : Elush eyes (s) with cool running water for at least 16 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s), itmediately seek medical attention. If iswallowed : Adverse health effects due to ingestion are not anticipated.			
Mixtures Components Chemical name CAS-No. Weight % Proprietary blend of polyolefinic Mixture 90.0 - 100.0 % 90.0 - 100.0 % Contains: Additives, stabilizers and fillers A FIRST AID MEASURES General advice Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : Flush eyes (s) with cool running water for at least 1% minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	No additional information ava	ailable.	
Wittures Sumption of polyolefinic Proprietary blend of polyolefinic Mixture 90.0 - 100.0 % polymers 00.0 - 100.0 % 90.0 - 100.0 % Contains: Additives, stabilizers and fillers Stringstrain General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large anounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : Flush eyes horoughly with cool running water for at least 1% minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. if swallowed : Adverse health effects due to ingestion are not anticipated.			
Chemical name CAS-No. Weight % Proprietary blend of polyolefinic Mixture 90.0 - 100.0 % Contains: Additives, stabilizers and fillers A. FIRST AID MEASURES General advice Final		UN INGREDIENTS	
Proprietary blend of polyolefinic Mixture 90.0 - 100.0 % Proprietary blend of polyolefinic Mixture 90.0 - 100.0 % Contains: Additives, stabilizers and fillers A. FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, mow the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	Components		
polymers Contains: Additives, stabilizers and fillers Contains: Additives, stabilizers and fillers A.FIRST AID MEASURES General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 13 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	Chemical name	CAS-No.	<u>Weight %</u>
Image: Second State Sta		Mixture	90.0 - 100.0 %
General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 19 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	Contains: Additives, stabilizers	and fillers	
General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 19 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.			
General advice : Take proper precautions to ensure your own health and safety before attempting rescue and providing first aid. If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 19 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.			
If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with cool running water for at least 19 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.		· Taka propar, procoutions to	oncure your own boalth and cafety
medical attention. In case of excessive inhalation of fumes that may be generated during heating of this material, move the person to fresh air. Obtain medical attention. Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove th skin. Obtain mimediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 11 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	General advice		
Iarge amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove th skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 1: minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	lf inhaled	medical attention. In case of excessive inhalati during heating of this materi Obtain medical attention. Keep person warm, if neces	ion of fumes that may be generated al, move the person to fresh air.
medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	In case of skin contact	large amounts of water to co Do not attempt to peel polyr skin. Obtain immediate emergeno	bol the affected tissue and polymer ner from skin as this will remove th
Continuously flush eye(s) with cool running water for at least 1 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated.	In case of eye contact		
		Continuously flush eye(s) wi minutes. Beyond flushing, DO NOT a adherent to the eye(s).	ith cool running water for at least 1
2 / 14	If swallowed	: Adverse health effects due	to ingestion are not anticipated.
		2 / 14	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Sequel 2392 SP NH167Version 1.2Revision Date	
Notes to physician	
Symptoms	: Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing.
Hazards	: Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns.
Treatment	: Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient.
5. FIRE-FIGHTING MEASURES	
Suitable extinguishing media	: SMALL FIRE: Use dry chemical, CO2, or water spray.
	: LARGE FIRES: Use water spray hose nozzles from a safe location.
Unsuitable extinguishing media	: None known.
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire.
	Cool storage containers with large volumes of water even after fire is out.
	3 / 14

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
	lyondellbasel
Sequel 2392 SP NH167 Version 1.2 Revision Date	
	10/02/2019 Finit Date 01/07/2022 3D3 No DE013
6. ACCIDENTAL RELEASE MEAS	SURES
Personal precautions	 Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth surfaces.
Environmental precautions	: Do not flush into surface water or sanitary sewer system.
Methods for containment / Methods for cleaning up	 On land, sweep/shovel into suitable disposal containers or vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any solid. All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible.
. Handling and storage	
Precautions for safe handling	-
Advice on safe handling	 Material is in a pellet form. If converted to small particles during further processing, handling, or by other means, may form combustible dust concentrations in air. Avoid dust accumulation in enclosed space. Use dust collection systems designed per NFPA 654 to avoid dust accumulation. Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion hazard. Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust explosion Electrostatic charge may build during conveying or handling. Equipment handling polymer should be conductive and
	4 / 14

		(+) 188	16996168		
		Poncip1	astics.com		
SAFETY DATA SH				lyonde	ellbasell
Seguel 2202 SD				Gen Variant:	SDS_US_GHS
Sequel 2392 SP Version 1.2 Revi	sion Date 10/	/02/2019	Print Date 01		SDS No.: BE6158
		Metal cont should be All electric codes and combustib After hand water. When brin may develo section 10 Refer to N Dust Explo	grounded and b al equipment sh regulatory requ le dusts. ling, always was ging the materia op may condens FPA 654, Stando osions from the	in the transfer of this	licable electric handling with soap and peratures vapors ntilation. See n of Fire and essing, and
Fire-fighting class	:	Polymer w	ill burn but does	s not easily ignite.	
Conditions for safe	storage, inc	luding any	, incompatibilit	ies	
Requirements for sto areas and containers	-	Use good and handli should be Store away oxidizing a Keep cont	ng. Process end used to avoid e y from excessiv igents. ainer closed to	practices during stora closures and adequa xcessive dust accum e heat and away fror prevent contamination the build up of elect	te ventilation nulation. m strong on.
Specific end use(s)		See Section	on 1.		
8. EXPOSURE CONTRO Control parameters	LS/PERSON/	AL PROTE	CTION		
Ingredients with w	orkplace con	trol param	eters		
Occupational Expo	sure Limits				
Components	CAS-No.	Туре	Limit Value	Basis Basis	Additional
Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust		TWA	10 mg/m3 inhalable	Revision Date US (ACGIH) 2005	Information
		5	/ 14		

$(+)\,18816996168$

Ponciplastics.com

SAFETY DATA SHEET

Sequel 2392 SP NH167L

Version 1.2 Revision Date 10/02/2019

Print Date 01/07/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE6158

Iyondellbasel

Materials that can	TWA	3 mg/m3	US (ACGIH)	
be formed when		respirable	2005	
handling this				
product: Non- specified (inert or				
nuisance) dust				
Materials that can	TWA	15 mg/m2		
be formed when	IVVA	15 mg/m3 total dust	US (OSHA) 2005	
		Iotal dust	2005	
handling this product: Non-				
specified (inert or				
nuisance) dust				
Materials that can	TWA	5 mg/m3	US (OSHA)	
be formed when		respirable	2005	
handling this		reopirabio	2000	
product: Non-				
specified (inert or				
nuisance) dust				

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection	 Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators. 	
Hand protection	: Wear gloves that provide thermal protection where there is a potential for contact with heated material.	
Eye and face protection	: Dust service goggles should be worn to prevent mechanical	
	6 / 14	

(+) 18816996168

	(+) 18810990108
SAFETY DATA SHEET	Ponciplastics.com lyondellbase
Sequel 2392 SP NH167 Version 1.2 Revision Date	
	injury or other irritation to eyes due to airborne particles which
	may result from handling this product.
Skin and body protection	: Wear suitable protective clothing.
Hygiene measures	 Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet
	facilities.
	Take off contaminated clothing and wash before reuse.
PHYSICAL AND CHEMICAL PI	ROPERTIES
Appearance Color	: Pellets. : Black
Odor	: Slight.
Odor Threshold	: No value available.
Flash point	: No Data Available.
Lower explosion limit	: The minimum explosive concentration (MEC) for polymer dua varies according to particle size distribution.
Upper explosion limit	: Not applicable.
Flammability (solid, gas)	: Polymer will burn but does not easily ignite.
Oxidizing properties	: Not considered an oxidizing agent.
Autoignition temperature	: > 300 °C
Decomposition temperature	: not determined
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: <1 g/cm3
Water solubility	: Insoluble.

SAFETY DATA SHEET Sequel 2392 SP NH167L Version 1.2 Revision Date 10/02/2019 Partition coefficient: n- cotanol/water Viscosity, dynamic : No Date Cotanol/water Viscosity, dynamic : Not app Relative vapor density : Not app Evaporation rate : Not app Evaporation rate : Not app Explosive properties : No Date Other Information : No add Other Information : No know Chemical stability : Stable of Hazardous reactions : Will not Conditions to avoid : Avoid c open fla Materials to avoid : Not exp products Thermal decomposition : Carbon amount	olicable. a Available. litional information available. wn reactivity hazards.
Version 1.2 Revision Date 10/02/2019 Partition coefficient: n- octanol/water Viscosity, dynamic : No Date octanol/water Viscosity, dynamic Relative vapor density : Not apper Evaporation rate Evaporation rate : Not apper Evaporation rate Explosive properties : No Date Other Information Other Information : No add Chemical stability : No know Chemical stability Hazardous reactions : Will not copen flat Materials to avoid : Avoid c open flat Hazardous decomposition products : Not exp products Thermal decomposition may be : Carbon amount may be	Gen. Variant: SDS_US_GHS Print Date 01/07/2022 SDS No.: BE615 a Available. blicable. blicable. a Available. litional information available.
Version 1.2 Revision Date 10/02/2019 Partition coefficient: n- octanol/water Viscosity, dynamic : No Date octanol/water Viscosity, dynamic Relative vapor density : Not apperention Evaporation rate Evaporation rate : Not apperention Explosive properties : No Date Other Information Other Information : No know Chemical stability : No know Conditions to avoid : Avoid c open flat Materials to avoid : Avoid c open flat Hazardous decomposition products : Not exp reducts Thermal decomposition : Carbon amount may be	Print Date 01/07/2022 SDS No.: BE613 a Available. blicable. blicable. a Available. litional information available.
Partition coefficient: n- octanol/water No Data Viscosity, dynamic Not app Relative vapor density Not app Evaporation rate Not app Explosive properties No Data Other Information No add 0. STABILITY AND REACTIVITY Reactivity No know Chemical stability Stable of Hazardous reactions Will not Conditions to avoid Avoid c open flat Materials to avoid Not exp Thermal decomposition Carbon amount may be 1. TOXICOLOGICAL INFORMATION	a Available. blicable. blicable. a Available. litional information available.
octanol/water Viscosity, dynamic: Not appleRelative vapor density: Not appleEvaporation rate: Not appleEvaporation rate: Not appleExplosive properties: No DateOther Information: No addOther Information: No knowChemical stability: Stable ofHazardous reactions: Will notConditions to avoid: Avoid c open flatMaterials to avoid: Not expHazardous decomposition products: Not expThermal decomposition amount may be: Carbon amount may be1. TOXICOLOGICAL INFORMATION	olicable. olicable. a Available. litional information available.
octanol/water Viscosity, dynamic: Not appleRelative vapor density: Not appleRelative vapor density: Not appleEvaporation rate: Not appleExplosive properties: No DateOther Information: No addOther Information: No knowChemical stability: Stable ofHazardous reactions: Will notConditions to avoid: Avoid c open flatMaterials to avoid: Not expHazardous decomposition: Not expproducts: Not expThermal decomposition: Carbon amount may be1. TOXICOLOGICAL INFORMATION	olicable. olicable. a Available. litional information available.
Viscosity, dynamic : Not apple Relative vapor density : Not apple Evaporation rate : Not apple Explosive properties : No Date Other Information : No add D. STABILITY AND REACTIVITY Reactivity : No know Chemical stability : Stable of Hazardous reactions : Will not Conditions to avoid : Avoid c Materials to avoid : Not explored Hazardous decomposition : Not explored products : Carbon Thermal decomposition : Carbon amount : may be	olicable. a Available. litional information available.
Evaporation rate : Not application Explosive properties : No Date Other Information : No add D. STABILITY AND REACTIVITY Reactivity Reactivity : No know Chemical stability : Stable of Hazardous reactions : Will not Conditions to avoid : Avoid c Materials to avoid : Material Hazardous decomposition : Not exp products : Carbon Thermal decomposition : Carbon amount : may be	olicable. a Available. litional information available. wn reactivity hazards.
Explosive properties : No Date Other Information : No add D. STABILITY AND REACTIVITY Reactivity Reactivity : No know Chemical stability : Stable of Hazardous reactions : Will not Conditions to avoid : Avoid c Materials to avoid : Materia Hazardous decomposition : Not exp products : Carbon Thermal decomposition : Carbon amount : may be	a Available. litional information available. wn reactivity hazards.
Other Information : No add D. STABILITY AND REACTIVITY Reactivity : No know Reactivity : No know Chemical stability : Stable of Hazardous reactions : Will not Conditions to avoid : Avoid c Materials to avoid : Materia Hazardous decomposition : Not exp products : Carbon Thermal decomposition : Carbon amount : may be	litional information available. wn reactivity hazards.
D. STABILITY AND REACTIVITY Reactivity : No know Chemical stability : Stable of Hazardous reactions : Will not Conditions to avoid : Avoid c Materials to avoid : Material Hazardous decomposition : Not exp products : Carbon Thermal decomposition : Carbon amount : may be	wn reactivity hazards.
Reactivity : No know Chemical stability : Stable of Hazardous reactions : Will not Conditions to avoid : Avoid c Materials to avoid : Materia Hazardous decomposition : Not exp products : Carbon Thermal decomposition : Carbon amount : may be	
Reactivity : No know Chemical stability : Stable of Hazardous reactions : Will not Conditions to avoid : Avoid c Materials to avoid : Materia Hazardous decomposition : Not exp products : Carbon Thermal decomposition : Carbon amount : may be	
Chemical stability : Stable of the stability Hazardous reactions : Will not Conditions to avoid : Avoid correction Materials to avoid : Material Hazardous decomposition : Not export of the stability products : Carbon amount may be I. TOXICOLOGICAL INFORMATION	
Hazardous reactions : Will not Conditions to avoid : Avoid c Materials to avoid : Material Materials to avoid : Material Hazardous decomposition : Not exp products : Carbon Thermal decomposition : Carbon amount : may be	under normal conditions
Conditions to avoid : Avoid c open fla Materials to avoid : Materia Hazardous decomposition : Not exp products Thermal decomposition : Carbon amount may be	under normal conditions.
open fla Materials to avoid : Materia Hazardous decomposition : Not exp products Thermal decomposition : Carbon amount may be I. TOXICOLOGICAL INFORMATION	occur.
Hazardous decomposition : Not exp products Thermal decomposition : Carbon amount may be	ontact with strong oxidizers, excessive heat, sparks or me.
products Thermal decomposition Carbon amount may be I. TOXICOLOGICAL INFORMATION	I may be softened by some hydrocarbons.
Thermal decomposition : Carbon amount may be	ected to decompose under normal conditions.
	monoxide, olefinic and paraffinic compounds, trace s of organic acids, ketones, aldehydes and alcohols formed.
Acute toxicity	
Acute oral toxicity : Not class	ssified
Acute inhalation toxicity : Not class	ssified
Acute dermal toxicity : Not clas	ssified
Skin corrosion/irritation : Not a s	
	kin irritant.
	kin irritant. eye irritant. iical irritation is possible.
	eye irritant.

	(+) 188	16996168	
AFETY DATA SHEET	Poncip1a	stics.com	lvoodollbaco
/			lyondellbase
Sequel 2392 SP NH167	Ľ		Gen. Variant: SDS_US_GHS
ersion 1.2 Revision Date		Print Date 01/07	/2022 SDS No.: BE61
Respiratory or skin sensitization	: Not classifi	ed	
Chronic toxicity			
Component Name	NTP	IARC	OSHA
Carbon Black Titanium Dioxide		2B 2B	Present Present
			riooont
Carcinogenicity	: Not classifi	ed	
	carcinogen This materi	ic to humans. al is encapsulated ase under normal	by IARC as possibly in a thermoplastic resin with conditions of use, transportation,
Germ cell mutagenicity	: Not classifi	ed	
Reproductive toxicity			
Effects on fertility / Effects on or via lactation	: Not classifi	ed	
Effects on Development	: Not classifi	ed	
Target Organ Systemic Toxicant - Single exposure		ance or mixture is n ant, single exposu	ot classified as specific target re.
Target Organ Systemic Toxicant - Repeated exposure		ance or mixture is n ant, repeated expo	ot classified as specific target osure.
Aspiration hazard	: Not applica	ble.	
. Ecological information			
Ecotoxicology Assessment			
Short-term (acute) aquatic hazard	: Not classifi	ed	
nazard Long-term (chronic)	: Not classifi	ed	
	9	/ 14	

	(+) 18816996168
SAFETY DATA SHEET	Ponciplastics.com
Sequel 2392 SP NH167	
Version 1.2 Revision Date	10/02/2019 Print Date 01/07/2022 SDS No.: BE6158
aquatic hazard	
Persistence and degradability	
Biodegradability	: Not expected to be biodegradable.
Bioaccumulative potential	
Bioaccumulation	: This material is not expected to bioaccumulate.
Mobility in soil	
Mobility	: no data available
Other adverse effects	
Environmental fate and pathways	: This material is not volatile and insoluble in water.
Other information	
Additional ecological information	 Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts.
13. Disposal considerations	
Waste treatment methods	
Product	: All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible.
	: This material is classified as a Non-hazardous Material by RCRA.
14. TRANSPORT INFORMATION	
	10 / 14

(+) 18816996168

Ponciplastics.com

Sequel 2392 SP NH167L

SAFETY DATA SHEET

Version 1.2

Revision Date 10/02/2019

Print Date 01/07/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE6158

lyondellbase

Not regulated for transport

15. REGULATORY INFORMATION

TSCA 12b

No substances are subject to TSCA 12(b) export notification requirements.

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material may contain trace levels of the following chemical substance(s) regulated under California Proposition 65. However, LyondellBasell has not tested for the presence of listed chemical substances. It is the responsibility of the California business owner to develop his or her own regulatory compliance plan. Contact Product Safety for further information at product.safety@lyb.com.

Substance	CASRN	Type of Toxicity			
		Carcinogen	Developmental	Repro-Male	Repro- Female
Hexachlorobenzene	118-74-1	Х	Х		

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

14807-96-6Talc, Magnesium Silicate

1333-86-4 Carbon Black

This product contains the following chemicals regulated by Massachusetts' Right to Know Law:

11 / 14

(+)	1881	69961	68
(.)	1001	00001	00

Ponciplastics.com

Sequel 2392 SP NH167L

SAFETY DATA SHEET

Version 1.2

Revision Date 10/02/2019

Print Date 01/07/2022

Gen. Variant: SDS US GHS

SDS No.: BE6158

Iyondellbase

14807-96-6	Talc, Magnesium Silicate
14808-60-7	Silica, Crystalline - Quartz

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

14807-96-6	Talc, Magnesium Silicate
1333-86-4	Carbon Black

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)


Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

12 / 14



Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet

13 / 14

			16996168			
SAFETY DATA	A SHEET	Poncipla	astics.com	lyon	dellbase	
Sequel 2392	SP NH167L				ant: SDS_US_GHS	
Version 1.2	Revision Date 10	0/02/2019	Print Date 01/07/	/2022	SDS No.: BE61	58