	(+) 188169	996168			
SAFETY DATA SHEET	Ponciplast	ics.com	lvoodollbacoll		
according to GB/T 16483-2008, GB/T 17519-2013			lyondellbasell		
Softell TKG 2039N C1 NAT	URAL		Gen. Variant: SDS_CN		
Version 1.0 Revision Date 20	21-08-03 Pr	int Date 20	022-01-07 SDS No.: BE15722		
1. IDENTIFICATION OF THE SUBSTA	NCE/MIXTURE	and of th	E COMPANY/UNDERTAKING		
	Softell TKG 2039 Mixture	ON C1 NAT	URAL		
Chemical name :	Compounded po				
Synonyms :	Polyolefin, Comp	ounded po	lymer		
	Manufacture of p or other conversi		es by injection molding, extrusion		
Prohibited uses :	FDA Class III medical devices; European class III medical devices; Health Canada class IV Medical Devices; Applications involving permanent implantation into the body; Life-sustaining medical applications				
Ltd.	Basell Advanced Polyolefins (Suzhou) Co.Product Safety+852-2585-0120Ltd.Tel : +86- 512-6283690036, Fangda Street, Suzhou Industrial Park				
Guangzhou Basell Advanced Polyolefins Co. Ltd.Product Safety Tel : +86-20-3909-8600No.9, GuangYe DaJie, Nansha District Guangzhou, Guangdong, ChinaProduct Safety Tel : +86-20-3909-8600					
E-mail address : product.safety@lyb.com Responsible/issuing person					
2. HAZARDS IDENTIFICATION					
Emergency Overview					
If small particles are generated during further processing, handling or by other means, may form combustible dust concentrations in air. At process temperatures irritating fumes may be produced. Molten polymer may cause thermal burns. Slipping hazard if spilled on hard smooth walking surface. The material can accumulate static charges which could be a source of ignition.					
GHS-Classification					
Not a hazardous substance or mixture according to the Globally Harmonized System (GHS).					
GHS-Labeling					

	(+) 18816996168				
AFETY DATA SHEET cording to GB/T 16483-2008, GB	Ponciplastics.com /T 17519-2013	lyondellbase			
oftell TKG 2039N C1 NA ersion 1.0 Revision Date 2		Gen. Variant: SDS_CN 022-01-07 SDS No.: BE157			
Not a hazardous substance or Physical-chemical, Health, En	-	bally Harmonized System (GHS). ion			
Health hazards					
Eyes:	Mechanical irritation is po	ssible.			
Ingestion:	Ingestion not a likely route	e of exposure.			
Inhalation:	Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. "Nuisance dust" such as polymer dust typically exhibit no significant health effect when they are reasonably controlled. Exposure to high concentrations of dust may cause slight irritation by mechanical action.				
Skin:	Molten polymer may caus	e thermal burns.			
No additional information ava	ilable.				
COMPOSITION/INFORMATION C					
COMPOSITION/INFORMATION C		Weight %			
COMPOSITION/INFORMATION C xtures Components	ON INGREDIENTS	<u>Weight %</u> 50.0 - 80.0 %			
COMPOSITION/INFORMATION C xtures Components Chemical name Proprietary blend of polyolefinic	CAS-No.				
COMPOSITION/INFORMATION C xtures Components Chemical name Proprietary blend of polyolefinic polymers	CAS-No.				
COMPOSITION/INFORMATION C xtures Components Chemical name Proprietary blend of polyolefinic polymers Contains: Additives, stabilizers a	ON INGREDIENTS CAS-No. Mixture and fillers	ensure your own health and safety			

SAFETY DATA SHEET according to GB/T 16483-2008, GB/T 17519-2013 SoftelTTKC 2039N C1 NATURAL Version 1.0 Revision Date 2021-08-03 Print Date 2022-01-07 SDS No.: BE15722 Version 1.0 Revision Date 2021-08-03 Print Date 2022-01-07 SDS No.: BE15722 Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. Notes to physician : Symptoms Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.		(+) 18816996168
Version 1.0 Revision Date 2021-08-03 Print Date 2022-01-07 SDS No.: BE15722 Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with work cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. Notes to physician : Symptoms Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical initation. Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES : LARGE FIRES: Use water spray hose nozzle	according to GB/T 16483-2008, GB	Jyondellbasell
Keep person warm, if necessary give Cardio-Pulmonary Resuscitation (CPR) In case of skin contact : If molten material contacts the skin, immediately flush with large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. In case of eye contact : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. Notes to physician : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES : Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location. : LARGE FIRES: Use water spray hose nozzles from a safe location.		
Iarge amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep or extensive. In case of eye contact : Flush eyes thoroughly with water for several minutes and seek medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. Notes to physician Symptoms Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location.	Version 1.0 Revision Date	Keep person warm, if necessary give Cardio-Pulmonary
medical attention if discomfort persists. : In case of eye contact with molten polymer: Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. Notes to physician : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Moiten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location.	In case of skin contact	large amounts of water to cool the affected tissue and polymer. Do not attempt to peel polymer from skin as this will remove the skin. Obtain immediate emergency medical attention if burn is deep
Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s). Immediately seek medical attention. If swallowed : Adverse health effects due to ingestion are not anticipated. Notes to physician Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient.	In case of eye contact	
Notes to physician Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location.		Continuously flush eye(s) with cool running water for at least 15 minutes. Beyond flushing, DO NOT attempt to remove the material adherent to the eye(s).
Symptoms : Inhalation of process fumes and vapors may cause soreness in the nose and throat and coughing. Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location.	If swallowed	: Adverse health effects due to ingestion are not anticipated.
Hazards : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location.	Notes to physician	
Molten polymer may cause thermal burns. Treatment : Treatment of overexposure should be directed at the control of symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location.	Symptoms	
symptoms and the clinical condition of the patient. 5. FIRE-FIGHTING MEASURES Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location.	Hazards	
Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location.	Treatment	
Use dry chemical, CO2, or water spray. : LARGE FIRES: Use water spray hose nozzles from a safe location.	5. FIRE-FIGHTING MEASURES	
Use water spray hose nozzles from a safe location.	Suitable extinguishing media	
Unsuitable extinguishing : None known.		
media	Unsuitable extinguishing media	: None known.

$(+)\,18816996168$ Ponciplastics.com

SAFETY DATA SHEET

according to GB/T 16483-2008, GB/T 17519-2013



sion 1.0 Revision Dat	e 2021-08-03 Print Date 2022-01-07 SDS No.: BE
SIOII 1.0 REVISIOII Dai	e 2021-08-05 Fillt Date 2022-01-07 SDS No BE
Specific hazards during fire fighting	 Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbo (smoke).
Special protective equipment for fire-fighters	: Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing.
Further information	 Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzl Heat from fire may melt, decompose polymer, and generate flammable vapors. Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved i fire. Cool storage containers with large volumes of water even af
	fire is out.
	SURES : Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface.
	 SURES Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth
	 SURES Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard.
CCIDENTAL RELEASE MEA Personal precautions	 SURES Equip responders with proper protection. Creates dangerous slipping hazard on any hard smooth surface. Equip emergency responders with proper personal protective equipment (PPE) Avoid generating dust. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth

	(+) 18816996168				
SAFETY DATA SHEET according to GB/T 16483-2008, GB/T	Ponciplastics.com	lyondellbasell			
Softell TKG 2039N C1 NATURAL Gen. Variant: SDS_CN					
Version 1.0 Revision Date 20	021-08-03 Print Date 20	022-01-07 SDS No.: BE15722			
7. Handling and storage					
Precautions for safe handling					
Advice on safe handling :	handling, or by other means concentrations in air. Avoid dust accumulation in Use dust collection systems dust accumulation. Avoid generating dust; fine presence of an ignition sour hazard. Static discharge (spark), or environments may ignite the explosion Electrostatic charge may bu Equipment handling polyme grounded (earthed) and bor Metal containers involved in should be grounded and bo All electrical equipment sho codes and regulatory require combustible dusts. After handling, always wash water. When bringing the material may develop may condense section 10. Refer to NFPA 654, Standa Dust Explosions from the M	s designed per NFPA 654 to avoid dust suspended in air and in the rece is a potential dust explosion other ignition sources, in high dust e dust and result in a dust wild during conveying or handling. er should be conductive and haded. In the transfer of this material inded. Uld conform to applicable electric			
Conditions for safe storage, including any incompatibilities					
Requirements for storage : areas and containers	and handling. Process encloshould be used to avoid exc Store away from excessive oxidizing agents. Keep container closed to pr	heat and away from strong			
Specific end use(s)					
Specific end use(s) : See Section 1.					

(+) **18816996168** Ponciplastics.com

SAFETY DATA SHEET according to GB/T 16483-2008, GB/T 17519-2013

Softell TKG 2039N C1 NATURAL

Version 1.0 Revision Date 2021-08-03

Print Date 2022-01-07

Gen. Variant: SDS_CN -07 SDS No.: BE15722

lyondellbasell

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Ingredients with workplace control parameters

Occupational Exposure Limits

Components	CAS-No.	Туре	Limit Value	Basis Revision Date	Additional Information
Materials that can be formed when		TWA	10 mg/m3 inhalable	US (ACGIH) 2005	
handling this					
product: Non- specified (inert or					
nuisance) dust					
Materials that can be formed when		TWA	3 mg/m3 respirable	US (ACGIH) 2005	
handling this					
product: Non- specified (inert or					
nuisance) dust					

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either

prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

: Use process enclosures, local exhaust ventilation, or other
engineering controls to keep airborne levels below
recommended exposure limits.
When workers are facing concentrations above the exposure
limit they must use appropriate certified respirators.

SAFETY DATA SHEET according to GB/T 16483-2008, GB Softell TKG 2039N C1 NA	TURAL	Iyondellbasell Gen. Variant: SDS_CN
Version 1.0 Revision Date	2021-08-03 Print Date 2	022-01-07 SDS No.: BE15722
	exceeds recommended limit Where workers could be ex	protection where atmosphere ts. posed to dust concentrations ey must use appropriate certified
Hand protection	: Wear gloves that provide th potential for contact with he	ermal protection where there is a ated material.
Eye and face protection		d be worn to prevent mechanical /es due to airborne particles which is product.
Skin and body protection	: Wear suitable protective clo	othing.
Hygiene measures	be based on an evaluation of of the protective equipment performed, conditions prese hazards and/or potential ha during use. Use good personal hygiene Wash hands before eating, facilities.	ent, duration of use, and the zards that may be encountered

9. PHYSICAL AND CHEMICAL PROPERTIES

: solid : Translucent to white
: Slight.
: No value available.
: No Data Available.
: The minimum explosive concentration (MEC) for polymer dust varies according to particle size distribution.
: Not applicable.
: Polymer will burn but does not easily ignite.
: Not considered an oxidizing agent.
: > 300 °C
: not determined

SAFETY DATA SHEET according to GB/T 16483-2008, (
Softell TKG 2039N C1 N Version 1.0 Revision Dat	NATURALGen. Variant:SDS_CNte 2021-08-03Print Date 2022-01-07SDS No.: BE157
Melting point/range	: 50 - 170 °C
Boiling point/boiling range	: Not applicable.
Vapor pressure	: Not applicable.
Density	: > 1 g/cm3
Water solubility	: Insoluble.
Partition coefficient: n- octanol/water	: No Data Available.
Viscosity, dynamic	: Not applicable.
Relative vapor density	: Not applicable.
Evaporation rate	: Not applicable.
Explosive properties	: No Data Available.
Other Information	: No additional information available.
D. STABILITY AND REACTIVITY Reactivity	: No known reactivity hazards.
Chemical stability	: Stable under normal conditions.
Hazardous reactions	: Will not occur.
Conditions to avoid	 Avoid contact with strong oxidizers, excessive heat, sparks or open flame.
Conditions to avoid Materials to avoid	•
Materials to avoid Hazardous decomposition	open flame.
Materials to avoid	open flame.Material may be softened by some hydrocarbons.
Materials to avoid Hazardous decomposition products	 open flame. Material may be softened by some hydrocarbons. Not expected to decompose under normal conditions. Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
Materials to avoid Hazardous decomposition products Thermal decomposition	 open flame. Material may be softened by some hydrocarbons. Not expected to decompose under normal conditions. Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
Materials to avoid Hazardous decomposition products Thermal decomposition 1. TOXICOLOGICAL INFORMAT	 open flame. Material may be softened by some hydrocarbons. Not expected to decompose under normal conditions. Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.
Materials to avoid Hazardous decomposition products Thermal decomposition 1. TOXICOLOGICAL INFORMAT Acute toxicity	 open flame. Material may be softened by some hydrocarbons. Not expected to decompose under normal conditions. Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed.

	(+) 18816996168	
SAFETY DATA SHEET according to GB/T 16483-2008, GI		lyondellbasell
Softell TKG 2039N C1 NA Version 1.0 Revision Date		Gen. Variant: SDS_CN 22-01-07 SDS No.: BE15722
	2021-00-05 11iiii Date 20	22-01-07 SD5 110 DL13722
Acute dermal toxicity	: Not classified	
Skin corrosion/irritation	: Not a skin irritant.	
Serious eye damage/eye irritation	: Not an eye irritant. Mechanical irritation is possi	ble.
Respiratory or skin sensitization	: Not classified	
Chronic toxicity		
Carcinogenicity	: Not classified	
Germ cell mutagenicity	: Not classified	
Reproductive toxicity		
Effects on fertility / Effects on or via lactation Effects on Development	: Not classified : Not classified	
Target Organ Systemic Toxicant - Single exposure	: The substance or mixture is organ toxicant, single exposit	
Target Organ Systemic Toxicant - Repeated exposure	: The substance or mixture is organ toxicant, repeated exp	not classified as specific target
Aspiration hazard	: Not applicable.	
12. Ecological information Ecotoxicology Assessment Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard	: Not classified : Not classified	

		(+) 18816996168		
		Ponciplastics.com		
SAFETY DATA SHEET according to GB/T 16483-2008, GB/	T⁄	17519-2013		lyondellbasell
Softell TKG 2039N C1 NA	TI	URAL		Gen. Variant: SDS_CN
Version 1.0 Revision Date 2			022-01	-07 SDS No.: BE15722
Persistence and degradability				
Biodegradability	: 1	Not expected to be biodegra	adable.	
Bioaccumulative potential				
Bioaccumulation	: -	This material is not expected	d to bio	accumulate.
Mobility in soil				
Mobility :	: r	no data available		
Other adverse effects				
Environmental fate and : pathways	: -	This material is not volatile a	and ins	oluble in water.
Other information				
Additional ecological : information	9 	Ecotoxicity is expected to be solubility of polymers. No data available on this pro other wildlife may eat pellets ntestinal tracts.	oduct.	However, birds, fish and
13. Disposal considerations				
Waste treatment methods				
Product :	t a		f or reclons and	aimed in conformance with d in conformance with good
14. TRANSPORT INFORMATION				
Not regulated for transport				
15. REGULATORY INFORMATION				
Other international regulations				

SAFETY DATA SHEET

(+) **18816996168** Ponciplastics.com

according to GB/T 16483-2008, GB/T 17519-2013

Softell TKG 2039N C1 NATURAL

Version 1.0 Revision Date 2021-08-03

Print Date 2022-01-07

SDS No.: BE15722

Iyondellbasell

Gen. Variant: SDS CN

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

First Edition

Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies. Y DATA SHEET Ponciplastics.com

(+) **18816996168**

SAFETY DATA SHEET according to GB/T 16483-2008, GB/T 17519-2013

Gen. Variant: SDS CN

Softell TKG 2039N C1 NATURAL

Version 1.0 I

Revision Date 2021-08-03 Print Date 2022-01-07

7 SDS No.: BE15722

Disclaimer

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet