| | (+) 18816996168 |
|---|---|
| SAFETY DATA SHEET | Ponciplastics.com |
| AFEIY DAIA SHEEI | lyondellbase |
| Softell TKG 442N E1 C | Gen. Variant: SDS_US_GH |
| Version 1.0 Revision Date | |
| | |
| IDENTIFICATION OF THE SUB | STANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING |
| Trade name | : Softell TKG 442N E1 C12A19 |
| CAS Number: | : Mixture |
| Chemical name Synonyms | Compounded polyolefinPolyolefin, Compounded polymer |
| Synonyms | . Polyoleini, compounded polymei |
| Identified uses | : Manufacture of plastic articles by injection molding, extrusion or other conversion process. |
| Prohibited uses | : FDA Class III medical devices; European class III medical |
| | devices; Health Canada class IV Medical Devices; |
| | Applications involving permanent implantation into the body; Life-sustaining medical applications |
| | |
| <u>Company Address</u> | Company Telephone |
| Equistar Chemicals, LP | Customer Service 888 777-0232 |
| LyondellBasell Tower, Suite 3 | 300 product.safety@lyb.com |
| 1221 McKinney St. P.O. Box 2583 | |
| Houston Texas 77252-2583 | |
| EQUISTAR 800-245-4532 E-mail address Responsible/issuing person | <u>ber</u> : product.safety@lyb.com |
| HAZARDS IDENTIFICATION | |
| GHS Classification | |
| Combustible dust | |
| | |
| Label elements | |
| Label elements Signal word | : Warning |
| | - |
| Signal word | If small particles are generated during further processing, handling or by other means, may form combustible dust |
| Signal word | : If small particles are generated during further processing, |
| Signal word | If small particles are generated during further processing, handling or by other means, may form combustible dust |
| Signal word Hazard Statements | If small particles are generated during further processing, handling or by other means, may form combustible dust |

| | (+) 18816996168 | |
|---|--|---|
| AFETY DATA SHEET | Ponciplastics.com | lyondellbase |
| | | |
| ersion 1.0 Revision Date | | Gen. Variant: SDS_US_GH 07/2022 SDS No.: BE27 |
| | | 01/2022 000 NO DE2/3 |
| | | |
| No additional information a | available. | |
| COMPOSITION/INFORMATION | ON INGREDIENTS | |
| xtures | | |
| Components | | |
| Chemical name | CAS-No. | <u>Weight %</u> |
| Proprietary blend of polyolefini polymers | c Mixture | 80.0 - 100.0 % |
| | ro and filloro | |
| Contains: Additives, stabilize | rs and fillers | |
| | | |
| FIRST AID MEASURES | | |
| General advice | : Take proper precautions t | o ensure your own health and safe |
| | before attempting rescue | and providing first aid. |
| If inhaled | · Pomovo porson to frosh a | ir. If signs/symptoms continue, get |
| | medical attention. | |
| | | ation of fumes that may be genera erial, move the person to fresh air. |
| | Obtain medical attention. Keep person warm, if nec | essary give Cardio-Pulmonary |
| | Resuscitation (CPR) | |
| In case of skin contact | : If molten material contacts | the skin, immediately flush with |
| | | cool the affected tissue and polym ymer from skin as this will remove |
| | skin. | |
| | or extensive. | ncy medical attention if burn is de |
| In case of eye contact | | n water for several minutes and se |
| | medical attention if discon | nfort persists. |
| | : In case of eye contact with Continuously flush eye(s) | n molten polymer: with cool running water for at leas |
| | minutes. | - |
| | adherent to the eye(s). | attempt to remove the material |
| | Immediately seek medical | attention. |
| If swallowed | : Adverse health effects due | e to ingestion are not anticipated. |
| | 2 / 13 | |
| | | |
| | | |

| SAFETY DATA SHEET | Ponciplastics.com |
|--|---|
| SAFELT DATA SHEET | Iyondellbasel |
| | Iyundenbaser |
| Softell TKG 442N E1 C | |
| Version 1.0 Revision Date | 04/08/2020 Print Date 01/07/2022 SDS No.: BE2793 |
| | |
| | |
| Notes to physician | |
| Symptoms | : Inhalation of process fumes and vapors may cause soreness the nose and throat and coughing. |
| Hazards | : Dust contact with the eyes can lead to mechanical irritation. Molten polymer may cause thermal burns. |
| Treatment | : Treatment of overexposure should be directed at the control or symptoms and the clinical condition of the patient. |
| | |
| . FIRE-FIGHTING MEASURES | |
| Suitable extinguishing media | : SMALL FIRE: Use dry chemical, CO2, or water spray. |
| | : LARGE FIRES: Use water spray hose nozzles from a safe location. |
| Unsuitable extinguishing media | : None known. |
| Specific hazards during fire fighting | Keep away from heat and sources of ignition. In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons |
| | (smoke). |
| Special protective equipment for fire-fighters | : Wear approved positive pressure self-contained breathing apparatus and firefighter protective clothing. |
| Further information | Combustible particulate solid, will decompose under fire conditions. Calorific Value: 8000 - 11000 kcal/kg Fight fire from safe distance with hose lines or monitor nozzle Heat from fire may melt, decompose polymer, and generate flammable vapors. |
| | Move containers from fire area if it can be done without risk. Evacuate immediately in the event of opening of storage container pressure relief devices or discoloration of container. Always stay away from tanks engulfed in fire. Do not attempt to get on top of storage containers involved in fire. |
| | Cool storage containers with large volumes of water even after fire is out. |
| | 3 / 13 |

| | (+) 18816996168 |
|-------------------------------|--|
| SAFETY DATA SHEET | Ponciplastics.com |
| SAFETY DATA SHEET | lyondellbasell |
| Softell TKG 442N E1 C12 | Gen. Variant: SDS_US_GHS |
| Version 1.0 Revision Date 04 | |
| | |
| | |
| | |
| 6. ACCIDENTAL RELEASE MEASU | RES |
| Personal precautions | : Equip responders with proper protection. |
| | Creates dangerous slipping hazard on any hard smooth surface. |
| | Equip emergency responders with proper personal protective equipment (PPE) |
| | Avoid generating dust. |
| | Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). |
| | Potential combustible dust hazard. Polymer particles create slipping hazard on hard smooth |
| | surfaces. |
| Environmental precautions | : Do not flush into surface water or sanitary sewer system. |
| | |
| Methods for containment / : | On land, sweep/shovel into suitable disposal containers or |
| Methods for cleaning up | vacuum using equipment which avoids ignition risk. On water, material is insoluble; collect and contain as any |
| | solid. All recovered material should be packaged, labeled, |
| | transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good |
| | engineering practices. Reclaim where possible. |
| | |
| | |
| 7. Handling and storage | |
| Precautions for safe handling | |
| Advice on safe handling : | Material is in a pellet form. If converted to small particles during further processing, |
| | handling, or by other means, may form combustible dust |
| | concentrations in air. Avoid dust accumulation in enclosed space. |
| | Use dust collection systems designed per NFPA 654 to avoid dust accumulation. |
| | Avoid generating dust; fine dust suspended in air and in the presence of an ignition source is a potential dust explosion |
| | hazard. |
| | Static discharge (spark), or other ignition sources, in high dust environments may ignite the dust and result in a dust |
| | explosion Electrostatic charge may build during conveying or handling. |
| | Equipment handling polymer should be conductive and |
| | 4 / 13 |
| | |
| | |

| grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electrosal equipment should be used. Fire-fighting class : Store in a dry location. Brequirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, trans and handling. Processive heat and away from strong oxidizing agents. Store away from excessive heat and away from strong oxidizing agents. Store away from excessive heat and away from strong oxidizing agents. Store away from excessive heat and away from strong oxidizing agents. Store away fr | | (+) 188. | 16996168 | | |
|---|---------------------------------|-------------------------|------------------------------------|------------------------|---------------------------|
| Softel I TKG 442N E1 C12AT Gen. Variant: SDS_UP Version 1.0 Revision Date 04/08/2020 Print Date 01/07/2022 SDS No.; grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable el codes and regulatory requirements for areas handling. Combustible dusts. All electrical equipment should conform to applicable el codes and regulatory requirements for areas handling. Section 10. Refer handling, always wash hands thoroughly with soa water. When bringing the material to processing temperatures may develop may condense in the exhaust ventilation. section 10. Refer to NFPA 654, Standard for the Prevention of Fire Dust Explosions from the Manufacturing, Processing, al Handling of Combustible Particulate Solids, for safe hard and ing of Combustible Particulate Solids, for safe hard handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive dust accumulati | | Poncip1a | astics.com | | |
| Version 1.0 Revision Date 04/08/2020 Print Date 01/07/2022 SDS No.: grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable el codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soa water. When bringing the material to processing temperatures may develop may condense in the exhaust ventilation. section 10. Refer to NFPA 654, Standard for the Prevention of Fire Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har Handling of Combustible Particulate Solids, for safe har Handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic of Specific end use(s) ExPOSURE CONTROLS/PERSONAL PROTECTION Control parameters Ingredients with workplace control parameters Docupational Exposure Limits Components CAS-No. Type Limit Value Revision Date Additi Inform Materials that can be formed when handling TWA 10 mg/m3 US (ACGIH) US (ACGIH) | | | | Iyonde | ellbase |
| Version 1.0 Revision Date 04/08/202 Print Date 01/07/202 SDS No.: grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable el codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soa water. When bringing the material to processing temperatures may develop may condense in the exhaust ventilation. section 10. Refer to NFPA 654, Standard for the Prevention of Fire Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har Handling of Combustible Particulate Solids, for safe har Handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic of Specific end use(s) EXPOSURE CONTROLS/PERSONAL PROTECTION Explored the workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Revision Date Additi Inform Materials that can be formed when handling this | | A10 | | Gen Variant: | SDS US GH |
| grounded (earthed) and bonded. Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electrical equipments for areas handling combustible dusts. After handling, always wash hands thoroughly with soa water. When bringing the material to processing temperatures may develop may condense in the exhaust ventilation. section 10. Refer to NFPA 654, Standard for the Prevention of Fire Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har and containers Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, trans and handling. Process enclosures and adequate ventila should be used to avoid excessive bust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic or specific end use(s) : See Section 1. : : Store in a dry location. : : Store in a d | | | Print Date 01 | | DS No.: BE27 |
| Metal containers involved in the transfer of this material should be grounded and bonded. All electrical equipment should conform to applicable electes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soal water. When bringing the material to processing temperatures. may develop may condense in the exhaust ventilation. section 10. Refer to NFPA 654, Standard for the Prevention of Fire Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har transfer of housekeeping practices during storage, trans and handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive dust accumulation. Store away from excessive dust accumulation. Take measures to prevent the build up of electrostatic or solidizing agents. Keep container closed to prevent the build up of electrostatic or solidizing agents. Keep container closed to prevent the build up of electrostatic or solidizing agents. Keep container closed to prevent the build up of electrostatic or solidizing agents. Keep container closed to prevent the build up of electrostatic or solidizing agents. Keep container store agent the workplace control parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Inform | | | | | |
| Metal containers involved in the transfer of this material should be grounded and bonded. Ail electrical equipment should conform to applicable electes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soal water. When bringing the material to processing temperatures. may develop may condense in the exhaust ventilation. section 10. Refer to NFPA 654, Standard for the Prevention of Fire Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har transfer storage, including any incompatibilities Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, trans and handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent the build up of electrostatic of specific end use(s) : See Section 1. Exprosure Controls/PERSONAL PROTECTION Components CAS-No. Type Limit Value Basis Addit Inform Materials that can be formed when handling this Type Limit Value Revision Date | | | | | |
| should be grounded and bonded. All electrical equipment should conform to applicable el codes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soal water. When bringing the material to processing temperatures may develop may condense in the exhaust ventilation. section 10. Refer to NFPA 654, Standard for the Prevention of Fire Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har Dust Explosions from the Manufacturing, Processing, a Handling, Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic or Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION components CAS-No. Type Limit Value Basis Addit Materials that can TWA | | | | | |
| All electrical equipment should conform to applicable elecodes and regulatory requirements for areas handling combustible dusts. After handling, always wash hands thoroughly with soat water. When bringing the material to processing temperatures may develop may condense in the exhaust ventilation. section 10. Refer to NFPA 654, Standard for the Prevention of Fire Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har and the prevention of Fire Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har and the prevention of storage including any incompatibilities Requirements for storage areas and containers Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers areas and containers Store in a dy location. Use good housekeeping practices during storage, trans and handling. Process enclosures and adequate wertila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic or a second to prevent strong oxidizing agents. EXPOSURE CONTROLS/PERSONAL PROTECTION control parameters Ingredients with workplace control parameters Occupational Exposure Limits Materials that can be formed when handling twis <td></td> <td></td> <td></td> <td></td> <td>s material</td> | | | | | s material |
| After handling, always wash hands thoroughly with soal water. When bringing the material to processing temperatures may develop may condense in the exhaust ventilation. section 10. Refer to NFPA 654, Standard for the Prevention of Fire Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har to NFPA 654, Standard for the Prevention of Fire Dust Explosions for stafe storage, including any incompatibilities Requirements for storage areas and containers Polymer will burn but does not easily ignite. Use good housekeeping practices during storage, trans and handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic or specific end use(s) EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Manding this TWA 10 mg/m3 US (ACGIH) | | All electrica codes and | al equipment sh regulatory requ | ould conform to app | |
| may develop may condense in the exhaust ventilation. section 10. Refer to NFPA 654, Standard for the Prevention of Fire Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, trans and handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic or specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addti Inform Materials that can handling TWA Materials that can handling it his TWA 10 mg/m3 US (ACGIH) 2005 | | After handl | | sh hands thoroughly | with soap and |
| Refer to NFPA 654, Standard for the Prevention of Fire Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe har Fire-fighting class : Polymer will burn but does not easily ignite. Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, trans and handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic or specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addti Inform Materials that can handling this TWA 10 mg/m3 US (ACGIH) 2005 | | may develo | p may condens | | |
| Dust Explosions from the Manufacturing, Processing, a Handling of Combustible Particulate Solids, for safe hardling of Combustible Particulate Solids, for safe hardling of Combustible Particulate Solids, for safe hardling combustible Particulate Solids, for safe hardling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic combustible Particulate Solids, for safe hardling combustible Particulate Solids, for safe hardling combustible Particulate Solids, for safe hardling combustible Particulate Solid combustible Particulates Soli | | | | ard for the Preventio | n of Fire and |
| Conditions for safe storage, including any incompatibilities Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, trans and handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic or specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Inform Materials that can Materials that can TWA 10 mg/m3 US (ACGIH) be formed when handling this | | Dust Explo | sions from the | Manufacturing, Proc | essing, and |
| Requirements for storage areas and containers : Store in a dry location. Use good housekeeping practices during storage, trans and handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic of Specific end use(s) : See Section 1. : See Section 1. : See Section 1. : Components CAS-No. Type Limit Value Basis Addit Inform Materials that can be formed when handling this TWA 10 mg/m3 US (ACGIH) 2005 | e-fighting class : | Polymer wi | ill burn but does | not easily ignite. | |
| areas and containers Use good housekeeping practices during storage, trans and handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic or Specific end use(s) Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Cas-No. Type Limit Value Basis Additi Inform Materials that can be formed when handling this TWA 10 mg/m3 US (ACGIH) 2005 Additi | onditions for safe storage, inc | cluding any | incompatibilit | ies | |
| and handling. Process enclosures and adequate ventila should be used to avoid excessive dust accumulation. Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic of Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits <u>Components CAS-No. Type Limit Value Basis Additi</u> <u>Inform</u> Materials that can be formed when handling this 10 mg/m3 US (ACGIH) 2005 | | | | practices during stora | age transferring |
| Store away from excessive heat and away from strong oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic of Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Revision Date Inform Materials that can TWA 10 mg/m3 US (ACGIH) be formed when a TWA 10 mg/m3 US (ACGIH) 2005 | | and handlin | ng. Process end | closures and adequa | te ventilation |
| oxidizing agents. Keep container closed to prevent contamination. Take measures to prevent the build up of electrostatic of Specific end use(s) : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Revision Date Inform Materials that can TWA 10 mg/m3 be formed when TWA 10 mg/m3 US (ACGIH) | | | | | |
| Take measures to prevent the build up of electrostatic of Specific end use(s) : See Section 1. : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Materials that can TWA 10 mg/m3 US (ACGIH) 2005 10 | | oxidizing a | gents. | - | - |
| : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits <u>Components</u> <u>CAS-No.</u> <u>Type</u> <u>Limit Value</u> <u>Basis</u> <u>Addit</u> <u>Revision Date</u> <u>Inform</u> <u>Materials that can</u> <u>TWA</u> <u>10 mg/m3</u> <u>US (ACGIH)</u> <u>be formed when</u> <u>Inhalable</u> <u>2005</u> | | | | | |
| : See Section 1. EXPOSURE CONTROLS/PERSONAL PROTECTION ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits <u>Components</u> <u>CAS-No.</u> <u>Type</u> <u>Limit Value</u> <u>Basis</u> <u>Addit</u> <u>Revision Date</u> <u>Inform</u> <u>Materials that can</u> <u>TWA</u> <u>10 mg/m3</u> <u>US (ACGIH)</u> <u>be formed when</u> <u>Inhalable</u> <u>2005</u> | pecific end use(s) | | | | |
| Ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Inform Materials that can be formed when handling this TWA 10 mg/m3 US (ACGIH) 2005 | | See Sectio | n 1. | | |
| Ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Inform Materials that can be formed when handling this TWA 10 mg/m3 US (ACGIH) 2005 | | | | | |
| Ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Inform Materials that can be formed when handling this TWA 10 mg/m3 US (ACGIH) 2005 | | | | | |
| Ontrol parameters Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Inform Materials that can be formed when handling this TWA 10 mg/m3 US (ACGIH) 2005 | | | | | |
| Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Inform Materials that can be formed when handling this TWA 10 mg/m3 US (ACGIH) 2005 1000000000000000000000000000000000000 | OSURE CONTROLS/PERSON/ | AL PROTE | CTION | | |
| Ingredients with workplace control parameters Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Inform Materials that can be formed when handling this TWA 10 mg/m3 US (ACGIH) 2005 1000000000000000000000000000000000000 | I narameters | | | | |
| Occupational Exposure Limits Components CAS-No. Type Limit Value Basis Addit Inform Materials that can be formed when handling this TWA 10 mg/m3 US (ACGIH) 2005 1000000000000000000000000000000000000 | - | | | | |
| ComponentsCAS-No.TypeLimit ValueBasis Revision DateAddit InformMaterials that can be formed when handling thisTWA10 mg/m3 inhalableUS (ACGIH) 2005 | gredients with workplace con | trol parame | eters | | |
| Materials that can be formed when handling thisTWA10 mg/m3 inhalableUS (ACGIH) 2005 | cupational Exposure Limits | | | | |
| be formed when inhalable 2005 handling this | components CAS-No. | Туре | Limit Value | | Additional Information |
| handling this | | TWA | - | US (ACGIH) | |
| | | | innaiable | 2005 | |
| | ict: Non- | | | | |
| specified (inert or nuisance) dust | ried (inert or | | | | |
| | | | | | |
| 5 / 13 | | | | | |
| | | 5 | / 13 | | |

| (+) | 1881 | 69961 | 68 |
|-----|------|-------|----|
| (.) | 1001 | 00001 | 00 |

Ponciplastics.com

Iyondellbasel - 111 Gen. Variant: SDS US GHS

| Softell TKG | 442N E1 C12A19 |
|-------------|--------------------------|
| Version 1.0 | Revision Date 04/08/2020 |

Print Date 01/07/2022

SDS No.: BE27939

| Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust | Т | WA | 3 mg/m3 respirable | US (ACGIH) 2005 | |
|---|---|----|------------------------|--------------------|--|
| Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust | Т | WA | 15 mg/m3 total dust | US (OSHA) 2005 | |
| Materials that can be formed when handling this product: Non- specified (inert or nuisance) dust | Т | WA | 5 mg/m3 respirable | US (OSHA) 2005 | |

Consult local authorities for acceptable exposure limits.

Exposure controls

Engineering measures

Follow the recommendations in NFPA 654 (as amended and adopted) for equipment used to handle this product.

Engineering controls, i.e. enclosed systems, should be used whenever feasible to maintain exposures below acceptable criteria. When such controls are not feasible, or sufficient to achieve full conformance, other engineering controls such as local exhaust ventilation should be used. Equipment and vessels handling combustible dust from this material should be designed to either prevent dust explosions (inerting) or safely vent dust explosions per NFPA 654 Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

| Respiratory protection | Use process enclosures, local exhaust ventilation, or other engineering controls to keep airborne levels below recommended exposure limits. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Use appropriate respiratory protection where atmosphere exceeds recommended limits. Where workers could be exposed to dust concentrations above the exposure limit they must use appropriate certified respirators. |
|-------------------------|---|
| Hand protection | : Wear gloves that provide thermal protection where there is a potential for contact with heated material. |
| Eye and face protection | : Dust service goggles should be worn to prevent mechanical |
| | 6 / 13 |
| | |

| AFETY DATA SHEET | lyondellbase |
|--|---|
| | |
| oftell TKG 442N E1 C ersion 1.0 Revision Dat | te 04/08/2020 Print Date 01/07/2022 SDS No.: BE27 |
| | |
| | injury or other irritation to eyes due to airborne particles whic may result from handling this product. |
| Skin and body protection | : Wear suitable protective clothing. |
| Hygiene measures | Selection of appropriate personal protective equipment should be based on an evaluation of the performance characteristic of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered during use. Use good personal hygiene practices. Wash hands before eating, drinking, smoking, or using toilet facilities. Take off contaminated clothing and wash before reuse. |
| | |
| PHYSICAL AND CHEMICAL F Appearance | : Pellets. |
| | : Pellets. : Black |
| Appearance Color | : Pellets. |
| Appearance Color Odor | : Pellets. : Black : Slight. |
| Appearance Color Odor Odor Threshold | Pellets. Black Slight. No value available. |
| Appearance Color Odor Odor Threshold Flash point | Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer due |
| Appearance Color Odor Odor Threshold Flash point Lower explosion limit | Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer data varies according to particle size distribution. |
| Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit | Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dayaries according to particle size distribution. Not applicable. |
| Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) | Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer day varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. |
| Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties | Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C |
| Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature | Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C |
| Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature | Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer dayaries according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined |
| Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range | Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C |
| Appearance Color Odor Odor Threshold Flash point Lower explosion limit Upper explosion limit Flammability (solid, gas) Oxidizing properties Autoignition temperature Decomposition temperature Melting point/range Boiling point/boiling range | Pellets. Black Slight. No value available. No Data Available. The minimum explosive concentration (MEC) for polymer du varies according to particle size distribution. Not applicable. Polymer will burn but does not easily ignite. Not considered an oxidizing agent. > 300 °C not determined 50 - 170 °C Not applicable. |

| | (+) 18816996168 |
|--|--|
| SAFETY DATA SHEET | Ponciplastics.com |
| Softell TKG 442N E1 C | Gen. Variant: SDS_US_GHS |
| Version 1.0 Revision Date | e 04/08/2020 Print Date 01/07/2022 SDS No.: BE27939 |
| | |
| Partition coefficient: n- octanol/water | : No Data Available. |
| Viscosity, dynamic | : Not applicable. |
| Relative vapor density | : Not applicable. |
| Evaporation rate | : Not applicable. |
| Explosive properties | : No Data Available. |
| Other Information | : No additional information available. |
| 10. STABILITY AND REACTIVITY | (|
| Reactivity | : No known reactivity hazards. |
| Chemical stability | : Stable under normal conditions. |
| Hazardous reactions | : Will not occur. |
| Conditions to avoid | : Avoid contact with strong oxidizers, excessive heat, sparks or open flame. |
| Materials to avoid | : Material may be softened by some hydrocarbons. |
| Hazardous decomposition products | : Not expected to decompose under normal conditions. |
| Thermal decomposition | : Carbon monoxide, olefinic and paraffinic compounds, trace amounts of organic acids, ketones, aldehydes and alcohols may be formed. |
| 11. TOXICOLOGICAL INFORMAT | ΓΙΟΝ |
| Acute toxicity | |
| Acute oral toxicity | : Not classified |
| Acute inhalation toxicity | : Not classified |
| Acute dermal toxicity | : Not classified |
| Skin corrosion/irritation | : Not a skin irritant. |
| Serious eye damage/eye irritation | : Not an eye irritant. Mechanical irritation is possible. |
| | 8 / 13 |

| | (+) 1881 | 6996168 | | | | |
|--|--|-----------------|----------|---|--|--|
| SAFETY DATA SHEET | Ponciplastics.com | | | ondellbase | | |
| | | | | | | |
| Softell TKG 442N E1 C12Version 1.0Revision Date 04 | | Print Date 01 | | . Variant: SDS_US_GHS SDS No.: BE279 | | |
| | | | | | | |
| | | | | | | |
| Respiratory or skin | Not classifie | èd | | | | |
| sensitization | | | | | | |
| Chronic toxicity | | | | | | |
| Component Name Titanium Dioxide | NTP | IARC 2B | | OSHA Present | | |
| Carbon Black | | 2B | | Present | | |
| Carcinogenicity | Not classifie | ed | | | | |
| Germ cell mutagenicity | utagenicity : Not classified | | | | | |
| Reproductive toxicity | | | | | | |
| Effects on fertility / : Effects on or via lactation | | | | | | |
| | Not classifie | | | | | |
| Target Organ Systemic | : The substance or mixture is not classified as specific target organ toxicant, single exposure. | | | | | |
| Target Organ Systemic Toxicant - Repeated exposure | : The substance or mixture is not classified as specific target organ toxicant, repeated exposure. | | | | | |
| Aspiration hazard | Not applicat | ble. | | | | |
| 12. Ecological information | | | | | | |
| Ecotoxicology Assessment | | | | | | |
| Short-term (acute) aquatic | Not classifie | ed | | | | |
| hazard Long-term (chronic) : aquatic hazard | : Not classified | | | | | |
| | | | | | | |
| Persistence and degradability | | | | | | |
| Biodegradability | Not expecte | ed to be biodeg | radable. | | | |
| Bioaccumulative potential | | | | | | |
| 9 / 13 | | | | | | |
| | | | | | | |
| | | | | | | |

| | (+) 18816996168 | | | | |
|---|---|--|--|--|--|
| SAFETY DATA SHEET | Ponciplastics.com | | | | |
| | lyondellbasell | | | | |
| Softell TKG 442N E1 C12 | | | | | |
| Version 1.0 Revision Date 04 | V08/2020 Print Date 01/07/2022 SDS No.: BE27939 | | | | |
| | | | | | |
| | This material is not expected to bioaccumulate. | | | | |
| Mobility in soil | | | | | |
| Mobility | no data available | | | | |
| Other adverse effects | | | | | |
| Environmental fate and | This material is not volatile and insoluble in water. | | | | |
| Other information | | | | | |
| Additional ecological | Ecotoxicity is expected to be minimal based on the low water solubility of polymers. No data available on this product. However, birds, fish and other wildlife may eat pellets which may obstruct their intestinal tracts. | | | | |
| | | | | | |
| 13. Disposal considerations | | | | | |
| Waste treatment methods | | | | | |
| Product | All recovered material should be packaged, labeled, transported and disposed of or reclaimed in conformance with applicable laws and regulations and in conformance with good engineering practices. Reclaim where possible. Recycle if possible. | | | | |
| | This material is classified as a Non-hazardous Material by RCRA. | | | | |
| 14. TRANSPORT INFORMATION | | | | | |
| Not regulated for transport | | | | | |
| 15. REGULATORY INFORMATION | | | | | |
| TSCA 12b | | | | | |
| No substances are subject to TSCA 12(b) export notification requirements. | | | | | |
| 10 / 13 | | | | | |
| | | | | | |
| | | | | | |

(+) **18816996168** Ponciplastics.com

SAFETY DATA SHEET

Softell TKG 442N E1 C12A19

Version 1.0

Revision Date 04/08/2020

Print Date 01/07/2022

Gen. Variant: SDS_US_GHS 22 SDS No.: BE27939

lyondellbase

Significant New Use Rules (SNUR)

No substances are subject to a Significant New Use Rule.

SARA 302/304

This product contains no known chemicals regulated under SARA 302/304.

SARA 311/312

Based upon available information, this material is classified as the following health and/or physical hazards according to Section 311 & 312:

Combustible dust

SARA 313

This product contains no known chemicals regulated under SARA 313.

State Reporting

This material does not contain listed substance(s) known to the State of California to cause cancer, birth defects, or other reproductive harm that would require warning under the California Proposition 65 State Drinking Water and Toxic Enforcement Act.

However, LyondellBasell has not tested for the presence of listed chemical substances.

This product contains the following chemicals regulated by New Jersey's Worker and Community Right to Know Act:

14807-96-6Talc, Magnesium Silicate1333-86-4Carbon Black

No components are subject to the Massachusetts Right to Know Act.

This product contains the following chemicals regulated by Pennsylvania's Right to Know Act:

| 1333-86-4 | Carbon Black |
|-----------|------------------|
| 1344-28-1 | aluminium oxide |
| 108-31-6 | Maleic Anhydride |

Other international regulations

Global Inventory Status

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

*Additional Explanatory Status Statements follow the table, as necessary.

| Country/Region | Inventory | Status Description |
|----------------|-----------|--------------------|
| | 11 / 13 | |
| | 11/13 | |
| | | |
| | | |

SAFETY DATA SHEET

Ponciplastics.com



Version 1.0

Revision Date 04/08/2020

Print Date 01/07/2022

Iyondellbase

Gen. Variant: SDS_US_GHS

SDS No.: BE27939

Australia AICS Compliant DSL Compliant Canada China **IECSC** Compliant See REACH Compliance Statement Europe REACH Japan ENCS Compliant KECI Not Determined Korea New Zealand NZIoC Compliant PICCS Not Determined Philippines United States of America TSCA Compliant Taiwan TCSCA Compliant

REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that all substances in this preparation have been registered under REACh, in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)


Contact product.safety@lyb.com for additional global inventory information.

16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 15 16

| HMIS Classification | : Health Hazard: 0 Flammability: 1 Physical hazards: 0 | 0 1 0 |
|---------------------|--|-------|
| NFPA Classification | : Health Hazard: 0 Fire Hazard: 1 Instability: 0 | |



Further information HMIS rating scale (0 = minimal hazard; 4 = severe hazard) 12 / 13

SAFETY DATA SHEET

Ponciplastics.com



Softell TKG 442N E1 C12A19

Version 1.0

Revision Date 04/08/2020

Print Date 01/07/2022

SDS No.: BE27939

NFPA rating scale (0 = minimal hazard; 4 = severe hazard)

Disclaimer

Information in this document is accurate to the best of our knowledge at the date of publication. The document is designed to provide users general information for safe handling, use, processing, storage, transportation, disposal and release and does not constitute any warranty or quality specification, either express or implied, including any warranty of merchantability or fitness for any particular purpose. Users shall determine whether the product is suitable for their use and can be used safely and legally.

In addition to any prohibitions of use specifically noted in this document, LyondellBasell may further prohibit or restrict the sale of its products into certain applications. For further information, please contact a LyondellBasell representative or visit the LyondellBasell website at: https://www.lyondellbasell.com/en/products-technology/product-safety-stewardship/ The Trade Name referenced in section 1 is a trademark owned or used by the LyondellBasell family of companies.

Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1.234,56 mg/kg.

Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

End of Material Safety Data Sheet