

# CELCON® F20-03 LOF

## CELCON®

- A low-emission (medium-viscosity) grade for general injection molding.
- Features improved heat stability

### Product information

Resin Identification	POM	ISO 1043
Part Marking Code	>POM<	ISO 11469

### Rheological properties

Melt mass-flow rate	9 g/10min	ISO 1133
Melt mass-flow rate, Temperature	190 °C	
Melt mass-flow rate, Load	2.16 kg	
Moulding shrinkage, parallel	2.0 %	ISO 294-4, 2577

### Typical mechanical properties

Tensile modulus	2750 MPa	ISO 527-1/-2
Tensile stress at yield, 50mm/min	65 MPa	ISO 527-1/-2
Tensile strain at yield, 50mm/min	10 %	ISO 527-1/-2
Nominal strain at break	35 %	ISO 527-1/-2
Flexural modulus	2550 MPa	ISO 178
Flexural strength	87 MPa	ISO 178
Charpy notched impact strength, 23 °C	6.5 kJ/m <sup>2</sup>	ISO 179/1eA
Charpy notched impact strength, -30 °C	5.5 kJ/m <sup>2</sup>	ISO 179/1eA
Poisson's ratio	0.37 <sup>[C]</sup>	

[C]: Calculated

### Thermal properties

Melting temperature, 10 °C/min	165 °C	ISO 11357-1/-3
Temperature of deflection under load, 1.8 MPa	100 °C	ISO 75-1/-2
Coefficient of linear thermal expansion (CLTE), parallel	120 E-6/K	ISO 11359-1/-2

### Electrical properties

Surface resistivity	>1E15 Ohm	IEC 62631-3-2
Electric strength	19 kV/mm	IEC 60243-1

### Physical/Other properties

Humidity absorption, 2mm	0.2 %	Sim. to ISO 62
Density	1410 kg/m <sup>3</sup>	ISO 1183

### Injection

Drying Recommended	no
Drying Temperature	100 °C
Drying Time, Dehumidified Dryer	3 - 4 h
Processing Moisture Content	≤0.2 %
Melt Temperature Optimum	185 °C
Min. melt temperature	180 °C
Max. melt temperature	190 °C

# CELCON® F20-03 LOF

## CELCON®

Screw tangential speed	≤0.3 m/s
Mold Temperature Optimum	70 °C
Min. mould temperature	60 °C
Max. mould temperature	80 °C
Hold pressure range	60 - 120 MPa

## Characteristics

Processing	Injection Moulding
Delivery form	Pellets
Special characteristics	Low emissions

## Automotive

OEM	STANDARD	ADDITIONAL INFORMATION
BMW	GS93016	Black, Ulsan, Korea
BYD	BYD-TY-D13F05-0043	F20-03 LOF BK2, Ulsan, Korea
BYD	BYD-TY-D13F05-0043	F20-03 LOF NAT2, Ulsan, Korea
Ford	WSK-M4D635-A2	ASN 3094
Ford	WSK-M4D635-A2	ASN 3094
General Motors	GMW17008P-POM-C2	Black
General Motors	GMW17008P-POM-C2	Natural
General Motors	GMW22P-POM-C2	Natural
General Motors	GMW22P-POM-C2	Black
Mercedes-Benz	DBL5410	
NIO	NIO-SM.51.007-C2	
Stellantis	B62 0300 / 61/30/U4/AD1/W1/E2/215E/C1	01994_16_00541
VW Group	TL 524 76	VW 50180