

KEPITAL® TE-22 LOF2

POM, toughened, medium-viscosity grade, low emission

KEPITAL® TE-22 LOF2 is a toughened, medium-viscosity grade for general injection molding. Suitable for applications requiring high impact resistance, reduced impact noise and quality surface. A low-emission grade featuring improved heat stability.

Product information

Part Marking Code

> POM-HI <

ISO 11469

Typical mechanical properties

Yield stress, 50mm/min	51 MPa	ISO 527-1/-2
Yield strain, 50mm/min	9.5 %	ISO 527-1/-2
Nominal strain at break	40 %	ISO 527-1/-2
Flexural Modulus	2000 MPa	ISO 178
Flexural Strength	68 MPa	ISO 178
Charpy notched impact strength, 23°C	10 kJ/m ²	ISO 179/1eA

Thermal properties

Melting temperature, 10°C/min	165 °C	ISO 11357-1/-3
-------------------------------	--------	----------------

Flammability

Burning Behav. at thickness h	HB class	UL 94
-------------------------------	----------	-------

Electrical properties

Volume resistivity	1E12 Ohm.m	IEC 62631-3-1
Surface resistivity	1E16 Ohm	IEC 62631-3-2

Other properties

Density	1370 kg/m ³	ISO 1183
---------	------------------------	----------